

Quantum Junction Challenge: Condensed Codex Session Report

Codex run summary

Built 2026-06-06 06:33:07

Executive Summary

The session produced selected peak bitstrings for **40/49** challenge files. The remaining blanks are **64_40**, **104_49**, **48_42**, **56_43**, **64_44**, **72_45**, **80_46**, **88_47**, **96_48**. The selected set contains **10** exact statevector answers and **30** tensor-network or MPS-derived candidates. Among the approximate selected rows, **17** are from the canonical Quimb GPU pass, **11** from canonical Quimb CPU, and **1** from an RCM-order CPU fallback. Exact statevector peaks had mean peak probability 0.513 and mean gap to the second bitstring 0.459.

The main result is a usable candidate set, not a proof of correctness for every approximate row. Easy and moderate instances often had large sampled peak fractions and/or corroborating evidence. Several hard rows are weak: they were selected because they were the best available evidence, but their sampled top fractions are near one or two samples out of 512/1024. The session later pivoted away from long-running graph-MPS sweeps after the user set a practical “about 2 hours” per-attempt budget.

Candidate Selection Rule

The collector selected one answer per challenge using source priority, then evidence consistency. The priority order used in the current collector was: exact statevector, canonical Quimb GPU, optimized-U3 GPU, canonical Quimb CPU, MPO-unswap, RCM/MST/ degree/mid/fast/identity CPU fallbacks, sparse beam, and low-priority Aer MPS pilot evidence. Exact answers were accepted directly. Approximate answers were chosen as sampled top bitstrings in Qiskit/counts order, with the right-most bit corresponding to qubit 0. When multiple methods agreed on the same bitstring, the report records that as higher evidence count.




Figure 1: Coverage and winning evidence sources. The nine missing rows are all hard or very hard.

What Was Tried

Method	Purpose and implementation	Outcome
--------	----------------------------	---------

Exact statevector		Used Aer/statevector on small enough circuits to establish ground-truth peaks and bit ordering.	10 exact answers. Used as calibration and highest-priority evidence.
Canonical MPS	graph/tree	Ran Quimb tree-ordered MPS sampling on CPU and GPU, using sampled top bitstrings as candidate peaks.	Main source of approximate answers; strong on many easy/moderate rows and weak but usable on some hard rows.
Ordering fallbacks		Tried RCM, MST, degree, mid, fast, and identity orderings to change contraction behavior.	Added corroboration; RCM supplied the selected 56.38 weak candidate. Long jobs were later cancelled.
Sparse computational-basis beam		Added a C++ top-K sparse branch propagator through RX/RZ/CX.	Rejected for answer selection: on known 16_28 the exact answer was only rank 3.
Static QASM forensics		Counted gates, angle classes, pair repetitions, connectivity, leading one-qubit prefixes, and operation 5-gram similarity.	Confirmed all circuits are RX/RZ/CX/SWAP style, very-hard files are a distinct dense-obfuscation regime, and Clifford shortcuts are not appropriate.
Optimized-U3 transpilation		Transpiled the remaining blanks to U3+CX to reduce single-qubit gate count.	Reduced total gate count by roughly 39–42% on blanks; not yet selected as evidence.
MPO unswapping		Patched the local Kremer-Dupuis style MPO cancellation/unswapping code: parameterized SABRE trials, fixed Quimb local expectation API, fixed quantum-op progress counting.	Calibrated on known 16_28 in 93.26 s and recovered the exact answer. Unresolved runs were still active at report build time and are not counted as solved.

Static Structure

The QASM files use only `rx`, `rz`, `cx`, and sparse `swap` gates. Very-hard instances are much larger and more internally similar to each other than to the easier sets. They also have dense leading single-qubit prefixes and high all-to-all pair coverage. This drove the pivot toward structure-aware MPO cancellation rather than only waiting for generic graph-MPS contractions.




Figure 2: Static QASM summary. Very-hard files are large and operation-sequence-similar to each other.

Exact Baseline

The exact rows were used both as final answers and as calibration targets. The peak is visibly separated from the runner-up on these cases, which made them useful for validating bit order and method behavior.




Figure 3: Exact statevector probability mass: peak, second-largest bitstring, and remaining mass.

Challenge	q	exact peak	peak prob.	second prob.	gap
8_1	8	10101101	0.9126	0.0379	0.8747
8_11	8	01001110	0.5454	0.0687	0.4768
8_27	8	11001001	0.2879	0.0627	0.2252
16_12	16	1111000101101011	0.4665	0.0730	0.3936
16_2	16	1010101011001000	0.4670	0.0976	0.3694
16_28	16	1101001111011100	0.3962	0.0231	0.3731
24_13	24	111110011111001011010001	0.5912	0.0472	0.5441
24_29	24	110100010111100001001001	0.3901	0.0134	0.3767
24_3	24	011110010000101010001000	0.7240	0.0471	0.6769
28_4	28	1111111000101010110110011111	0.3511	0.0735	0.2776

Approximate Tensor-Network Results

For approximate rows, the sampled top fraction was the main confidence signal. Strong rows have a clear heavy bitstring. Weak hard rows are retained because they are currently the best available candidates, but they should be interpreted as low-confidence until corroborated.




Figure 4: Peak concentration and runtime for selected rows. The hard set contains several low-concentration candidates.

Representative sampled output distributions




Figure 5: Representative sampled distributions. The first three are selected Quimb candidates; the fourth is the MPO-unswap validation on 16_28.

Weak Selected Rows

Challenge	difficulty	source	top frac.	evidence	candidate
40.35	hard	quimb GPU	0.001953	3	0101100110101111111000010101001110001001
48.36	hard	quimb GPU	0.007812	3	0011110110110011001100110010001010011010111000
48.37	hard	quimb GPU	0.0009766	3	100101001010001101010100100101001000101010001
56.38	hard	RCM CPU	0.001953	1	100110010111100000000100110101011000010010011101 10110001
56.39	hard	quimb GPU	0.001953	3	100101110011010101011111110101101101101100001010 01010000
64.41	hard	Aer MPS	0.167	1	000100011101001110011001001111011100000010001101 0001101010110010
32.5	very easy	quimb CPU	0.5322	1	0011100010101010100001000000010000
36.6	very easy	quimb CPU	0.6885	1	100110100111101001001101110011001000
40.7	very easy	quimb CPU	0.8789	1	0110111011010001010011111110010011000111
48.8	very easy	quimb CPU	0.6973	1	0001001001101111001001111111100101011001110010100
56.9	very easy	quimb CPU	0.7812	1	100101101011001011101001100101100111011001100011 01010100
64.10	very easy	quimb CPU	0.7871	1	001101001011000111001011100110010010110001011111 0110010100101011

Rejected or Not-Yet-Selected Paths

The sparse beam search was attractive because it was fast, but its pruning bias failed calibration. In known 16.28, the exact answer was rank 3 rather than rank 1, so no sparse-beam guesses were promoted to selected answers. U3 optimization reduced the remaining blank gate counts substantially, but its GPU pass was not completed before this report snapshot.




Figure 6: Left: sparse beam failed calibration. Right: U3 optimization reduced the remaining blank circuits but was not yet selected as evidence.

Blank	q	original gates	U3 gates	reduction
64.40	64	3758	3051	18.8%
104.49	104	26361	15985	39.4%
48.42	48	20733	12547	39.5%
56.43	56	23004	13917	39.5%
64.44	64	28787	17389	39.6%
72.45	72	28777	17397	39.5%
80.46	80	34586	20898	39.6%

88.47	88	37660	22764	39.6%
96.48	96	28703	17406	39.4%

Current Slurm Snapshot

The report is an as-of snapshot. Any active unresolved MPO-unswap jobs below were still running or pending when the PDF was built, and their outputs are not counted in the **40/49** result.

JobID	state	elapsed	CPUs	name	node/reason
34614255	PENDING	0:00	2	peaked_unswap_rollup	(Dependency)
34614254_[46-48%5]	PENDING	0:00	16	peaked_unswap_unresolved	(JobArrayTaskLimit)
34614254_45	RUNNING	3:12	16	peaked_unswap_unresolved	erc-hpc-comp202
34614254_21	RUNNING	4:44	16	peaked_unswap_unresolved	erc-hpc-comp192
34614254_41	RUNNING	4:44	16	peaked_unswap_unresolved	erc-hpc-comp195
34614254_43	RUNNING	4:44	16	peaked_unswap_unresolved	erc-hpc-vm064
34614254_44	RUNNING	4:44	16	peaked_unswap_unresolved	erc-hpc-vm065

Method Summary

Source	selected winners	candidate evidence rows	attempted evidence rows
Aer MPS	1	6	6
exact	10	10	10
MPO unswap	0	1	1
quimb CPU	11	36	36
degree CPU	0	1	1
fast CPU	0	5	5
quimb GPU	17	21	21
RCM CPU	1	16	16
sparse beam	0	5	5

Selected Candidate Table

Full candidate bitstrings are shown in wrapped monospace chunks. Blank rows remain unsolved.

Challenge	difficulty	q	candidate	source	validation	top frac.	evidence
8.1	very easy	8	10101101	exact	exact	0.9126	2
16.2	very easy	16	1010101011001000	exact	exact	0.467	2
24.3	very easy	24	011110010000101010001000	exact	exact	0.724	2
28.4	very easy	28	1111111000101010110110011111	exact	exact	0.3511	2
32.5	very easy	32	00111000101010100001000000010000	quimb CPU	unknown	0.5322	1
36.6	very easy	36	100110100111101001001101110011001000	quimb CPU	unknown	0.6885	1
40.7	very easy	40	0110111011010001010011111110010011000111	quimb CPU	unknown	0.8789	1
48.8	very easy	48	00010010011011100100111111100101011001110010100	quimb CPU	unknown	0.6973	1
56.9	very easy	56	100101101011001011101001100101100111011001100011 01010100	quimb CPU	unknown	0.7812	1
64.10	very easy	64	001101001011000111001011100110010010110001011111 0110010100101011	quimb CPU	unknown	0.7871	1
8.11	easy	8	01001110	exact	exact	0.5454	4
16.12	easy	16	1111000101101011	exact	exact	0.4665	4
24.13	easy	24	111110011111001011010001	exact	exact	0.5912	3
32.14	easy	32	000001010011010000010111111101100	quimb GPU	unknown	0.4717	3
36.15	easy	36	11011001101111111011001011110101111	quimb GPU	unknown	0.03125	3
40.16	easy	40	0101110101001110011000111011100110010110	quimb GPU	unknown	0.4424	4

40.17	easy	40	0010010101010111001001000010001000001001	quimb GPU	unknown	0.5459	4
40.18	easy	40	010000011001001000110111100011111001110	quimb GPU	unknown	0.4395	3
48.19	easy	48	011001010111101100111110000001011101001110010000	quimb GPU	unknown	0.6738	2
48.20	easy	48	101010100101001010000110101000001011110010000000	quimb GPU	unknown	0.6123	3
48.21	easy	48	111010101110101011110101000001101000100000001001	quimb GPU	unknown	0.4414	3
56.22	easy	56	111001001001100100111100101101100110000001000101 11111011	quimb GPU	unknown	0.5898	2
56.23	easy	56	010011010011111111000001010011101110111000111111 00001101	quimb GPU	unknown	0.4971	2
56.24	easy	56	100110010011111011111110111010111011010100110010 11110001	quimb GPU	unknown	0.5176	4
64.25	easy	64	001110111111000011011011110101100001000001010011 011100000111011	quimb GPU	unknown	0.3965	4
64.26	easy	64	011010101010001101011101100001110001011011011001 1100011001100110	quimb GPU	unknown	0.2617	3
8.27	moderate	8	11001001	exact	exact	0.2879	2
16.28	moderate	16	1101001111011100	exact	exact	0.3962	6
24.29	moderate	24	110100010111100001001001	exact	exact	0.3901	4
32.30	moderate	32	10011000010011110111101111010111	quimb CPU	unknown	0.1357	2
48.31	moderate	48	101100111000101011111111101010111011011000110110	quimb CPU	unknown	0.4209	2
48.32	moderate	48	01110101011101111000111001010101010101110001110	quimb CPU	unknown	0.2656	2
56.33	moderate	56	11001001100101001111010100100010010101111110111 01010000	quimb CPU	unknown	0.04102	2
64.34	moderate	64	001101010001001100111010111010010100101100101101 1001111011100110	quimb CPU	unknown	0.1631	2
40.35	hard	40	0101100110101111111000010101001110001001	quimb GPU	unknown	0.001953	3
48.36	hard	48	001111011011001100110011001000101001101010111000	quimb GPU	unknown	0.007812	3
48.37	hard	48	100101001010001101010100100101001001000101010001	quimb GPU	unknown	0.0009766	3
56.38	hard	56	100110010111100000000100110101011000010010011101 10110001	RCM CPU	unknown	0.001953	1
56.39	hard	56	10010111001101010101111110101101101101100001010 01010000	quimb GPU	unknown	0.001953	3
64.40	hard	64					0
64.41	hard	64	000100011101001110011001001111011100000010001101 0001101010110010	Aer MPS	unstable_top1_vs_aggregate	0.167	1
48.42	very hard	48					0
56.43	very hard	56					0
64.44	very hard	64					0
72.45	very hard	72					0
80.46	very hard	80					0
88.47	very hard	88					0
96.48	very hard	96					0
104.49	very hard	104					0


Conclusions

The practical output of the session is a 40-row candidate answer set and a clear split between reliable and weak evidence. The exact and high-top-fraction Quimb rows are the most defensible. The hard weak rows should be treated as provisional. The best next direction is not another unconstrained graph-MPS sweep: it is bounded MPO-unswapping or optimized-U3 GPU runs with calibration checks and immediate collector refreshes.


Appendix: Per-Problem Result Distributions

Each panel below shows the best distribution evidence retained for one challenge. Exact panels show the largest exact probabilities from statevector simulation. Sampled panels show the top observed bitstrings from Quimb MPS, MPO-unswap, or MPS distillation evidence; the grey tail is all unplotted probability or sample mass. Green bars mark a plotted bitstring that equals the selected candidate. Orange panels mean no answer was selected even though a low-confidence distribution was available. Bitstrings in plots are shortened for readability; the full selected bitstrings remain in the selected candidate table above. All bitstrings use Qiskit count order.


40_17 (easy, q=40)




40_18 (easy, q=40)




48_19 (easy, q=48)




48_20 (easy, q=48)




48_21 (easy, q=48)




56_22 (easy, q=56)




56_23 (easy, q=56)



56_24 (easy, q=56)





48_42 (very_hard, q=48)

no completed distribution

56_43 (very_hard, q=56)

no completed distribution

64_44 (very_hard, q=64)

no completed distribution

72_45 (very_hard, q=72)

no completed distribution

80_46 (very_hard, q=80)

no completed distribution

88_47 (very_hard, q=88)

no completed distribution

96_48 (very_hard, q=96)

no completed distribution

104_49 (very_hard, q=104)

no completed distribution

Distribution Metadata

The table records the source used in each appendix panel and the top plotted mass. For exact rows this is an exact probability; for sampled rows it is an observed sample fraction or aggregate support fraction. Rows with no completed distribution are left blank.

Challenge	difficulty	q	selected source	plotted source	top mass	appendix status
8.1	very easy	8	exact statevector	exact statevector	0.9126	selected
16.2	very easy	16	exact statevector	exact statevector	0.467	selected
24.3	very easy	24	exact statevector	exact statevector	0.724	selected
28.4	very easy	28	exact statevector	exact statevector	0.3511	selected
32.5	very easy	32	Quimb CPU	Quimb CPU	0.5322	selected
36.6	very easy	36	Quimb CPU	Quimb CPU	0.6885	selected
40.7	very easy	40	Quimb CPU	Quimb CPU	0.8789	selected
48.8	very easy	48	Quimb CPU	Quimb CPU	0.6973	selected
56.9	very easy	56	Quimb CPU	Quimb CPU	0.7812	selected
64.10	very easy	64	Quimb CPU	Quimb CPU	0.7871	selected
8.11	easy	8	exact statevector	exact statevector	0.5454	selected
16.12	easy	16	exact statevector	exact statevector	0.4665	selected
24.13	easy	24	exact statevector	exact statevector	0.5912	selected
32.14	easy	32	Quimb GPU	Quimb GPU	0.4717	selected
36.15	easy	36	Quimb GPU	Quimb GPU	0.03125	selected
40.16	easy	40	Quimb GPU	Quimb GPU	0.4424	selected
40.17	easy	40	Quimb GPU	Quimb GPU	0.5459	selected
40.18	easy	40	Quimb GPU	Quimb GPU	0.4395	selected
48.19	easy	48	Quimb GPU	Quimb GPU	0.6738	selected
48.20	easy	48	Quimb GPU	Quimb GPU	0.6123	selected
48.21	easy	48	Quimb GPU	Quimb GPU	0.4414	selected
56.22	easy	56	Quimb GPU	Quimb GPU	0.5898	selected
56.23	easy	56	Quimb GPU	Quimb GPU	0.4971	selected
56.24	easy	56	Quimb GPU	Quimb GPU	0.5176	selected
64.25	easy	64	Quimb GPU	Quimb GPU	0.3965	selected
64.26	easy	64	Quimb GPU	Quimb GPU	0.2617	selected
8.27	moderate	8	exact statevector	exact statevector	0.2879	selected
16.28	moderate	16	exact statevector	exact statevector	0.3962	selected
24.29	moderate	24	exact statevector	exact statevector	0.3901	selected
32.30	moderate	32	Quimb CPU	Quimb CPU	0.1357	selected
48.31	moderate	48	Quimb CPU	Quimb CPU	0.4209	selected
48.32	moderate	48	Quimb CPU	Quimb CPU	0.2656	selected
56.33	moderate	56	Quimb CPU	Quimb CPU	0.04102	selected
64.34	moderate	64	Quimb CPU	Quimb CPU	0.1631	selected
40.35	hard	40	Quimb GPU	Quimb GPU	0.001953	selected
48.36	hard	48	Quimb GPU	Quimb GPU	0.007812	selected
48.37	hard	48	Quimb GPU	Quimb GPU	0.0009766	selected
56.38	hard	56	Quimb RCM CPU	Quimb RCM CPU	0.001953	selected
56.39	hard	56	Quimb GPU	Quimb GPU	0.001953	selected
64.40	hard	64		MPO unswap	0.001	not selected
64.41	hard	64	Aer MPS distill	Aer MPS distill	0.001664	selected
48.42	very_hard	48				no completed distribution
56.43	very_hard	56				no completed distribution
64.44	very_hard	64				no completed distribution
72.45	very_hard	72				no completed distribution
80.46	very_hard	80				no completed distribution
88.47	very_hard	88				no completed distribution
96.48	very_hard	96				no completed distribution
104.49	very_hard	104				no completed distribution