

AD155A0 Datasheet

Zhuhai Jieli Technology Co.,LTD

Version: V1.1

Date: 2021.07.05

AD155A0 Features

CPU Core

- 32-bit CPU, Built-in ICACH, can be connected to Flash for expansion of code
- The main frequency is up to 120MHz

Memory

- Built-in 28Kbytes of SRAM
- 8Kbytes 2-Way Icache

Clock Source

- RC Clock frequency about 16MHz
- LRC(low power RC) clock frequency about 200KHz

Digital I/O

- Up to 19 programmable digital I/O pins
- General the IO supports pull-up(10k), pull-down(60k), strong, weak output, input and high impedance
- Up to 12 external interrupt/wake-up source(low power available, can be multiplexed to any I/O, with hardware filter)
- Input channel and Output channel, provide arbitrary IO input and output options for some modules

Digital peripherals

- Two UART Controllers(UART0/1) supports DMA and Flow Control

- Two SPI Controllers with DMA(SPI0/1) support master mode and slave mode
- One Spi Flash Controller to run code
- One SD host controller
- Three 32-bit Asynchronous Divider Timers
- One IIC Controller
- Four channel PWM output
- Infrared remote control decoder
- Watchdog
- 64-bit EFUSE

Analog Peripherals

- 0.5 watt Class-D audio amplifier output
- 10-bit high precision ADC
- Low voltage protection
- Power on reset

Operating Conditions

- Working voltage
VBAT: 2.0v - 5.5v
VDDIO: 2.0v - 3.4v
- Operating Temperature: -40°C to +85°C

Package

- QSOP24

Application

- Sound Toy
- Audio player

1、 Pin Definition

1.1 Pin Assignment




Figure 1-1 AD155A0_QSOP24 Package Diagram

1.2 Pin Description

Table 1-1 AD155A0_QSOP24 Pin Description

PIN NO.	Name	Type	Drive (mA)	Function	Description
1	PD2	I/O	8/64	GPIO (pull up)	SPI0CSA:SPI0 Chip Select(A); SFCCSA:SFC Chip Select(A);
2	PD1	I/O	8/64	GPIO	SPI0DOA(0):SPI0 Data0 Out(A); SFCDOA(0):SFC Data0 Out(A);
3	PD0	I/O	8/64	GPIO	SPI0CLKA:SPI0 Clock(A); SFCCLKA:SFC Clock(A);
4	PA7	I/O	8/64	GPIO	ADC7:ADC Input Channel 7; SPI1DOC:SPI1 Data Out(C); UART0RXA:Uart0 Data In(A); I2C_SDA(C); PWM1:PWM Channel1 Output;
5	PA6	I/O	8/64	GPIO	ADC6:ADC Input Channel 6; SPI1CLKC:SPI1 Clock(C); UART0TXA:Uart0 Data Out(A); I2C_SCL(C); TMR2:Timer2 Clock In; PWM0:PWM Channel0 Output;
6	PA3	I/O	8/64	GPIO	ADC3:ADC Input Channel 3; SPI0DIB(1):SPI0 Data1 In(B); SD0DATA:SD0 Data(A); CLKOUT; PWM2(B); MCAP0:Motor Timer0 Capture;
7	PA2	I/O	8/64	GPIO	ADC2:ADC Input Channel 2; SPI0DOB(0):SPI0 Data0 Out(B); SD0CMDA:SD0 Command(A); I2C_SDA(B); PWM2(A);
8	PA1	I/O	8/64	GPIO	ADC1:ADC Input Channel 1; SPI0CLKB:SPI0 Clock(B); SD0CLKA:SD0 Clock(A); UART0RXB:Uart0 Data In(B); I2C_SCL(B); CAP2:Timer2 Capture;

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

9	PA0	I/O	8/64	GPIO (pull up)	Long Press Reset; ADC0:ADC Input Channel 0; UART0TXB:Uart0 Data Out(B);
10	VDDIO	P	/		Digital Power; (Internal linear regulator output)
11	VBAT	P	/		Battery Power Supply;
12	VSS	G	/		Ground;
13	DACP	O	/		Class-D APA Positive Output;
14	DACN	O	/		Class-D APA Negative Output;
15	PB9	I/O	8	GPIO (High Voltage Resistance)	SPI1DOD:SPI1 Data Out(D); UART1TRXB:Uart1 Data In/Out(B); I2C_SDA(D); CAP1:Timer1 Capture;
16	PB8	I/O	8	GPIO (High Voltage Resistance)	SPI1CLKD:SPI1 Clock(D); I2C_SCL(D); OSCIA:Crystal Oscillator Input(A);
17	PB6	I/O	8/64	GPIO	SD0DATC:SD0 Data(C);
18	PB5	I/O	8/64	GPIO	ADC13:ADC Input Channel 13; SD0CMDC:SD0 Command(C);
19	PB4	I/O	8/64	GPIO	ADC12:ADC Input Channel 12; SD0CLKC:SD0 Clock(C);
20	PB2	I/O	8/64	GPIO	SPI1DIA:SPI1 Data In(A); SD0DATB:SD0 Data(B);
21	PB1	I/O	8/64	GPIO (pull down)	ADC11:ADC Input Channel 11; SPI1DOA:SPI1 Data Out(A); SD0CMDB:SD0 Command(B); I2C_SDA(A);
22	PB0	I/O	8/64	GPIO (pull down)	ADC10:ADC Input Channel 10; SPI1CLKA:SPI1 Clock(A); SD0CLKB:SD0 Clock(B); I2C_SCL(A);
23	PA12	I/O	8/64	GPIO	PWM3:PWM Channel3 Output;
24	PA11	I/O	8/64	GPIO	TMR0:Timer0 Clock In; PWM2:PWM Channel2 Output;

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2、Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Tamb	Ambient Temperature	-40	+85	°C
Tstg	Storage temperature	-65	+150	°C
VBAT	Supply Voltage	-0.3	5.5	V
V _{VDDIO33}	3.3V IO Input Voltage	-0.3	3.6	V

Note : The chip can be damaged by any stress in excess of the absolute maximum ratings listed below

2.2 PMU Characteristics

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.0	3.7	5.5	V	—
V _{VDDIO}	Voltage output	2.0	3.0	3.4	V	VBAT = 3.7V, 100mA loading
I _{VDDIO}	Loading current	—	—	100	mA	VBAT=3.7V

2.3 IO Input/Output Electrical Logical Characteristics

Table 2-3

IO input characteristics						
Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
V _{IL}	Low-Level Input Voltage	-0.3	—	0.3* VDDIO	V	VDDIO = 3.3V
V _{IH}	High-Level Input Voltage	0.7* VDDIO	—	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V _{OL}	Low-Level Output Voltage	—	—	0.33	V	VDDIO = 3.3V
V _{OH}	High-Level Output Voltage	2.7	—	—	V	VDDIO = 3.3V

2.4 Internal Resistor Characteristics

Table 2-4


Port	General Output	High Drive	Internal Pull-Up Resistor	Internal Pull-Down Resistor	Comment
PA0~PA12 PB0~PB7 PD0~PD2	8mA	64mA	10K	60K	1、PA0,PD2 default pull up 2、PB0 & PB1 default pull down 3、internal pull-up/pull-down resistance accuracy $\pm 20\%$
PB8,PB9	8mA	—	10K	60K	

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

3、 Package Information

3.1 QSOP24



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	—	—	1.75
A1	0.10	0.15	0.25
A2	1.30	1.40	1.50
A3	0.60	0.65	0.70
b	0.23	—	0.31
b1	0.22	0.25	0.28
c	0.20	—	0.24
c1	0.19	0.20	0.21
D	8.55	8.65	8.75
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e	0.635BSC		
h	0.30	—	0.50
L	0.50	—	0.80
L1	1.05REF		
θ	0	—	8°

Figure 3-1. AD155A0_QSOP24 Package

4、 Package Type Specification



①Represents different packages

②Represents different memory sizes

0: No memory

2: 2Mbit Flash

4: 4Mbit Flash

8: 8Mbit Flash

5、 Revision History

Date	Revision	Description
2021.03.17	V1.0	Initial Release
2021.07.05	V1.1	Modify the IO list

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.