AD142A0 Datasheet

Zhuhai Jieli Technology Co.,LTD

Version：V1.1

Date：2023.03.20

AD142A0 Features

CPU Core

- 32-bit CPU,the highest frequency is 160MHz

Clock Source

- RC Clock frequency about 16MHz
- LRC(low power RC) clock frequency about 32KHz
- HTC(low drift internal high frequency RC)clock frequency is 5MHz

Digital I/O

- 8 programmable digital I/O pins
- USB DP/DM can be configured to normal I/O pins
- General the IO supports pull-up(10k),pull-down(60k), strong,weak output,input and high impedance
- Up to 8 external interrupt/wake-up source(low power available,can be multiplexed to any I/O, with hardware filter)
- Input channel and Output channel, provide arbitrary IO input and output options for some modules

Digital peripherals

- One Full Speed USB 1.1 PHY
- Two UART Controllers(UART0/1) UART1 supports DMA and Flow Control
- Two SPI Controllers with DMA(SPI0/1) support master mode and slave mode.
- One Spi Flash Controller to run code
- One SD host controller
- Two 16-bit Asynchronous Divider Timers
- One IIC Controller
- Four channel PWM output
- 0.5 watt Class-D audio amplifier output
- Infrared remote control decoder
- Watchdog

Analog Peripherals

- MIC amplifier circuit
- Two analog audio input channels
- 10-bit high precision ADC
- 16-bit high precision ADC (mainly as recording)
- 16-bit high precision DAC
- Low voltage protection
- Power on reset

Operating Conditions

- Working voltage
  VBAT: 2.0v - 5.5v
  VDDIO: 2.0v - 3.4v
- Operating Temperature: -40°C to +85°C

Package

- SOP16

Application

- Sound Toy
- Audio player

1、Pin Definition

1.1 Pin Assignment



Figure 1-1 AD142A0_SOP16 Package Diagram

1.2 Pin Description

Table 1-1 AD142A0_SOP16 Pin Description

PIN NO.	Name	Type	Drive (mA)	Function	Description
1	PD2	I/O	8/64	GPIO (pull up)	SPI0CSA:SPI0 Chip Select(A); SFCCSA:SFC Chip Select(A);
2	PD1	I/O	8/64	GPIO	SPI0DOA(0):SPI0 Data0 Out(A); SFCDOA(0):SFC Data0 Out(A);
3	PD0	I/O	8/64	GPIO	SPI0CLKA:SPI0 Clock(A); SFCCLKA:SFC Clock(A);
4	USBDM	I/O	10	USB Negative Data (pull down)	ADC5:ADC Input Channel 5; SPI1DOA:SPI1 Data Out(A); UART1TXA:Uart1 Data Out(A); I2C_SDA(A);
5	USBDP	I/O	10	USB Positive Data (pull down)	ADC4:ADC Input Channel 4; SPI1CLKA:SPI1 Clock(A); UART1RXA:Uart1 Data In(A); I2C_SCL(A);
6	PA0	I/O	8/64	GPIO (pull up)	Long Press Reset; ADC0:ADC Input Channel 0; UART0TXB:Uart0 Data Out(B);
	PA13	I/O	8/64	GPIO	ADC10:ADC Input Channel 10; AUX0:Analog Channel 0 Input; MIC_BIAS:Microphone Bias Output; CAP0:Timer0 Capture
7	PB1	I/O	8/64	GPIO	MIC_IN：MIC Input Channel;
8	AGND	G	/		Analog Ground;
9	PB0	I/O	8/64	GPIO	**DAC:Analog Audio Output;** ADC13:ADC Input Channel 13; LVD:Low Voltage Detect；
10	VDDIO	P	/		GPIO Power;
11	VBAT	P	/		Battery Power Supply;
12	GND	G	/		Digital Ground;
13	DACPO	O	/		Class-D APA Positive Output;
14	DACNO	O	/		Class-D APA Negative Output;
15	PA12	I/O	8/64	GPIO	SPI1DOB:SPI1 Data Out(B); MCAP3:Motor Timer3 Capture;
16	PA11	I/O	8/64	GPIO	ADC9:ADC Input Channel 9; SPI1CLKB:SPI1 Clock(B); MCAP2:Motor Timer2 Capture;

	PA9	I/O	8	GPIO (High Voltage Resistance)	UART1TXB:Uart1 Data Out(B); UART1RXB:Uart1 Data In(B); I2C_SDA(D); CAP1:Timer1 Capture; PWM3:PWM Channel3 Output;

2、Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Tamb	Ambient Temperature	-40	+85	℃
Tstg	Storage temperature	-65	+150	℃
VBAT	Supply Voltage	-0.3	5.5	V
$V_{VDDIO33}$	3.3V IO Input Voltage	-0.3	3.6	V

Note : The chip can be damaged by any stress in excess of the absolute maximum ratings listed below.

2.2 PMU Characteristics

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.0	3.7	5.5	V	_
V_{VDDIO}	Voltage output	2.0	3.0	3.4	V	VBAT = 3.7V, 100mA loading
I_{VDDIO}	Loading current	_	_	100	mA	VBAT=3.7V

2.3 IO Input/Output Electrical Logical Characteristics

Table 2-3

IO input characteristics						
Symbol	**Parameter**	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
V_{IL}	Low-Level Input Voltage	-0.3	_	0.3* VDDIO	V	VDDIO = 3.3V
V_{IH}	High-Level Input Voltage	0.7* VDDIO	_	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V_{OL}	Low-Level Output Voltage	_	_	0.33	V	VDDIO = 3.3V
V_{OH}	High-Level Output Voltage	2.7	_	_	V	VDDIO = 3.3V

2.4 Internal Resistor Characteristics

Table 2-4

Port	General Output	High Drive	Internal Pull-Up Resistor	Internal Pull-Down Resistor	Comment
PA0、PA11、PA12、PA13 PB0、PB1、PD0~PD2	8mA	64mA	10K	60K	1、PA0&PD2 default pull up 2、USBDM & USBDP default pull down 3、internal pull-up/pull-down resistance accuracy ±20%
PA9 (high voltage I/O)	8mA	_	10K	60K	
USBDP	10mA	_	1.5K	15K	
USBDM	10mA	_	180K	15K	

2.5 Audio DAC(PB0) Characteristics

Table 2-5

Parameter	Min	Typ	Max	Unit	Test Conditions
Frequency Response	20	_	16K	Hz	1KHz/0dB 100kohm loading With A-Weighted Filter
THD+N	_	-65	_	dB	
S/N	_	95	_	dB	
Output Swing	_	0.54	_	Vrms	
Dynamic Range	_	92	_	dB	1KHz/-60dB 100kohm loading With A-Weighted Filter
Output Resistance	_	8.3	_	K	_

2.6 Audio ADC Characteristics

Table 2-6

Parameter	Min	Typ	Max	Unit	Test Conditions
Dynamic Range	_	75	_	dB	1KHz/210mVrms line mode :6dB with cap PGAIS=2
S/N	_	79	_	dB	
THD+N	_	-70	_	dB	

3、 Package Information

3.1 SOP16



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	—	—	1.75
A1	0.10	—	0.225
A2	1.30	1.40	1.50
A3	0.60	0.65	0.70
b	0.39	—	0.47
b1	0.38	0.41	0.44
c	0.20	—	0.24
c1	0.19	0.20	0.21
D	9.80	9.90	10.00
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e	1.27BSC		
h	0.25	—	0.50
L	0.50	—	0.80
L1	1.05REF		
θ	0	—	8°

Figure 3-1. AD142A0_SOP16 Package

4、 Revision History

Date	Revision	Description
2021.03.09	V1.0	Initial Release.
2023.03.20	V1.1	Modify Features.