

Documentation For Package xjtlumath

Guanyuming He

<https://github.com/Little-He-Guan/A-XJTLU-Math-Club-LaTeX-Template>

July 27, 2021

Copyright

Copyright © Guanyuming He 2021-2021. The document is licensed under the MIT license.

Contents

I	General Information	iii
1	What is this package?	iii
2	History	iii
3	How to read this document	iv
II	Tutorials	1
4	Tutorial 1: Ashley’s First Material	1
4.1	Installation and Configuration	1
4.2	Basic Writings	1
4.3	Adjust fonts	3
4.4	Typing Mathematical Formulae	4
4.5	Space Management	6
4.6	Lists and Other Environments	7
5	Tutorial 2: Delilah and Complex Math Formulae	10
5.1	Multiple Lined Formulae	10
5.2	Matrices	12
5.3	Texts and Operator Names	13
5.4	Delimiters	15
5.5	Symbols	16
6	Tutorial 3: Yue Handling Floats	18
6.1	Inserting Images	18
6.2	Tables	18
6.3	Placement of Floats	21
6.4	Table of Floats	21
6.5	A Suggestion About Images	22
7	Tutorial 4: The Story of ZiYou and Abigail	23
7.1	Managing Notes In L ^A T _E X	23
7.2	Merging Works Of The Team	24
7.3	Background, Headers, and Footers	25
7.4	Index And Bibliography	25
7.5	Twosided printing	27
7.6	An End Of Their Story	28

8 Tutorial 5: Raúl Typesetting An Exam Paper	29
8.1 The exampaper Environment	29
8.2 Multiple Choice Questions	30
8.3 Space And Rules	31
 III Templates	 33
9 For Material Use	33
9.1 Book in English	33
9.2 Book in Chinese	33
9.3 Article in English	33
9.4 Article in Chinese	34
 10 For General Use	 34
 IV Internal Documentation	 35
11 Package xjtlubase	35
12 Package xjtlumaththm	35
13 Package xjtlumathstyle	36
14 Package xjtlumaterial	38
15 Package xjtluexam	38
16 Package mydoc	41

Part I

General Information

1 What is this package?

This \LaTeX package was originally intended to be used by the materials dept. of XJTLU math club. Yet I found that my university lack \LaTeX templates for students, therefore I decided to extend it into a template for all users.

The package contains several useful commands and environments for mathematical documents, and redefines some existing styles so that they suit the university's style.

2 History

At the year 2020, I joined the materials dept. of XJTLU math club. This department makes materials about math and distribute them to students to help them. At that time, the materials were being prepared with Microsoft Word and MathType. I saw that it was a good opportunity to enhance the materials with the power of \LaTeX , so I proposed to prepare the documents using \LaTeX .

The proposition was passed and our team started to transfer our working environment. During this process, I wrote a tiny package, a predecessor of this package, which was used in our works. Many people in our department knew nearly nothing about \LaTeX , and as I promised that the new preparation process would not be very hard, I managed to define the overall procedure, shared some necessary knowledge about \LaTeX , and taught them how to use the package.

I admit that I was a bit irresponsible at that time. Truly I described how the working procedure was and how should my package be used, but I shared few about \LaTeX . My package and workflow simplified some concepts so that the team didn't need to care about some parts of \LaTeX such as the documentclass and preamble, though \LaTeX itself is still a lot different from Word. I underestimated the difficulty for my colleagues to learn basic \LaTeX typing skills so it was a torment for some of them. I some kind of realized this problem in the later stages, but I was occupied by my own businesses, and didn't pay enough attention to it.

The final results were generally successful and mostly good enough. Yet I feel sorry for my colleagues because this thing was in fact not that easy for them. In addition, I recently took part in the 15th anniversary of XJTLU math club and this somehow strengthened my sense of belonging to the math club. For these reasons, I decided to leave something for XJTLU's students in the future. I rewrote the whole package and added a series of tutorials that covers the basics of \LaTeX as well as making materials, so that people in the material dept. will do much less to make a material in \LaTeX . The tutorials are in the form of a stories, since I think this method adds more fun to the studying.

Apart from that, the general students of XJTLU or even other \LaTeX users may find this package and documentation useful. So its final form was decided to be a template with documentation that is published as a GitHub repository under my personal account. This is because the math club it self doesn't have a GitHub account currently. I will transfer this repository to its official account once it has established one.

3 How to read this document

For members of the materials department who are new to \LaTeX and this package, the tutorial part, except the tutorial 4, should be read thoroughly in the order they are present, since some content relies on the previous ones. If one is additionally associated with workings concerning past exam papers, then tutorial 5 is necessary for him to read.

For team leaders, tutorial 4 is then as important as the first three. It teaches about how to manage a team's work and some high level controls.

For someone who knows \LaTeX and who just wants to take advantage of this package, the tutorials may serve as a reference to the functionality provided by this package. The templates part gives description about what all the templates do.

For someone who wants to improve this package, see the implementation detail, or finds some bugs about this package, the Internal Documentation is a good place to go. Feel free to contact me at [my university email](#). I appreciate any response, suggestion, or correction regarding this tiny package. I hope one day, XJTLU can have a big \LaTeX community and many \LaTeX packages and templates, but that is a work that needs everyone's contribution.

Part II

Tutorials

4 Tutorial 1: Ashley's First Material

Ashley joined the material department recently. Now he is assigned to write a part of the material that covers basic calculus. He is very excited because this will be his first material as well as his first try on \LaTeX . First, he needs to know how to use \LaTeX and the package on his PC. In this tutorial, we will follow Ashley and see what he learns in the material preparation.

4.1 Installation and Configuration

To use \LaTeX , Ashley needs a \TeX distribution (and probably an editor) installed on his computer. There are several popular distributions listed on the \LaTeX official website: <https://www.latex-project.org/get/>. The installation and configuration of these distributions are quite easy and Ashley completed them in a few minutes.

Then, Ashley wants to have an editor for writing \LaTeX documents. He learns that \TeX studio is a good one, so he downloads and installs it.

What Ashley needs to do now is to obtain a copy of this package and install it. Ashley has to go to the GitHub repository <https://github.com/Little-He-Guan/A-XJTLU-Math-Club-LaTeX-Template> to fetch a copy. He navigates to the repository and goes to the most recent release <https://github.com/Little-He-Guan/A-XJTLU-Math-Club-LaTeX-Template/releases>, from where he downloads the xjtlumath.zip under the most recent release.

Now he has the package and have unzipped it. The operating system on his PC is Windows, so he can simply copy the contents to where his document is being prepared and run the install.bat.

For other operating systems, after copying the contents, one has to enter the command line, navigate to the directory, and type

```
latex xjtlumath.ins
```

to extract the package.

4.2 Basic Writings

Ashley, waiting breathlessly to begin his first work, clicks open the Templates folder and navigates into the material-book folder. He opens encapsulation.tex and notices that it is like this:

```
... Some code ...

\input{chapters.tex}

... Some code ...
```

As the file name suggests, this is for making a material that -is to be published as a book. A book contains some chapters, and in the material writing, each chapter is a specific part of the material topic. For example, Ashley's work is part of the calculus material, so he needs to start a chapter for his work. He opens `chapter.tex` and finds a blank document. He then adds the following command to start his first chapter and runs `LATEX` on `encapsulation.tex` to check the output (On the left is the result of his command(s), appearing in a different font family, and on the right is his commands, with a gray background):

1 Key points in calculus

```
\chapter{Key points in calculus}
```

`\chapter{...}` is a `LATEX` *command*, which starts with a `\`. The words being wrapped with the curly brackets `{}` form an *argument* for the command. At this place, they are the caption of the chapter. Ashley notices that `LATEX` automatically enlarges the font and makes them bold. Being different with many other typesetting software, `LATEX` only needs the logical idea of what to do (e.g. there will be a chapter named xxx at some place), and it will control the appearance for the author.

Ashley is satisfied with that result. He then types some of paragraphs. In `LATEX`, paragraphs are separated by one blank line.

1 Key points in calculus

What does Ashley write in these paragraphs? Well, in fact, I don't know. You may find him and ask him yourself.

But, wait a minute, how do I find Ashley when he doesn't really exist? Well, this is a good question.

```
\chapter{Key points in calculus}
What does Ashley write in these
paragraphs? Well, in fact, I don't know.
You may find him and ask him yourself.
```

```
But, wait a minute, how do I find Ashley
when he doesn't really exist? Well,
this is a good question.
```

Ashley notices that paragraphs are automatically indented by `LATEX`. Yet he also notices that the paragraph directly under the chapter is not indented.

Apart from `chapter`, `LATEX` also provides these sectioning commands:

- `section`
- `subsection`
- `subsubsection`
- `paragraph`
- `subparagraph`

You may notice that `paragraph` is included here. In fact, the sectioning command `\paragraph` generates a title for the paragraphs like other sectioning commands.

When Ashley turns to the whole output, he sees that his chapter appears in the table of contents:

Contents

1	Key points in calculus	1	<code>\chapter{Key points in calculus}</code>
---	---	---	---

\LaTeX generates the table of contents for all sectioning commands¹. For this reason, Ashley has to run \LaTeX twice on `encapsulation.tex` for a correct table of contents.

When Ashley once writes a very long caption for a section, the table of contents become quite ugly. To solve this, Ashley can specify a short form of the section that is used in the table of contents, as shown below:

Contents

1	A Short Name	1	<code>\chapter[A Short Name]{A very very long Caption}</code>
---	-------------------------------	---	---

4.3 Adjust fonts

So far, Ashley knows how to instruct \LaTeX to do some basic things. Although he feels full of energy and is writing at full speed, he soon encounters some problems. Ashley wants to emphasize some keywords such as “limit”. He later learns that the command `\emph` instructs \LaTeX to emphasize the text passed to it, as shown below.

Calculus is the study of *limits*.

Calculus is the study of `\emph{limits}`.

This thing is quite \LaTeX , as Ashley only tells \LaTeX to emphasize it, and has no control of how \LaTeX does it. Although most of times it is enough, Ashley wants more. He wonder how can one explicitly control the appearance of the texts, since \LaTeX cannot cover all needs in every situations. \LaTeX does provide certain default operations on fonts, and Ashley can use them to control the size, family, and style of his texts.

Ashley can tell \LaTeX to adjust the font size like:

very very small the size of scripts the size of foot notes small
font just being normal a bit bigger large text

very big huge damn huge

Ashley can tell `\LaTeX{}` to adjust the font size like:

```
{\tiny very very small} {\scriptsize the size
of scripts} {\footnotesize the size of foot
notes} {\small small font} {\normalsize just
being normal} {\large a bit bigger} {\Large
large text} {\LARGE very big} {\huge huge} {\HUGE damn huge}
```

This time Ashley sees something different from the command `\emph{}`. The

¹whose depth are below the table of contents (toc) depth. The actual process of how toc is generated is a bit complex, so I will not cover it here

texts here are inside curly brackets, and the commands are just given inside the brackets along with the texts. Something enclosed by a pair of curly brackets is said to be inside a *group*. Commands called inside the group influence the whole group.

Apart from the sizes, Ashley is also able to control the style and family of fonts. As shown in Table 1, L^AT_EX provides these commands to control font style and family:

Command	Used in a group	Action
<code>\textrm{...}</code>	<code>{\rmfamily...}</code>	Text in Roman family
<code>\textsf{...}</code>	<code>{\sffamily...}</code>	Text in sans serif family
<code>\texttt{...}</code>	<code>{\ttfamily...}</code>	Text in typewriter family
<code>\textmd{...}</code>	<code>{\mdseries...}</code>	Text in medium series
<code>\textbf{...}</code>	<code>{\bfseries...}</code>	Text in bold series
<code>\textup{...}</code>	<code>{\upshape...}</code>	Text in upright shape
<code>\textit{...}</code>	<code>{\itshape...}</code>	Text in <i>italic</i> shape
<code>\textsl{...}</code>	<code>{\slshape...}</code>	Text in <i>slanted</i> shape
<code>\textsc{...}</code>	<code>{\scshape...}</code>	Text in SMALL CAPS shape
<code>\emph{...}</code>	<code>{\em...}</code>	Text <i>emphasized</i>
<code>\textnormal{...}</code>	<code>{\normalfont...}</code>	Text in default font

Table 1: Standard font-changing commands and declarations

Many of these commands provide both an used-in-group version and a normal version. Ashley can choose which version to use depend on his needs.

Ashley also wants to learn how to change the color of fonts. He is surprised that this package documentation does not provide such a description. After contacting with the package author, he learns that this topic is not covered because the materials are printed in black and white, so it would be nearly useless to change colors.

4.4 Typing Mathematical Formulae

It comes the most exciting part of Ashley’s work — typing formulae! Even though he had little experience in L^AT_EX before, he already learned that L^AT_EX produces high-quality math formulae, as he previously saw at some sites like Math Stack Exchange (<https://math.stackexchange.com/>) and ZhiHu (<https://www.zhihu.com/>).

Because of his previous experience on these sites, he knows a little bit about how to write formulae in L^AT_EX.

Generally, formulae in L^AT_EX are classified into two types: *inline* and *displayed*. Formulae of the former type are enclosed in a pair of dollar sign: \dots , while formulae of the latter type are enclosed in a pair of double dollar sign:
$$\dots$$
. These delimiters are the original T_EX ones. L^AT_EX provides additionally two pairs of delimiters for inline and displayed math, respectively: $\langle \dots \rangle$

and `\[...\]`. In fact, the \TeX shorthand `$$...$$` for displayed math should be avoided, as it may lead to strange problems in \LaTeX .

As their name suggest, an inline formula is in a line of texts, while a displayed formula is displayed outside of the main texts.

The derivative of a function f can be written as f' , or as

$$\frac{df}{dx}$$

```
The derivative of a function $f$ can
be written as $f'$, or as
\[\frac{df}{dx}\]
```

Here, Ashley uses a command provided by `xjtlumath`: `\frdt`. This command takes two argument, where the first one is optional with the default value f . They represent the function and the variable, respectively. When Ashley wants to typeset the derivative of g to x , he will write `\frdt[g]{x}`, which gives $\frac{dg}{dx}$. The optional argument is passed to the command in the embrace of a pair of two square brackets. As careful as Ashley, you may notice that in inline mode, a formula is shrunk to some extent so that it can fit in one line.

Ashley is quite satisfied with the rendering effect. He then writes some equations and texts. But when he wants to reference a equation, a problem arises. How does he address the equation he wants to reference? Here Ashley is introduced with another way of giving a displayed math: the `equation` environment.

The fundamental theorem of calculus can be expressed in the form of Equation 1

$$\int_a^b f(x) dx = F(b) - F(a) \quad (1)$$

```
The fundamental theorem of calculus can
be expressed in the form of Equation \
ref{eq:fundthmcal}
\begin{equation}
\int_a^b f(x) dx = F(b) - F(a) \label{
eq:fundthmcal}
\end{equation}
```

Ashley understands the equation by his previous knowledge: the underscore (`_`) introduces the subscript (a) to the integral symbol \int (`\int`), while the caret (`^`) introduces the superscript (b) to it. The command `\dx` is provided by `xjtlumath`. If Ashley types `dx` directly, the result will be like this $\int f(x)dx$, which is ugly. `\dx` refines the result. Note that `\dx` can only be used to represent the integral variable, because it adds a little space before it. If Ashley needs to use other variables, he needs to use the command `\dd`. `xjtlumath` also provides the same facility for multiple integrals.

$$\int f(t) \, dt, \quad \iint f(x, y) \, dx \, dy, \quad \iiint f(x, y, z) \, dx \, dy \, dz$$
$$\iint f \, dr \, d\theta, \quad \iiint f \, dz \, dr \, d\theta, \quad \iiint f \, d\rho \, d\theta \, d\phi$$

```

\[\int f(t) \, dt, \quad \int \int f(x,y) \, dx dy, \quad \int \int \int f(x,y,z) \, dx dy dz\]
\[\int \int f \, dr dt, \quad \int \int \int f \, dz dr dt, \quad \int \int \int f \, dr dt dp\]

```

However, Ashley knows nothing about cross-referencing in \LaTeX as well as the equation environment. Let's explain them to Ashley. In \LaTeX , an environment is started by the `\begin` command and ends at the `\end` command. The name of the environment is passed to the pair of commands. The equation environment gives a displayed math equation that is *counted*. The `\label` command at the end of the equation catches the counter as well as some other information like its location and store it in the label represented by the name given to `\label`. To use the label, Ashley needs the `\ref` command, which prints the counter².

The equation environment gives a numbered counted, while \[\] doesn't. Using a label inside this causes the label to be directed to another counter, so use a label only when that thing is counted.

4.5 Space Management

The space management in L^AT_EX is a bit more complex than just typing white spaces. Ashley is a careful person, he soon finds that the space after a sentence is a little bit larger than the space between words (you may zoom in the .pdf file to see this). L^AT_EX decides a space as a space at the end of a sentence if

1. A full stop (.) or right quotation mark (') is immediately followed by the space, and
2. if it is a full stop being followed, the letter immediately before the full stop is in lowercase.

Most sentences end according to the above rules, though there are some exceptions. For example, `\LaTeX` may take a `Mr.` as the sign of a sentence ending, and thus produces wrong spacing. Under such circumstances, Ashley needs to configure `\LaTeX` manually by `~` and `\@`.

In another world, Mr. Ashley was once loved by Miss Scarlett. In this world, Mr. Ashley has a PC. He loves programming on his PC.

In another world, Mr.~Ashley was once loved by Miss Scarlett. In this world, Mr.~Ashley has a PC\@. He loves programming on his PC.

²and in addition generates a clickable hyperlink, which on click navigates to the location of the equation, and which is the effect of the hyperref package loaded by the template.

Ashley is happy as he learned how to manage the spaces. Yet soon he finds another problem.

Some commands like `\LaTeX` seems to eat the space after it.

To solve this problem, Ashley needs to add an empty group (`{ }`) at the end of the command.

As for mathematical formulae, things become different. `\LaTeX` ignores all white spaces in math mode, whether it is inline or displayed. To add extra spaces, Ashley has to use the commands shown in Table 2.

Command	Effect (approximately)
<code>\,</code>	$\frac{3}{18}$ quad (\ll)
<code>\:</code>	$\frac{4}{18}$ quad (\ll)
<code>\;</code>	$\frac{5}{18}$ quad (\ll)
<code>\</code> (<code>\</code> followed by a space)	a space
<code>\quad</code>	Width of 'M' in current font (\ll)
<code>\qquad</code>	2 quad (\ll)

Table 2: Spacing in Math Mode

4.6 Lists and Other Environments

Now Ashley has learned about dealing with texts, he continues his writing. Soon he has to break again as he is working on a list. At first, he hard-codes the list like this:

- | | |
|--------------|--------------|
| 1. Something | 1. Something |
| 2. Something | 2. Something |
| 3. Something | 3. Something |

Yet this solution looks rather silly. In addition, if Ashley wants to change the number, he needs to do it manually. He wonders if `\LaTeX` has some more convenient way to do it.

Fortunately there is. `\LaTeX` provides several environment to deal with lists. One example is shown below.

1. Something
2. Something
3. Something

```
\begin{enumerate}
\item Something
\item Something
\item Something
\end{enumerate}
```

Now Ashley has nearly everything he needs to know. He is content with what he has written and feels happy. The only thing that matters for him is that he wants to show theorems, definitions, and other things in a more fancy fashion so that his readers can focus on these.

xjtlumath provides some fancy environments just for this purpose.

Definition 4.1: Absolute Convergence

An infinite series $\sum_{n=0}^{\infty} a_n$ is said to be absolutely convergent iff

$$\sum_{n=0}^{\infty} |a_n|$$

converges

```
\begin{definition}[Absolute
Convergence]
An infinite series  $\sum_{n=0}^{\infty} a_n$  is said to be absolutely
convergent iff
\[\sum_{n=0}^{\infty} |a_n|
\]
converges
\end{definition}
```

xjtlumath loads amsthm, which gives the proof environment. When Ashley uses this environment to write proofs, he finds that a q.e.d. sign appears at the end of the environment.

Now we prove the mean value theorem for definite integrals. That is, for a continuous function f that is bounded on $[a, b]$, the definite integral $\int_a^b f(x) dx = f(c)(b - a)$, where $c \in [a, b]$.

Proof. Let m, M be the infimum and supremum of $f([a, b])$, respectively. Therefore, $m \leq f \leq M$, and

$$\int_a^b m dx \leq \int_a^b f(x) dx \leq \int_a^b M dx$$

, which gives

$$\begin{aligned} m(b-a) &\leq \int_a^b f(x) dx \leq M(b-a) \\ m &\leq \frac{\int_a^b f(x) dx}{b-a} \leq M \end{aligned} \quad (2)$$

Since that f is continuous, it can reach every value between the infimum and supremum of its range. That is, $\exists c \in [a, b], f(c) = \frac{\int_a^b f(x) dx}{b-a}$. Substitute $f(c)$ back to equation 2 gives what the theorem states. \square

Ashley is able to control where the q.e.d. sign appears by using the `\qedhere` command provided by proof. If this command is given before, then it will not appear at the end.

Proof. Some words...

$$a + b = c$$

Som words...

```
Now we prove the mean value theorem for
definite integrals. That is, for a continuous
function $f$ that is bounded on $[a,b]$, the
definite integral $\int_a^b f(x) \, dx = f(c)(b-
a)$, where $c \in [a,b]$.
\begin{proof}
Let $m,M$ be the infimum and supremum of $f([a
,b])$, respectively.
Therefore, $m \le f \le M$, and
\[\int_a^b m \, dx \le \int_a^b f(x) \, dx \le \int_a^b M \, dx\]
, which gives
\begin{align}
m(b-a) &\le \int_a^b f(x) \, dx \le M(b-a) \\
m &\le \frac{\int_a^b f(x) \, dx}{b-a} \le M
\end{align}
\label{eq:meanvalint}
\end{proof}
```

Since that f is continuous, it can reach every value between the infimum and supremum of its range. That is, $\exists c \in [a,b], f(c) = \frac{\int_a^b f(x) \, dx}{b-a}$. Substitute $f(c)$ back to equation \ref{eq:meanvalint} gives what the theorem states.

```
\begin{proof}
Some words...
\[\[
a+b=c \, \qedhere
\]]
Som words...
\end{proof}
```

Besides of definition and proof, Ashley is also able to use theorem, proposition, corollary, lemma, axiom, and example. Except for proof, these environments own their individual counters, and Ashley can simply use label to reference them.

However, one colleague of Ashley, Chao, complains that the English caption of these environments conflicts with the Chinese material he is writing. For this purpose, `xjtlumath` additionally provides Chinese version environments in replace of them in Chinese materials. Appending a 'c' to the environments' names gives the names of the Chinese version environments.

These facilities greatly help Ashley in his material preparation, and he will finish his work soon...

5 Tutorial 2: Delilah and Complex Math Formulae

Delilah is working on a part of a material about linear algebra. As her work proceeds, she will obtain the ability to deal with complex mathematical formulae in \LaTeX , especially those methods provided by the `ams` packages loaded in `xjtlumath`.

5.1 Multiple Lined Formulae

A system of linear equations is a fundamental part of linear algebra. When Delilah tries to type a group of equations, she encounters a problem. In the predefined `\[\]` and environment `equation`, she finds no option to start a new line. Even the line-break options of \LaTeX like `\\` and `\newline` do not work there. Of course the equations should not be put in one line, so what should she do now? Later she learns that the environment *aligned* is designed to allow a system of equations to be aligned in multiple lines:

$$\begin{aligned} x + y &= 1 \\ x - y &= 2 \end{aligned}$$

```
\[
\begin{aligned}
x+y &= 1\\
x-y &= 2
\end{aligned}
\]
```

Here, the ampersand sign `&` is used before the symbols according to which the equations are to be aligned. The line break sign `\\` starts a new line of equation. Note that other line-break operations cannot be used here.

Delilah likes the result, but she feels that the equations are too lonely. She thinks that adding a large curly bracket for them will comfort them. \LaTeX supports a syntax to put things before and after a group of things.

$$\left\{ \begin{aligned} x + y &= 1 \\ x - y &= 2 \end{aligned} \right.$$

```
\[
\left\{
\begin{aligned}
x+y &= 1\\
x-y &= 2
\end{aligned}
\right.
\]
```

The `\left` command defines what is to be put on the left, and the `\right` command defines what is to be put on the right. Delilah does not want to put anything on the right, so she writes `.` for nothing.

For a group of equations that requires no alignment, or for a single equation that is too long to fit in one line, the environment *gathered* that does no alignment is a better choice:

$$\cos z = 1 - \frac{z^2}{2!} + \frac{z^4}{4!} - \frac{z^6}{6!} + \dots$$

$$= \sum_{n=0}^{\infty} \frac{(-1)^n z^{2n}}{(2n!)}$$

```
\[
\begin{gathered}
\cos {z} = 1 - \frac{z^2}{2!} + \frac{z^4}{4!} - \cdots \\
= \sum_{n=0}^{\infty} \frac{(-1)^n z^{2n}}{(2n!)}
\end{gathered}
\]
```

After writing several groups of equations, Delilah wants to reference one of them. She uses the equation environment instead of `\[\]`, but finds out that the equations are numbered as a whole.

$$\begin{aligned} x + y &= 1 \\ x - y &= 2 \end{aligned} \quad (3)$$

```
\begin{equation}
\begin{aligned}
x+y &= 1 \\
x-y &= 2
\end{aligned}
\end{equation}
```

So it is difficult for her to reference a single equation in a group. `amsmath` provides the environment `align` for this purpose:

$$\begin{aligned} x + y &= 1 \\ x - y &= 2 \end{aligned} \quad \begin{matrix} (4) \\ (5) \end{matrix}$$

```
\begin{align}
x+y &= 1 \\
x-y &= 2
\end{align}
```

If she doesn't want to number a single equation, she needs to append `\nonumber` at the end of that line.

$$\begin{aligned} x + y &= 1 \\ z &= 10 \\ x - y &= 2 \end{aligned} \quad \begin{matrix} (6) \\ \\ (7) \end{matrix}$$

```
\begin{align}
x+y &= 1 \\
z &= 10 \nonumber \\
x-y &= 2
\end{align}
```

Without the “ed” suffix, *gather* is also a standalone environment that does what *gathered* do. But there is a major difference between the normal version and “ed”ed version. Delilah finds it impossible to put the bracket again before a *align* or *gather*, because they don't need to be surrounded by mathematical environments. Also, their width are fixed to be the width of texts, while their “ed”ed versions can be of any width.

As the same as the equation environment, their starred versions give no number by default.

$$\begin{aligned}x + y &= 1 \\x - y &= 2\end{aligned}$$

```
\begin{align*}
x+y &= 1\\
x-y &= 2 \\
\end{align*}
```

Delilah is able to put multiple groups of equations in one align, just by adding ampersands between the groups.

$$\begin{aligned}x + y &= 1 & a + b &= 3 \\x - y &= 2 & a - b &= 4\end{aligned}$$

```
\begin{align*}
x+y &= 1 & a+b &= 3\\
x-y &= 2 & a-b &= 4 \\
\end{align*}
```

The space between the groups is adjusted automatically by align.

5.2 Matrices

Matrices are vital to linear algebra, as they represent linear mappings from a vector space to another in specific bases. Also, the coefficient matrix and the augmented matrix are convenient in operating linear equations.

amsmath provides several environments for typing matrices.

$$\begin{bmatrix}1 & 2 & 3 & 4 \\ 5 & 6 & 7 & 8 \\ 9 & 10 & 11 & 12 \\ 13 & 14 & 15 & 16\end{bmatrix}$$

```
\[
\begin{bmatrix}
1&2&3&4\\
5&6&7&8\\
9&10&11&12\\
13&14&15&16
\end{bmatrix}
\end{bmatrix}
```

The environments pmatrix, Bmatrix, vmatrix, and Vmatrix produce delimiters of $()$, $\{ \}$, $| |$, and $| | \quad | |$, respectively.

To use matrices in inline mode, Delilah uses the environment smallmatrix, which has no p,b,B,v,V versions in amsmath, as it is the author's responsibility to decide the delimiters.

The matrix $\begin{pmatrix} a & b \\ c & d \end{pmatrix}$ is so small and cute!

```
The matrix  $\left(\begin{smallmatrix} a&b \\ c&d \end{smallmatrix}\right)$  is so small and cute!
```

When Delilah tries to put fractions inside a matrix, she finds something annoying.

$$\begin{bmatrix} 1 & \frac{1}{2} & \frac{1}{3} \\ 1 & \frac{1}{4} & \frac{1}{5} \end{bmatrix}$$

```
\[
\begin{bmatrix}
1&\frac{1}{2}&\frac{1}{3}\\
1&\frac{1}{4}&\frac{1}{5}
\end{bmatrix}
\]
```

The fractions above and below are so close that they touch each other! This is not what Delilah wants and she is surprised that L^AT_EX doesn't detect this and do something. Fortunately, in amsmath environments, an optional argument is allowed to be passed to `\` to define the actual vertical space between lines. For fractions, `2ex` is a good option. Also, the fractions are in inline mode. The `\dfrac` command gives displayed fractions.

$$\begin{bmatrix} 1 & \frac{1}{2} & \frac{1}{3} \\ 1 & \frac{1}{4} & \frac{1}{5} \end{bmatrix}$$

```
\[
\begin{bmatrix}
1&\dfrac{1}{2}&\dfrac{1}{3}\\
1&\dfrac{1}{4}&\dfrac{1}{5}
\end{bmatrix}
\]
```

Sometimes a matrix is too large to be displayed fully. At these times, the use of ellipses (plural of ellipsis, not ellipse) is important. When Delilah writes the inverse of a matrix, she uses ellipses.

$$A^{-1} = \frac{1}{\det A} \begin{bmatrix} C_{11} & C_{21} & \cdots & C_{n1} \\ C_{12} & C_{22} & \cdots & C_{n2} \\ \vdots & \vdots & \ddots & \vdots \\ C_{n2} & C_{n2} & \cdots & C_{nn} \end{bmatrix}$$

```
\[
A^{-1} = \frac{1}{\det A}
\begin{bmatrix}
C_{11} & C_{21} & \cdots & C_{n1} \\
C_{12} & C_{22} & \cdots & C_{n2} \\
\vdots & \vdots & \ddots & \vdots \\
C_{n2} & C_{n2} & \cdots & C_{nn}
\end{bmatrix}
\]
```

5.3 Texts and Operator Names

To put text inside math environments, Delilah uses the `\text` command provided by amsmath.

Definition 5.1: Null Space

The null space of an $m \times n$ matrix A , written as $\text{Nul } A$, is the set of all solutions of the homogeneous equation $A\mathbf{x} = \mathbf{0}$. In set notation,

$$\text{Nul } A = \{\mathbf{x} : \mathbf{x} \text{ is in } \mathbb{R}^n \text{ and } A\mathbf{x} = \mathbf{0}\}$$

```
\begin{definition}[Null Space]
The null space of an  $m \times n$ 
matrix  $A$ , written as  $\text{Nul } A$ , is
the set of all solutions
of the homogeneous equation  $A\mathbf{vec}\{
\mathbf{x}\} = \mathbf{vec}\{0\}$ . In set notation,
\[\text{Nul } A = \{\mathbf{vec}\{x\} : \mathbf{vec}\{x\} \text{ \textit{is in } } \mathbb{R}^n \text{ \textit{and } } A\mathbf{vec}\{x\} = \mathbf{vec}\{0\} \}
\end{definition}
```

The commands like `\Nul`, `\sin`, ... are math operators. Part of predefined math operators in \LaTeX are shown in Table 3.

Result	Command	Result	Command	Result	Command
\arccos	<code>\arccos</code>	\arcsin	<code>\arcsin</code>	\arctan	<code>\arctan</code>
\cos	<code>\cos</code>	\sin	<code>\sin</code>	\tan	<code>\tan</code>
\cot	<code>\cot</code>	\sec	<code>\sec</code>	\csc	<code>\csc</code>
\cosh	<code>\cosh</code>	\sinh	<code>\sinh</code>	\tanh	<code>\tanh</code>
\lim	<code>\lim</code>	\liminf	<code>\liminf</code>	\limsup	<code>\limsup</code>
\ln	<code>\ln</code>	\log	<code>\log</code>	\lg	<code>\lg</code>
\max	<code>\max</code>	\min	<code>\min</code>	\sup	<code>\sup</code>
\inf	<code>\inf</code>				
\ker	<code>\ker</code>	\det	<code>\det</code>	\exp	<code>\exp</code>

Table 3: Some Predefined Math Operators

In fact, operator `\Nul` and `\Span` are defined by `xjtlumath` as in the forms in the year 1 linear algebra textbook of XJTLU. Also, `xjtlumath` changes the default `\vec` command in \LaTeX so that vectors appear in bold form rather than with a arrow above them.

Some operators, like `\lim`, are designed to support taking limits. That is, in displayed mode, when one tries to give one of such operators a subscript using `_`, the subscript will appear at the bottom of the operator.

$$\lim_{x \rightarrow 0} f(x)$$

```
\[
\lim_{x \to 0} f(x)
\]
```

Delilah is able to explicitly control the limit style by using `\limits` and `\nolimits`. Note that these two commands can only be used after a operation that supports taking limits.

$$\lim_{x \rightarrow 0} f(x)$$

$$\lim_{x \rightarrow 0} f(x)$$

```
$\lim\limits_{x \to 0} f(x)$
\[
\lim\limits_{x \to 0} f(x)
\]
```

5.4 Delimiters

Delilah already knows how to type basic delimiters. For parentheses and square brackets, plain text will do; and since the curly brackets are reserved by \LaTeX , Delilah needs to add a backslash before each of them.

The range of a function may be expressed explicitly by its domain and itself: the range of $f : X \rightarrow Y$ is $f(X)$.

In some context the arguments of a function are enclosed by square brackets: $f[x]$.

Curly brackets are often used to show a set: $S := \{2, 4, \dots\}$.

The range of a function may be expressed explicitly by its domain and itself: the range of $f : X \rightarrow Y$ is $f(X)$.

In some context the arguments of a function are enclosed by square brackets: $f[x]$.

Curly brackets are often used to show a set: $S := \{2, 4, \dots\}$.

Yet in some conditions where the expression being enclosed has a different height, the result becomes unsatisfactory. \LaTeX provides a mechanism to enable the user to automatically or manually adjust the size of delimiters.

Adding `\left` and `\right` around a pair of delimiters automatically adjust their size to match the expression being enclosed. However, sometimes we want the delimiters to be a bit bigger or smaller, and that's when we need to manually adjust the size.

$$\left(\frac{1}{2}\right)\left(\left(\left((x)\right)\right)\right)$$

```
\[
\left(\frac{1}{2}\right)\Big(\big(\big(\big(x\big)\big)\big)\Big)
\]
```

Delilah once mismatched a pair of delimiters, but she found that the height of the two symbols are still the same. She learns in addition that the dot ‘`.`’ can be used to inform \LaTeX to insert nothing.

$$\mathbb{R} \quad \mathbb{Q} \quad \mathbb{Z} \quad \mathbb{N} \quad \mathbb{N}^+$$

```
\[
\setr \quad \quad \setq \quad \quad \setz \quad \quad \setn \quad
\quad \quad \setnp
\]
```

Other font controlling methods are like what we have talked about in subsection 4.3. For example, `\mathrm` gives font in Roman family, and `\mathbf` gives font in **bold** series.

$$\text{Like normal text} \quad \mathbf{bold}$$

```
\[
\mathrm{Like normal text} \quad \quad \mathbf{bold}
\]
```

6 Tutorial 3: Yue Handling Floats

Yue is preparing her material for the monthly of math club. She wants to make her material interesting and easy to understand, so she utilizes many figures and tables.

Figures, tables and many other things that occupy an (often large) area of random width and height are treated as *floats* in \LaTeX . Floats are common in today's documents, yet they cause great troubles in typesetting. In this section, we will work along with Yue to see how floats are handled in \LaTeX .

6.1 Inserting Images

To insert images in \LaTeX , package `graphicx` (loaded by the template files) is a good option. It provides the `\includegraphics` that accepts the input image filename and some optional specifiers.



```
\includegraphics[width=\textwidth]{assets/
examplelogo.jpg}
```

Yue soon finds out that simply using this command is not a good option, because if there is not enough vertical space for the image, it will be placed on the next page, leaving a large vacant area, which is quite ugly. Also, she is unable to provide the image with a caption or to reference it.

So, Yue wraps the image with the figure environment that makes the image a *figure*.



Figure 1: Example Logo

```
\begin{figure}
\includegraphics[width=\textwidth]{assets/
examplelogo.jpg}
\caption{Example Logo}
\label{fig:example}
\end{figure}
Figure \ref{fig:example} shows the figure Yue
uses.
```

Figure 1 shows the figure Yue uses.

\LaTeX automatically gives a number to it so that Yue is able to reference it. Note that due to implementation reasons, `\label` should only be placed immediately after a `\caption` lest the reference be wrong.

6.2 Tables

Even if using figures does require an extra environment, it is still quite simple and Yue soon becomes familiar with it. Dealing with tables, however, is more complex in \LaTeX .

To generate a table-like content in \LaTeX , Yue has to use special environments. `tabular` and `array` are two specific examples of them. In fact, the two

environments are alike in most of the aspects, with one major difference being that array is often used in math mode.

The syntax of array and tabular resembles the one of matrix environments used by Delilah, though here Yue has to explicitly specify the column behavior.

Entry 1	Entry 2
a	b

```
\begin{tabular}{|c|c|}
\hline
Entry 1 & Entry 2\\
\hline
a & b\\
\hline
\end{tabular}
```

Yue doesn't quite understand what `|c|c|` means, so she searches on the Internet for this. It tells her that this argument passed to `tabular` specifies each column. The letter `c` tells `tabular` that the contents in this column should be centered. And two other alignment specifier `l` and `r` are available for "left" and "right", respectively. The vertical bar indicates that at this place a vertical line should be inserted (c.f. The `\hline` command that instructs a horizontal line to be inserted at the top of the current row)

The width of a column is determined by the width of the contents when either `c`, `l`, and `r` is given. Yue is able to control the width of a column by using another specifier "p", in which the content is left-aligned.

Entry 1	Entry 2
a	b

```
\begin{tabular}{|c|p{2cm}|}
\hline
Entry 1 & Entry 2\\
\hline
a & b\\
\hline
\end{tabular}
```

When there is many columns with the same specifier, Yue can use this syntax `*{num}{spe}` to repeat the specifiers, where `num` is the number of repetitions, and `spe` is the specifier.

a	a	a	a	a	a	a
a	a	a	a	a	a	a

```
\begin{tabular}{|*{7}{c}|}
\hline
a&a&a&a&a&a&a\\
\hline
a&a&a&a&a&a&a\\
\hline
\end{tabular}
```

Yue doesn't like line-separated tables because she considers them not tidy. She wants to use space to separate contents. She can use `@{\hspace{}}{}` between column specifiers to specify the inter-column space and use `\vspace{}`

6.3 Placement of Floats

Yue used to use Microsoft Word, which places floats wherever the user wants to place it at. Everything had been fine since she had turned to \LaTeX for some time, but now Yue has a problem. A figure “disappeared” from the output. After checking her code and the output again and again, she accidentally finds that the figure appears in the next page. This really confuses her. Due to the internal algorithm of \TeX , it is technically impossible to arrange every float at where the user wants to place them. According to *the \LaTeX Companion*,

“Floats are often problematic in the present version of \LaTeX , because the system was developed at a time when documents contained considerably less graphical material than they do today.”

Yet \LaTeX does give some option to allow the Yue to control the placement of a float to some extent. For a figure or table environment, Yue is able to pass to it an optional argument that specify the desired placement. There are five placement specifiers and they can be combined together in any order.

! Ignores some \LaTeX limitation³ when trying to place the float.

h Tries to place the float exactly at where the the environment is issued. If the attempt fails and no other specifier other than **!** is given, the specifier will be changed to **t**.

t Tries to place the float at the top of the page.

b Tries to place the float at the bottom of the page.

p Tries to place the float at a float page (a page that is generated by \LaTeX to place floats)

\LaTeX tries to place a float according to the specifiers in the order of the above list from the top to the bottom. Generally all floats of a document can be handled properly. But should a float proves impossible to handle, the author should adjust (probably reduce) its width and height.

6.4 Table of Floats

As mentioned at the beginning, in Yue’s material, there are many floats. She wonders if there is a way to provide a quick reference to them.

Like `\tableofcontents`, \LaTeX provides the following two commands to print a list of all figures and a list of all tables used in a document, respectively.

`\listoffigures` and `\listoftables`

The name of a float that appears on the list is defined by the caption of the float. If the captions appears to be too long, Yue can pass to caption an optional argument that will instead be shown on the list. Also, don’t forget to compile the file at least twice for the lists to show properly.

³ \LaTeX has some limitations when it tries to place floats. For example, if the height of a float is larger than a degree of page height, then it cannot be placed at the bottom of a page.

6.5 A Suggestion About Images

Yue is suggested to use vector graph for images, as vector graph is lossless when the image is scaled along with the output file.

There are several packages that enables drawing images directly in \LaTeX , yet they all require great efforts. It is suggested to use modern tools to generate appropriate images (e.g. Mathematica is able to export the math plots drawn.).

To give a resolution about what noting style is to be used, ZiYou suggests that they play Tic Tac Toe, and Abigail thinks this is a good idea. After a few minutes, Abigail narrowly wins the game. ZiYou jokes that maybe she should let him win the next time, whereupon Abigail smilingly replies, “That remains to be seen”. Nevertheless, she has a dim feeling that ZiYou deliberately lets her be the winner, but can’t prove it from ZiYou’s regretful expression.

7.2 Merging Works Of The Team

ZiYou and Abigail only need to collect the `chapter.tex` from the team members. They rename the files according to each person in a way that they can easily identify who is responsible for each file. After that, they input each file into the `chapter.tex` of an empty template. The final output can then be generated from the `encapsulation.tex` of the template.

Directly copying the contents is not a good option for inputting the files. ZiYou is about to search this on the Internet when Abigail discovers in the `encapsulation.tex` that the `chapter.tex` is directed into this file by the command `\input`. The following code shows what is written in `encapsulation.tex`.

```
\input{chapter.tex}
```

The argument passed to this command is the relative path of the target file. Abigail doesn't know what the term relative path means, so ZiYou, who has certain knowledge in computer science, explains to her that, the relative directory is the path of a file relative to the file in which the path is used. In this example, the file in which the relative directory is used is `encapsulation.tex`, and as a consequence of the two files being in the same folder, the relative directory of the `chapter.tex` is simply its name. If ZiYou and Abigail decide to put the files of the team members into a folder named `Files` for organization, then the directory should contain the folder's name plus a `/` or `\`, depending on the file system, at the beginning. Since that `\` is a keyword in `LATEX`, they should use `/`.

Not until they have completed the inputting had ZiYou had a glimpse at the search result on the Internet, where he finds another command, `\include`. After seeing this webpage in detail, he then tells Abigail that `\include` is a better choice here, for it somehow improves the compilation speed. Abigail has no clue about what compilation is and isn't interested in such technical stuffs, but she trusts ZiYou. She also kind of likes it when ZiYou, patiently and tenderly, explains what she doesn't understand to her. So she pretends to be curious and asks ZiYou to explain compilation to her.

So the final form of their `chapters.tex` is like this:

```
\include{Files/The first file}  
  
\include{Files/The second file}  
  
\include{Files/The third file}  
...
```

Note that the file extension (`.tex`) is not allowed to be used in `\include`, while it can be used in `\input`. Also, they have to make sure that the team members have not taken advantage of `\include`, as it cannot be used in a file that is included by another. Fortunately, they can ascertain it since none of them knows about the command.

7.3 Background, Headers, and Footers

ZiYou and Abigail notice that the template for materials automatically adds the background, and the header and footer for each page. The `encapsulation.tex` loads the package `background` for background, and the package `fancyhdr` for headers and footers.

The headers and footers are set in the `encapsulation.tex` by the following code: (A line begins with a `%` is *commented*, so it will have no effect on the output .pdf file.)

```
% Define the header and footer for pages.

% Place the number of the current page.
\fancyhead[LEH,ROH]{\bfseries\thepage}

% Beautify the display of chapter and section marks.
\renewcommand{\chaptermark}[1]{%
\markboth{#1}{} }
\renewcommand{\sectionmark}[1]{%
\markright{\thesection\ #1}}

\fancyhead[LOH]{\bfseries\rightmark}
\fancyhead[REH]{\bfseries\leftmark}

% Add copyright in the footer
\fancyfoot[COF,CEF]{\bfseries\copyright{} The XJTLU Math Club
— All rights reserved}
```

The header is controlled by the command `\fancyhead` and the footer is controlled by the command `\fancyfoot`. By inspecting the optional arguments, ZiYou makes a guess that L and R represent left and right, E and O represent even and odd (page number), and H and F represent header and footer, respectively. A look into the documentation of `fancyhdr` confirms this. He asks Abigail if she likes the page style. Abigail thinks that the author has a good taste, so they decide not to change this.

The background is set to the logo of math club. In fact, adding this graph somehow makes the document ugly, and even I didn't understand why this must be added to all materials. The head of the department at that time told me that this is a defense for those who use the materials in a prohibited way.

I really hope that this environment can improve to a state that even the materials are distributed by the most free licenses, there will be no one to steal our intelligent property.

7.4 Index And Bibliography

ZiYou and Abigail would like to listen to the readers' opinions about the previous materials so that they can refine the coming one according to them. A few number of the readers pointed out that it took them a lot of efforts to find

specific terms in the materials and they would appreciate it if a list of important terms is added.

Abigail recalls that once when she tried to find something in a calculus textbook's appendix, she flipped the pages too much and turned to a section called Index, where terms are listed according to their pages. So ZiYou makes a search on the Internet and found that Indexing in L^AT_EX can be easily done by a few commands.

First, for any important terms that they want to list in the Index page, they mark it with the command `\index`. To print the Index page, the command `\printindex` needs to be called, and before the document environment the command `\makeindex` should be called. In the `encapsulation.tex`, simply uncomment the relating lines of code to do that. Finally, for the Index page to be printed, they have to, first, run L^AT_EX once on `encapsulation.tex`, then, run `MakeIndex` once on the file, and finally, run L^AT_EX twice on the file. The following example show the result of using Index.

Index

limit, vi, 3
derivative, 3-5

```
% At page vi
\index{limit}
% At page 3
\index{limit}
\index{derivative}
% At page 4
\index{derivative}
% At page 5
\index{derivative}
```

ZiYou makes definite integral and indefinite integral two separate index entries, while Abigail argues that they should be under the same term integral. To use subterms, the following syntax should be applied.

Index

integral, 5
 definite integral, 11
 indefinite integral, 7

```
% At page 5
\index{integral}
% At page 7
\index{integral!definite integral}
% At page 11
\index{integral!indefinite integral}
```

Abigail remembers that for the sake of academic integrity, they should add reference for each work of other people. B^IB_T_EX is a good tool handling references (bibliographies). To use this tool, they have to prepare a B^IB_T_EX database. This is a file with the extension `.bib`, in which entries are contained. Filling in the entries is a tedious work, but fortunately most academic websites provides the facility to allow an user to directly download a `.bib` file for the source he wants to use. The following code shows a typical database entry:

```
@article{may1979alpha,
  title="Alpha-particle-induced soft errors in dynamic
  memories",
```

```

    author="T.C. {May} and M.H. {Woods}",
    journal="IEEE Transactions on Electron Devices",
    ...
}

```

ZiYou and Abigail need not to worry about the details in the entry. The only thing they need to remember is the label of the entry, the one immediately after the `{`, because it is to be used in the `\cite` command to produce a reference to that source. Each source that is referenced in the document appears in the Bibliography page, which is controlled by the two following commands:

```

\bibliography{file-list}
\bibliographystyle{style}

```

, where `file-list` is a list of database files, and `style` is the bibliography style according to which the bibliography is to be printed. https://www.overleaf.com/learn/latex/Bibtex_bibliography_styles shows all predefined BibTeX styles.

7.5 Twosided printing

Now ZiYou and Abigail have finished combining the separate documents and are planning a break after the work, but there is something more waiting for them.

By default, when the documentclass is `book`, L^AT_EX uses twosided printing. At first ZiYou and Abigail didn't notice this (they didn't know) until Abigail saw that the pages of the output are not aligned. That is, at one page the content sticks out to the left and at the next page the content sticks out to the right. Abigail doesn't want to trouble ZiYou again, so she makes a search herself and finds that this is what is called twoside, which is used particularly for books.

Abigail tries to comprehend this by opening a book and inspecting its layout. She notices that a portion of the inner part⁴ of the pages are stuck together to keep them form a book. She guesses that twoside leaves extra spaces for each page at the inner part. The result, however, contradicts with her instinct. On twoside mode, L^AT_EX shrinks the inner part of each page. This is because L^AT_EX wants to give more space for the margins that reside on the outer parts.

ZiYou learns this from Abigail so they start another review for it. They soon find a problem. For table of contents and some other pages like preface, the template uses roman numbering. For the main text, the page numbering is changed to arabic. The layout of a page, however, is not decided by if it will appear on the left or right. Rather, it is entirely decided by the number of the page. If, say, the roman number ends at *iii*, then when the arabic number starts at 1, the corresponding page will appear on the left, which is a disaster. To solve this problem, ZiYou finds the command `\cleardoublepage` that is designed for

⁴When one opens a book, the first page appearing on the right is numbered 1, and all odd pages appears on the right side have odd numbers as a consequence.

twoside mode. It ensures that the content after the command will appear at a page on the right by (possibly) adding a new page. The new page would be empty, of course. But Abigail thinks that a reader may misinterpret this as a sign of a printing failure. To explicitly identify this behavior, in `xjtlumath` (in precise, the subpackage `xjtlumaterial` loaded by the template), the command is renewed to add the sentence “This page is intentionally left blank” at each empty page this command adds.

7.6 An End Of Their Story

The very story of ZiYou and Abigail about their material writing comes to an end, yet as said in one old saying, “An end is also a beginning,” their other stories just begin. Abigail admires ZiYou’s broad knowledge in computer science and enjoys it when ZiYou teaches her about it. ZiYou also is inspired by Abigail’s energy, particularly in the working. He feels lucky to find such a girl as interesting and beautiful as Abigail, whose humor has made ZiYou laughing several times.

So the two ordered seats in a romantic restaurant to celebrate their collaboration, while I, sitting alone in my dormitory, work hard to complete this documentation. Nevertheless, I hope you, the members of the math club in the future, can find not only knowledge and experience, but also love as ZiYou and Abigail do, except not in an imaginary story.

8 Tutorial 5: Raúl Typesetting An Exam Paper

One task of the department is to elucidate the past exam papers of those math courses. In this tutorial, we will see how Raúl takes advantage of the package `xjtluexam` to typeset an exam paper.

8.1 The `exampaper` Environment

To begin an exam paper, Raúl uses the `exampaper` environment. The environment itself gives no output, but provides several commands⁵.

Then, Raúl types `\question` to start a question.

1. Justify whether $\sum_{n=1}^{\infty} a_n$ converges or not when $a_n \rightarrow 0$.

2. Evaluate

$$\int x^5 e^{x^2} dx$$

```
\begin{exampaper}
\question Justify whether  $\sum_{n=1}^{\infty} a_n$  converges or not if  $a_n \rightarrow 0$ .
\question Evaluate
\begin{mathdisplay}
\int x^5 e^{x^2} dx
\end{mathdisplay}
\end{exampaper}
```

The question counter can be referenced normally.

1. Justify whether $\sum_{n=1}^{\infty} a_n$ converges or not when $a_n \rightarrow 0$.

2. Evaluate

$$\int x^5 e^{x^2} dx$$

A solution to Question 2 is ...

```
\begin{exampaper}
\question Justify whether  $\sum_{n=1}^{\infty} a_n$  converges or not when  $a_n \rightarrow 0$ .
\question \label{ques:examques} Evaluate
\begin{mathdisplay}
\int x^5 e^{x^2} dx
\end{mathdisplay}
\end{exampaper}
A solution to Question \ref{ques:examques} is ...
```

Subquestions may be given, and the numbering for them is alphabetical.

1. Given the function $f = \dots$
 - (a) Evaluate $f(3)$
 - (b) Prove a proposition about f .

```
\begin{exampaper}
\question Given the function  $f = \dots$ 
\subquestion Evaluate  $f(3)$ 
\subquestion Prove a proposition about  $f$ .
\end{exampaper}
```

⁵In fact, the commands are not *provided* by this environment. It merely does some initialization works so that these commands can function normally.

8.2 Multiple Choice Questions

Multiple choice questions (MCQs) appear in exam papers quite often. xjtluexam package designs several environments and commands just for them.

To introduce the choices of a MCQ, Raúl begins a choice environment. There are two choice environments: *shortchoices* and *longchoices*. As their name suggest, they are used to introduce short choices (multiple choices are in one line) and long choices (one choice occupies one line), respectively.

Inside one of the environments, a choice number is given by the `\choicenumber` command. The space after a choice is given by the command `\choicespace`. Raúl doesn't want a space at the end of the last choice, so he only uses the command between choices.

1. Evaluate

$$\int_{-1}^1 x^2 \cosh x \, dx$$

- A $\frac{2 \sinh 1}{3}$ B $-\frac{2 \sinh 1}{3}$ C $\frac{2 \cosh 1}{3}$ D $-\frac{2 \cosh 1}{3}$

```
\begin{exampaper}
\question Evaluate
\[ \int_{-1}^1 x^2 \cosh x \, dx ]
\begin{shortchoices}
\choicenumber $\frac{2 \sinh 1}{3}$
\choicespace \choicenumber $-\frac{2 \sinh 1}{3}$
\choicespace \choicenumber $\frac{2 \cosh 1}{3}$
\choicespace \choicenumber $-\frac{2 \cosh 1}{3}$
\end{shortchoices}
\end{exampaper}
```

If Raúl feels that the space is too tight, he can freely break the lines

1. Evaluate

$$\int_{-1}^1 x^2 \cosh x \, dx$$

- A $\frac{2 \sinh 1}{3}$ B $-\frac{2 \sinh 1}{3}$
C $\frac{2 \cosh 1}{3}$ D $-\frac{2 \cosh 1}{3}$

```
\begin{exampaper}
\question Evaluate
\[ \int_{-1}^1 x^2 \cosh x \, dx ]
\begin{shortchoices}%
\choicenumber $\frac{2 \sinh 1}{3}$ \choicespace
\choicenumber $-\frac{2 \sinh 1}{3}$ \choicespace
\choicenumber $\frac{2 \cosh 1}{3}$ \choicespace
\choicenumber $-\frac{2 \cosh 1}{3}$ %
\end{shortchoices}
\end{exampaper}
```

Here, Raúl uses the comment sign `%` to eliminate the line break character, which would be treated as a white space by \LaTeX if not removed.

For *longchoices* environment, the usage is similar, except that Raúl doesn't need to care about the line breaks, as one choice itself begins a new line at its end.

1. Which of the following functions satisfy Laplace's Equation

$$\frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2} = 0$$

- A $f(x, y) := x^3y - xy^3$
 B $f(x, y) := \log(4x^2 + 4y^2)$
 C $f(x, y) := 3x^4y^5 - 2x^2y^3$
 D $f(x, y) := \cos(2x^2 - 2y^2)$

```
\begin{exampaper}
\question Which of the following functions
satisfy Laplace's Equation
\[\frpdt[2 f]{x^2} + \frpdt[2 f]{y^2} = 0\]
\begin{longchoices}%
\choicenumber $f(x,y):=x^3y-xy^3$\choicespace%
\choicenumber $f(x,y):=\log\{(4x^2+4y^2)\}$\
choicespace%
\choicenumber $f(x,y):=3x^4y^5-2x^2y^3$\
choicespace%
\choicenumber $f(x,y):=\cos\{(2x^2-2y^2)\}$%
\end{longchoices}
\end{exampaper}
```

8.3 Space And Rules

It is conventional to leave a vertical space after a comprehensive question is given. To add a certain amount of vertical space, Raúl uses command `\vspace`.

1. Find ...

```
\question Find ...
\vspace{.8cm}
\question Prove ...
```

2. Prove ...

He is quite satisfied with this result, though he wonders how to evenly distribute questions on a page. The command `\stretch`, when used in `\vspace`, gives a space with respect to the number given to it. For example, if Raúl wants to place three questions evenly on a page, he writes:

1. Find ...

```
\question Find ...
\vspace{\stretch{1}}
\question Prove ...
\vspace{\stretch{1}}
\question Evaluate ...
```

2. Prove ...

3. Evaluate ...

The number can be changed for a relatively larger space. For example, if Raúl writes

```
\question Find ...
\vspace{\stretch{2}}
\question Prove ...
\vspace{\stretch{1}}
\question Evaluate ...
```

, then the empty space left will be evenly divided into $2 + 1 = 3$ pieces. Two of them are given to the place where `\stretch{2}` is given, and the other one is given to the place where `\stretch{1}` is given.

To create questions that require a student to fill in the blanks, Raúl has to draw the blanks, that is, to draw a line under each of the blanks. In \LaTeX , a horizontal line can be drawn by the command

`\rule[lift]{width}{height}`

, where lift is with respect to the baseline.

To simplify the work, `xjtluexam` provides the command `\blankline` to draw a line with a given width (default 1cm).

1. $(3\mathbf{i} - 9\mathbf{j}) \times (2\mathbf{i} + 1\mathbf{j}) = \underline{\hspace{2cm}}$
2. $\frac{d \cos^2 x \sin x}{dx} = \underline{\hspace{2cm}}$

```
\begin{exampaper}
\question  $(3\mathbf{vec{i}}-9\mathbf{vec{j}}) \times (2\mathbf{vec{i}}+1\mathbf{vec{j}}) =$   $\blankline$ 
\question  $\frac{d \cos^2 x \sin x}{dx} =$   $\blankline[1.5cm]$ 
\end{exampaper}
```

Now Raúl has everything he needs to know, and an exam paper will be ready soon...

Part III

Templates

This part describes all templates given. They are inside the folder `Templates`.

9 For Material Use

In this section all templates are made for writing materials. They are inside the folder `For Materials`.

9.1 Book in English

The folder `Book_en-us` gives the template for writing a material in English that is to be published as a book. Long materials should be prepared in the form of this template. It loads all `xjtlumath` packages so all functionalities provided by this package are available.

At the beginning of the environment document, page numbering is changed to roman, page style is set to plain and the table of contents is given. You may add a title page before this. Also, other prefaces like acknowledge and dedication should be included here.

Then there begins the main text, where page numbering is arabic and the style is fancy, which is defined by several previous `fancyhdr` commands.

At the end of the document environment, you may uncomment some commands to use index and bibliography (One command is required at the beginning for index).

9.2 Book in Chinese

The folder `Book_zh-cn` gives the template for writing a material in Chinese that is to be published as a book. It is the same as the previous one except that the `documentclass` is `ctexbook` provided by package `ctex` for Chinese styles.

9.3 Article in English

The folder `Article_en-us` gives the template for writing a material in English that is to be published as an article. Materials of moderate size should be prepared in the form of this template. It loads all `xjtlumath` packages so all functionalities provided by this package are available.

It is similar to the template for English books, except that some options for `twoside` are adjusted to fit `oneside`.

9.4 Article in Chinese

The folder `Article_zh-cn` gives the template for writing a material in Chinese that is to be published as an article. It is the same as the previous one except that the documentclass is `ctexart` provided by package `ctex` for Chinese styles.

10 For General Use

In this section all templates are made for general use. They are inside the folder `General Use`.

Currently they are the same as the templates for materials, except that they don't load the package `xjtlumaterial` and don't have some styles.

Part IV

Internal Documentation

This part is the internal documentation for xjtlumath. It is automatically generated by the tool doc. This part is for the maintenance of the package and is not recommended to be read by the general users of the package unless they want to know the implementation details about the package.

11 Package xjtlubase

This packages is the base for some components of xjtlumath. <*base>

```
\ProvidesPackage{xjtlubase}[2021 by Guanyuming He]
\NeedsTeXFormat{LaTeX2e}
```

```
\RequirePackage{ifthen}
```

`englishorchinese` This boolean is used for determine if the document is writing in English or in Chinese. True for English, false for Chinese. The default value is true.

```
\newboolean{englishorchinese}
\setboolean{englishorchinese}{true}
```

</base>

12 Package xjtlumathtbm

This package defines the thm environments. <*thm>

```
\ProvidesPackage{xjtlumathtbm}[2021 by Guanyuming He]
\NeedsTeXFormat{LaTeX2e}
```

```
\RequirePackage{xjtlubase}
\RequirePackage{amsthm}
\RequirePackage[framemethod=TikZ]{mdframed}
```

```
\mdfsetup{nobreak=false}
```

These counters are used for the thm environments.

```
\newcounter{thmcnt}[section]
\newcounter{deficnt}[section]
\newcounter{lemmacnt}[section]
\newcounter{propcnt}[section]
\newcounter{corocnt}[section]
\newcounter{axiomcnt}[section]
\newcounter{examcnt}[section]
```

`\newmdthmenv` This command is used to create thm environments using package mdframed.


```

\newcommand{\newmdthmenv}[3]{%
% #1 caption
\newenvironment{#1}[1][]{%
\stepcounter{#2}%
\ifstrempy{#1}%
{%
\mdfsetup{%
frametitle={%
\tikz[baseline=(current bounding box.east),outer sep=0pt]%
\node[anchor=east,rectangle,fill=blue!20]
{\strut #3~\thesection.\arabic{#2}};}}
}%
}%
{
\mdfsetup{%
frametitle={%
\tikz[baseline=(current bounding box.east),outer sep=0pt]%
\node[anchor=east,rectangle,fill=blue!20]
{\strut #3~\thesection.\arabic{#2}:~##1};}}
}
}
\mdfsetup{innertopmargin=0,linecolor=blue!20,linewidth=2pt,topline=true,frametitleaboveskip=-1em}
\begin{mdframed}[]\relax%
}%
{%
\end{mdframed}
}%
}

```

Definition of the thm environments

```

\newmdthmenv{theorem}{thmcnt}{Theorem}
\newmdthmenv{proposition}{procnt}{Proposition}
\newmdthmenv{corollary}{corocnt}{Corollary}
\newmdthmenv{lemma}{lemmacnt}{Lemma}
\newmdthmenv{definition}{deficnt}{Definition}
\newmdthmenv{axiom}{axiomcnt}{Axiom}
\newmdthmenv{example}{examcnt}{Example}

</thm>

```

13 Package xjtlumathstyle

This package defines new math styles and refines some existing ones. <*style>

```

\ProvidesPackage{xjtlumathstyle}[2021 by Guanyuming He]
\NeedsTeXFormat{LaTeX2e}

\RequirePackage{xjtlubase}
\RequirePackage{amsmath}
\RequirePackage{amssymb}

```

Improved 'd' in integrals

```
\newcommand{\dd}{\ensuremath{\mathrm{d}}}
\newcommand{\dx}{\ensuremath{\mathrm{d} x}}
```

New name for nabla in gradients

```
\newcommand{\grad}{\ensuremath{\nabla}}
```

Simplify writing FRactional DerivaTives (1 function 2 variable)

```
\newcommand{\frdt}[2][f]{\ensuremath{\frac{\mathrm{d}\#1}{\mathrm{d}\#2}}}
\newcommand{\frpdt}[2][f]{\ensuremath{\frac{\partial \#1}{\partial \#2}}}
```

Infinite series (1: sequence 2: subscript 3: starting count)

```
\newcommand{\infseries}[3][a]{\ensuremath{\sum_{\#2=\#3}^{\infty}\#1_{\#2}}}
```

Multiple integrals

```
\newcommand{\dxdy}{\ensuremath{\mathrm{d} x \mathrm{d} y}}
\newcommand{\dxdydz}{\ensuremath{\mathrm{d} x \mathrm{d} y \mathrm{d} z}}
```

Polar coordinates

```
\newcommand{\drdt}{\ensuremath{\mathrm{d} r \mathrm{d} \theta}}
```

Cylindrical

```
\newcommand{\dzdrdt}{\ensuremath{\mathrm{d} z \mathrm{d} r \mathrm{d} \theta}}
```

Spherical

```
\newcommand{\drdt dp}{\ensuremath{\mathrm{d} \rho \mathrm{d} \theta \mathrm{d} \phi}}
```

Linear algebra part

Bold font for vectors

```
\renewcommand{\vec}[1]{\ensuremath{\mathbf{\#1}}}
```

Operators

```
\DeclareMathOperator{\Nul}{Nul}
\DeclareMathOperator{\Span}{Span}
```

Delimiters

\DefineDelimiters 1: new delimiters name 2: left delimiter 3: right delimiter
inner 1: delimiter resizer (default to be left right); inner 2: expression being enclosed

```
\newcommand{\DefineDelimiters}[3]{%
\expandafter\newcommand\csname\#1\endcsname[2][{%
\ifx\#1\% \#1 is empty
\ensuremath{\left\#2 \#2 \right\#3}%
\else% \#1 is non-empty
\ensuremath{\#1\#2 \#2 \#1\#3}%
\fi%
}%
}
```

```
\DefineDelimiters{rbra}{\{ \}}
\DefineDelimiters{sbra}{\[ \]}
```

```

\DefineDelimiters{cbracket}{\{ \}}

\DefineDelimiters{abs}{|}{|}

\DefineDelimiters{ceiling}{\lceil}{\rceil}
\DefineDelimiters{floor}{\lfloor}{\rfloor}

Miscellaneous
\newcommand{\setR}{\ensuremath{\mathbb{R}}}
\newcommand{\setQ}{\ensuremath{\mathbb{Q}}}
\newcommand{\setZ}{\ensuremath{\mathbb{Z}}}
\newcommand{\setN}{\ensuremath{\mathbb{N}}}
\newcommand{\setNp}{\ensuremath{\mathbb{N}^+}}
</style>

```

14 Package xjtlumaterial

This package defines some styles and also refines some commands for material writings. <*material>

```

\ProvidesPackage{xjtlumaterial}[2021 by Guanyuming He]
\NeedsTeXFormat{LaTeX2e}

```

`\cleardoublepage` Renew the command to add “This page is intentionally left blank” for any empty pages added.

```

\renewcommand{\cleardoublepage}{\clearpage%
\if@twoside%
\ifodd\c@page\else%
\vspace*{5cm}
\begin{center}
This page is intentionally left blank.
\end{center}
\thispagestyle{empty}
\newpage
\if@twocolumn%
\hbox{}\newpage%
\fi%
\fi%
}
</material>

```

15 Package xjtluexam

This package enables one to typeset exam papers.

```

\ProvidesPackage{xjtluexam}[2021 by Guanyuming He]
\NeedsTeXFormat{LaTeX2e}

```

Counters

questioncnt should be reset whenever an exam paper begins. choicecnt (for MCQ questions) is reset by the choice environments.

subquestioncnt does not reset when questioncnt is changed. It is reset to 0, not 1 at the beginning of each question, and the command `\subquestion` refsteps it at the beginning.

```
\newcounter{questioncnt}
\newcounter{subquestioncnt}
```

```
\newcounter{choicecnt}
```

These two commands may be redefined by the choice environments.

`\choicenumber` This command gives the choicecnt in Alph and steps the counter.

```
\newcommand{\choicenumber}{\refstepcounter{choicecnt}\Alph{choicecnt}\hspace{1em}}
```

`\choicespace` This command gives a space depending on the choice environment in which it is given.

```
\newcommand{\choicespace}{\hspace{\stretch{1}}}
```

Choice environments

`shortchoices` This environment is used to create short choices (multiple choices are in one line). The lines can be breaked normally.

```
\newenvironment{shortchoices}%
{\setcounter{choicecnt}{0}\renewcommand{\choicespace}{\hspace{\stretch{1}}}}%
{}
```

`longchoices` This environment is used to create long choices (one choice occupies one line or more).

```
\newenvironment{longchoices}%
{\setcounter{choicecnt}{0}\renewcommand{\choicespace}{\vspace{5pt}\par\noindent}%
\choicespace}%
{}
```

Question commands

`\question` This command introduces a question

```
\newcommand{\question}{\refstepcounter{questioncnt}\par\noindent%
\thequestioncnt.\hspace{1em}%
\setcounter{subquestioncnt}{0}}
```

`\subquestion` This command introduces a sub question

```
\newcommand{\subquestion}{\refstepcounter{subquestioncnt}\par\indent(\alph{subquestioncnt})\hspace{1em}}
```

`exampaper` Write an exam paper in this

```
\newenvironment{exampaper}%
{\setcounter{questioncnt}{0}\par\noindent}%
{\par}
```

For “Fill in the blanks”

`\blankline` This command gives a rule with a given width (default 1cm)
`\newcommand{\blankline}[1][1cm]{\rule{#1}{.4pt}}`

16 Package mydoc

This package is only used for writing the documentation.

```
\ProvidesPackage{mydoc}
```

```
\RequirePackage{calc}
```

Lengths used for presenting examples

```
\newlength{\examtop}
```

```
\newlength{\exambot}
```

```
\newlength{\exammid}
```

```
\setlength{\examtop}{.5em}
```

```
\setlength{\exambot}{.6em}
```

```
\setlength{\exammid}{5pt}
```

Examples may be allowed to stick into margins, so we define two length here to represent textwidth and the length of text plus margin. Their values are defined later, because we cannot decide the page layout in the package file.

```
\newlength{\textandmarginlen}
```

```
\newlength{\textonlylen}
```

Boxes that stick into the margin raise “overfull hbox” warnings. To suppress these, set the length hfuzz to a bigger value. Note that in XeLaTeX the warnings may still be shown.

```
\newlength{\originalhfuzz}
```

```
\setlength{\originalhfuzz}{\hfuzz}
```

```
\newcommand{\enlargehfuzz}{\setlength{\hfuzz}{\maxdimen}}
```

```
\newcommand{\restorehfuzz}{\setlength{\hfuzz}{\originalhfuzz}}
```

used to save verbatim like contents inside a box

```
\newlength{\safeverblen} \newsavebox{\safeverbbox}
```

safeverb 1: width

```
\newenvironment{safeverb}[1]{%
```

```
\setlength{\safeverblen}{#1}%
```

```
\begin{lrbox}{\safeverbbox}%
```

```
\begin{minipage}[c]{\safeverblen}%
```

```
}%
```

```
{%
```

```
\end{minipage}%
```

```
\end{lrbox}%
```

```
\usebox{\safeverbbox}%
```

```
}
```

Internalminiexam verbatim like contents cannot be used inside a place where command/environment parameters are being parsed, so we must put them inside a environment.
1: left width 2: full width (right width = full – left – mid sep) 3: left content.
Right content is included inside this env.

```
\newenvironment{Internalminiexam}[3]{%
```

```

{%
\vspace{\examtop}%
\par\noindent% no par indent
%
\begin{minipage}[c]{#1}%
\sffamily%
#3%
\end{minipage}%
%
\hspace{\exammid}% mid sep
%
\begin{safeverb}{#2-#1-\exammid}%
}%
{%
\end{safeverb}%
\vspace{\exambot}%
}

```

Internalparexam 1: left width 2: full width (right width = full – left – mid sep) 3: left content.
Right content is included inside this env.

```

\newenvironment{Internalparexam}[3]%
{%
\vspace{\examtop}%
\par\noindent% no par indent
%
\parbox[c]{#1}{\sffamily #3}%
%
\hspace{\exammid}% mid sep
%
\begin{safeverb}{#2-#1-\exammid}%
}%
{%
\end{safeverb}%
\vspace{\exambot}%
}

```

1: left width 2: left content

```

\newenvironment{miniexammar}[2]
{\begin{Internalminiexam}{#1}{\textandmarginlen}{#2}%
\enlargehfuzz}%
{\end{Internalminiexam}\restorehfuzz}
\newenvironment{miniexamtext}[2]
{\begin{Internalminiexam}{#1}{\textonlylen}{#2}}%
{\end{Internalminiexam}}

\newenvironment{parexammar}[2]
{\begin{Internalparexam}{#1}{\textandmarginlen}{#2}%
\enlargehfuzz}%
{\end{Internalparexam}\restorehfuzz}

```

```
% 1: left width 2: left content
\newenvironment{parexamtext}[2]
{\begin{Internalparexam}{#1}{\textonlylen}{#2}}%
{\end{Internalparexam}}
```

Fake commands because some commands cannot or should not be used in the examples

```
\newcommand{\faketoc}{%
{\LARGE \bfseries Contents}%
\par \noindent
\vspace{.6cm}%
}
```

1: number 2: content 3: page

```
\newcommand{\fakecontentsline}[3]{%
\hspace{1.5em}#1\hspace{2em}#2\dotfill#3%
}
```

1 number 2 indent 3 content 4 before skip 5 end skip

```
\newcommand{\fakesectioning}[5]
{%
\vspace{#4}
\par\noindent%
\hspace{#2}{\bfseries\Large #1}\hspace{1.5em}%
{\bfseries\Large #3}\hfill%
\vspace{#5}%
\par\noindent
}
```

% with default value 2 number 3 content

```
\newcommand{\fakesectioningdef}[2]{\fakesectioning{#1}{0pt}{#2}{10pt}{15pt}}
```

Show lengths in L^AT_EX

```
\newcommand{\showwidth}[1]{\rule{.3pt}{.8em}\rule{#1}{.3pt}\rule{.3pt}{.8em}}
```

Calculate lengths at the beginning of the doc

```
\AtBeginDocument{%
\setlength{\textonlylen}{\textwidth}%
\setlength{\textandmarginlen}{\textwidth+\marginparsep+\marginparwidth}
}
```