


Graphs

- Definitions
- Special graphs
- Data structures
- Reading Assignment CLRS textbook
 - Appendix B.4 and B.5
 - Chapter 10
 - Chapter 3 (in case you forgot)

Definitions

- Undirected graph
 - Notation
- Directed graph
 - Notation

Undirected Graph



Galen H. Sasaki

EE 607 University of Hawaii

3

Why are we interested? Some examples:

- Is the graph connected?
- Find a path between two nodes.
- Find a “shortest” (or least costly) path between two nodes.
- Find a subgraph that includes all the nodes.

Galen H. Sasaki

EE 607 University of Hawaii

4


Undirected Graph: Definitions

Simple graphs have at most one edge between a pair of nodes

Multigraphs may have more.

Node 2 is
adjacent
to 1 and 3, i.e.,
are *neighbors*

Edge (1,2)
is *incident* to node 2



Galen H. Sasaki


EE 607 University of Hawaii

5

Undirected Graphs: Definitions

Path = a sequence of nodes, where consecutive nodes
have edges between them. *Length* = # hops

Simple path = path with distinct nodes.



Galen H. Sasaki


EE 607 University of Hawaii

6

Undirected Graphs: Definitions

Cycle = a path, but where the first and last nodes are the same.

Simple cycle = a cycle, but where all intermediate nodes are distinct.



Galen H. Sasaki


EE 607 University of Hawaii

7

Undirected Graphs: Definitions

A subgraph is a graph that is a subset of a graph.

The red nodes induce the red subgraph




Galen H. Sasaki

EE 607 University of Hawaii

8


Undirected Graphs: Definitions

A graph is connected if all pairs of nodes have a path between them.



Galen H. Sasaki

EE 607 University of Hawaii



9

Undirected Graphs: Notation


- **Graph $G = (V, E)$**
- **Nodes V .** Typically, $\{1, 2, \dots, |V|\}$.
 $|V|$ = size or “cardinality” of set V .
- **Edges E .** An edge between nodes u and v : (u, v) . Note $(u, v) = (v, u)$.
- **Path:** $\langle v_0, v_1, \dots, v_k \rangle$, a sequence of nodes.

Galen H. Sasaki

EE 607 University of Hawaii


10

Notation



- $V = \{1, 2, 3, 4, 5, 6\}$
- $E = \{(1,2), (1,3), (2,3), (2,4), (3,6), (4,5), (4,6), (5,6)\}$


Directed Graphs



Directed edges or links

Directed Graphs

Undirected path



Directed path

Directed paths follow the direction of edges


Galen H. Sasaki

EE 607 University of Hawaii


13

Directed Graphs

Strongly connected = directed paths between any (ordered) pair of nodes



Connected, but not strongly



Strongly connected


Galen H. Sasaki

EE 607 University of Hawaii

14

Directed Graphs: Notation


- Extension of notation for directed graphs
- (u,v) is not the same as (v,u) if u and v are distinct.



Special Graphs


- Rings
- Complete Graphs
- Bipartite Graphs
- Trees

Ring



$$|V| = |E|$$

Complete Graph




Every pair of nodes has a link

Bipartite Graph

$$B = (U, V, E)$$

- U has no edges between them
- V has no edges between them
- B has only even cycles



Example Application: Matchmaking
U = grooms, V = brides


Galen H. Sasaki

EE 607 University of Hawaii

19


Trees

(No cycles)
A **tree** is a **connected**, **acyclic**, undirected graph



Tree

Galen H. Sasaki



Not acyclic

EE 607 University of Hawaii

20


Trees

Theorem. Let G be an undirected graph. The following statements are equivalent

- ↓ • G is a tree: a connected acyclic graph
- ↓ • Any two vertices in G are connected to
by a unique simple path
- ↓ • G is connected, but if any edge is removed from
 E , the resulting graph is disconnected
- ↓ • G is connected, and $|E| = |V| - 1$
- ↓ • G is acyclic, and $|E| = |V| - 1$
- ↓ • G is acyclic, but if any edge is added to E , the
resulting graph contains a cycle.

Proof by Contradiction: We'll use this

Given A is true then B is true




Given B is false then A is false

Properties of Trees

- ↓
- G is a tree (**connected** and **acyclic**)
 - Any two vertices in G are connected to by a **unique simple path**

1. **Connectedness** implies there is a **simple path**
2. There is **unique path** (*proof by contradiction*):
Suppose there are multiple paths



Galen H. Sasaki

EE 607 University of Hawaii

23


Properties of Fat Trees

- ↓
- Any two vertices in G are **connected** to by a **unique simple path**
 - G is **connected**, but if any edge is removed from E , the resulting graph is disconnected

1. G is connected is immediate

2. Arbitrary edge

- Unique path between u and v
- Delete it means u and v are disconnected



Galen H. Sasaki

EE 607 University of Hawaii

24

Properties of Fat Trees


- G is connected, but if any edge is removed from E , the resulting graph is disconnected
- G is connected, and $|E| = |V| - 1$

G is connected is immediate

We can grow a subgraph G_n ($n = |V| - 1$) of G that contains all the nodes and has $|V| - 1$ edges

Properties of Trees

We can grow a subgraph G_n of G that contains all the nodes and has $|V| - 1$ edges



Show an algorithm that can create G_n

- G_1 = some node
- for $k = 1, \dots, |V| - 2$ do
Find an edge (u, v) where u in G_k and v is not $G_{k+1} = G_k \cup \{v\}$

We can do this since G is connected

$G_n, n = |V|$

- Connects all nodes
- Has $|V| - 1$ edges

Properties of Trees

- G is **connected**, but if any edge is removed from E , the resulting graph is disconnected
- G is **connected**, and $|E| = |V| - 1$

G_n , $n = |V|$

- connects all nodes
- has $|V| - 1$ edges

$G = G_n$, i.e., no extra edges. Why?

- Removing any extra edge will leave G still a superset of G_n and so G remains connected
- Thus, G has $|V| - 1$ edges.

Galen H. Sasaki

EE 607 University of Hawaii


27

Properties of Trees

- G is **connected**, and $|E| = |V| - 1$
- G is **acyclic**, and $|E| = |V| - 1$

Proof by contradiction: we'll show G is acyclic

Suppose G has a cycle of length (size) k



Cycle: k nodes, k edges

The rest: $|V| - k$ nodes

$|V| - k$ edges

Total edges $\geq |V|$

Contradiction!


Galen H. Sasaki

EE 607 University of Hawaii

28

Properties of Trees

- G is acyclic, and $|E| = |V| - 1$
- G is acyclic, but if any edge is added to E , the resulting graph contains a cycle.



Any new edge causes a cycle.

Galen H. Sasaki

EE 607 University of Hawaii

All connected and acyclic
--> trees!


$$\begin{aligned} |E| &= |V1| - 1 \\ &\quad + |V2| - 1 \\ &\quad + |V3| - 1 \\ &= |V| - 3 \end{aligned}$$

Since $|E| = |V| - 1$ it implies
one component
 G is connected

29

Properties of Trees

- G is acyclic, but if any edge is added to E , the resulting graph contains a cycle.
- G is a fat tree (i.e., acyclic and *connected*)



- Suppose the graph is disconnected
- Then there are two nodes u and v without a path between them
- Adding the link (u,v) causes a cycle
- Thus, the nodes have two paths
 - $\{u,v\}$
 - Another path from u to v
- The other path already existed in G
- Contradiction

Galen H. Sasaki

EE 607 University of Hawaii

30

Trees

Theorem. Let G be an undirected graph. The following statements are equivalent

- G is a tree
- Any two vertices in G are connected to by a unique simple path
- G is connected, but if any edge is removed from E , the resulting graph is disconnected
- G is connected, and $|E| = |V| - 1$
- G is acyclic, and $|E| = |V| - 1$
- G is acyclic, but if any edge is added to E , the resulting graph contains a cycle.

Galen H. Sasaki

EE 607 University of Hawaii

31

Facts About Trees and Rings

- A *spanning tree* T of a graph G is a subgraph that is a tree that contains all the nodes
- A tree is a connected graph, but one edge deletion makes it disconnected
- A tree has $|E| = |V| - 1$
- Ring has $|E| = |V|$, and will survive any single node or edge deletion.
Survive means remains connected

Galen H. Sasaki

EE 607 University of Hawaii

32


Spanning Trees

Grow-Tree

Input: $G = (V, E)$

Output: (V', E') a spanning tree in G if one exists

1. $V' = v$, some node in V . $E' =$ empty set.
2. **while** V' not equal to V
3. **do** find an edge (u, v) such that
 u is in V' and v is not
4. add u to V'
5. add (u, v) to E'



Galen H. Sasaki

EE 607 University of Hawaii

33

Spanning Trees

Theorem. Grow-Tree finds a spanning tree in G if G is connected.

- Initially (V', E') is connected (trivial, single node)
- Since G is connected, we can always find a (u, v) leaving (V', E') .
- Adding the edge (u, v) to (V', E') keeps it connected and (V', E') has an additional node.
- When $V' = V$, what are we left with?
 - (V', E') is connected and has $|V|-1$ edges.
 - Thus, it is a spanning tree.

Galen H. Sasaki

EE 607 University of Hawaii

34

Time Complexity

Grow-Tree

Input: $G = (V, E)$

Output: (V', E') a spanning tree in G if one exists

1. $V' = \{v\}$, some node in V . $E' =$ empty set.
2. **while** V' not equal to V
3. **do** find an edge (u, v) such that
 u is in V' and v is not
4. add u to V'
5. add (u, v) to E'

$O(f(V))$

Time Complexity = $O(|V|f(V))$

Data Structures

- Arrays
- Link lists
- Adjacency matrix
- Adjacency list

Arrays

Array: $A[0...n] = A[0], A[1], \dots, A[n]$.

2D array: $A[i,j]$ for all $i, j = 0, \dots, n$.

C Language:



```
int A[100];  
int A[10][10];  
A[5] = 20;  
A[0][3] = 85;
```

Galen H. Sasaki

EE 607 University of Hawaii

37

Linked Lists



Galen H. Sasaki

EE 607 University of Hawaii

38

Linked List


```
typedef struct listnode
{
    int                data
    struct listnode    *nextptr
    struct listnode    *prevptr
} ListNode
```

Undirected Graphs

Adjacency-matrix

$a(i,j) = 1$ if (i,j) is edge
0 otherwise

Notice: $a(i,j) = a(j,i)$




	1	2	3	4
1	0	0	1	1
2	0	0	1	0
3	1	1	0	1
4	1	0	1	0

Directed Graphs

Adjacency-matrix

$a(i,j) = 1$ if (i,j) is edge
 0 otherwise

Notice: $a(i,j) = a(j,i)$




Galen H. Sasaki

EE 607 University of Hawaii

41

Undirected Graphs

Adjacency-List




Galen H. Sasaki

EE 607 University of Hawaii

42

Directed Graphs



Adjacency-List

