

**UNIVERSITY OF LIMERICK  
OLLSCOIL LUIMNIGH**

**FACULTY OF SCIENCE AND ENGINEERING**

**DEPARTMENT OF ELECTRONIC AND COMPUTER ENGINEERING**

<b>MODULE CODE:</b>	<b>ET4725</b>
<b>MODULE TITLE:</b>	<b>Operating Systems 1</b>
<b>SEMESTER:</b>	<b>Autumn 2018/19</b>
<b>DURATION OF EXAM:</b>	<b>2.5 Hours</b>
<b>LECTURER:</b>	<b>H. Trifonov</b>

**IMPORTANT INSTRUCTIONS TO CANDIDATES:**

- **Answer any THREE questions**
- **This exam represents 70% of the full module assessment**
- **Module's percentage allocation of components:**
  - Final exam(this exam): 70%
  - Laboratory assignments: 20%
  - In-class tests during term: 10%
- **All questions are of equal weight**
- **If you answer more than three questions you will be marked on the three best answers only**

## Q1

33 Marks

a)

15 marks (5 marks each)

Using the UNIX/Linux **bash** shell commands, write **one line** solutions for each of the three problems below.

- i) Find how many **directory files** are in your **home** directory. Put the answer in a variable called **countDir**.
- ii) Find out how many times the "**cd**" **command** had been used in the past **200 history** lines
- iii) Find and display the size of the file system, where your current directory resides, in **human readable** form. Put the answer in a file called **diskSizeFile** in current directory.

b)

18 marks

Consider the following Bash script program.

```
#!/bin/bash
# The main code is here
./progB &      # start program progB in the background
# simple loop to simulate some activity
while true; do
    echo " Looping continuously "
    sleep 1
done
exit
```

Modify the above program so that it will include a **signal trap**. The **trap** will do the following:

- Acts on the receipt of a **SIGINT** signal (i.e. Ctrl+C from keyboard)
- Contains a function called **trap\_func()**
- The **trap\_func()** does the following:
  - displays (echoes) a simple message to say what is the **PID** for **progB**
  - sends a **TERM** signal to the running **progB** program
  - properly exits the script program without **orphaning** progB

Q2

33 Marks

a)

6 marks (3 marks each)

- (i) Briefly state what is meant by a **pipe** in the context of an operating system.
- (ii) The Linux OS supports **named pipes** and **unnamed pipes**. Briefly describe each of these pipe types. Highlight the differences between them.

b)

12 marks

To check the amount of disk space available on your home disk partition, write a **bash** shell script program to display this information. If there is less than **10GB available** then issue a warning message to the user, to advise that the disk space is running low.

Assume that the output of the **df -h** command is as follows:

Filesystem	Size	Used	Avail	Use%	Mounted on
/dev/sda1	57G	13G	44G	23%	/

**NOTE:** In the Addendum of this paper there is a list of common bash shell commands.

c)

15 marks (5 marks each)

Answer the following in relation to Microsoft Windows OS thread scheduling:

- (i) Briefly state what is meant by a thread in the context of a Windows operating system. Briefly summarise the key differences between a **process** and a **thread**, highlighting any advantages for using threads.
- (ii) Briefly explain what is a **priority boosting scheme** in the context of Microsoft Windows thread scheduling.
- (iii) Briefly state how is the **starvation prevention policy** applied in the context of Microsoft Windows thread scheduling.

## Q3

33 Marks

a)

13 marks

Write a **bash shell script program** to do the following:

- ❖ Find the **largest** file in the **/home/user** directory and save its name and size in variables **f\_name** and **f\_size**. The output from the command **ls -l** is in **Table 1** below.
- ❖ If the largest file is greater or equal than **4096** bytes in size, then report the file size and its name to the user.

-rw-rw-r--	1	joe2018	joe2018	995	Feb	1	12:22	test1
-rw-rw-r--	1	joe2018	joe2018	1055	Jan	31	14:33	test2
drwxr-xr-x	26	joe2018	joe2018	4096	Mar	3	15:34	Documents
-rw-rw-r--	1	joe2018	joe2018	2596	Jun	22	08:05	test5
drwxr-xr-x	9	joe2018	joe2018	4096	Dec	31	15:12	Downloads
-rw-rw-r--	1	joe2018	joe2018	345	Nov	30	21:33	test3
-rw-rw-r--	1	joe2018	joe2018	170	May	2	15:12	test4
-rw-rw-r--	1	joe2018	joe2018	4870	Sep	20	10:47	test6

**Table 1**

b)

10 marks

Draw a **block diagram** for a computer system that has the following features, and **clearly** identify each feature on your diagram:

A single physical rack server has a **Type-1** hypervisor installed. There are four **VMs** hosted on this system where one guest runs **Windows 10**, another runs **Fedora 27**, another runs **Lubuntu 18.04** and the other runs **FreeBSD**. Various applications run under each one of the four guest operating systems. A **service/management console** is used in the scheme.

c)

10 marks

Calculate the **rotational delay ( $t_r$ )** and the **raw read/write data transfer rate (R/W data rate)** in **Mbits/sec** for a single **track** on a mechanical hard drive that has the following specifications:

- Spindle rotational speed of **7200 RPM**
- Average seek access time ( $t_s$ ) is **12 milliseconds (ms)**
- Track contains **1024 sectors**
- Each sector is **512 bytes**

**Q4****33 Marks****a)****10 marks**

In the context of a UNIX style file system, draw a typical UNIX **i-node** structure, labelling each field entry. In your diagram show how the i-node's **pointers** are used to keep track of a file's disk blocks.

**c)****23 marks**

Write a bash shell script to do the following.

- Create a text file named **testFile**, using **dd**, with a file size of 890MBytes.
- Write a function called **file\_copy()** to do the following:
  - The function is called with a file name parameter (positional parameter \$1)
  - Copy (**cp**) the **testFile** (represented by \$1) to any file name
  - Calculate the size of the file that is copied using the **wc** command
  - Measure the elapsed time for the file copy operation (use **date** command to read time)
  - Calculate the data transfer **rate** for the file copy operation (i.e. file size/elapsed time) in **Mbytes/sec**
  - Print a summary output to show: file name, file size, elapsed time, transfer rate.

**NOTE** – In the Addendum B of this paper there is a list of common bash shell commands.

## ADDENDUM: Commands

### Quick Command Reference Chart

The bash shell commands and utilities – a brief summary card (8/Dec/15)

Command/Util	Brief description
awk	Scans a file(s) and performs an action on lines that match a condition. General format: <i>awk 'condition { action } ' filename</i> Example: <i>awk '/University/ {print \$3,"t", \$11}' myFile</i>
bc	Arbitrary precision calculator Example: <i>echo "scale=3; (1 + sqrt(5))/2"   bc</i> .... calculates phi to 3 places
cal	Display a calendar output
cat	Concatenate file to the standard output
cd	Change directory
chmod	Change file access permissions
chown	Change file owner/group
cp	Copy files and subdirectories
cut	Cut columns from a data file Example: <i>cut -c 49-59 logfile</i> ... extract column defined between characters 49 to 59
dd	Copy a file, converting and formatting Example: <i>dd if=/dev/zero of=myFile bs=1k count=10</i> ... makes myFile of 10 kiloBytes
date	Display current time, set date etc. Example: <i>date +%s%N</i> ...time with nanosecond resolution, <i>date +%S(00..60)seconds</i>
df	Display disk space information
diff	Compare files line by line to find differences
du	Display disk usage information
echo	Display a line of text
exit	Exit the process e.g.: <i>exit 0</i> ... exits with the code 0
find	Search for files Examples: <i>find / -type d -print</i> ... find directory files starting at root and display <i>find . -name "verse"</i> ... find all files, starting at the current directory, with "verse" string at start of name
grep	Scans text files looking for a string match. Examples: <i>grep "and" myFile</i> ... search for lines containing "and" <i>grep "^The" myFile</i> ... search for lines that begin with "The" <i>grep "floor\$" myFile</i> ... search for lines that end with "floor"
head	Display a number of lines at the head of a file
history	Display previous commands
kill	Sends a signal Example: <i>kill -HUP 43165</i> ... send HUP signal to process 43165
less	Outputs a file to the console, a page at a time
ls	List directory(s) content <i>ls -l</i> long listing to show file details <i>ls -R</i> list subdirectories recursively <i>ls -a</i> list all files, including ones that start with a .
mkdir	Make directories
mkfifo	Make a named pipe

	Example: <i>mkfifo mypipe</i>
more	Outputs a file to the console, a page at a time
mv	Move files (effectively means to rename files)
ps	Show process status ps au show all processes, for all users
pwd	Print the name of the current working directory
read	Read user input
rm	Remove files and/or directories
rm -R	rm -r (or rm -R) will remove files recursively
rmdir	Remove directories (assuming directory is empty).
sed	A stream editor Example: <i>sed 's/Jack/Jill' filebook</i> ... substitute the string 'Jill' for 'Jack' in file filebook
seq	Generates a sequence of numbers. Examples: <i>seq 1 9</i> ... generates numbers 1 to 9, line by line <i>seq -s "-" 1 9</i> ... default separator can be changed, using the -s option
set	If no options are used, set displays the names and values of all shell variables Examples: <i>set</i> .... shows all shell variables <i>set   grep "USER"</i> ... shows shell variables with a specified string
sort	Sort lines in a text file <i>sort -g</i> general numeric sort <i>sort -r</i> reverse result of sort <i>sort -k</i> sort for a key position <i>sort -n</i> sort to string numerical value
tail	Display a number of lines at the end of a file
tee	Diverts a piped input to a second separate output Example: <i>cat demo_file   sort   tee demo_file   sorted   more</i>
trap	Defines actions to take upon receipt of a signal or signals Example: <i>trap 'echo "This is my trap"' SIGHUP</i> .... echo some text on receipt of HUP
uniq	Output a file's lines, discarding all but one successive identical lines
wc	Count number of lines, words, bytes etc. in a file <i>wc -l</i> count number of lines <i>wc -c</i> count number of bytes <i>wc -m</i> count number of characters
wait	Wait for child process to exit before finishing. e.g.: wait

#### Some common built-in shell variables

Variable	Description
\$?	Exit status of the previous command
\$\$	Process ID for the shell process
\$_	Process ID for the last background command
\$0	Name of the shell or shell script
\$PPID	Process ID for the parent process
\$UID	User ID of the current process
\$HOME	The home directory
\$SHELL	The shell

**Bash function example**

```
# Example script program that uses two function parameters.
# The function calculates the product of the # two arguments:
# #!/bin/bash

# product is declared as a function and defined
product () {
  (( product_var = $1 * $2 )) # global variable
}

# The main program

product 22 3 # The product function is called, with two arguments
echo "The answer is: $product_var"
exit
```

**Bash array example**

```
#!/bin/bash

my_array=("black" "brown" "red" "sea blue")
for colour in "${my_array[@]}"; do
  echo "$colour"
done
exit 0
```