

STVAE

Spatial Transformation VAE

Zhenya Liu

Spatial Transformation

We can get a good generative model by implementing VAE.

However, the latent variable \mathbf{z} does not have any interpretability.

For example, we hope to disentangle part of \mathbf{z} to get latent variable \mathbf{u} such that \mathbf{u} provides position information of generated \mathbf{x} .

Spatial Transformation

Idea

Consider \mathbf{u} is made of some variables controlling affine transformations.

Spatial Transformation

What is **Affine transformation**?

Easily speaking,

$$\mathbf{y} = f(\mathbf{x}) = A\mathbf{x} + \mathbf{b}$$

Example

Translation $\begin{pmatrix} a \\ b \end{pmatrix}$

Rotation

$$R = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix}$$

Shearing

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} x + my \\ y \end{pmatrix} = \begin{pmatrix} 1 & m \\ 0 & 1 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} x \\ mx + y \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ m & 1 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

Spatial Transformation

In the paper [?],

The affine transformation in 2 d space is given by the matrix below:

$$\begin{bmatrix} S_x \cos \psi & -S_x \sin \psi & S_x T_x \\ S_y \sin \psi & S_y \cos \psi & S_y T_y \end{bmatrix}$$

where ψ gives the rotation, (S_x, S_y) gives the shearing, and (T_x, T_y) is the translation. In the case of affine transformation, we use 6 latent variables to account for the 6 entries in the transformation matrix.

TVAE

Now consider training one VAE with two latent variables \mathbf{z} and \mathbf{u} , and assume they are **independent**, then

$$\text{ELBO} = E_{(z,u) \sim Q_{\Psi}(\cdot|x)} \{ \log P_{\Phi}(x | z, u) \} - D_{KL}(Q_{\Psi}(z | x) \| P_{\Phi}(z)) - D_{KL}(Q_{\Psi}(u | x) \| P_{\Phi}(u))$$

TVAE




Figure 1: Architectures of VAE and T-VAE. Left: Vanilla VAE as in [7], x is the input image, x' is the reconstructed image; Right: T-VAE, y' is the reconstructed upright image

STVAE






Figure 3: Architecture of S-TVAE


STVAE




(a)



(b)



(c)



(d)

Figure: STVAE Generations

Reference



Heqing, Ye, 2019, Variational Auto-encoder with Spatial Transformations.

Temporary page!

L^AT_EX was unable to guess the total number of pages correctly. As there was some unprocessed data that should have been added to the final page this extra page has been added to receive it.

If you rerun the document (without altering it) this surplus page will go away, because L^AT_EX now knows how many pages to expect for this document.