

# Inferring Functional Connectivity in fMRI data

Shashank Singh

Advisors: Barnabás Póczos, Timothy Verstynen

36-757 ADA I

February 25, 2014


# Outline

- 1 Data
- 2 Goals
- 3 Methods

# Outline


- 1 Data - multiple views
- 2 Goals
- 3 Methods

# Local Brain Activity View




Each time frame is a snapshot of  $V \approx 1.6 \times 10^5$  voxel activities.

# Time Series View



Each voxel is 683 point time series.

# Brain Parcellation




Parcellate to reduce dimension ( $R = 600$ ).

# Outline

- 1 Data
- 2 **Goals**
- 3 Methods

# Higher-Order Connectivity and Information Flow

Want to test for (conditional) dependence between voxels





# Goals

- Want to evaluate methods for inferring functional connectivity
  - “whole-brain” (high-dimensional) context
  - account for vascular anatomy
  - Want to distinguish higher-order (indirect) connectivity

# Outline

- 1 Data
- 2 Goals
- 3 **Methods**

# Statistical Methods

- ① Time Series Methods
  - Granger Causality/Transfer Entropy

# Statistical Methods

- ① Time Series Methods
  - Granger Causality/Transfer Entropy
- ② Sparse Prediction Methods
  - Lasso/Elastic Net, FuSSO

# Statistical Methods

- ① Time Series Methods
  - Granger Causality/Transfer Entropy
- ② Sparse Prediction Methods
  - Lasso/Elastic Net, FuSSO
- ③ Graphical Model Learning Methods
  - Chow-Liu/PC algorithms with novel independence tests

# Thanks!

Questions?