

NOTES

## Paper Summary

---

**Yu Chen**

*The Chinese University of HongKong, Department of Mechanical and Automation Engineering*

*E-mail:* [anschen@link.cuhk.edu.hk](mailto:anschen@link.cuhk.edu.hk)

---

## Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Policy Gradient Methods for Reinforcement Learning with Function Approximation</b>             | <b>1</b>  |
| <b>2</b> | <b>GTD–gradient temporal difference</b>   | <b>4</b>  |
| 2.1      | Policy gradient methods for reinforcement learning with function approximation                    | 4         |
| 2.2      | Fast Gradient-Descent Methods for Temporal-Difference Learning with Linear Function Approximation | 5         |
| 2.3      | GTD( $\lambda$ )  | 6         |
| <b>3</b> | <b>Off Policy Actor-Critic</b>  | <b>9</b>  |
| <b>4</b> | <b>DDPG</b>   | <b>12</b> |
| 4.1      | Deterministic Policy Gradient Algorithms  | 12        |

---

## 1 Policy Gradient Methods for Reinforcement Learning with Function Approximation

This article[1] show theoretical possibility of using approximator to encode a policy. In this paper, the author prove the results for both two value functions, one is average reward,

$$V^\pi(s) = \lim_{n \rightarrow \infty} \frac{1}{n} \mathbb{E}[r_1 + r_2 + \dots + r_n | s, \pi] \quad (1.1)$$

$$Q^\pi(s, a) = \mathbb{E}\left[\sum_{t=1}^{+\infty} r_t - V^\pi(s) | s, a, \pi\right], \quad (1.2)$$

the other is state-by-state reward,

$$V^\pi(s) = \mathbb{E}\left[\sum_{t=1}^{\infty} \gamma^{t-1} r_t | s, \pi\right], \quad (1.3)$$

$$Q^\pi(s, a) = \mathbb{E}\left[\sum_{k=1}^{\infty} \gamma^{k-1} r_{t+k} | s_t = s, a_t = a, \pi\right] \quad (1.4)$$

We use parameters  $\theta$  to approximate policy  $\pi$ , which means  $\pi(s, a) = \pi(s, a; \theta)$ .

**Theorem 1.0.1** (Policy Gradient). *For any MDP, in either the average-reward or state-state formulations,*

$$\frac{\partial V^\pi(s)}{\partial \theta} = \int ds da \rho^\pi(s) \frac{\partial \pi(s, a)}{\partial \theta} Q^\pi(s, a), \quad (1.5)$$

where  $\rho^\pi(s)$  is discounted density for state  $s$ , defined as,

$$\rho^\pi(s) = \lim_{t \rightarrow \infty} p(s_t | s_0, \pi), \text{ stationary distribution for average reward,} \quad (1.6)$$

$$\rho^\pi(s) = \sum_{t=0}^{\infty} \gamma^t p(s_t = s | s_0, \pi), \text{ state - state formulation.} \quad (1.7)$$

*Proof:*

**Lemma 1.0.1.** *The state value function can be written as,*

$$V^\pi(s) = \int ds da \rho^\pi(s) \pi(s, a) R_s^a, \quad (1.8)$$

where  $R_s^a = \int ds' r p(s', s | s, a)$ , where  $p(s', s | s, a)$  is transition probability of MDPs.

Now, we firstly prove average-reward scheme.

$$\frac{\partial V^\pi(s)}{\partial \theta} = \frac{\partial}{\partial \theta} \sum_a \pi(s, a) Q^\pi(s, a) \quad (1.9)$$

$$= \sum_a \partial_\theta \pi Q^\pi + \pi \partial_\theta Q^\pi \quad (1.10)$$

$$= \sum_a \partial_\theta \pi Q^\pi + \pi \partial_\theta \left( R_s^a - V^\pi(s) + \sum_{s'} p(s' | s, a) V^\pi(s') \right) \quad (1.11)$$

$$= \sum_a \left( \partial_\theta \pi Q^\pi + \pi \sum_{s'} p(s' | s, a) \partial_\theta V^\pi(s') \right) - \partial_\theta V^\pi(s). \quad (1.12)$$

Since, for averaged reward, the value function depends on the final stationary distribution, we can,

$$\begin{aligned} \sum_s \rho^\pi(s) \partial_\theta V^\pi(s) &= \sum_{s,a} \rho^\pi(s) Q^\pi(s, a) \partial_\theta \pi(s, a) + \sum_{s,a,s'} p(s' | s, a) \pi(s, a) \rho^\pi(s) \partial_\theta V^\pi(s') \\ &\quad - \sum_s \rho^\pi(s) \partial_\theta V^\pi(s) \\ &= \sum_{s,a} \rho^\pi(s) Q^\pi(s, a) \partial_\theta \pi(s, a) + \sum_{s'} \rho^\pi(s') \partial_\theta V^\pi(s') - \sum_s \rho^\pi(s) \partial_\theta V^\pi(s) \\ &= \sum_{s,a} \rho^\pi(s) Q^\pi(s, a) \partial_\theta \pi(s, a). \end{aligned} \quad (1.13)$$

QED.

For state-state formulation, we can compute as,

$$\partial_\theta V^\pi(s) = \sum_a \partial_\theta \pi Q^\pi + \pi \partial_\theta Q^\pi \quad (1.14)$$

$$= \sum_a \partial_\theta \pi Q^\pi + \pi \partial_\theta \sum_{s'} rp(r, s'|s, a) + \gamma p(s'|s, a) V^\pi(s') \quad (1.15)$$

$$= \sum_a \partial_\theta \pi(s, a) Q^\pi(s, a) + \pi(s, a) \gamma p(s'|s, a) \partial_\theta V^\pi(s') \quad (1.16)$$

$$\dots \quad (1.17)$$

$$= \sum_s \rho^\pi(s) \sum_a Q^\pi(s, a) \partial_\theta \pi(s, a). \quad (1.18)$$

From the above, we can find gradient of policy depends only on  $Q^\pi(s, a)$  and is independent of  $\partial_\theta Q^\pi$ , which brings great convenience. Then, we can introduce another approximation with parameters  $\omega$  to approximate  $Q$  value function, denoted by  $f_w(s, a)$ . To make  $f_w \rightarrow Q$ , the following equation should be satisfied,

$$\begin{aligned} \partial_w \sum_s \sum_a \rho^\pi(s, a) \pi(s, a) (Q(s, a) - f_w(s, a))^2 &= 0 \\ \Leftrightarrow \sum_s \sum_a \rho^\pi(s, a) \pi(s, a) (Q(s, a) - f_w(s, a)) \partial_w f_w(s, a) &= 0. \end{aligned} \quad (1.19)$$

**Theorem 1.0.2** (Policy Gradient with Function Approximation). *If  $f_w$  satisfies Eq.(1.19) and,*

$$\frac{\partial f_w(s, a)}{\partial \omega} = \frac{\partial \pi(s, a)}{\partial \theta} \frac{1}{\pi(s, a)}, \quad (1.20)$$

then,

$$\frac{\partial V^\pi(s)}{\partial \theta} = \sum_s \rho^s(\pi) \sum_a \frac{\partial \pi(s, a)}{\partial \theta} f_w(s, a). \quad (1.21)$$

The proof is obvious. In the following, we can discuss Eq.(1.20), and construct approximators satisfying it. For example, we use a Gibbs distribution to parameterize  $\pi(s, a)$  as,

$$\pi(s, a; \theta) = \frac{e^{\theta^T \phi(s, a)}}{\sum_{a'} e^{\theta^T \phi(s, b)}}. \quad (1.22)$$

And then, we obtain,

$$\frac{1}{\pi(s, a)} \frac{\partial \pi(s, a)}{\partial \theta} = \phi(s, a) - \sum_b \pi(s, b) \phi(s, b) \quad (1.23)$$

Hence, we just need to parameterize  $f_w(s, a)$  as,

$$f_w(s, a) = w^T (\phi(s, a) - \sum_b \pi(s, b) \phi(s, b)). \quad (1.24)$$

**Theorem 1.0.3** (Policy Iteration with Function Approximation). *Let  $\pi$  and  $f_w$  be any differential function approximators for the policy and value function respectively that satisfy*

the compatibility condition 1.20 and for which  $\max_{\theta, s, a, i, j} |\frac{\partial^2 \pi(s, a)}{\partial \theta_i \partial \theta_j}| < B < \infty$ . Let  $\{\alpha_k\}_{k=0}^{+\infty}$  be any step-size sequence such that  $\lim_{k \rightarrow \infty} \alpha_k = 0$  and  $\sum_k \alpha_k = \infty$ . Then for any MDP with bounded rewards, the sequence  $\{V^{\pi_k}\}$ , defined by any  $\theta_0, \pi_k$ , and,

$$w_k = w \text{ such that } \sum_s \rho^{\pi_k} \sum_a \pi_k(s, a) (Q^{\pi_k}(s, a) - f_w(s, a)) \partial_w f_w(s, a) = 0, \quad (1.25)$$

$$\theta_{k+1} = \theta + \alpha_k \sum_s \rho^{\pi_k}(s) \sum_a f_{w_k}(s, a) \partial_\theta \pi_k(s, a), \quad (1.26)$$

converges such that  $\lim_{k \rightarrow \infty} \frac{\partial V^{\pi_k}(s)}{\partial \theta} = 0$

## 2 GTD-gradient temporal difference

### 2.1 Policy gradient methods for reinforcement learning with function approximation

The article [2] firstly raises idea for off-policy gradient temporal difference with a linear function approximator. We denote the stationary distribution of behavior policy  $b$  as  $\rho^b(s)$ . The observation of state  $s$  is given by  $\phi_s \in \mathbb{R}^n$ , so the  $\delta_t$  is,

$$\delta_t = r_t + \gamma V_t(s_{t+1}) - V_t(s_t) = r_t + \gamma \theta^T \phi_{t+1} - \theta^T \phi_t. \quad (2.1)$$

Intutively, we wish the  $\delta_t$  approaches to 0, when we reach a local minimum or maximum. In other words, we can define our objective function as  $L2$  norm,

$$J(\theta) = \mathbb{E}[\delta \phi]^T \mathbb{E}[\delta \phi], \quad (2.2)$$

where  $\mathbb{E}$  is over the stationary distribution  $\rho^b(s)$ . The gradient is,

$$\nabla_\theta J(\theta) = 2 \nabla_\theta \mathbb{E}[\delta \phi^T] \mathbb{E}[\delta \phi] \quad (2.3)$$

$$= -2 \mathbb{E}[(\phi - \gamma \phi') \phi^T] \mathbb{E}[\delta \phi]. \quad (2.4)$$

where  $\phi' = \phi_{t+1}$ . Hence, there are two approaches to find this gradient. Firstly, it stores the expectation of the first term and samples the second term; secondly, it stores the expectation of the second term and samples the first term. (Note: why we do not store both expectation is that it will introduce bias brought by the correlation of these two terms). Mathematically, we have  $\phi_1, r_1, \phi_2, r_2, \dots, \phi_k, r_k, \phi_{k+1}, r_{k+1}$ ,

$$A_k = \frac{1}{k} \sum_{j=1}^k (\phi_j - \gamma \phi_{j+1}) \phi_j^T, \quad (2.5)$$

$$\theta_{k+1} = \theta_k + \alpha_k A_k \delta_k \phi_k, \quad (2.6)$$

where  $\delta_k = r_k + \gamma \theta_k^T \phi_{k+1} - \theta_k^T \phi_k$ . The disadvantage of this method is that finding  $A_k \in \mathbb{R}^{n \times n}$  costs our  $n^2$  complexity. Hence, the most case we use the second approach,

$$w_{k+1} = w_k + \beta_k (\delta_k \phi_k - w_k), \quad (2.7)$$

$$\theta_{k+1} = \theta_k + \alpha_k (\phi_k - \gamma \phi_{k+1}) \phi_k^T w_k \quad (2.8)$$

## 2.2 Fast Gradient-Descent Methods for Temporal-Difference Learning with Linear Function Approximation

This article [3] give an improvement of the above algorithm, named GTD2 and TDC(TD with gradient correction). GTD2 uses a different objective function,

$$J(\theta) = \mathbb{E}[\delta\phi]^T \mathbb{E}[\phi\phi^T]^{-1} \mathbb{E}[\delta\phi]. \quad (2.9)$$

The idea of this objective function comes from the following facts. The ultimate goal of these algorithm is to find an approximator  $V_\theta$ , which can approximates  $V$  as exactly as possible. As we known, the true  $V$  satisfies the Bellman equation,

$$V = TV, \quad (2.10)$$

where  $T$  is Bellman transition matrix. Hence, we hope our approximator can satisfies this property too, in other words, we wish  $\|V_\theta - TV_\theta\|_{\rho^b}^2 \equiv \int ds \rho^b(s) |V_\theta(s) - TV_\theta(s)|^2 \rightarrow 0$ . Unfortunately,  $TV_\theta$  may not stay in the space  $V_\theta$ . Instead, we denote a projector  $\Pi$ , which projects any  $v$  to space  $V_\theta$  as  $\Pi v$ . To find  $\Pi$ , we firstly find  $\theta$  minimizing  $\|v - \Phi\theta\|_D$ , where  $D \in \mathbb{R}^{|\mathcal{S}| \times |\mathcal{S}|}$  is diagonal matrix with element  $\rho^b(s)$ , and  $\Phi$  with rows  $\phi_s$ .

$$\nabla_\theta \|v - \Phi\theta\|_D^2 = -2\Phi^T D(v - \Phi\theta), \quad (2.11)$$

which means  $\theta = (\Phi^T D \Phi)^{-1} \Phi^T D v$ , and we know  $\Pi v = \Phi\theta, \forall v$ . Hence,

$$\Pi = \Phi(\Phi^T D \Phi)^{-1} \Phi^T D \quad (2.12)$$

We define mean-squared projected Bellman error as,

$$\text{MSPBE}(\theta) \equiv \|V_\theta - \Pi TV_\theta\|_D^2. \quad (2.13)$$

By using the facts,

$$\begin{aligned} \mathbb{E}[\phi\phi^T] &= \sum_s d_s \phi_s \phi_s^T = \Phi^T D \Phi, \\ \mathbb{E}[\delta\phi] &= \sum_s d_s \phi_s (R_s + \gamma \sum_{s'} p_{s,s'} V_\theta(s') - V_\theta(s)) = \Phi^T D (TV_\theta - V_\theta), \\ \Pi^T D \Pi &= D^T \Phi (\Phi^T D \Phi)^{-1} \Phi^T D. \end{aligned} \quad (2.14)$$

we can simplify  $\text{MSPBE}(\theta)$  as

$$\begin{aligned} \text{MSPBE}(\theta) &= \|V_\theta - \Pi TV_\theta\|_D^2 \\ &= (V_\theta - \Pi TV_\theta)^T D (V_\theta - \Pi TV_\theta) \\ &= (V_\theta - TV_\theta)^T \Pi^T D \Pi (V_\theta - TV_\theta) \\ &= (V_\theta - TV_\theta)^T D^T \Phi (\Phi^T D \Phi)^{-1} \Phi^T D (V_\theta - TV_\theta) \\ &= \mathbb{E}[\delta\phi]^T \mathbb{E}[\phi\phi^T]^{-1} \mathbb{E}[\delta\phi]. \end{aligned} \quad (2.15)$$

The gradient is,

$$\nabla_\theta \text{MSPBE}(\theta) = -2\mathbb{E}[(\phi - \gamma\phi')\phi^T] \mathbb{E}[\phi\phi^T]^{-1} \mathbb{E}[\delta\phi]. \quad (2.16)$$

We use  $w$  to approximate  $\mathbb{E}[\phi\phi^T]^{-1}\mathbb{E}[\delta\phi]$ , so the update rule is,

$$w_{k+1} = w_k + \beta_k(\delta_k - \phi_k^T w_k)\phi_k, \quad (2.17)$$

$$\theta_{k+1} = \theta_k + \alpha_k(\phi_k - \gamma\phi_k')(\phi_k^T w_k). \quad (2.18)$$

TDC appriximates this gradient more exactly,

$$-\frac{1}{2}\nabla_{\theta}\text{MSPBE}(\theta) = \mathbb{E}[(\phi - \gamma\phi')\phi^T]\mathbb{E}[\phi\phi^T]^{-1}\mathbb{E}[\delta\phi] \quad (2.19)$$

$$= \mathbb{E}[\delta\phi] - \gamma\mathbb{E}[\phi'\phi^T]\mathbb{E}[\phi\phi^T]^{-1}\mathbb{E}[\delta\phi] \quad (2.20)$$

$$\approx \mathbb{E}[\delta\phi] - \gamma\mathbb{E}[\phi'\phi^T]w \quad (2.21)$$

Hence, TDC update  $\theta$  as,

$$\theta_{k+1} = \theta_k + \alpha_k\delta_k\phi_k - \alpha\gamma\phi_k'(\phi_k^T w_k). \quad (2.22)$$

#### Gradient Temporal Difference

$$w_{k+1} = w_k + \beta_k(\delta_k - \phi_k^T w_k)\phi_k, \quad (2.23)$$

$$\theta_{k+1} = \theta_k + \alpha_k(\phi_k - \gamma\phi_k')(\phi_k^T w_k) \quad \textbf{(GTD2)}, \quad (2.24)$$

$$\theta_{k+1} = \theta_k + \alpha_k\delta_k\phi_k - \alpha\gamma\phi_k'(\phi_k^T w_k) \quad \textbf{(TDC)}. \quad (2.25)$$

### 2.3 GTD( $\lambda$ )

Above two algorithms are about GTD(0), in these section, the author introduce the final version of GTD–GTD( $\lambda$ )[4]. Firstly, we can write  $\lambda$ –return as,

$$G_t^\lambda = r_{t+1} + \gamma \left( (1 - \lambda)V(s_{t+1}) + \lambda G_{t+1}^\lambda \right). \quad (2.26)$$

Obviously, when  $\lambda = 1$  it is MC method,  $\lambda = 0$  is dynamical programming. For simplicity, we also use linear approximation, so the  $\delta$  return is,

$$G_t^\lambda = r_{t+1} + \gamma(1 - \lambda)\theta^T\phi_{t+1} + \gamma\lambda G_{t+1}^\lambda, \quad (2.27)$$

$$\delta_t^\lambda = G_t^\lambda - \theta^T\phi_t \quad (2.28)$$

Similarly, we can define a new operator as,

$$\mathcal{P}_b^\pi \delta_t^\lambda \phi_t := \sum_s \rho^b(s) \mathbb{E}[\delta_t^\lambda | S_t = s, \pi] \phi(s) \quad (2.29)$$

We can find it has the following properties,

$$\mathbb{E}[\delta_t^\lambda | S_t = s, \pi] = \mathbb{E}[G_t^\lambda - \theta^T\phi_s | S_t = s, \pi] = TV_\theta(s) - V_\theta(s) \quad (2.30)$$

then,

$$\mathcal{P}_b^\pi \delta_t^\lambda \phi_t = \sum_s \rho^b(s) \mathbb{E}[\delta_t^\lambda | S_t = s, \pi] \phi(s) \quad (2.31)$$

$$= \sum_s \rho^b(s) (TV_\theta(s) - V_\theta(s)) \phi(s) \quad (2.32)$$

$$= \Phi^T D(TV_\theta - V_\theta). \quad (2.33)$$

Hence,

$$\text{MSPBE}(\theta) = \|V_\theta - \Pi TV_\theta\|_D^2 = (\mathcal{P}_b^\pi \delta_t^\lambda \phi_t)^T \mathbb{E}[\phi_t \phi_t^T]^{-1} \mathcal{P}_b^\pi \delta_t^\lambda \phi_t. \quad (2.34)$$

Here there is a problem  $\mathcal{P}_b^\pi \delta_t^\lambda \phi_t$  is along trajectory by  $\pi$ , but our sample is along  $b$ . Hence we need to use importance sampling to solve it. To this end, we define,

$$G_t^{\lambda\rho}(\theta) = \rho_t(r_{t+1} + \gamma((1 - \lambda)\theta^T \phi_t + \lambda G_t^{\lambda\rho}(\theta))), \quad (2.35)$$

$$\delta_t^{\lambda\rho}(\theta) = G_t^{\lambda\rho}(\theta) - \theta^T \phi_t. \quad (2.36)$$

where  $\rho_t = \frac{\pi(S,A)}{b(S,A)}$ .

**Theorem 2.3.1** (Off-policy with importance sampling).

$$\mathcal{P}_b^\pi \delta_t^\lambda(\theta) \phi_t = \mathbb{E}[\delta_t^{\lambda\rho}(\theta) \phi_t]. \quad (2.37)$$

*Proof:* To prove this, we only need to prove the following,

$$\mathbb{E}[G_t^{\lambda\rho} \phi_t | S_t = s] = \mathbb{E}[G_t^\lambda \phi_t | S_t = s, \pi]. \quad (2.38)$$

We compute the left side,

$$\begin{aligned} \mathbb{E}[G_t^{\lambda\rho} | S_t = s] &= \mathbb{E}[\rho_t R_{t+1} + \rho_t \gamma(1 - \lambda)\theta^T \phi_t | S_t = s] + \gamma \lambda \mathbb{E}[\rho_t G_{t+1}^{\lambda\rho} | S_t = s] \\ &= \mathbb{E}[R_{t+1} + \gamma(1 - \lambda)\theta^T \phi_t | S_t = s, \pi] + \\ &\quad + \gamma \lambda \sum_{s'} p(s' | s, a) b(s, a) \frac{\pi(s, a)}{b(s, a)} \mathbb{E}[G_{t+1}^\lambda | S_{t+1} = s'] \\ &= \mathbb{E}[R_{t+1} + \gamma(1 - \lambda)\theta^T \phi_t | S_t = s, \pi] + \lambda \gamma \mathbb{E}[G_{t+1}^\lambda | S_t = s, \pi] \\ &= \mathbb{E}[G_t^\lambda | S_t = s, \pi]. \end{aligned} \quad (2.39)$$

Hence,

$$\text{MSPBE}(\theta) = \mathbb{E}[\delta_t^{\lambda\rho} \phi_t]^T \mathbb{E}[\phi_t \phi_t^T]^{-1} \mathbb{E}[\delta_t^{\lambda\rho} \phi_t]. \quad (2.40)$$

This is forward view, to implement this algorithm, we need to find  $e_t$  such that  $\mathbb{E}[\delta_t^{\lambda\rho} \phi_t] = \mathbb{E}[\delta_t e_t]$ , where  $\delta_t$  is common TD difference  $\delta_t = r_{t+1} + \gamma \theta^T \phi_{t+1} - \theta^T \phi_t$ .

**Theorem 2.3.2** (Equivalence of the TD forward-view and backward-view). *The forward-view is equivalent to the following backward-view:*

$$\mathbb{E}[\delta_t^{\lambda\rho} \phi_t] = \mathbb{E}[\delta_t e_t] \quad (2.41)$$

with updating rule,

$$e_t = \rho_t(\phi_t + \gamma \lambda e_{t-1}). \quad (2.42)$$



*Proof:* We simplify  $\delta_t^{\lambda\rho} = G_t^{\lambda\rho} - \theta^T \phi_t$  step by step.

$$G_t^{\lambda\rho} = \rho_t(r_{t+1} + \gamma\theta^T \phi_{t+1} - \theta^T \phi_t) + \rho_t\theta^T \phi_t - \lambda\gamma\rho_t\theta^T \phi_{t+1} + \lambda\gamma\rho_t G_{t+1}^{\lambda\rho} \quad (2.43)$$

$$= \rho_t\delta_t(\theta) + \rho_t\theta^T \phi_t + \lambda\gamma\rho_t\delta_{t+1}^{\lambda\rho}. \quad (2.44)$$

Hence,

$$\delta_t^{\lambda\rho} = \rho_t\delta_t + (\rho_t - 1)\theta^T \phi_t + \lambda\gamma\rho_t\delta_{t+1}^{\lambda\rho}. \quad (2.45)$$

We firstly prove the second term vanishes under expectation,

$$\mathbb{E}[(1 - \rho_t)\theta^T \phi_t \phi_t] = \sum_{s,a} b(s,a)\rho^b(s)(1 - \frac{\pi(s,a)}{b(s,a)})\theta^T \phi_s \phi_s \quad (2.46)$$

$$= \sum_{s,a} \rho^b(s)(b(s,a) - \pi(s,a))\theta^T \phi_s \phi_s \quad (2.47)$$

$$= \sum_s \rho^b(s)(1 - 1)\theta^T \phi_s \phi_s = 0. \quad (2.48)$$

Hence,

$$\begin{aligned} \mathbb{E}[\delta_t^{\lambda\rho} \phi_t] &= \mathbb{E}[\rho_t\delta_t\phi_t + \lambda\gamma\rho_t\delta_{t+1}^{\lambda\rho}\phi_t] \\ &= \mathbb{E}[\rho_t\delta_t\phi_t] + \lambda\gamma\mathbb{E}[\rho_{t-1}\delta_t^{\lambda\rho}\phi_{t-1}] \\ &= \mathbb{E}[\rho_t\delta_t\phi_t + \lambda\gamma\rho_{t-1}\phi_{t-1}\rho_t\phi_t] + \gamma^2\lambda^2\mathbb{E}[\rho_{t-1}\rho_t\delta_{t+1}^{\lambda\rho}\phi_{t-1}\phi_t] \\ &\quad \vdots \\ &= \mathbb{E}[\delta_t\rho_t(\phi_t + \lambda\gamma\phi_{t-1}\rho_{t-1} + \dots)] \\ &= \mathbb{E}[\delta_te_t], \end{aligned} \quad (2.49)$$

with  $e_t = \phi_t(\phi_t + \gamma\lambda e_{t-1})$ .

Now, we can find gradient of  $\text{MSPBE}(\theta) = \mathbb{E}[\delta_te_t]^T \mathbb{E}[\phi_t\phi_t^T]^{-1} \mathbb{E}[\delta_te_t]$ .

$$-\frac{1}{2}\nabla_{\theta}\text{MSPBE}(\theta) = -\mathbb{E}[\gamma(\phi_{t+1} - \phi_t)e_t^T]\mathbb{E}[\phi_t\phi_t^T]^{-1}\mathbb{E}[\delta_te_t]. \quad (2.50)$$

To simplify it, we use the following equalities,

$$\mathbb{E}[\phi_t\rho_t\phi_t^T] = \mathbb{E}[\phi_t\phi_t^T], \mathbb{E}[\phi_{t+1}\rho_te_t^T] = \mathbb{E}[\phi_{t+1}e_t^T] \quad (2.51)$$

$$\mathbb{E}[\phi_te_t^T] = \mathbb{E}[\phi_t\rho_t(\phi_t^T + \lambda\gamma e_{t-1}^T)] \quad (2.52)$$

$$= \mathbb{E}[\phi_t\phi_t^T] + \gamma\lambda\mathbb{E}[\phi_{t+1}e_t^T]. \quad (2.53)$$

$$\begin{aligned} -\frac{1}{2}\nabla_{\theta}\text{MSPBE}(\theta) &= \mathbb{E}[\delta_te_t] - \gamma(1 - \lambda)\mathbb{E}[\phi_{t+1}e_t^T]\mathbb{E}[\phi_t\phi_t^T]^{-1}\mathbb{E}[\delta_te_t] \\ &\approx \mathbb{E}[\delta_te_t] - \gamma(1 - \lambda)\mathbb{E}[\phi_{t+1}e_t^T]w. \end{aligned} \quad (2.54)$$

Hence updating rule is,

$$\theta_{t+1} = \theta_t + \alpha_t(\delta_te_t - \gamma(1 - \lambda)(e_t^T w_t)\phi_{t+1}), \quad (2.55)$$

$$w_{t+1} = w_t + \beta_t(\delta_te_t - (w_t^T \phi_t)\phi_t), \quad (2.56)$$

$$e_{t+1} = \rho_t(\phi_t + \gamma\lambda e_{t-1}). \quad (2.57)$$

### GTD( $\lambda$ ) with linear function approximation

Initialize  $w_0$  to 0, and  $\theta_0$  arbitrarily.

Choose  $\alpha, \beta, \gamma, \lambda$

Repeat for each episode:

Initialize  $e = 0$

Take  $A_t$  from  $S_t$  according to  $b(a|s)$  and observe  $(\phi_t, r_{t+1}, \phi_{t+1})$

Update as:

$$\delta_t \leftarrow r_{t+1} + \gamma \theta^T \phi_{t+1} - \theta^T \phi_t.$$

$$\rho_t \leftarrow \frac{\pi(a_t|s_t)}{b(a_t|s_t)}$$

$$e_t \leftarrow \rho_t(\phi_t + \lambda \gamma e_{t-1})$$

$$\theta_{t+1} \leftarrow \theta_t + \alpha_t [\delta_t e_t - \gamma(1 - \lambda)(e_t^T w_t) \phi_{t+1}]$$

$$w_{t+1} \leftarrow w_t + \beta_t (\delta_t e_t - (\phi_t^T w_t) \phi_t).$$

### 3 Off Policy Actor-Critic

This article[5] introduce the first actor-critic method that can be applied off-policy, give off-policy gradient theorem and convergence proof. In this paper, author use  $b$  to denote the behaviour policy, and stationary distribution or discounted distribution is  $\rho^b(s)$  in our notations. The objective function is,

$$J(\pi_\theta) = \int ds \rho^b(s) V^{\pi_\theta}(s). \quad (3.1)$$

Obviously, we should updata  $\theta$  along the direction  $\nabla_\theta J(\pi_\theta)$ , which is given by,

$$\begin{aligned} \nabla_\theta J(\pi_\theta) &= \int ds da \rho^b(s) \nabla_\theta (\pi_\theta(s, a) Q^{\pi_\theta}(s, a)) \\ &= \int ds da \rho^b(s) (\nabla \pi_\theta Q + \pi_\theta \nabla_\theta Q) \\ &\equiv g(\theta) + \int ds da \rho^b(s) \pi_\theta \nabla_\theta Q. \end{aligned} \quad (3.2)$$

Actually, the second term is very difficult to compute, the following theorem proves that ignoring it is good approximation.

**Theorem 3.0.1** (Policy Improvement). *Given any policy with parameters  $\theta$ , let,*

$$\theta' = \theta + \alpha g(\theta). \quad (3.3)$$

*Then there exists an  $\varepsilon > 0$  such that, for all possible  $\alpha < \varepsilon$ ,*

$$J(\pi_{\theta'}) > J(\pi_\theta). \quad (3.4)$$

*Further, if  $\pi$  has a tabular representation, then*

$$V^{\pi_{\theta'}}(s) > V^{\pi_\theta}(s), \forall s. \quad (3.5)$$

*Proof:* It is easy to show,

$$\begin{aligned} J(\pi_\theta) &= \int ds da \rho^b(s) \pi_\theta(s, a) Q^{\pi_\theta}(s, a) \\ &\leq \int ds da \rho^b(s) \pi_{\theta'}(s, a) Q^{\pi_\theta}(s, a). \end{aligned} \quad (3.6)$$

Since we have  $f(x + \alpha \nabla f) - f(x) = \alpha (\nabla f)^2 > 0$ . Then we repeat applying the above inequality, we can find,

$$J(\pi_\theta) \leq \mathbb{E}_{s \sim \rho^b, a \sim \pi_{\theta'}} Q^{\pi_\theta}(s, a) \quad (3.7)$$

$$= \mathbb{E}_{s \sim \rho^b} \mathbb{E}_{a \sim \pi_{\theta'}} [r_{t+1} + \gamma V^{\pi_\theta}(s_{t+1})] \quad (3.8)$$

$$\leq \mathbb{E}_{s \sim \rho^b} \mathbb{E}_{a \sim \pi_{\theta'}} [r_{t+1} + \gamma r_{t+2} + \gamma V^{\pi_\theta}(s_{t+2})] \quad (3.9)$$

$$\vdots \quad (3.10)$$

$$= J(\pi_{\theta'}). \quad (3.11)$$

The second part is similar since

$$V^{\pi_\theta} = \int da \pi_\theta(s, a) Q^{\pi_\theta}(s, a) \leq \int da \pi_{\theta'}(s, a) Q^{\pi_\theta}(s, a). \quad (3.12)$$

By repeating the above formula, we can prove the second part.

**Theorem 3.0.2** (Off Policy Gradient Theorem). *Let  $\mathbb{Z} = \{\theta | \nabla_\theta J(\pi_\theta) = 0\}$  and  $\tilde{\mathbb{Z}} = \{\theta | g(\theta) = 0\}$ , which are both non-empty by some assumptions. If the value function can be represented by our function class, then,*

$$\mathbb{Z} \in \tilde{\mathbb{Z}}. \quad (3.13)$$

Moreover, if we use a tabular representation for policy  $\pi$ , then

$$\mathbb{Z} = \tilde{\mathbb{Z}}. \quad (3.14)$$

*Proof:* This first part is very trivial because of off policy improvement theorem. More specifically, any  $\theta^*$  such that  $\nabla_\theta J(\pi_\theta)|_{\theta^*} = 0$  must means  $g(\theta^*) = 0$ , otherwise there exists a direction  $\frac{g(\theta^*)}{\|g(\theta^*)\|}$  such that  $J(\theta)$  increases, which is contradict to  $\nabla_\theta J(\theta)|_{\theta^*} = 0$ .

For the second part, we have a tabular representation, which means each weight corresponds to exactly one state. Without loss of generality, weights  $\theta_{s,1}, \theta_{s,2}, \dots, \theta_{s,s_n}$  are relative to state  $s$ . Since  $g(\theta^*) = 0$ ,

$$\int ds' da \rho^b(s) \partial_{\theta_{s,j}} \pi_\theta(s', a) Q^{\pi_\theta}(s', a) = \rho^b(s) \partial_{\theta_{s,j}} \pi_\theta(s, a) Q^{\pi_\theta}(s, a) = 0, \forall j = 1, \dots, s_n. \quad (3.15)$$

If there exists  $k$  such that,

$$\int ds' da \pi_\theta(s', a) \partial_{\theta_{s,k}} Q^{\pi_\theta}(s', a) \neq 0, \quad (3.16)$$

which means  $J(\pi_\theta)$  will increase for local increasement of  $Q^{\pi_\theta}(s, a)$ . In other words, we can change our policy a little to increase our objective function, which means,

$$\sum_{j=1}^{n_s} \int ds' da \partial_{\theta_{s,j}} \pi_\theta(s', a) Q^{\pi_\theta}(s', a) \neq 0. \quad (3.17)$$

Contracted to Eq.(3.15).

Then, we can rewrite  $g(\theta)$  as,

$$g(\theta) = \int ds \rho^b(s) Q^{\pi_\theta}(s, a) \nabla_\theta \pi_\theta(a|s) \quad (3.18)$$

$$= \int ds \rho^b(s) b(a|s) \rho(a|s) Q^{\pi_\theta}(s, a) \nabla \log \pi_\theta(a|s) \quad (3.19)$$

$$= \mathbb{E}[\rho(s, a) \psi(s, a) Q^{\pi_\theta}(s, a)]. \quad (3.20)$$

There is a famous result that an arbitrary function of state can be introduced into these equations as a baseline without changing the expected value. Hence, we can write  $g(\theta)$  as,

$$g(\theta) = \mathbb{E}[\rho(s, a) \psi(s, a) (Q^\pi(s, a) - V(s))] \approx \mathbb{E}[\rho(s, a) \psi(s, a) (R_t^\lambda - V(s))]. \quad (3.21)$$

where  $R_t^\lambda$  is off-policy  $\lambda$ -return, defined as,

$$R_t^\lambda = r_{t+1} + \gamma(1 - \lambda)V(s_{t+1}) + \gamma\lambda\rho_t R_{t+1}^\lambda \quad (3.22)$$

To find a backward-view implement, we need to find  $e_t$  such that,

$$\mathbb{E}[\rho(s, a) \psi(s, a) (R_t^\lambda - V(s))] = \mathbb{E}[\delta_t e_t], \quad (3.23)$$

where  $\delta_t = r_{t+1} + \gamma V(s_{t+1}) - V(s_t)$ . As shown in paper, updating rule of  $e_t$  is given by,

$$e_t = \rho_t(\psi_t + \lambda\gamma e_{t-1}). \quad (3.24)$$

#### Off-PAC algorithm

Initialize the vectors  $e_v, e_u$  and  $w$  to zero

Initialize the vectors  $v, u$  arbitrarily

Initialize the state  $s$

For each step:

Choose an action  $a$ , according to  $b(a|s)$

Observer resultant reward  $r$ , and next state  $s'$ ,

$$\delta \leftarrow r + \gamma v^T \phi_{s'} - v^T \phi_s$$

$$\rho \leftarrow \pi_u(a|s)/b(a|s)$$

Update the critic (GTD( $\lambda$ ) algorithm):

$$e_v \leftarrow \rho(\phi_s + \gamma \lambda e_v)$$

$$v \leftarrow v + \alpha_v [\delta e_v - \gamma(1 - \lambda)(w^T e_v) \phi_s]$$

$$w \leftarrow w + \alpha_w [\delta e_v - (w^T \phi_s) \phi_s]$$

Update the actor:

$$e_u \leftarrow \rho \left[ \frac{\nabla_u \pi_u(a|s)}{\pi_u(a|s)} + \gamma \lambda e_u \right]$$

$$u \leftarrow u + \alpha_u \delta e_u$$

$$s \leftarrow s'$$

## 4 DDPG

### 4.1 Deterministic Policy Gradient Algorithms

In the previous paper, we have introduced policy gradient methods for stochastic policy. The author in this paper [6] show that the deterministic policy gradient does indeed exist, and furthermore it has a simple model-free form that simply follows the gradient of the action-value function. In addition, they show that the deterministic policy gradient is the limiting case, as policy variance tends to zero, of the stochastic policy gradient. In this paper, we use  $\mu_\theta(s)$  denote a deterministic policy, which means when we meet state  $s$ , we take action  $\mu_\theta(s)$ .

**Theorem 4.1.1** (Deterministic Policy Gradient Theorem). *Suppose that the MDP satisfies some conditions, these imply that  $\nabla_{\mu_\theta}$  and  $\nabla_a Q^\mu(s, a)$  exist and that the deterministic policy gradient exists. Then*

$$\nabla_\theta V^{\mu_\theta} = \int ds \rho^\mu(s) \nabla_\theta \mu_\theta(s) \nabla_a Q^\mu(s, a)|_{a=\mu(s)}. \quad (4.1)$$

*Proof:*

$$\nabla_{\theta} V^{\mu_{\theta}} = \nabla_{\theta} Q^{\mu}(s, \mu(s)) \quad (4.2)$$

$$= \nabla_{\theta} \left( R_{s, \mu(s)} + \gamma \int ds' p(s'|s, \mu(s)) V^{\mu}(s') \right) \quad (4.3)$$

$$= \nabla_{\theta} \mu \nabla_a R_{s, a} + \gamma \int ds' \nabla_{\theta} \mu \nabla_a p(s'|s, a) V^{\mu}(s') + p(s'|s, a) \nabla_{\theta} V^{\mu}(s') \quad (4.4)$$

$$= \nabla_{\theta} \mu \nabla_a \left( R_{s, a} + \gamma \int ds' p(s'|s, a) V^{\mu}(s') \right) + \gamma \int ds' p(s'|s, a) \nabla_{\theta} V^{\mu}(s') \quad (4.5)$$

$$= \nabla_{\theta} \mu \nabla_a Q^{\mu}(s, a) + \gamma \int ds' p(s'|s, a) \nabla_{\theta} V^{\mu}(s') \quad \dots \quad (4.6)$$

$$= \int ds \rho^{\mu}(s) \nabla_{\theta} \mu \nabla_a Q^{\mu}(s, a) \quad (4.7)$$

**Theorem 4.1.2.** *Consider a stochastic policy  $\pi_{\mu_{\theta}, \sigma}$  such that  $\pi_{\mu_{\theta}, \sigma}(a|s) = \nu_{\sigma}(\mu_{\theta}(s), \sigma)$ , where  $\sigma$  controls variance and  $\nu_{\sigma}$  satisfies some conditions, then*

$$\lim_{\sigma \downarrow 0} \nabla_{\theta} V^{\pi_{\mu_{\theta}, \sigma}} = \nabla_{\theta} V^{\mu_{\theta}} \quad (4.8)$$

Instead of author's proof, I use a more abstract notation to show the same thing. We can write the deterministic policy  $\mu_{\theta}$  as the stochastic policy with density  $\pi(a|s) = \delta(\mu(s) - a)$ . Using the stochastic policy gradient theorem, we can have,

$$\nabla_{\theta} V^{\mu_{\theta}} = \int ds da \rho^{\mu}(s) \nabla_{\theta} \delta(\mu_{\theta}(s) - a) Q^{\mu}(s, a) \quad (4.9)$$

$$= - \int ds da \rho^{\mu}(s) \nabla_{\theta} \mu \nabla_a \delta(a - \mu(s)) Q^{\mu}(s, a) \quad (4.10)$$

$$= \int ds \rho^{\mu}(s) \nabla_{\theta} \mu \nabla_a Q^{\mu}(s, \mu(s)), \quad (4.11)$$

where we use integral by parts to obtain the last equality. To implement, we use  $Q^w$  to approximate  $Q^{\mu}$  with parameters  $w$ . If we use the on-policy to choose action, then updating rule is,

**Algorithm 4.1.1** (OPDAC(on-policy deterministic actor-critic)).

$$\begin{aligned} \delta_t &= r_{t+1} + \gamma Q^w(s_{t+1}, a_{t+1}) - Q^w(s_t, a_t), \\ w_{t+1} &= w_t + \alpha_w \delta_t \nabla_w Q^w(s_t, a_t), \\ \theta_{t+1} &= \theta_t + \alpha_{\theta} \nabla_{\theta} \mu_{\theta}(s_t) \nabla_a Q^w(s_t, a_t)|_{a=\mu_{\theta}(s_t)}. \end{aligned} \quad (4.12)$$

**Algorithm 4.1.2** (OPDAC(off-policy deterministic actor-critic)). *In this algorithm, we use  $Q$ -learning to update critic, then*

$$\begin{aligned} \delta_t &= r_{t+1} + \gamma Q^w(s_{t+1}, \mu_{\theta}(s_{t+1})) - Q^w(s_t, a_t), \\ w_{t+1} &= w_t + \alpha_w \delta_t \nabla_w Q^w(s_t, a_t), \\ \theta_{t+1} &= \theta_t + \alpha_{\theta} \nabla_{\theta} \mu_{\theta}(s_t) \nabla_a Q^w(s_t, a_t)|_{a=\mu_{\theta}(s_t)}. \end{aligned} \quad (4.13)$$

Here, we should notice a problem that we can not use arbitrary approximator  $Q^w$  to approximate  $Q^\mu$ , since  $\nabla_a Q^w(s, a)$  may be different with  $\nabla_a Q^\mu(s, a)$ . The following theorem resolve this problem.

**Theorem 4.1.3.** *A function approximator  $Q^w$  is compatible with a deterministic policy  $\mu_\theta$ ,  $\nabla_\theta J(\theta) = \mathbb{E}_b[\nabla_\theta \mu_\theta(s) \nabla_a Q^w(s, a)|_{a=\mu_\theta(s)}]$ ,*

•

$$\nabla_a Q^w(s, a)|_{a=\mu_\theta(s)} = \nabla_\theta \mu_\theta(s)^T w \quad (4.14)$$

- $w$  minimises the mean-squared error,  $\text{MSE}(\theta, w) = \mathbb{E}[\varepsilon(s; \theta, w)^T \varepsilon(s; \theta, w)]$ , where  $\varepsilon(s; \theta, w) = \nabla_a Q^w(s, a) - \nabla_a Q^\mu(s, a)$ .

*Proof:* The proof is very simple. To minimize MSE, we wish

$$0 = \nabla_w \mathbb{E}[\varepsilon^T \varepsilon] = \mathbb{E}[\nabla_\theta \mu_\theta(s)^T w \varepsilon], \quad (4.15)$$

which means,

$$\mathbb{E}[\nabla_\theta \mu_\theta(s)^T \nabla_a Q^w(s, a)] = \mathbb{E}[\nabla_\theta \mu_\theta(s)^T \nabla_a Q^\mu(s, a)] = \nabla_\theta J(\theta). \quad (4.16)$$

QED.

And now, we should construct  $Q^w(s, a)$  satisfying the first condition, the simple choice is,

$$Q^w(s, a) = (a - \mu_\theta(s))^T \nabla_\theta \mu_\theta(s)^T w + V^v(s), \quad (4.17)$$

where  $V^v(s) = v^T \phi_s$  is a baseline only depending on  $s$  such that  $Q^w$  looks like an advantage function. For convenience, we denote  $\phi(s, a) = \nabla_\theta \mu_\theta(s)(a - \mu_\theta)$ . Hence,

$$Q^w = \phi(s, a)^T w + v^T \phi_s. \quad (4.18)$$

The second condition is very difficult to satisfies in practice. Instead, we just use  $Q$ -learning, SARSA, or other algorithms to update  $w$ .

**Algorithm 4.1.3 (COPDAC-Q).** *Compatible off policy deterministic actor-critic with  $Q$ -learning critic updates as,*

$$\delta_t = r_t + \gamma Q^w(s_{t+1}, \mu_\theta(s_{t+1})) - Q^w(s_t, \mu_\theta(s_t)), \quad (4.19)$$

$$\theta_{t+1} = \theta_t + \alpha_\theta \nabla_\theta \mu_\theta(s) (\nabla_\theta \mu_\theta(s)^T w), \quad (4.20)$$

$$w_{t+1} = w_t + \alpha_w \delta_t \nabla_w Q^w = w_t + \alpha_w \delta_t \phi(s_t, a_t), \quad (4.21)$$

$$v_{t+1} = v_t + \alpha_v \delta_t \phi_{s_t} \quad (4.22)$$

It is well-known that off-policy  $Q$ -learning may diverge using linear function approximation. Hence, we use GTD to update critic by the following algorithm,

**Algorithm 4.1.4** (COPDAC-GQ). *Compatible off policy deterministic actor-critic with gradient Q-learning algorithm(TDC) updates as,*

$$\delta_t = r_t + \gamma Q^w(s_{t+1}, \mu_\theta(s_{t+1})) - Q^w(s_t, \mu_\theta(s_t)), \quad (4.23)$$

$$\theta_{t+1} = \theta_t + \alpha_\theta \nabla_\theta \mu_\theta(s) (\nabla_\theta \mu_\theta(s)^T w), \quad (4.24)$$

$$w_{t+1} = w_t + \alpha_w \delta_t \phi(s_t, a_t) - \alpha_w \gamma \phi(s_{t+1}, \mu_\theta(s_{t+1})) (\phi(s_t, a_t)^T u_t), \quad (4.25)$$

$$v_{t+1} = v_t + \alpha_v \delta_t \phi(s_t) - \alpha_v \gamma \phi(s_{t+1}) (\phi(s_t, a_t)^T u_t), \quad (4.26)$$

$$u_{t+1} = u_t + \alpha_u (\delta_t - \phi(s_t, a_t)^T u_t) \phi(s_t, a_t). \quad (4.27)$$

#### DDPG algorithm

Randomly initialize critic network  $Q^w(s, a)$  and  $\pi_\theta(s)$  with weights  $w$  and  $\theta$ .

Initialize target network  $Q_{\text{target}}$  and  $\pi_{\text{target}}$  with  $w^- \leftarrow w$  and  $\theta^- \leftarrow \theta$ ;

Initialize replay buffer  $B$

for episode = 1,  $M$  do

    Initialise a noisy random process  $\mathcal{N}$  for action exploration

    Receive initial observation states  $s_1$

    for  $t = 1, T$  do

        Select action  $a_t = \pi(s_t, \theta) + \mathcal{N}$

        Store transition  $(s_t, a_t, r_t, s_{t+1})$  in  $B$ .

        Sample random mini-batch of  $N$  transitions  $(s_i, a_i, r_i, s_{i+1})$  from  $B$

        Set  $y_i = r_i + \gamma Q_{\text{target}}(s_{i+1}, \pi_{\text{target}}(s_{i+1}))$ .

        Update critic by minimising the loss  $L(w) = \frac{1}{N} \sum_{i=1}^N (y_i - Q^w(s_i, a_i))^2$ .

        Update actor policy using the sampled policy gradient:

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_q \nabla_a Q^w(s, a)|_{s=s_i, a=a_i} \nabla_\theta \pi_\theta(s)|_{s=s_i}.$$

    Update target networks following soft updates:

$$w^- \leftarrow \tau w + (1 - \tau) w^-$$

$$\theta^- \leftarrow \tau \theta + (1 - \tau) \theta^-.$$



## References

- [1] Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pages 1057–1063, 2000.
- [2] Richard S Sutton, Hamid R. Maei, and Csaba Szepesvári. A convergent  $o(n)$  temporal-difference algorithm for off-policy learning with linear function approximation. In D. Koller, D. Schuurmans, Y. Bengio, and L. Bottou, editors, *Advances in Neural Information Processing Systems 21*, pages 1609–1616. Curran Associates, Inc., 2009.
- [3] Richard S Sutton, Hamid Reza Maei, Doina Precup, Shalabh Bhatnagar, David Silver, Csaba Szepesvári, and Eric Wiewiora. Fast gradient-descent methods for temporal-difference learning with linear function approximation. In *Proceedings of the 26th Annual International Conference on Machine Learning*, pages 993–1000. ACM, 2009.
- [4] Hamid Reza Maei. Gradient temporal-difference learning algorithms. 2011.
- [5] Thomas Degris, Martha White, and Richard S Sutton. Off-policy actor-critic. *arXiv preprint arXiv:1205.4839*, 2012.
- [6] David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *ICML*, 2014.