





Python. Requests module

Бутенко Сергій

План лекції









Make a Request

Making a request with Requests is very simple.

Begin by importing the Requests module:

```
>>> import requests
```

Now, let's try to get a webpage. For this example, let's get GitHub's public timeline:

```
>>> r = requests.get('https://api.github.com/events')
```

Now, we have a **Response** object called r. We can get all the information we need from this object.

Requests' simple API means that all forms of HTTP request are as obvious. For example, this is how you make an HTTP POST request:

```
>>> r = requests.post('https://httpbin.org/post', data={'key': 'value'})
```

Nice, right? What about the other HTTP request types: PUT, DELETE, HEAD and OPTIONS? These are all just as simple:

```
>>> r = requests.put('https://httpbin.org/put', data={'key': 'value'})
>>> r = requests.delete('https://httpbin.org/delete')
>>> r = requests.head('https://httpbin.org/get')
>>> r = requests.options('https://httpbin.org/get')
```



```
→ Become QA Auto git:(master) pip3 install requests --user

Requirement already satisfied: requests in /usr/lib/python3/dist-packages (2.22.0)
```



```
Collecting requests
  Downloading requests-2.28.1-py3-none-any.whl (62 kB)
                                        62 kB 2.0 MB/s
Requirement already satisfied: idna<4,>=2.5 in /usr/local/lib/python3.8/site-packages (from requests)
 (2.10)
Collecting charset-normalizer<3,>=2
  Downloading charset normalizer-2.1.0-py3-none-any.whl (39 kB)
Collecting urllib3<1.27,>=1.21.1
  Downloading urllib3-1.26.11-py2.py3-none-any.whl (139 kB)
                                       139 kB 3.8 MB/s
Collecting certifi>=2017.4.17
 Downloading certifi-2022.6.15-py3-none-any.whl (160 kB)
                                        160 kB 4.5 MB/s
Installing collected packages: charset-normalizer, urllib3, certifi, requests
```



```
→ Become QA Auto git:(master) sudo pip3 install requests --user
Requirement already satisfied: requests in /usr/lib/python3/dist-packages (2.22.0)
→ Become QA Auto git:(master)
```

О Практика



```
EXPLORER
                                                    pytest.ini
                                                                   test api.py X
                                                    tests > api > 💠 test_api.py
> OPEN EDITORS
                                                           You, seconds ago | 1 author (You)

∨ BECOME QA AUTO

                                                           import pytest
 > .pytest cache
 > config
 > modules
                                                           @pytest.mark.change
 ∨ tests
                                                           def test remove name(user):
  > __pycache__
                                                               user.name = ''
                                                               assert user.name == ''
  ∨ api
   > _pycache_
   test_api.py
                                                           @pytest.mark.check
                                                     10
   test_fixtures.py
                                                           def test_name(user):
                                                      11
  ∨ ui
                                                               assert user.name == 'Sergii'
                                                      12
   > _pycache_
                                                      13
   test_ui.py
                                                      14
                                                     15
                                                           @pytest.mark.check
  conftest.py
                                                           def test second name(user):
                                                      16
  = pytest.ini
                                                      17
                                                               assert user.second name == 'Butenko'
                                                      18
                                                     TERMINAL PROBLEMS DEBUG CONSOLE OUTPUT
> OUTLINE
> TIMELINE
> NPM SCRIPTS
```








```
test http.py X
  EXPLORER
 OPEN EDITORS
                               tests > api > dest http.py > ...
                                      import pytest

∨ BECOME QA AUTO

                                      import requests
  > .pytest cache
  > config
  > modules
                                      @pytest.mark.http
 ∨ tests
                                      def test first request():
   > pycache
                                           r = requests.get('https://api.github.com/zen')
                                           print(r.text)
                                 8
  ∨ api
   > __pycache__
   test_api.py
                         M
   test_fixtures.py
                         U
   test http.py
                         U
```









О Практика



Практика



```
EXPLORER
  OPEN EDITORS
∨ BECOME QA AUTO
  > .pytest cache
  > config
  > modules
 ∨ tests
   > __pycache__

√ api

    > pycache
    test_api.py
                           M
    test fixtures.py
                           U
    test http.py
                         1, U
   ∨ ui
    > pycache
    test ui.py
  conftest.py
                           U
  pytest.ini
                           U
```

```
test http.py X
                = pytest.ini
tests > api > dest http.py > ...
       import pytest
      import requests
      @pytest.mark.http
      def test first request():
           r = requests.get('https://api.github.com/zen')
           print(f"Response is {r.text}")
      @pytest.mark.http
 10
      def test second request():
 11
           r = requests.get('https://api.github.com/users/defunkt')
 12
           print(f"Response is {r.text}")
 13
 14
```

О Практика



```
Become OA Auto git:(master) X pytest -m http -s
------ test session starts ------
platform linux -- Python 3.8.10, pytest-7.1.2, pluggy-0.13.1
rootdir: /home/sbutenko/repos/LnD/Become QA Auto, configfile: pytest.ini
plugins: Faker-4.1.1, rerunfailures-9.1.1, forked-1.3.0, anyio-3.4.0, xdist-1.32
.O, allure-pytest-2.8.16, html-2.1.1, metadata-1.10.0, ordering-0.6, instafail-0
.4.2
collected 7 items / 5 deselected / 2 selected
tests/api/test http.py Response is Responsive is better than fast.
Response is {"login":"defunkt","id":2,"node id":"MDQ6VXNlcjI=","avatar url":"ht
tps://avatars.qithubusercontent.com/u/2?v=4","gravatar id":"","url":"https://api
aithub.com/users/defunkt"."html url":"https://aithub.com/defunkt"."followers ur.
l":"https://api.github.com/users/defunkt/followers","following url":"https://api
.github.com/users/defunkt/following{/other user}"."gists url":"https://api.githu
b.com/users/defunkt/qists{/qist id}","starred url":"https://api.qithub.com/users
/defunkt/starred{/owner}{/repo}","subscriptions_url":"https://api.github.com/use
rs/defunkt/subscriptions","organizations url":"https://api.github.com/users/defu
nkt/orgs","repos url":"https://api.github.com/users/defunkt/repos","events_url":
"https://api.github.com/users/defunkt/events{/privacy}","received events url":"h
ttps://api.github.com/users/defunkt/received events","type":"User","site admin":
false,"name":"Chris Wanstrath","company":null,"blog":"http://chriswanstrath.com/
 ."location":null."email":null."hireable":null."bio":" 🚭 ."twitter username":nul
 "public repos":107,"public gists":273,"followers":21451,"following":210,"creat,
ed at":"2007-10-20T05:24:19Z","updated at":"2022-06-01T23:46:26Z"}
```

Підсумки



- **Requests модуль** це модуль, який використовується для того, щоб відправити запити із коду
- Створили 2 теста, що відправляють запити на сервер ГітХаба