

Become QA Auto






НТТР. Як тестувати НТТР

Бутенко Сергій

⊙ План лекції







⊙ Задача





Написати тести для перевірки НТТР

© Тестування HTTP





© Тестування HTTP



Що перевіряти	Як перевіряти
HTTP response статус код	 Чи прийшов вам саме той статус код на який ви очікували
HTTP response тіло	• Чи вірні дані в тілі запиту
HTTP response заголовки	• Чи вірні дані в заголовках



```
EXPLORER
  OPEN EDITORS

∨ BECOME QA AUTO

  > .pytest cache
  > config
  > modules

∨ tests

   > __pycache__
   ∨ api
    > _pycache
    test api.py
    test fixtures.py
    test_http.py
                          1, U
   ∨ ui
    > _pycache
    test ui.py
   confrest ny
```

```
test http.py X
                = pytest.ini
tests > api > dest http.py > test second request
      import pytest
      import requests
      @pytest.mark.http
      def test first request():
           r = requests.get('https://api.github.com/zen')
           print(f"Response is {r.text}")
  9
      @pytest.mark.http
 10
      def test second request():
 11
 12
           r = requests.get('https://api.github.com/users/defunkt')
           print(f"Response Body is {r.json()}")
 13
           print(f"Response Status code is {r.status code}")
 14
           print(f"Response Headers are {r.headers}")
 15
 16
```



```
EXPLORER
  OPEN EDITORS

∨ BECOME QA AUTO

  > .pytest cache
  > config
  > modules

∨ tests

   > __pycache__
   ∨ api
    > _pycache
    test api.py
    test fixtures.py
    test_http.py
                          1, U
   ∨ ui
    > _pycache
    test ui.py
   confrest ny
```

```
test http.py X
                = pytest.ini
tests > api > dest http.py > test second request
      import pytest
      import requests
      @pytest.mark.http
      def test first request():
           r = requests.get('https://api.github.com/zen')
           print(f"Response is {r.text}")
  9
      @pytest.mark.http
 10
      def test second request():
 11
 12
           r = requests.get('https://api.github.com/users/defunkt')
           print(f"Response Body is {r.json()}")
 13
           print(f"Response Status code is {r.status code}")
 14
           print(f"Response Headers are {r.headers}")
 15
 16
```



```
test http.py X
                                              = pytest.ini
 EXPLORER
                             tests > api > dest http.py > test second request
 OPEN EDITORS
                                    import pytest

✓ BECOME OA AUTO

                                    import requests
 > .pytest cache
 > config
 modules
                                    @pytest.mark.http
 tests
                                    def test first request():
  > __pycache__
                                         r = requests.get('https://api.github.com/zen')
                                         print(f"Response is {r.text}")
                                8

✓ api

                                9
   > __pycache__
                                    @pytest.mark.http
                               10
   test api.py
                        M
                                    def test second request():
                               11
   test fixtures.py
                                         r = requests.get('https://api.github.com/users/defunkt')
                               12
   test_http.py
                      1, U
                                         print(f"Response Body is {r.json()}")
                               13
  ∨ ui
                                         assert r.status code == 200
                               14
                                         print(f"Response Headers are {r.headers}")
   > pycache
                               15
```



```
rootdir: /home/sbutenko/repos/LnD/Become QA Auto, configfile: pytest.ini
plugins: Faker-4.1.1, rerunfailures-9.1.1, forked-1.3.0, anyio-3.4.0, xdist-1.32.0, allure-pytest-2.8.16, html-2.1.1, metadata-1.
10.0, ordering-0.6, instafail-0.4.2
collected 7 items / 5 deselected / 2 selected
tests/api/test http.py Response is Mind your words, they are important.
Response Body is {'login': 'defunkt', 'id': 2, 'node id': 'MDQ6VXNlcjI=', 'avatar url': 'https://avatars.githubusercontent.com/u
/2?v=4', 'gravatar id': '', 'url': 'https://api.github.com/users/defunkt', 'html url': 'https://github.com/defunkt', 'followers u
rl': 'https://api.github.com/users/defunkt/followers', 'following url': 'https://api.github.com/users/defunkt/following{/other us
er}', 'gists_url': 'https://api.github.com/users/defunkt/gists{/gist_id}', 'starred_url': 'https://api.github.com/users/defunkt/s
tarred{/owner}{/repo}', 'subscriptions url': 'https://api.github.com/users/defunkt/subscriptions', 'organizations url': 'https://
api.github.com/users/defunkt/orgs', 'repos url': 'https://api.github.com/users/defunkt/repos', 'events url': 'https://api.github.
com/users/defunkt/events{/privacy}', 'received_events_url': 'https://api.github.com/users/defunkt/received_events', 'type': 'User
', 'site admin': False, 'name': 'Chris Wanstrath', 'company': None, 'blog': 'http://chriswanstrath.com/', 'location': None, 'emai
l': None, 'hireable': None, 'bio': '🍣', 'twitter username': None, 'public repos': 107, 'public gists': 273, 'followers': 21451,
'following': 210, 'created at': '2007-10-20T05:24:19Z', 'updated at': '2022-06-01T23:46:26Z'}
Response Headers are {'Server': 'GitHub.com', 'Date': 'Mon, 20 Jun 2022 19:02:29 GMT', 'Content-Type': 'application/json; charset
=utf-8', 'Cache-Control': 'public, max-age=60, s-maxage=60', 'Vary': 'Accept, Accept-Encoding, Accept, X-Requested-With', 'ETag':
 'W/"a139706aa40019d7e06c9bd50ba4626e24c8d51cd1d1c01854f4c6a72ad3f612"', 'Last-Modified': 'Wed, 01 Jun 2022 23:46:26 GMT', 'X-Git
Hub-Media-Type': 'github.v3; format=json', 'Access-Control-Expose-Headers': 'ETag, Link, Location, Retry-After, X-GitHub-OTP, X-R
ateLimit-Limit, X-RateLimit-Remaining, X-RateLimit-Used, X-RateLimit-Resource, X-RateLimit-Reset, X-OAuth-Scopes, X-Accepted-OAut
h-Scopes, X-Poll-Interval, X-GitHub-Media-Type, X-GitHub-SSO, X-GitHub-Request-Id, Deprecation, Sunset', 'Access-Control-Allow-Or
igin': '*', 'Strict-Transport-Security': 'max-age=31536000; includeSubdomains; preload', 'X-Frame<u>-Options': 'deny', 'X-Content-Ty</u>
pe-Options': 'nosniff', 'X-XSS-Protection': '0', 'Referrer-Policy': 'origin-when-cross-origin, strict-origin-when-cross-origin',
'Content-Security-Policy': "default-src 'none'", 'Content-Encoding': 'gzip', 'X-RateLimit-Limit': '60', 'X-RateLimit-Remaining':
'40'. 'X-RateLimit-Reset': '1655752270'. 'X-RateLimit-Resource': 'core'. 'X-RateLimit-Used': '20'. 'Accept-Ranges': 'bytes'. 'Con
tent-Length': '484', 'X-GitHub-Request-Id': '4EB8:4F1B:1ECBC2E:1FE54DD:62B0C445'}
```



```
rootdir: /home/sbutenko/repos/LnD/Become QA Auto, configfile: pytest.ini
plugins: Faker-4.1.1, rerunfailures-9.1.1, forked-1.3.0, anyio-3.4.0, xdist-1.32.0, allure-pytest-2.8.16, html-2.1.1, metadata-1.
10.0, ordering-0.6, instafail-0.4.2
collected 7 items / 5 deselected / 2 selected
tests/api/test http.py Response is Mind your words, they are important.
Response Body is {'login': 'defunkt', 'id': 2, 'node id': 'MDQ6VXNlcjI=', 'avatar url': 'https://avatars.githubusercontent.com/u
/2?v=4', 'gravatar id': '', 'url': 'https://api.github.com/users/defunkt', 'html url': 'https://github.com/defunkt', 'followers u
rl': 'https://api.github.com/users/defunkt/followers', 'following url': 'https://api.github.com/users/defunkt/following{/other us
er}', 'gists_url': 'https://api.github.com/users/defunkt/gists{/gist_id}', 'starred_url': 'https://api.github.com/users/defunkt/s
tarred{/owner}{/repo}', 'subscriptions url': 'https://api.github.com/users/defunkt/subscriptions', 'organizations url': 'https://
api.github.com/users/defunkt/orgs', 'repos url': 'https://api.github.com/users/defunkt/repos', 'events url': 'https://api.github.
com/users/defunkt/events{/privacy}', 'received_events_url': 'https://api.github.com/users/defunkt/received_events', 'type': 'User
', 'site admin': False, 'name': 'Chris Wanstrath', 'company': None, 'blog': 'http://chriswanstrath.com/', 'location': None, 'emai
l': None, 'hireable': None, 'bio': '🍣', 'twitter username': None, 'public repos': 107, 'public gists': 273, 'followers': 21451,
'following': 210, 'created at': '2007-10-20T05:24:19Z', 'updated at': '2022-06-01T23:46:26Z'}
Response Headers are {'Server': 'GitHub.com', 'Date': 'Mon, 20 Jun 2022 19:02:29 GMT', 'Content-Type': 'application/json; charset
=utf-8', 'Cache-Control': 'public, max-age=60, s-maxage=60', 'Vary': 'Accept, Accept-Encoding, Accept, X-Requested-With', 'ETag':
 'W/"a139706aa40019d7e06c9bd50ba4626e24c8d51cd1d1c01854f4c6a72ad3f612"', 'Last-Modified': 'Wed, 01 Jun 2022 23:46:26 GMT', 'X-Git
Hub-Media-Type': 'github.v3; format=json', 'Access-Control-Expose-Headers': 'ETag, Link, Location, Retry-After, X-GitHub-OTP, X-R
ateLimit-Limit, X-RateLimit-Remaining, X-RateLimit-Used, X-RateLimit-Resource, X-RateLimit-Reset, X-OAuth-Scopes, X-Accepted-OAut
h-Scopes, X-Poll-Interval, X-GitHub-Media-Type, X-GitHub-SSO, X-GitHub-Request-Id, Deprecation, Sunset', 'Access-Control-Allow-Or
igin': '*', 'Strict-Transport-Security': 'max-age=31536000; includeSubdomains; preload', 'X-Frame<u>-Options': 'deny', 'X-Content-Ty</u>
pe-Options': 'nosniff', 'X-XSS-Protection': '0', 'Referrer-Policy': 'origin-when-cross-origin, strict-origin-when-cross-origin',
'Content-Security-Policy': "default-src 'none'", 'Content-Encoding': 'gzip', 'X-RateLimit-Limit': '60', 'X-RateLimit-Remaining':
'40'. 'X-RateLimit-Reset': '1655752270'. 'X-RateLimit-Resource': 'core'. 'X-RateLimit-Used': '20'. 'Accept-Ranges': 'bytes'. 'Con
tent-Length': '484', 'X-GitHub-Request-Id': '4EB8:4F1B:1ECBC2E:1FE54DD:62B0C445'}
```



```
rootdir: /home/sbutenko/repos/LnD/Become QA Auto, configfile: pytest.ini
plugins: Faker-4.1.1, rerunfailures-9.1.1, forked-1.3.0, anyio-3.4.0, xdist-1.32.0, allure-pytest-2.8.16, html-2.1.1, metadata-1.
10.0, ordering-0.6, instafail-0.4.2
collected 7 items / 5 deselected / 2 selected
tests/api/test http.py Response is Mind your words, they are important.
Response Body is {'login': 'defunkt', 'id': 2, 'node id': 'MDQ6VXNlcjI=', 'avatar url': 'https://avatars.githubusercontent.com/u
/2?v=4', 'gravatar id': '', 'url': 'https://api.github.com/users/defunkt', 'html url': 'https://github.com/defunkt', 'followers u
rl': 'https://api.github.com/users/defunkt/followers', 'following url': 'https://api.github.com/users/defunkt/following{/other us
er}', 'gists_url': 'https://api.github.com/users/defunkt/gists{/gist_id}', 'starred_url': 'https://api.github.com/users/defunkt/s
tarred{/owner}{/repo}', 'subscriptions url': 'https://api.github.com/users/defunkt/subscriptions', 'organizations url': 'https://
api.github.com/users/defunkt/orgs', 'repos url': 'https://api.github.com/users/defunkt/repos', 'events url': 'https://api.github.
com/users/defunkt/events{/privacy}'. 'received events url': 'https://api.github.com/users/defunkt/received events'. 'type': 'User
', 'site admin': False, <mark>'</mark>name': 'Chris Wanstrath', 'company': None, 'blog': 'http://chriswanstrath.com/', <sup>'</sup>location': None, 'emai
l': None, 'hireable': None, 'bio': 😓 , 'twitter username': None, 'public repos': 107, 'public gists': 273, 'followers': 21451,
'following': 210, 'created at': '2007-10-20T05:24:19Z', 'updated at': '2022-06-01T23:46:26Z'}
Response Headers are {'Server': 'GitHub.com', 'Date': 'Mon, 20 Jun 2022 19:02:29 GMT', 'Content-Type': 'application/json; charset
=utf-8', 'Cache-Control': 'public, max-age=60, s-maxage=60', 'Vary': 'Accept, Accept-Encoding, Accept, X-Requested-With', 'ETag':
 'W/"a139706aa40019d7e06c9bd50ba4626e24c8d51cd1d1c01854f4c6a72ad3f612"', 'Last-Modified': 'Wed, 01 Jun 2022 23:46:26 GMT', 'X-Git
Hub-Media-Type': 'github.v3; format=json', 'Access-Control-Expose-Headers': 'ETag, Link, Location, Retry-After, X-GitHub-OTP, X-R
ateLimit-Limit, X-RateLimit-Remaining, X-RateLimit-Used, X-RateLimit-Resource, X-RateLimit-Reset, X-OAuth-Scopes, X-Accepted-OAut
h-Scopes, X-Poll-Interval, X-GitHub-Media-Type, X-GitHub-SSO, X-GitHub-Request-Id, Deprecation, Sunset', 'Access-Control-Allow-Or
igin': '*', 'Strict-Transport-Security': 'max-age=31536000; includeSubdomains; preload', 'X-Frame<u>-Options': 'deny', 'X-Content-Ty</u>
pe-Options': 'nosniff', 'X-XSS-Protection': '0', 'Referrer-Policy': 'origin-when-cross-origin, strict-origin-when-cross-origin',
'Content-Security-Policy': "default-src 'none'", 'Content-Encoding': 'gzip', 'X-RateLimit-Limit': '60', 'X-RateLimit-Remaining':
'40'. 'X-RateLimit-Reset': '1655752270'. 'X-RateLimit-Resource': 'core'. 'X-RateLimit-Used': '20'. 'Accept-Ranges': 'bytes'. 'Con
tent-Length': '484', 'X-GitHub-Request-Id': '4EB8:4F1B:1ECBC2E:1FE54DD:62B0C445'}
```



```
test http.py X
                                              = pytest.ini
 EXPLORER
                             tests > api > dest http.py > test second request
 OPEN EDITORS
                                    import pytest

✓ BECOME OA AUTO

                                    import requests
 > .pytest cache
 > config
 modules
                                    @pytest.mark.http
 tests
                                    def test first request():
  > __pycache__
                                         r = requests.get('https://api.github.com/zen')
                                         print(f"Response is {r.text}")
                                8
  ∨ api
   > __pycache__
                                    @pytest.mark.http
                               10
   test api.py
                        M
                                    def test second request():
                               11
   test fixtures.py
                                         r = requests.get('https://api.github.com/users/defunkt')
                               12
   test_http.py
                      1, U
                                         print(f"Response Body is {r.json()}")
                               13
  ∨ ui
                                         assert r.status code == 200
                               14
                                         print(f"Response Headers are {r.headers}")
   > pycache
                               15
```



```
EXPLORER
                            tests > api > dest_http.py > ...
 OPEN EDITORS
                                   import pytest

∨ BECOME OA AUTO

                                   import requests
 > .pytest cache
 > config
 > modules
                                   @pytest.mark.http

∨ tests

                                   def test first request():
  > pycache
                                       r = requests.get('https://api.github.com/zen')
                                       print(f"Response is {r.text}")
                               8
  ∨ api
   > pycache
                                   @pytest.mark.http
                              10
   test_api.py
                       M
                                   def test second request():
                              11
   test fixtures.py
                              12
                                       r = requests.get('https://api.github.com/users/defunkt')
   test http.py
                      1, U
                                       body = r.json()
                              13
  ∨ ui
                              14
                                       assert body['name'] == 'Chris Wanstrath'
                              15
   > __pycache__
                                       assert r.status code == 200
                              16
   test ui.py
                                       print(f"Response Headers are {r.headers}")
                              17
  conftest.pv
```



```
Become OA Auto git:(master) X pytest -m http -s
platform linux -- Python 3.8.10, pytest-7.1.2, pluggy-0.13.1
rootdir: /home/sbutenko/repos/LnD/Become QA Auto, configfile: pytest.ini
plugins: Faker-4.1.1, rerunfailures-9.1.1, forked-1.3.0, anyio-3.4.0, xdist-1.32.0, allure-pytest-2.8.16, html-2.1.1, metadata-1.
10.0. ordering-0.6. instafail-0.4.2
collected 7 items / 5 deselected / 2 selected
tests/api/test http.py Response is Responsive is better than fast.
Response Headers are {'Server': 'GitHub.com', 'Date': 'Mon, 20 Jun 2022 19:19:14 GMT', 'Content-Type': 'application/json; charse
t=utf-8', 'Cache-Control': 'public, max-age=60, s-maxage=60', 'Varv': 'Accept, Accept-Encoding, Accept, X-Requested-With', 'ETag'
 'W/"a139706aa40019d7e06c9bd50ba4626e24c8d51cd1d1c01854f4c6a72ad3f612"', 'Last-Modified': 'Wed, 01 Jun 2022 23:46:26 GMT', 'X-Gi
tHub-Media-Type': 'github.v3; format=json', 'Access-Control-Expose-Headers': 'ETag, Link, Location, Retry-After, X-GitHub-OTP, X-
RateLimit-Limit, X-RateLimit-Remaining, X-RateLimit-Used, X-RateLimit-Resource, X-RateLimit-Reset, X-OAuth-Scopes, X-Accepted-OAu
th-Scopes, X-Poll-Interval, X-GitHub-Media-Type, X-GitHub-SSO, X-GitHub-Request-Id, Deprecation, Sunset', 'Access-Control-Allow-O
rigin': '*', 'Strict-Transport-Security': 'max-age=31536000; includeSubdomains; preload', 'X-Frame-Options': 'deny', 'X-Content-T
vpe-Options': 'nosniff'. 'X-XSS-Protection': '0'. 'Referrer-Policy': 'origin-when-cross-origin. strict-origin-when-cross-origin',
'Content-Security-Policy': "default-src 'none'", 'Content-Encoding': 'gzip', 'X-RateLimit-Limit': '60', 'X-RateLimit-Remaining':
'55', 'X-RateLimit-Reset': '1655756230', 'X-RateLimit-Resource': 'core', 'X-RateLimit-Used': '5', 'Accept-Ranges': 'bytes', 'Con
tent-Length': '484', 'X-GitHub-Request-Id': '7097:0C89:1EF6AEB:1FB5898:62B0C832'}
```

Перевірка заголовків ріспонсу



```
EXPLORER
                            tests > api > dest_http.py > ...
 OPEN EDITORS
                                   import pytest

∨ BECOME OA AUTO

                                   import requests
 > .pytest cache
 > config
 > modules
                                   @pytest.mark.http

∨ tests

                                   def test first request():
  > pycache
                                       r = requests.get('https://api.github.com/zen')
                                       print(f"Response is {r.text}")
                               8
  ∨ api
   > pycache
                                   @pytest.mark.http
                              10
   test_api.py
                       M
                                   def test second request():
                              11
   test fixtures.py
                              12
                                       r = requests.get('https://api.github.com/users/defunkt')
   test http.py
                      1, U
                                       body = r.json()
                              13
  ∨ ui
                              14
                                       assert body['name'] == 'Chris Wanstrath'
                              15
   > __pycache__
                                       assert r.status code == 200
                              16
   test ui.py
                                       print(f"Response Headers are {r.headers}")
                              17
  conftest.py
```

Перевірка заголовків ріспонсу



```
test http.py X
                                               = pytest.ini
 EXPLORER
 OPEN EDITORS
                              tests > api > dest http.py > ...
                                     import pytest
∨ BECOME QA AUTO
                                     import requests
 > .pytest cache
 > config
 > modules
                                     @pytest.mark.http

∨ tests

                                     def test first request():
   > __pycache__
                                         r = requests.get('https://api.github.com/zen')
                                         print(f"Response is {r.text}")
  ∨ api
   > pycache
                                     @pytest.mark.http
                               10
   test api.py
                                     def test second request():
                               11
   test fixtures.py
                               12
                                         r = requests.get('https://api.github.com/users/defunkt')
   test http.py
                       1, U
                               13
                                         body = r.json()
  ∨ ui
                                         headers = r.headers
                               14
                               15
    > pycache
                                         assert body['name'] == 'Chris Wanstrath'
                               16
   test ui.py
                               17
                                         assert r.status code == 200
  conftest.pv
                                         assert headers['Server'] == 'GitHub.com'
                               18
  = putact ini
```



```
Become OA Auto git:(master) X pytest -m http -s
platform linux -- Python 3.8.10, pytest-7.1.2, pluggy-0.13.1
rootdir: /home/sbutenko/repos/LnD/Become OA Auto, configfile: pytest.ini
plugins: Faker-4.1.1. rerunfailures-9.1.1. forked-1.3.0. anvio-3.4.0. xdist-1.32.0. allure-pytest-2.8.16. html-2.1.1. metadata-1.
10.0. ordering-0.6. instafail-0.4.2
collected 7 items / 5 deselected / 2 selected
tests/api/test http.pv_Response is_Responsive is_better_than_fast.
Response Headers are {'Server': 'GitHub.com', 'Date': 'Mon, 20 Jun 2022 19:19:14 GMT', 'Content-Type': 'application/json; charse
t<u>=utf-8', 'Cache</u>-Control: public, max-age=ov, s-maxage=60', 'Vary': 'Accept, Accept-Encoding, Accept, X-Requested-With', 'ETag'
 'W/"a139706aa40019d7e06c9bd50ba4626e24c8d51cd1d1c01854f4c6a72ad3f612"', 'Last-Modified': 'Wed, 01 Jun 2022 23:46:26 GMT', 'X-Gi
tHub-Media-Type': 'qithub.v3; format=json', 'Access-Control-Expose-Headers': 'ETaq, Link, Location, Retry-After, X-GitHub-OTP, X-
RateLimit-Limit. X-RateLimit-Remaining. X-RateLimit-Used. X-RateLimit-Resource. X-RateLimit-Reset. X-OAuth-Scopes. X-Accepted-OAu
th-Scopes, X-Poll-Interval, X-GitHub-Media-Type, X-GitHub-SSO, X-GitHub-Request-Id, Deprecation, Sunset', 'Access-Control-Allow-O
rigin': '*', 'Strict-Transport-Security': 'max-age=31536000; includeSubdomains; preload', 'X-Frame-Options': 'deny', 'X-Content-T
vpe-Options': 'nosniff'. 'X-XSS-Protection': '0'. 'Referrer-Policy': 'origin-when-cross-origin. strict-origin-when-cross-origin'.
'Content-Security-Policy': "default-src 'none'", 'Content-Encoding': 'gzip', 'X-RateLimit-Limit': '60', 'X-RateLimit-Remaining':
'55', 'X-RateLimit-Reset': '1655756230', 'X-RateLimit-Resource': 'core', 'X-RateLimit-Used': '5', 'Accept-Ranges': 'bytes', 'Con
tent-Length': '484', 'X-GitHub-Request-Id': '7097:0C89:1EF6AEB:1FB5898:62B0C832'}
```



Негативний тест



```
test http.py X
                                               = pytest.ini
 EXPLORER
                              tests > api > 🕏 test_http.py > 😭 test_status_code_request
 OPEN EDITORS

∨ BECOME QA AUTO

                                         print(f"Response is {r.text}")
                                8
 > .pytest cache
                               10
                                     @pytest.mark.http
 > config
                                     def test second request():
                               11
  modules
                                         r = requests.get('https://api.github.com/users/defunkt')
                               12
 ∨ tests
                                         body = r.json()
                               13
  > pycache
                                         headers = r.headers
                               14

√ api

                               15
   > _pycache
                                         assert body['name'] == 'Chris Wanstrath'
                               16
                               17
                                         assert r.status code == 200
   test api.py
                                         assert headers['Server'] == 'GitHub.com'
                               18
   test fixtures.py
                               19
   test http.py
                       1, U
                               20
  ∨ ui
                               21
                                     @pytest.mark.http
    > pycache
                                     def test status code request():
                               22
   test ui.py
                                         r = requests.get('https://api.github.com/users/sergii butenko')
                               23
  conftest.pv
                        U
                               24
                               25
                                         assert r.status code == 200
                        U
 = pytest.ini
```

Негативний тест



```
Become QA Auto git:(master) X pytest -m http -s
   platform linux -- Python 3.8.10, pytest-7.1.2, pluggy-0.13.1
rootdir: /home/sbutenko/repos/LnD/Become OA Auto, configfile: pytest.ini
plugins: Faker-4.1.1, rerunfailures-9.1.1, forked-1.3.0, anyio-3.4.0, xdist-1.32.0, a
llure-pytest-2.8.16, html-2.1.1, metadata-1.10.0, ordering-0.6, instafail-0.4.2
collected 8 items / 5 deselected / 3 selected
tests/api/test http.py Response is It's not fully shipped until it's fast.
     @pytest.mark.http
   def test status code request():
      r = requests.get('https://api.github.com/users/sergii butenko')
      assert r.status code == 200
                 :25: AssertionError
FAILED tests/api/test http.py::test status code request - assert 404 == 200
                      d. 2 passed. 5 deselected
```

Негативний тест



```
EXPLORER
                              test http.py ×
                                               = pytest.ini
                              tests > api > 🟓 test_http.py > ...
 OPEN EDITORS

∨ BECOME QA AUTO

                                         print(f"Response is {r.text}")
 > .pytest cache
                               10
                                     @pytest.mark.http
 > config
                                     def test second request():
                               11
 > modules
                               12
                                          r = requests.get('https://api.github.com/users/defunkt')
 v tests
                               13
                                         body = r.json()
   > __pycache__
                                         headers = r.headers
                               14
  ∨ api
                               15
    > __pycache__
                                          assert body['name'] == 'Chris Wanstrath'
                               16
                                          assert r.status code == 200
                               17
   test_api.py
                                          assert headers['Server'] == 'GitHub.com'
                               18
   test fixtures.py
                               19
   test http.py
                       1, U
                               20
  ∨ ui
                                     @pytest.mark.http
                               21
   > pycache
                               22
                                     def test status code request():
   test ui.py
                               23
                                          r = requests.get('https://api.github.com/users/sergii butenko')
  conftest.py
                        U
                               24
                               25
                                          assert r.status code == 404
 = pytest.ini
```

О Негативний тест



О Підсумки



- Навчилися:
- Тестувати статус код
- **Тестувати** тіло ріспонса
- **Тестувати** заголовки