

Question 1

- (1) FALSE ("ai" occurs 3 times)
- (2) TRUE (if both child nodes have the same majority class, then the parent node will also have that same majority class)
- (3) FALSE (they are equivalent if they have the same skeleton and *v-structures*)
- (4) FALSE (each split)
- (5) TRUE
- (6) TRUE (candidates are generated by taking a frequent tree, and adding a node with a frequent label using right-most extension)
- (7) TRUE
- (8) FALSE
- (9) FALSE (Counterexample: r = AD, s = ABD, d = ABCD)
- (10) TRUE

Question 2

x <= 10, x <= 14, x <= 18

Question 3

g(t) = (8/100-0)/(5-1) = 2/100 = 0.02

Question 4

Most unfavorable case for the root node is if each class has relative frequency 1/3.
Then the resubstitution error is 2/3 and total cost of the root is 2/3 + a.
Most favorable case for Tmax is when 2 splits are sufficient to get pure leaf nodes.
Then total cost of Tmax is 0 + 3a. Total cost is equal when 2/3 + a = 3a, hence for a = 1/3.
Therefore the root node is guaranteed to have the same or lower total cost than Tmax for a >= 0.33.

Question 5

- (a) The maximum likelihood fitted counts are given by the formula: n(A,B,D)n(C,D)/n(D).
- (b) The number of u-terms is 10.

Question 6

Level 2 generators: BD, CD
Closed frequent item sets: ABC, BC, CD, BCD, D.

Question 7

- (a) 1/7
- (b) 361/655

Question 8

- (a) 1/(1+exp(-0.4)) = 0.5986877, so the answer is: 0.60
- (b) -0.4 + 0.05x = 0, ==> x = 8, so 8 minutes.
- (c) exp(10*0.05)= 1.648721, so 65 percent.

Question 9

- (a) 1721 * log(1721/2000) + 279 * log(279/2000) = -808.1096, so the answer is -808.11
- (b) 429 * log(429/495) + 66 * log(66/495) + 1292 * log(1292/1505) + 213 * log(213/1505) = -808.0045, so the answer is -808.00
- (c) There are 29 parameters in the model, at log(2000)/2 = 3.800451 each, so the total size of the complexity penalty is 29 * 3.800451 = 110.21

Question 10

remove(A --> D) and remove(C --> D)