

NAME

pidswallow – swallow using pid(s).

SYNOPSIS

pidswallow [-Vg] [-s|-v|-t <WINDOW_ID>] [-s|-v|-t <WINDOW_ID>]...

pidswallow [-Vg] WINDOW_ID

pidswallow [-Vg] [-l]

DESCRIPTION

pidswallow A super easy to config script written to auto hide the terminal window. (so that you don't have to). Window Manager agnostic.

OPTIONS

- s **--swallow** <WINDOW_ID>
Hides parent window of the given child window id.
- v **--vommit** <WINDOW_ID>
Unhides parent window of the given child window id.
- t **--toggle** <WINDOW_ID>
Toggle between swallow and vomit. (default if no flag is specified)
- g **--glue**
Treat if parent and child window are same. (recommended)
- l **--loop**
Listen and hide / unhide window on launch / remove. (Blocking)
- V **--verbose**
Shows useful information.

EXAMPLES

pidswallow -Vs <WINDOW_ID>
Swallow the parent window and print details.

xdotool getwindowfocus | pidswallow -t
Toggle the window (use WINDOW_ID of the focused window).

pidswallow -Vgl
Listens window events and automatically swallow/vomit windows, print details and treat if they are glued together.

BUGS

Report here: <https://github.com/Liupold/pidswallow/issues>

AUTHORS

- Rohn Chatterjee <rohnc@protonmail.ch>
- SeerLite <seerlite@tuta.io>