«««< HEAD ======= »»»> cb384a004be5a3fb57bbb060fd858090f90efe12

GHXTox: Peptide toxicity prediction by fusing a task-adaptive protein language model with pLDDT-aware multi-scale 3D structural modeling

LaLaLa, LaLaLa, LaLaLa, LaLaLa

Abstract

As biomedical research advances from the cellular to the molecular level, peptides have become increasingly important as a versatile class of bioactive molecules and are now widely used in the targeted treatment of diseases such as Parkinson's disease and cancer. However, toxicity assessment remains a critical bottleneck in peptide-based drug development. Existing methods have begun to explore multi-dimensional (multimodal) feature fusion and toxicity prediction based on the three-dimensional (3D) conformations of peptides, yet most of them still underutilize 3D structural information, and systematic multi-dimensional fusion remains rare. Here, we propose GHXTox, a hierarchical dual-level fusion framework. In the first level, a sequence-enhanced 3D structural expert integrates sequence semantics with spatial structural features through predicted local-distance difference test (pLDDT)-aware cross-attention. In the second level, this structural expert is fused with a task-adaptive one-dimensional (1D) sequence expert at the probability level, using weights frozen on training out-of-fold (OOF) predictions. The 1D branch analyzes sequences with a task-adaptive protein language model (ProtT5 fine-tuned with low-rank adaptation, LoRA) and a bidirectional Mamba state-space model. The 3D expert integrates an ESMFold-derived structural anchor, pLDDT-aware residue geometry, full-atom-derived chemical sites, and an availability-masked conformer-statistics residual for peptides with valid ensemble information; samples without conformer statistics fall back exactly to the single-structure pathway. On the frozen historical benchmark test sets, GHXTox achieves Test1 MCC of 0.8750 and AUPRC of 0.9668, and Test2 MCC of 0.6673 and AUPRC of 0.8012, while providing more detailed biological interpretations for peptide toxicity prediction.

Keywords: peptide toxicity prediction; multimodal deep learning; protein language model; bidirectional Mamba; pLDDT-aware multi-scale 3D modeling; interpretability

1 INTRODUCTION

As biomedical research advances from the cellular to the molecular level, peptides have become increasingly important as a versatile class of bioactive molecules and are now widely used in the targeted treatment of diseases such as Parkinson's disease and cancer [CITE: peptide-based therapeutics review]. Peptide toxicity is a critical safety consideration throughout the drug development pipeline, and the accurate and efficient identification of toxic peptides remains a major bottleneck in peptide-based drug discovery [CITE: ToxMSRC, Zhang et al. 2025]. Because conventional experimental toxicity assays are costly, time-consuming, and difficult to scale, reliable computational predictors are highly desirable.

Computational peptide toxicity prediction has evolved from traditional machine learning methods based on handcrafted physicochemical features toward deep learning approaches with stronger representation-learning capability. Current mainstream methods can be roughly grouped into two categories. The first category operates on sequence-level (one-dimensional, 1D) and/or atomic-level (two-dimensional, 2D) representations. For example, ToxMSRC combines continuous bag-of-words (CBOW) embeddings, multi-scale convolutional neural networks,

and a bidirectional long short-term memory network with residual connections, achieving strong performance on the benchmark dataset [CITE: ToxMSRC, Zhang et al. 2025]. ToxPLTC integrates pooled ProtT5 embeddings, borderline-SMOTE augmentation, and a text convolutional neural network [CITE: ToxPLTC, Liang et al. 2026]. ToxiPep fuses context-aware sequence representations with atomic-level graphs through a cross-attention mechanism [CITE: ToxiPep, Guan et al. 2025]. HyPepTox-Fuse further combines embeddings from multiple protein language models with conventional descriptors [CITE: HyPepTox-Fuse, Tran et al. 2025]. Although these models achieve strong performance within their respective modalities, they largely neglect the three-dimensional (3D) conformations of peptides, which are closely related to toxicity; cross-dimensional information interaction and mutual validation remain limited, and their interpretability is mostly confined to the sequence level.

The second category attempts to exploit 3D structural information. PeptiTox uses ESM2 sequence embeddings together with ESMFold-predicted 3D structures and geometric graph neural networks [CITE: PeptiTox, Wang et al. 2025]. StrucToxNet feeds ProtT5 sequence embeddings and ESMFold-predicted structures into an equivariant graph neural network (EGNN) and systematically analyzes structural quality [CITE: StrucToxNet, Jiao et al. 2025]. These studies demonstrate the value of 3D conformations for toxicity prediction. However, such methods are constrained by the limited accuracy of current structure prediction models on short peptides and typically rely on a single predicted conformation; structural confidence, i.e., the predicted local distance difference test (pLDDT) score, is either discarded through hard filtering or ignored, and multi-conformer ensembles are not considered. Moreover, the fusion between the sequence and structure branches remains relatively shallow, and no systematic multi-dimensional fusion that combines a task-adaptive sequence model with confidence-aware multi-scale structure modeling has been established.

To address these limitations, we propose GHXTox, an interpretable hierarchical dual-level fusion framework for peptide toxicity prediction. In the first level, a sequence-enhanced 3D structural expert integrates sequence semantics with spatial structural features through pLDDT-aware cross-attention. In the second level, this structural expert is fused with a task-adaptive 1D sequence expert at the probability level, with weights frozen on training out-of-fold (OOF) predictions. In the 1D branch, a task-adaptive protein language model (ProtT5 fine-tuned with low-rank adaptation, LoRA) is combined with a bidirectional Mamba state-space model for sequence analysis [CITE: ProtT5, LoRA, Mamba]. In the 3D branch, ESMFold provides a common single-structure anchor for all peptides, while an optional availability-masked conformer-statistics residual is incorporated for the prespecified PepFlow-covered subset [CITE: ESMFold and conformer-generation models]. On this basis, we design a multi-scale structural information extraction strategy that progressively captures structural cues from local residue functional groups (chemical sites) to the whole peptide, and the pLDDT confidence output by structure prediction models is exploited through continuous down-weighting and dynamic gating of structural features. The 1D ensemble probability is first calibrated using training out-of-fold predictions, after which the calibrated 1D probability and the structural-expert probability are combined using OOF-frozen fusion weights. Ablation experiments demonstrate that the two dimensions complement each other effectively and that the fusion improves several fixed-threshold and probability-quality measures on Test1 while maintaining broadly comparable performance on Test2; interpretability analyses provide more detailed biological explanations for the predictions.

In summary, the main contributions of this work are threefold: (1) we propose GHXTox, an interpretable hierarchical dual-level fusion framework that integrates a task-adaptive 1D protein language model with pLDDT-aware multi-scale 3D structure modeling; (2) the 3D branch designs a multi-scale structural information extraction strategy spanning from local residue functional groups to the whole peptide, and incorporates pLDDT confidence into structural feature processing through continuous down-weighting and dynamic gating; and (3) extensive

experiments on the frozen historical benchmark test sets show that GHXTox improves several fixed-threshold and probability-quality measures on Test1 while maintaining broadly comparable performance on Test2, and ablation, robustness, and interpretability analyses confirm the effectiveness and complementarity of the two dimensions.

2 MATERIALS AND METHODS

2.1 Datasets

We evaluate GHXTox on the benchmark datasets constructed by CAPTP [CITE: CAPTP] and subsequently adopted by ToxMSRC [CITE: ToxMSRC, Zhang et al. 2025]. Following the data construction protocol of ToxMSRC [CITE: ToxMSRC, Zhang et al. 2025], toxic peptide sequences were merged from three databases, namely CSM-Toxin [CITE: CSM-Toxin], ToxinPred2 [CITE: ToxinPred2], and ATSE [CITE: ATSE], and sequences longer than 50 residues were removed. Non-toxic sequences were retrieved from UniProt [CITE: UniProt] using the query "NOT KW-0800 AND NOT KW-0020 AND reviewed:true", and sequences containing non-standard amino acids or exceeding 50 residues were excluded. After combining the two groups and removing samples with conflicting labels, CD-HIT [CITE: CD-HIT] was applied with a sequence-identity threshold of 0.9 to eliminate redundant sequences, yielding 2,138 toxic and 5,375 non-toxic peptides. Following the same partition as ToxMSRC [CITE: ToxMSRC, Zhang et al. 2025], we used 85% of the data as the training set and the remaining 15% as the benchmark Test1 set, resulting in 1,818 toxic and 4,569 non-toxic training peptides and 320 toxic and 806 non-toxic Test1 peptides. An additional benchmark Test2 set, containing 46 toxic and 536 non-toxic peptides, is used for frozen historical evaluation. Both Test1 and Test2 had been observed during historical project development and are therefore treated as frozen historical benchmarks rather than newly blinded external validation sets; their labels were not used in the formal OOF calibration, fusion-weight selection, or threshold-freezing procedure. Table **??** summarizes the statistics of the datasets used in this study.

Table 1: Statistics of the datasets used in this study.

Dataset	Toxic	Non-toxic	Total	Use
Training (benchmark)	1,818	4,569	6,387	Model training
Test1 (benchmark)	320	806	1,126	Benchmark test
Test2	46	536	582	Benchmark test

2.2 Overview of the Model

Figure **??** shows an overview of GHXTox, a hierarchical dual-level fusion framework for peptide toxicity prediction. The framework consists of a task-adaptive one-dimensional (1D) sequence expert, a sequence-enhanced three-dimensional (3D) structural expert, and a probability fusion module driven by training out-of-fold (OOF) predictions. Within the structural expert, GHXTox first performs feature-level interaction between sequence semantics and spatial structural information through pLDDT-aware cross-attention. At the top level of the model, the prediction probabilities produced by the 1D sequence expert and the 3D structural expert are then fused at the decision level. GHXTox therefore combines intra-expert feature-level fusion with inter-expert probability-level fusion, preserving the independent discriminative capability of each branch while exploiting complementary information from amino acid sequences, spatial geometry, local chemical environments, and conformational variability.

Figure 1: Overall architecture of GHXTox. GHXTox adopts a hierarchical dual-level fusion design. The task-adaptive 1D sequence expert extracts toxicity-related sequence features with a LoRA-fine-tuned ProtT5 encoder and a bidirectional Mamba network, followed by three-seed ensembling and out-of-fold (OOF) Platt calibration to produce p_{1D}. The sequence-enhanced 3D structural expert extracts multi-scale structural information through an ESM2-enhanced sequence encoder, a pLDDT-aware equivariant graph neural network, full-atom chemical-site modeling, and an availability-masked conformer residual branch. Within this expert, sequence and spatial residue representations are integrated through pLDDT-aware cross-attention to produce p_{SE3D}. The two expert probabilities are fused with frozen weights of 0.72 and 0.28, and the final toxicity decision is obtained with a threshold of 0.4702.

2.2.1 Task-Adaptive 1D Sequence Expert

The task-adaptive 1D sequence expert takes the amino acid sequence of a peptide as input. After tokenization, the sequence is processed by the ProtT5 protein language model [CITE: ProtT5, Elnaggar et al. 2021] to obtain contextualized, residue-level representations. To adapt this general-purpose protein language model to peptide toxicity prediction, we employ low-rank adaptation (LoRA) [CITE: LoRA, Hu et al. 2022] for parameter-efficient fine-tuning, learning task-specific updates while the majority of the pretrained backbone parameters remain frozen. The resulting residue-level representations are then fed into a bidirectional Mamba state-space network [CITE: Mamba, Gu and Dao 2023], which models residue dependencies in both the N-to-C and C-to-N directions. After residual connections, layer normalization, and masked pooling, a classification head produces the sequence-level toxicity probability. To reduce the variance arising from random initialization, we train three models on the full training set with different random seeds and average their output probabilities. The ensemble probability is then calibrated with Platt scaling [CITE: Platt 1999] fitted exclusively on training out-of-fold (OOF) predictions, yielding the final 1D expert probability p_{1D}.

2.2.2 Sequence-Enhanced 3D Structural Expert

The sequence-enhanced 3D structural expert comprises four subbranches: an internal sequence-semantic subbranch, a spatial-geometric subbranch, a full-atom chemical-site subbranch, and an availability-masked conformer-ensemble residual subbranch. Collectively, these components cover five complementary representation scales: residue-level semantics, atom-level chemical sites, spatial residue neighborhoods, peptide-level global properties, and conformer-ensemble statistics. In the sequence-semantic subbranch, amino acid residue types, functional-group properties, explicit physicochemical descriptors, and ESM2 residue embeddings [CITE: ESM2] are projected into a shared feature space and then processed by a two-layer Transformer encoder [CITE: Transformer] to generate contextualized sequence representations. In parallel, the spatial-geometric subbranch constructs a hybrid residue graph that combines sequential adjacency edges with spatial-neighborhood edges derived from the predicted peptide structure. Residue physicochemical properties, local geometric descriptors, ESM2 embeddings, three-dimensional coordinates, and residue-level pLDDT scores are then fed into three pLDDT-aware equivariant graph neural network (EGNN) [CITE: EGNN] layers to update the residue states and spatial representations.

To characterize local chemical environments that cannot be fully captured by «««< HEAD a C_α-based residue graph alone, we extract chemical sites corresponding to ======= a Cα-based residue graph alone, we extract chemical sites corresponding to »»»> cb384a004be5a3fb57bbb060fd858090 charged, aromatic, and hydrophobic groups as well as hydrogen-bond donors and acceptors from the full-atom peptide structure. Message passing [CITE: MPNN, Gilmer et al. 2017] is then performed over these sites using pairwise distances, directional relationships, interaction

types, and structural confidence. The resulting chemical-site features are mapped back into the corresponding residue-level representations through a zero-initialized residual projection. This design allows the model to progressively learn toxicity-related local spatial–chemical patterns while preserving the initial geometric backbone. For peptides with available conformer ensembles, the model further extracts residue-level root-mean-square fluctuation (RMSF), pairwise distance variance, contact occupancy under multiple distance cutoffs, and peptide-level root-mean-square deviation (RMSD) and radius of gyration. These statistics are incorporated through an availability-masked residual branch to refine the structural expert's output. When conformer-ensemble information is unavailable, this residual contribution is constrained to exactly zero.

Within the structural expert, the contextualized sequence and confidence-aware spatial representations are integrated through pLDDT-aware cross-attention, followed by peptide-level confidence gating; the detailed construction is given in Section 2.4.6. After masked mean pooling, fusion with global peptide-level physicochemical features, and multilayer perceptron (MLP) classification, the sequence-enhanced structural expert obtains a base structural logit. The base structural logit is further corrected by an availability-masked, zero-initialized conformer residual before being transformed into the structural-expert probability p_{SE3D}.

2.2.3 Hierarchical Fusion and Toxicity Decision

At the top level of the model, the calibrated 1D sequence expert and the sequence-enhanced 3D structural expert are not combined through further intermediate-feature concatenation; instead, their outputs are fused with fixed weights in the probability space. The final toxicity probability is defined as

$$p_{\mathrm{GHXTox}} = 0.62\, p_{\mathrm{1D}} + 0.38\, p_{\mathrm{SE3D}}. \tag{1}$$

The larger sequence-expert weight is an empirical outcome of the OOF fusion search rather than a manually assigned prior; the structural expert provides complementary evidence on spatial geometry, local chemical environments, and conformational dynamics. The fusion weights are determined exclusively from group-aware training out-of-fold (OOF) predictions and are frozen before evaluation on the frozen historical benchmark test sets. In the implementation, the two expert probabilities are likewise combined linearly, without re-optimizing the fusion parameters on the test data.

Finally, the fused probability is converted into a binary toxicity prediction using a fixed decision threshold:

$$\hat{y} = \begin{cases} 1, & p_{\mathrm{GHXTox}} \geq 0.4702, \\ 0, & p_{\mathrm{GHXTox}} < 0.4702, \end{cases} \tag{2}$$

where $\hat{y} = 1$ denotes a toxic peptide and $\hat{y} = 0$ denotes a non-toxic peptide. The probability-calibration parameters, expert-fusion weights, and classification threshold are all determined solely from training out-of-fold (OOF) predictions; Test1 and Test2 are reserved exclusively for final frozen evaluation. This hierarchical design enables fine-grained sequence–structure interaction through pLDDT-aware cross-attention inside the structural expert, while the frozen probability-level fusion at the top level enhances inter-expert complementarity and predictive stability.

2.3 Task-Adaptive 1D Sequence Modeling

The 1D sequence expert is designed to learn toxicity-related contextual semantics and sequential dependencies directly from peptide amino acid sequences. Instead of reducing a frozen protein-language-model output to a fixed mean vector, GHXTox preserves the residue-level representations generated by ProtT5 and adapts the pretrained encoder to the peptide toxicity

prediction task through low-rank adaptation (LoRA). The resulting residue-level representations are then processed by a bidirectional Mamba state-space encoder to jointly model local residue patterns, N-to-C dependencies, and C-to-N dependencies. The encoded residue features are aggregated via masked mean pooling and passed to a linear classification head to produce the single-model toxicity probability. Finally, three models trained on the full training set with different random seeds are combined by equal-weight probability averaging, followed by Platt calibration fitted exclusively on training out-of-fold (OOF) predictions, yielding the final 1D expert probability p_{1D}.

This design organizes pretrained protein semantics, parameter-efficient task adaptation, bidirectional sequence modeling, and probability calibration into a coherent processing pipeline. While most of the pretrained knowledge in ProtT5 is retained, LoRA enables task-specific adaptation of the residue representations. The bidirectional Mamba encoder further reorganizes these representations according to toxicity-related sequential patterns, whereas multi-seed ensembling and out-of-fold calibration reduce training variance and align the calibrated probability scale with that of the downstream structural expert.

2.3.1 Residue Tokenization and LoRA-Adapted ProtT5

Given a peptide sequence of length L, we first convert its amino acid residues into the space-separated format required by the ProtT5 tokenizer and map them to token indices. Special tokens are inserted automatically, and sequences of different lengths are padded to a uniform length within each batch. The maximum token length is set to 128, which is sufficient for all peptides used in this study. Under the current ProtT5 tokenizer configuration, the first L token positions correspond to the L amino acid residues, followed by the EOS token and, when required, padding tokens. Accordingly, the implementation constructs the residue-validity mask directly from the original peptide length:

$$\mathcal{S} = (a_1, a_2, \ldots, a_L), \qquad m_i = \begin{cases} 1, & 1 \le i \le L, \\ 0, & i > L. \end{cases} \tag{3}$$

where $m_i = 1$ denotes an actual amino acid position and $m_i = 0$ denotes a special or padding position; the same mask is applied in the Mamba scans and the subsequent global pooling.

The tokenized sequence is then processed by the ProtT5-XL-UniRef50 encoder [CITE: ProtT5, Elnaggar et al.] to generate contextualized residue-level representations:

$$\mathbf{H}^{\mathrm{PLM}} = \mathrm{ProtT5}_{\mathrm{LoRA}}(\mathcal{S}), \qquad \mathbf{H}^{\mathrm{PLM}} \in \mathbb{R}^{L \times 1024}. \tag{4}$$

Retaining the complete residue-level representation matrix enables the downstream encoder to preserve position-specific contextual semantics. Each residue vector thus encodes not only its amino acid identity but also its conditional context within the complete peptide sequence.

To adapt the general-purpose ProtT5 encoder to the peptide toxicity prediction task, we apply low-rank adaptation (LoRA) [CITE: LoRA, Hu et al., 2022] to the linear transformations within the encoder. For an original linear layer $\mathbf{y} = \mathbf{W}_0\mathbf{x} + \mathbf{b}$, the pretrained weight matrix $\mathbf{W}_0$ is frozen, and the task-specific update is factorized into two trainable low-rank matrices:

$$\mathbf{W} = \mathbf{W}_0 + \frac{\alpha}{r}\mathbf{B}\mathbf{A}, \qquad \mathbf{A} \in \mathbb{R}^{r \times d_{\mathrm{in}}}, \quad \mathbf{B} \in \mathbb{R}^{d_{\mathrm{out}} \times r}. \tag{5}$$

The LoRA-augmented forward pass is therefore

$$\mathbf{y} = \mathbf{W}_0\mathbf{x} + \mathbf{b} + \frac{\alpha}{r}\mathbf{B}\mathbf{A}\,\mathrm{Dropout}(\mathbf{x}). \tag{6}$$

We set the LoRA rank to $r = 8$, the scaling coefficient to $\alpha = 16$, and the LoRA dropout rate to 0.1, yielding a scaling factor of $\alpha/r = 2$. Matrix $\mathbf{A}$ is initialized with Kaiming initialization,

whereas $\mathbf{B}$ is initialized to zero; consequently, the LoRA branch initially leaves the pretrained transformation unchanged and progressively learns toxicity-specific updates during training.

Unlike conventional configurations that apply LoRA only to selected attention projections, the current implementation augments all linear layers within the ProtT5 encoder. The pretrained base transformations and embeddings remain frozen, whereas the low-rank parameters and the downstream sequence- classification modules are trainable.

The 1024-dimensional ProtT5 representations are then projected into the 192-dimensional hidden space used by the Mamba encoder [CITE: Mamba, Gu and Dao]:

$$\mathbf{X}^{(0)} = \mathrm{Dropout}\left(\mathrm{GELU}\left[\mathrm{LN}\left(\mathbf{H}^{\mathrm{PLM}}\mathbf{W}_p + \mathbf{b}_p\right)\right]\right), \qquad \mathbf{X}^{(0)} \in \mathbb{R}^{L\times 192}. \tag{7}$$

where LN denotes layer normalization. The projection block consists of a linear transformation, layer normalization, GELU activation, and dropout. It reduces the computational dimension for the downstream state-space encoder while providing a task-specific nonlinear transformation of the ProtT5 residue representations.

2.3.2 Bidirectional Mamba Sequence Encoder

Although ProtT5 provides contextualized residue representations, these representations primarily encode general protein semantics learned during large-scale pretraining. To further model the sequential dependencies specifically associated with peptide toxicity, two bidirectional Mamba layers are placed after the ProtT5 projection block. Mamba employs an input-dependent selective state-space mechanism that dynamically controls which residue information is retained, updated, or suppressed during sequential scanning [CITE: Mamba, Gu and Dao].

For a unidirectional Mamba scan, the input representation $\mathbf{X} \in \mathbb{R}^{L\times d_{\mathrm{model}}}$ with $d_{\mathrm{model}} = 192$ is first projected into a content branch and a gating branch:

$$[\mathbf{U}, \mathbf{Z}] = \mathbf{X}\mathbf{W}_{\mathrm{in}} + \mathbf{b}_{\mathrm{in}}, \qquad \mathbf{U}, \mathbf{Z} \in \mathbb{R}^{L\times d_{\mathrm{inner}}}, \quad d_{\mathrm{inner}} = 2d_{\mathrm{model}} = 384, \tag{8}$$

i.e., the projection expands the feature dimension from 192 to 768 and splits it into two branches, each of dimension $d_{\mathrm{inner}} = 384$. The content branch is processed by a depthwise one-dimensional convolution with a kernel width of 4, followed by a SiLU activation:

$$\widetilde{\mathbf{U}} = \mathrm{SiLU}(\mathrm{DWConv1D}(\mathbf{U})), \qquad \widetilde{\mathbf{U}}^{\mathrm{m}}_t = m_t\widetilde{\mathbf{U}}_t, \tag{9}$$

where $\widetilde{\mathbf{U}}^{\mathrm{m}}_t$ denotes the convolved feature after applying the residue-validity mask. This local convolution extracts short-range residue patterns before the state-space scan, enabling the module to combine local sequence motifs with the longer-range context accumulated through state recurrence. Input-dependent projections then generate the discretization step size and the state-space parameters from the masked feature:

$$[\delta_t, \mathbf{B}_t, \mathbf{C}_t] = \mathrm{Linear}(\widetilde{\mathbf{U}}^{\mathrm{m}}_t), \qquad \Delta_t = \mathrm{Softplus}(\mathbf{W}_\Delta\delta_t + \mathbf{b}_\Delta). \tag{10}$$

The state-transition matrix is parameterized to be negative and is discretized according to the input-dependent step size:

$$\mathbf{A} = -\exp(\mathbf{A}_{\log}), \qquad \bar{\mathbf{A}}_t = \exp(\Delta_t\mathbf{A}), \qquad \bar{\mathbf{B}}_t = \Delta_t\mathbf{B}_t, \tag{11}$$

where $\mathbf{A}_{\log} \in \mathbb{R}^{d_{\mathrm{inner}}\times d_{\mathrm{state}}}$ is a learnable parameter matrix. The selective state recurrence is expressed as

$$\mathbf{S}_t = \bar{\mathbf{A}}_t \odot \mathbf{S}_{t-1} + \bar{\mathbf{B}}_t \odot \widetilde{\mathbf{U}}^{\mathrm{m}}_t, \qquad Y_t = \sum_{n=1}^{d_{\mathrm{state}}} S_{t,n}C_{t,n}, \tag{12}$$

where the state dimension is set to $d_{\text{state}} = 16$. The state-space output at position t is subsequently combined with the gating branch and the skip term:

$$\mathbf{O}_t = \mathbf{W}_{\text{out}} \left[\mathbf{Y}_t \odot \text{SiLU}(\mathbf{Z}_t) + \mathbf{D} \odot \widetilde{\mathbf{U}}_t^{\text{m}} \right]. \tag{13}$$

At invalid positions, $\widetilde{\mathbf{U}}_t^{\text{m}}$ is zero and Δ_t is also zeroed, preventing padding tokens from injecting information into the recurrent states.

A unidirectional scan accesses only one side of the sequence context, whereas peptide toxicity may depend on residue patterns associated with both termini and with interactions spanning different sequence positions. Therefore, in the ℓ-th bidirectional Mamba layer, forward and backward scans are applied to the normalized sequence using the residue-validity mask $\mathbf{m}$:

$$\begin{aligned} \mathbf{F}^{(\ell)} &= \mathcal{M}_f^{(\ell)}(\text{LN}(\mathbf{X}^{(\ell)}), \mathbf{m}), \\ \mathbf{R}^{(\ell)} &= \text{Reverse}\left[\mathcal{M}_b^{(\ell)} \left(\text{Reverse}\left[\text{LN}(\mathbf{X}^{(\ell)}) \right], \text{Reverse}(\mathbf{m}) \right) \right], \end{aligned} \tag{14}$$

where the backward-scan output is restored to the original residue order. The two directional outputs, each of dimension 192, are concatenated along the feature dimension (384 in total) and fused by a linear layer that projects the representation back to 192 dimensions:

$$\mathbf{M}^{(\ell)} = \text{GELU}\left(\text{Dropout}\left(\mathbf{W}_m \left[\mathbf{F}^{(\ell)} \parallel \mathbf{R}^{(\ell)} \right] + \mathbf{b}_m \right) \right), \qquad \mathbf{X}^{(\ell+1)} = \mathbf{X}^{(\ell)} + \text{Dropout}(\mathbf{M}^{(\ell)}), \tag{15}$$

where $\parallel$ denotes feature concatenation, the dropout inside the GELU block is applied within the fusion module, and the second dropout is applied before the residual addition. Two bidirectional Mamba layers are stacked in the final model. The first layer reconstructs bidirectional residue dependencies from the task-adapted ProtT5 features, whereas the second layer further aggregates the resulting contextual representations. This design allows each residue position to receive conditional information from both its N-terminal and C-terminal contexts.

2.3.3 Masked Pooling and Class-Weighted Classification

After two bidirectional Mamba layers, the model produces residue-level sequence representations:

$$\mathbf{X}^{(2)} = [\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_L], \qquad \mathbf{X}^{(2)} \in \mathbb{R}^{L \times 192}. \tag{16}$$

Because peptide sequences have variable lengths, GHXTox does not rely on a fixed-position classification token. Instead, masked mean pooling is applied over the valid amino acid positions:

$$\mathbf{h}_{1D} = \frac{\sum_{i=1}^{L} m_i \mathbf{x}_i}{\sum_{i=1}^{L} m_i}, \tag{17}$$

where the denominator equals the number of valid residue positions. This operation converts the variable-length residue sequence into a fixed 192-dimensional peptide-level representation while ensuring that EOS and padding positions do not contribute to the pooled feature. In contrast to global max pooling, masked mean pooling aggregates distributed evidence across the entire peptide and avoids a representation dominated by a single extreme activation.

The peptide-level representation is first normalized and then passed through a single-output linear classification head:

$$z_{1D} = \mathbf{w}_c^{\top} \text{LN}(\mathbf{h}_{1D}) + b_c, \qquad p_{1D}^{\text{raw}} = \sigma(z_{1D}) = \frac{1}{1 + \exp(-z_{1D})}, \tag{18}$$

where z_{1D} denotes the 1D expert logit and p_{1D}^{raw} the corresponding uncalibrated toxicity probability. The classification head of the current 1D expert consists of layer normalization followed by a single linear layer, rather than a multilayer perceptron; it is therefore referred to as a linear classification head throughout the architecture and Methods sections.

Because non-toxic peptides substantially outnumber toxic peptides in the training data, a positive-class-weighted binary cross-entropy loss is used in the current 1D expert instead of SMOTE or Borderline-SMOTE. For a training partition containing N_+ toxic and N_- non-toxic peptides, the positive-class weight is defined as

$$w_+ = \frac{N_-}{N_+}, \tag{19}$$

and the class-weighted objective is expressed as

$$\mathcal{L}_{\mathrm{WBCE}} = -\frac{1}{N}\sum_{j=1}^{N}\left[w_+ y_j \log\sigma(z_j) + (1-y_j)\log(1-\sigma(z_j))\right]. \tag{20}$$

During five-fold out-of-fold training, w_+ is calculated independently from the class counts of each fold's training partition; for full-data training, it is recalculated using the complete training set. This strategy increases the contribution of the minority toxic class without generating synthetic peptide sequences or feature vectors, while preventing any information from the held-out validation fold from entering the training procedure.

2.3.4 Three-Seed Ensemble and OOF Platt Calibration

The predictions of deep neural networks may vary because of parameter initialization, mini-batch ordering, and stochastic optimization. To reduce the variance associated with an individual training run, three 1D expert models are trained under identical data, architecture, and optimization settings using the random seeds 42, 123, and 2025. The deployed ensemble consists of three models trained on the complete training set, rather than the fold-specific checkpoints produced during cross-validation.

For sample j, the toxicity probability produced by the model trained with seed k is denoted by $p_j^{(k)} = \sigma(z_j^{(k)})$, $k \in \{1,2,3\}$, and the uncalibrated ensemble score is obtained by equal-weight arithmetic averaging:

$$s_j = \frac{1}{3}\sum_{k=1}^{3} p_j^{(k)}. \tag{21}$$

No individual seed is selected according to its performance on Test1 or Test2, and no seed-specific ensemble weight is introduced. All members share the same architecture and training protocol; the different random seeds provide averaging over a limited set of initialization and optimization stochasticities.

Although probability averaging reduces prediction variance, neural-network probabilities may remain systematically overconfident or underconfident. Moreover, the top-level GHXTox framework subsequently combines the 1D expert with the structural expert, making probability-scale compatibility particularly important. Therefore, Platt scaling [CITE: Platt 1999] is applied after the three-model probability average.

Training out-of-fold predictions are first generated using the fixed group-aware five-fold partition. Each training peptide receives an OOF probability from a model trained without the fold containing that peptide. The OOF probabilities from the three random seeds are then averaged to obtain the OOF ensemble score s_j^{OOF}. A two-parameter logistic calibrator is fitted using only these training OOF scores and their labels:

$$p_{1D,j} = \sigma\left(a\,\mathrm{logit}\left(\widetilde{s}_j\right) + b\right), \tag{22}$$

where $\mathrm{logit}(s) = \ln(s/(1-s))$, $\widetilde{s}_j = \mathrm{clip}(s_j, \varepsilon, 1-\varepsilon)$ with $\varepsilon = 10^{-6}$, and a and b denote the Platt calibration parameters; the clip prevents infinite logits for probabilities of exactly 0 or 1, and the same clipping is applied to the OOF scores used in fitting. The parameters are estimated as

$$(a,b) = \arg\min_{a,b}\sum_{j=1}^{N}\mathrm{BCE}\left[y_j,\ \sigma\left(a\,\mathrm{logit}\left(\widetilde{s}_j^{\mathrm{OOF}}\right) + b\right)\right]. \tag{23}$$

The scaling parameter is reparameterized as $a = \mathrm{clip}(\exp(\eta),\, 0.02, 50) > 0$, which guarantees a monotonic probability transformation and therefore preserves the sample ranking of the ensemble score; AUROC and AUPRC are consequently unchanged by calibration. For benchmark test or previously unseen peptides, the output probabilities of the three full-data models are first averaged, after which the frozen calibration parameters are applied:

$$p_{1\mathrm{D}} = \sigma\left(a\,\mathrm{logit}\left(\mathrm{clip}\left(\frac{1}{3}\sum_{k=1}^{3} p^{(k)},\ \varepsilon,\ 1-\varepsilon\right)\right) + b\right). \tag{24}$$

The labels of Test1 and Test2 are not used for ensemble-member selection, calibration fitting, or 1D threshold optimization. The calibrated probability $p_{1\mathrm{D}}$ is the sequence-expert output used in the top-level probability fusion described in Section 2.2.3. No additional Platt calibrator is fitted after the final GHXTox probability fusion. The complete order of operations is therefore

3-seed probabilities → averaging → OOF-fitted Platt calibration → $p_{1\mathrm{D}}$ → 1D/3D fusion.

««««< HEAD ======= Calibration is performed within the 1D expert before the top-level 1D/3D fusion; no additional Platt calibrator is fitted after the final GHXTox probability fusion. »»»»> cb384a004be5a3fb57bbb060fd858090f90efe12

2.4 pLDDT-Aware Multi-Scale 3D Structural Modeling

Peptide toxicity is influenced not only by amino acid composition and linear residue order but also by the three-dimensional (3D) arrangement of charged groups, hydrophobic regions, aromatic systems, and sulfur-containing moieties. However, peptides are generally short, conformationally flexible, and poorly covered by experimentally determined structures. Treating a single predicted conformation as an error-free structural observation may therefore amplify structure-prediction errors. Conversely, representing a peptide with ««««< HEAD only C_α coordinates or peptide-level summary descriptors fails to capture the ======= only Cα coordinates or peptide-level summary descriptors fails to capture the »»»»> cb384a004be5a3fb57bbb060fd858090f90efe12 local spatial-chemical environments that are relevant to toxicity.

To address these limitations, GHXTox employs a pLDDT-aware multi-scale structural expert that captures complementary information at five levels: residue semantics, spatial residue neighborhoods, full-atom chemical sites, peptide-level global properties, and conformer-ensemble statistics. The model ««««< HEAD first extracts residue-level C_α coordinates, full-atom coordinates, and ======= first extracts residue-level Cα coordinates, full-atom coordinates, and »»»»> cb384a004be5a3fb57bbb060fd858090f90efe12 normalized pLDDT confidence scores from the predicted structure. An internal sequence-semantic subbranch combines amino acid residue types, functional-group categories, explicit physicochemical descriptors, and ESM2 residue embeddings to generate contextualized sequence states. In parallel, a spatial-geometric subbranch constructs a hybrid residue graph containing both sequential adjacency edges and spatial-neighborhood edges and propagates geometric information through pLDDT-aware equivariant graph layers.

««««< HEAD To overcome the limited chemical resolution of a C_α-only residue graph, ======= To overcome the limited chemical resolution of a Cα-only residue graph, »»»»> cb384a004be5a3fb57bbb060fd858090f90efe12 GHXTox additionally extracts typed chemical sites from the full-atom structure and performs message passing using dual-scale distances, directional relationships, interaction-compatibility channels, and structural confidence. For peptides with available conformer ensembles, an additional statistical residual branch summarizes residue fluctuations, distance variation, and contact occupancy. The residual is constrained to exactly zero when conformer information is unavailable.

Rather than discarding low-confidence structures through hard filtering, GHXTox treats pLDDT as a continuous reliability signal and incorporates it into geometric edge weighting, chemical-site messages, residue-level structural gating, and peptide-level structural gating. Low-confidence structural evidence is therefore down-weighted rather than removed, preserving structural coverage while limiting the influence of uncertain coordinates. Importantly, pLDDT is interpreted here as a local confidence estimate produced by the structure-prediction model, rather than an experimentally determined measure of structural accuracy, conformational flexibility, or biological activity. The detailed architecture of the structural expert is illustrated in Figure **??**.

Figure 2: Detailed architecture of the sequence-enhanced structural expert. The structural expert integrates ESM2-enhanced residue semantics, a pLDDT-aware geometric residue graph, full-atom chemical-site message passing, and availability-masked conformer-ensemble statistics. Residue-level structural states are continuously modulated by node-level confidence before serving as keys and values in sequence–structure cross-attention. A peptide-level confidence gate further controls the fused structural context, while conformer statistics provide a zero-initialized logit residual only when valid ensemble information is available.

2.4.1 Peptide Structure Prediction and Conformer Preparation

For a peptide sequence of length L, $S = (a_1, a_2, \ldots, a_L)$, ESMFold is first used to predict its three-dimensional structure [CITE: ESMFold]. The predicted structure is stored as a full-atom PDB file, «««< HEAD from which residue-level C_α coordinates, backbone coordinates, ======= from which residue-level Cα coordinates, backbone coordinates, »»»> cb384a004be5a3fb57bbb060fd858090f90efe12 full-atom-derived chemical-site coordinates, and pLDDT scores are extracted. This operation is denoted as

$$(\mathbf{X}, \mathcal{A}, \mathbf{q}) = \mathrm{ESMFold}(\mathcal{S}), \qquad \mathbf{X} = [\mathbf{x}_1, \ldots, \mathbf{x}_L]^\top \in \mathbb{R}^{L\times 3}, \quad \mathbf{q} = (q_1, \ldots, q_L) \in [0,1]^L, \tag{25}$$

«««< HEAD where $\mathbf{X}$ contains the C_α coordinates, $\mathcal{A}$ denotes the residue-organized full-atom coordinate set, and $\mathbf{q}$ contains the residue-level pLDDT confidence scores rescaled to $[0,1]$. The C_α coordinates ======= where $\mathbf{X}$ contains the Cα coordinates, $\mathcal{A}$ denotes the full-atom-PDB-derived backbone and chemical-site geometry, and $\mathbf{q}$ contains the residue-level pLDDT confidence scores rescaled to $[0,1]$. The Cα coordinates »»»> cb384a004be5a3fb57bbb060fd858090f90efe12 serve as the primary spatial variables of the residue-level equivariant graph, whereas the full-atom coordinates are used to construct local chemical sites. Before geometric encoding, the coordinates are centered at the peptide centroid to remove the effect of absolute translation.

A single predicted structure provides a common structural anchor but cannot represent potential conformational heterogeneity. Therefore, the current default GHXTox configuration additionally uses conformer-ensemble statistics on a prespecified subset of peptides covered by PepFlow [CITE: PepFlow]. Up to eight validated and aligned conformers are retained for each available peptide, with residue indices matched to a common sequence order. The PepFlow pilot250 subset covers 111 toxic and 139 non-toxic peptides with sequence lengths of 11–15 residues and up to eight conformers per peptide. The ensemble is represented as

$$\mathcal{C} = \{\mathbf{X}^{(1)}, \mathbf{X}^{(2)}, \ldots, \mathbf{X}^{(M)}\}, \qquad 1 \le M \le 8, \quad \mathbf{X}^{(m)} \in \mathbb{R}^{L\times 3}, \tag{26}$$

«««< HEAD where $\mathbf{X}^{(m)}$ denotes the C_α coordinates of conformer m. Rigid-body ======= where $\mathbf{X}^{(m)}$ denotes the Cα coordinates of conformer m. Rigid-body »»»> cb384a004be5a3fb57bbb060fd858090f alignment is performed before the ensemble statistics are calculated, ensuring that the resulting variation reflects internal geometric changes rather than arbitrary global rotations or translations.

Because conformer ensembles are not available for every training peptide, a binary availability indicator is defined as

$$c_{\text{conf}} = \begin{cases} 1, & \text{if valid ensemble statistics are available,} \\ 0, & \text{otherwise.} \end{cases} \tag{27}$$

When $c_{\text{conf}} = 0$, the conformer-statistics tensors are filled with zeros, and the corresponding residual contribution is explicitly suppressed by the availability indicator. Missing ensemble information is therefore not interpreted as evidence of structural rigidity; instead, the model falls back exactly to the single-structure pathway. No conformer ensembles are available for Test1 or Test2 in the current evaluation assets; hence, their conformer-residual contribution is exactly zero.

The generated conformers are computational samples rather than experimentally determined trajectories or rigorous thermodynamic ensembles. Consequently, RMSF, contact occupancy, and distance variance are interpreted as sampling-derived descriptors of conformational variation rather than direct measurements of peptide dynamics in solution.

2.4.2 Residue Feature Construction and Hybrid Geometric Graph

The structural expert constructs both an internal sequence representation and a spatial-geometric representation at the residue level. Importantly, the internal sequence-semantic subbranch described here uses frozen ESM2 residue embeddings and a lightweight Transformer. It is distinct from the LoRA-ProtT5 and bidirectional Mamba expert described in Section 2.3. The former supports residue-level sequence–structure alignment inside the structural expert, whereas the latter acts as an independent top-level 1D prediction expert.

For residue i, the input to the internal sequence-semantic subbranch is

$$\mathbf{u}_i^{\text{seq}} = \left[\mathbf{e}_i^{\text{AA}} \parallel \mathbf{e}_i^{\text{group}} \parallel \mathbf{f}_i^{\text{res}} \parallel P_{\text{ESM}}\left(\mathbf{e}_i^{\text{ESM2}}\right)\right], \tag{28}$$

where $\mathbf{e}_i^{\text{AA}} \in \mathbb{R}^{32}$ is the amino acid category embedding, $\mathbf{e}_i^{\text{group}} \in \mathbb{R}^{12}$ is the functional-group category embedding, $\mathbf{f}_i^{\text{res}} \in \mathbb{R}^{42}$ denotes the explicit residue-level physicochemical descriptors, and $\mathbf{e}_i^{\text{ESM2}} \in \mathbb{R}^{1280}$ is the ESM2-650M residue representation; the projection P_{ESM} maps the ESM2 representation to 128 dimensions. Stacking the residue-level feature vectors yields the sequence-feature matrix $U_{\text{seq}} \in \mathbb{R}^{L\times 214}$, where $214 = 32+12+42+128$. After a linear projection and positional encoding, the sequence is processed by a two-layer Transformer encoder with hidden dimension 128, four attention heads, and a feed-forward dimension of 512:

$$\mathbf{H}^{\text{seq}} = \text{Transformer}_2\left[P_{\text{seq}}\left(U_{\text{seq}}\right) + E_{\text{pos}}\right], \qquad \mathbf{H}^{\text{seq}} \in \mathbb{R}^{L\times 128}, \tag{29}$$

This representation encodes the contextual sequence semantics of each residue and subsequently serves as the query representation in the sequence–structure cross-attention module.

In the spatial subbranch, the initial representation of residue i is constructed as

$$\mathbf{h}_i^{(0)} = P_{\text{sp}}\left[\mathbf{f}_i^{\text{res}} \parallel \mathbf{g}_i^{\text{geo}} \parallel q_i \parallel P_{\text{ESM}}\left(\mathbf{e}_i^{\text{ESM2}}\right)\right], \tag{30}$$

where $\mathbf{g}_i^{\text{geo}} \in \mathbb{R}^{16}$ is a lightweight «««< HEAD geometric descriptor derived from the C_α coordinates and pLDDT scores. The 16-dimensional descriptor includes (i) residue-level pLDDT and local confidence statistics; (ii) radial position, contact fractions, and soft spatial density; (iii) nearest-neighbor, nonlocal-neighbor, and local sequential distances; and (iv) sine/cosine encodings of the C_α-trace angles ======= geometric descriptor derived from the Cα coordinates and pLDDT scores. The 16-dimensional descriptor includes (i) residue-level pLDDT and local confidence statistics; (ii) radial position, contact fractions, and soft spatial density; (iii) nearest-neighbor, nonlocal-neighbor, and local sequential distances; and (iv) sine/cosine encodings of

the Cα-trace angles »»»> cb384a004be5a3fb57bbb060fd858090f90efe12 and torsions. These explicit descriptors provide stable local geometric priors without introducing an overly complex handcrafted representation for short and uncertain predicted peptide structures.

GHXTox then constructs a hybrid residue graph:

$$\mathcal{G} = (\mathcal{V}, \mathcal{E}_{\text{seq}} \cup \mathcal{E}_{\text{knn}}), \tag{31}$$

where each residue corresponds to one node. Sequential edges $\mathcal{E}_{\text{seq}}$ connect adjacent residues and preserve peptide-chain continuity, whereas $\mathcal{E}_{\text{knn}}$ connects each residue to its 10 nearest spatial neighbors and is symmetrized. The hybrid graph therefore captures both covalent sequence order and nonlocal spatial contacts while avoiding large variations in graph density that may arise from a single fixed-distance cutoff. Equivalently, $A_{ij} \in \{0, 1\}$ denotes whether residues i and j are connected by a sequential or k-nearest-neighbor edge in the hybrid graph.

«««< HEAD For residues i and j, the C_α distance is ======= For residues i and j, the Cα distance is »»»> cb384a004be5a3fb57bbb060fd858090f90efe12

$$d_{ij} = \|\mathbf{x}_i - \mathbf{x}_j\|_2, \qquad \phi_k(d_{ij}) = \exp\left[-\gamma\,(d_{ij} - \mu_k)^2\right], \quad \gamma = \frac{1}{(\mu_{k+1} - \mu_k)^2}, \quad k = 1, \ldots, 16, \tag{32}$$

where the centers μ_k are uniformly spaced over the range 0–24 Å. The base edge representation additionally includes the pairwise structural confidence and the normalized sequence separation:

$$c_{ij} = \sqrt{q_i q_j}, \qquad s_{ij} = \frac{\log(1 + |i - j|)}{\log(L + 1)}. \tag{33}$$

Thus, sequentially adjacent residues receive small values, whereas residues separated by longer sequence intervals approach one. The resulting edge feature is therefore $\mathbf{e}_{ij} = [\boldsymbol{\phi}(d_{ij}) \parallel c_{ij} \parallel s_{ij}]$. This formulation allows the model to distinguish sequentially adjacent contacts, long-range spatial contacts, and contacts supported by different levels of structural confidence.

2.4.3 pLDDT-Aware Equivariant Graph Encoding

To learn three-dimensional representations without relying on a particular global coordinate frame, the spatial branch employs three E(3)-equivariant graph neural network layers [CITE: EGNN]. The network updates residue features using rotation- and translation-invariant quantities while updating coordinates equivariantly. Consequently, a global rigid transformation of the peptide structure does not change the predicted toxicity, whereas intermediate coordinate representations transform consistently with the input.

At layer ℓ, the message from residue j to residue i is computed as

$$\mathbf{m}_{ij}^{(\ell)} = \phi_e^{(\ell)}\left[\mathbf{h}_i^{(\ell)} \parallel \mathbf{h}_j^{(\ell)} \parallel \mathbf{e}_{ij}^{(\ell)}\right], \tag{34}$$

where $\phi_e^{(\ell)}$ is a message multilayer perceptron. To prevent uncertain or distant contacts from contributing as strongly as local high-confidence contacts, a continuous edge weight is defined as

$$w_{ij}^{(\ell)} = A_{ij}\,\exp\left(-\frac{d_{ij}^{(\ell)}}{12}\right)\left[q_{\min} + (1 - q_{\min})\,c_{ij}^{\rho}\right], \qquad q_{\min} = 0.1, \quad \rho = 1.5, \tag{35}$$

The term $\exp(-d_{ij}^{(\ell)}/12)$ imposes a smooth distance decay with a characteristic decay length of 12 Å, and both the distance and the edge weight are recomputed at each layer from the current coordinates. Here, $A_{ij} \in \{0, 1\}$ is the adjacency indicator of the hybrid graph defined in Section 2.4.2, and c_{ij} is the pairwise structural confidence defined in Section 2.4.2. The minimum weight $q_{\min}$ prevents low-confidence regions from being completely disconnected, whereas the

exponent ρ increases the relative contribution of high-confidence contacts. The distance-decay term further reduces the influence of more distant spatial neighbors.

Messages received by node i are aggregated with a normalization floor:

$$\mathbf{m}_i^{(\ell)} = \frac{\sum_j w_{ij}^{(\ell)} \mathbf{m}_{ij}^{(\ell)}}{\max\left(\sum_j w_{ij}^{(\ell)},\, 1\right)}. \tag{36}$$

The aggregated message is used to update the node representation with a residual connection followed by layer normalization:

$$\mathbf{h}_i^{(\ell+1)} = \mathrm{LN}\left\{\mathbf{h}_i^{(\ell)} + \phi_h^{(\ell)}\left[\mathbf{h}_i^{(\ell)} \parallel \mathbf{m}_i^{(\ell)}\right]\right\}. \tag{37}$$

In addition to updating node features, the EGNN refines residue coordinates using pairwise relative vectors. A bounded scalar coordinate-update coefficient is generated from the edge message, and the coordinate update is

$$\begin{aligned} \alpha_{ij}^{(\ell)} &= \tanh\left[\phi_x^{(\ell)}\left(\mathbf{m}_{ij}^{(\ell)}\right)\right] w_{ij}^{(\ell)}, \\ \mathbf{x}_i^{(\ell+1)} &= \mathbf{x}_i^{(\ell)} + 0.05\, \frac{\sum_j \alpha_{ij}^{(\ell)}\left(\mathbf{x}_i^{(\ell)} - \mathbf{x}_j^{(\ell)}\right)}{\max\left(\sum_j w_{ij}^{(\ell)},\, 1\right)}. \end{aligned} \tag{38}$$

The coordinates are recentered after every layer to reduce numerical drift. Because the update depends only on scalar messages, distances, and relative coordinate vectors, the operation remains equivariant to rigid rotations and translations.

Three EGNN layers are stacked to progressively enlarge the spatial receptive field. The first layer primarily encodes direct geometric neighbors, whereas subsequent layers integrate higher-order spatial environments through repeated message passing. Unlike approaches that simply append pLDDT as an ordinary node feature, GHXTox uses pLDDT to directly modulate the strength of geometric messages, allowing structural uncertainty to influence representation learning at the propagation stage.

Continuous down-weighting does not imply that a low-pLDDT residue is biologically unimportant. Low confidence may arise from prediction error or potential conformational flexibility; the model reduces the reliability assigned to uncertain coordinate evidence while preserving the residue's sequence-semantic and physicochemical features.

2.4.4 Full-Atom Chemical-Site Message Passing

«««< HEAD A C_α-based residue graph describes the global fold and spatial neighborhoods ======= A Cα-based residue graph describes the global fold and spatial neighborhoods »»»> cb384a004be5a3fb57bbb060fd858090f90efe12 but cannot distinguish chemically distinct regions within the same side chain. For example, tyrosine contains both an aromatic ring and a hydroxyl group, whereas tryptophan contains an aromatic system and an indole nitrogen. Compressing each side chain into a single centroid would mix these chemically different moieties. GHXTox therefore extracts chemistry-aware pseudo-sites from the predicted full-atom PDB structure and processes them with a dedicated local chemical branch.

Up to two chemical sites are retained for each residue. Site identity is represented as an eight-dimensional multi-hot vector allowing overlapping types:

$$\mathbf{t}_{ir} \in \{0,1\}^8, \tag{39}$$

corresponding to positive, negative, donor, acceptor, aromatic, hydrophobic, sulfur, and conformational, where r indexes the chemical site within residue i. Multiple types may be assigned to the same site. For example, the cysteine sulfur site is labeled as donor, hydrophobic, and

sulfur-containing, whereas the proline ring is labeled as hydrophobic and conformationally constrained. The aromatic ring and hydroxyl group of tyrosine are represented as separate sites, as are the aromatic system and the indole NE1 nitrogen (donor) of tryptophan.

A site coordinate is obtained from the mean position of the heavy atoms defining the corresponding chemical moiety. Site orientation is represented by either a bond direction or an unsigned plane normal. Because the sign of a plane normal is arbitrary, downstream directional features use absolute cosines, preserving rotation invariance and eliminating orientation-sign ambiguity.

The initial representation of site r in residue i is

$$\mathbf{z}_{ir}^{(0)} = \phi_{\text{site}}\left[\mathbf{t}_{ir} \parallel q_i \parallel o_{ir}^{\text{valid}}\right], \tag{40}$$

where q_i is the pLDDT score of the parent residue and o_{ir}^{valid} indicates whether a reliable orientation could be constructed; the input is projected into a 64-dimensional hidden space.

Chemical-site edges are established between valid sites separated by no more than 16 Å. In the current configuration, same-residue site edges are retained, preserving spatial relationships between chemically different moieties in complex side chains. Each edge contains four complementary feature families. First, the raw distance in Å is encoded using 16 radial basis functions, $\boldsymbol{\phi}_{\text{raw}}(d_{uv}) \in \mathbb{R}^{16}$. Second, a peptide-size-normalized distance is constructed. The radius of «««< HEAD gyration of the C_α coordinates is ======= gyration of the Cα coordinates is »»»> cb384a004be5a3fb57bbb060fd858090f90efe12

$$R_g = \sqrt{\frac{1}{L}\sum_{i=1}^{L}\|\mathbf{x}_i - \bar{\mathbf{x}}\|_2^2}, \qquad \bar{\mathbf{x}} = \frac{1}{L}\sum_{i=1}^{L}\mathbf{x}_i, \qquad \bar{d}_{uv} = \frac{d_{uv}}{R_g}, \tag{41}$$

«««< HEAD where $\bar{\mathbf{x}}$ denotes the centroid of the valid C_α coordinates, and ======= where $\bar{\mathbf{x}}$ denotes the centroid of the valid Cα coordinates, and »»»> cb384a004be5a3fb57bbb060fd858090f90efe12 the normalized distance is encoded by eight radial basis functions over the interval 0–4, $\boldsymbol{\phi}_{\text{norm}}(\bar{d}_{uv}) \in \mathbb{R}^8$. The raw representation describes the physical separation in Å, whereas the normalized representation describes the separation relative to the overall peptide size. Their combination allows the model to distinguish, for example, an 8 Å contact in a compact short peptide from an 8 Å contact in a larger peptide.

Third, four rotation-invariant orientation features are used:

$$\mathbf{o}_{uv} = \left[|\mathbf{o}_u \cdot \mathbf{r}_{uv}|,\ |\mathbf{o}_v \cdot \mathbf{r}_{vu}|,\ |\mathbf{o}_u \cdot \mathbf{o}_v|,\ o_{uv}^{\text{valid}}\right], \tag{42}$$

which describe the alignment of the source orientation with the intersite direction, the alignment of the target orientation with the reverse direction, the mutual orientation of the two sites, and orientation availability. Fourth, six explicit compatibility channels are defined:

$$\mathbf{c}_{uv}^{\text{chem}} = [c_{\text{opp}}, c_{\text{DA}}, c_{\text{aro}}, c_{\text{cat-}\pi}, c_{\text{SS}}, c_{\text{hyd}}], \tag{43}$$

««««< HEAD representing opposite-charge, donor–acceptor, aromatic–aromatic, positive–aromatic (cation–π$), sulfur–sulfur, and hydrophobic–hydrophobic compatibility. These channels encode candidate chemical compatibility patterns available to the model; they do not imply that a true salt bridge, hydrogen bond, cation–π$ interaction, disulfide bond, or hydrophobic core is ======= representing opposite-charge, donor–acceptor, aromatic–aromatic, positive–aromatic (cation–π), sulfur–sulfur, and hydrophobic–hydrophobic compatibility. These channels encode candidate chemical compatibility patterns available to the model; they do not imply that a true salt bridge, hydrogen bond, cation–π interaction, disulfide bond, or hydrophobic core is »»»> cb384a004be5a3fb57bbb060fd858090f90efe12 present in the predicted structure.

The full chemical-site edge representation is

$$\mathbf{e}_{uv}^{\text{chem}} = \left[\boldsymbol{\phi}_{\text{raw}}(d_{uv}) \parallel \boldsymbol{\phi}_{\text{norm}}(\bar{d}_{uv}) \parallel \mathbf{o}_{uv} \parallel \mathbf{c}_{uv}^{\text{chem}} \parallel \sqrt{q_u q_v}\right]. \tag{44}$$

At layer l, the site message, its pairwise-confidence-weighted form, and the confidence-normalized aggregation are

$$\begin{aligned}
\mathbf{m}_{uv}^{(l)} &= \phi_{\text{chem}}^{(l)}\left[\mathbf{z}_u^{(l)} \parallel \mathbf{z}_v^{(l)} \parallel \mathbf{e}_{uv}^{\text{chem}}\right], \\
\tilde{\mathbf{m}}_{uv}^{(l)} &= \sqrt{q_u q_v}\,\mathbf{m}_{uv}^{(l)}, \\
\bar{\mathbf{m}}_v^{(l)} &= \frac{\sum_{u\in\mathcal{N}(v)} \tilde{\mathbf{m}}_{uv}^{(l)}}{\max\left(\sum_{u\in\mathcal{N}(v)} \sqrt{q_u q_v},\, 1\right)}.
\end{aligned} \tag{45}$$

After two message-passing layers, valid sites belonging to the same residue are mean-pooled, and a residue-level chemical residual is obtained:

$$\begin{aligned}
\Delta\mathbf{h}_i^{\text{chem}} &= \mathbf{W}_{\text{chem}} \operatorname*{Mean}_{r\in\mathcal{S}_i}\left(\mathbf{z}_{ir}^{(2)}\right), \\
\mathbf{W}_{\text{chem}}^{(0)} &= 0, \quad \mathbf{b}_{\text{chem}}^{(0)} = 0, \\
\mathbf{h}_i^{\text{sp}} &= \mathbf{h}_i^{\text{EGNN}} + \Delta\mathbf{h}_i^{\text{chem}},
\end{aligned} \tag{46}$$

where the projection $\mathbf{W}_{\text{chem}}$ and its bias $\mathbf{b}_{\text{chem}}$ are initialized to zero, so that $\Delta\mathbf{h}_i^{\text{chem}} = 0$ at the beginning of training. This conservative residual design allows the new chemical-site branch to progressively learn useful corrections from an intact geometric backbone rather than perturbing the existing spatial representation with a randomly initialized contribution.

2.4.5 Availability-Masked Conformer-Ensemble Residual

A single predicted structure provides a deterministic spatial anchor, whereas a peptide may adopt multiple related conformations. Running the complete geometric network independently on every conformer would be computationally expensive and could allow the model to exploit differences between conformer generators or uneven ensemble coverage. The current GHXTox model therefore uses a lightweight conformer-statistics residual. The single-structure expert remains the base predictor, and ensemble statistics are permitted to correct its logit only when valid conformer information is available.

For a peptide with M aligned conformers, the residue-level root-mean-square fluctuation is

$$\text{RMSF}_i = \sqrt{\frac{1}{M}\sum_{m=1}^{M}\left\|\mathbf{x}_i^{(m)} - \bar{\mathbf{x}}_i\right\|_2^2}, \qquad \bar{\mathbf{x}}_i = \frac{1}{M}\sum_{m=1}^{M}\mathbf{x}_i^{(m)}. \tag{47}$$

For each residue pair i, j, the mean distance and the distance standard deviation are

$$\bar{d}_{ij} = \frac{1}{M}\sum_{m=1}^{M} d_{ij}^{(m)}, \qquad \sigma_{ij}^{d} = \sqrt{\frac{1}{M}\sum_{m=1}^{M}\left(d_{ij}^{(m)} - \bar{d}_{ij}\right)^2}. \tag{48}$$

For a distance cutoff $r \in \{6, 8, 10\}$ Å, the contact occupancy and the 8 Å contact-occupancy uncertainty are

$$O_{ij}^{(r)} = \frac{1}{M}\sum_{m=1}^{M}\mathbb{I}\left(d_{ij}^{(m)} < r\right), \qquad U_{ij}^{(8)} = O_{ij}^{(8)}\left(1 - O_{ij}^{(8)}\right). \tag{49}$$

Values close to zero or one indicate contacts that are consistently absent or present across the sampled conformers, whereas values near 0.5 indicate contact switching.

The ensemble statistics are organized into an eight-dimensional residue-level descriptor $\mathbf{r}_i^{\text{conf}} \in \mathbb{R}^8$, containing the residue RMSF; the mean pairwise distance to other residues; the standard deviation of the mean pairwise distances associated with the residue; the mean pairwise-distance standard deviation; the mean contact occupancies at 6, 8, and 10 Å; and the mean 8 Å

contact-occupancy uncertainty, which together form the eight-dimensional descriptor. A twelve-dimensional peptide-level descriptor $\mathbf{g}^{\text{conf}} \in \mathbb{R}^{12}$ is also constructed, containing the normalized number of conformers; the mean, standard deviation, and maximum of RMSF; the mean, standard deviation, and maximum of the conformer RMSD; the mean and standard deviation of the radius of gyration; the mean and maximum of the pair-distance standard deviation; and the global mean of $U_{ij}^{(8)}$, which together form the twelve-dimensional descriptor. Before neural encoding, distance- and fluctuation-based statistics are rescaled by fixed constants to place heterogeneous descriptors on comparable numerical ranges; the exact scaling factors are reported in the implementation-details table.

The residue-level ensemble features are encoded and aggregated using both masked mean and masked maximum pooling, whereas the global descriptor is processed by a separate encoder:

$$\mathbf{h}_{\text{conf}}^{\text{res}} = \left[\text{MeanPool}\left(\phi_r\left(\mathbf{R}^{\text{conf}}\right)\right) \parallel \text{MaxPool}\left(\phi_r\left(\mathbf{R}^{\text{conf}}\right)\right)\right], \qquad \mathbf{h}_{\text{conf}}^{\text{global}} = \phi_g\left(\mathbf{g}^{\text{conf}}\right). \tag{50}$$

The base structural embedding, the residue-level ensemble embedding, and the global ensemble embedding are concatenated to produce a raw logit residual:

$$\Delta z_{\text{conf}}^{\text{raw}} = \phi_{\text{conf}}\left[\mathbf{h}_{\text{base}} \parallel \mathbf{h}_{\text{conf}}^{\text{res}} \parallel \mathbf{h}_{\text{conf}}^{\text{global}}\right]. \tag{51}$$

The final linear layer of the conformer residual head is initialized to zero. Using the availability indicator c_{conf} defined in Eq. (**??**), the learnable conformer weight, the effective residual, and the final structural-expert logit are

$$\begin{aligned} \beta_{\text{conf}}^{(0)} &= \text{logit}(0.25), \\ \lambda_{\text{conf}} &= \sigma\left(\beta_{\text{conf}}\right), \\ \Delta z_{\text{conf}} &= c_{\text{conf}}\, \lambda_{\text{conf}}\, \Delta z_{\text{conf}}^{\text{raw}}, \\ z_{\text{SE3D}} &= z_{\text{base}} + \Delta z_{\text{conf}}, \qquad c_{\text{conf}} = 0 \;\Rightarrow\; z_{\text{SE3D}} = z_{\text{base}}. \end{aligned} \tag{52}$$

where the effective conformer weight is initialized to 0.25 at the beginning of training through $\beta_{\text{conf}}^{(0)} = \text{logit}(0.25)$, so that $\sigma(\beta_{\text{conf}}^{(0)}) = 0.25$. Zero-filled feature tensors alone would not guarantee a zero correction because the residual network may contain nonzero biases; the additional hard availability mask ensures an exact fallback to the single-structure prediction. The conformer branch is permitted only to refine the single-structure predictor rather than replace the geometric backbone, reducing the risk of overfitting to limited and uneven ensemble coverage.

2.4.6 pLDDT-Aware Sequence–Structure Cross-Attention

After the EGNN and the chemical-site residual are applied, the model obtains the chemical-enhanced spatial representation

$$\mathbf{H}^{\text{sp}} = [\mathbf{h}_1^{\text{sp}}, \ldots, \mathbf{h}_L^{\text{sp}}]^\top \in \mathbb{R}^{L \times 128}, \tag{53}$$

where $\mathbf{h}_i^{\text{sp}}$ is defined in Eq. (**??**). Spatial information alone does not determine whether a structural pattern is relevant to the current sequence context. For example, similar hydrophobic contacts may have different implications depending on residue identities and sequence positions. GHXTox therefore uses pLDDT-aware cross-attention within the structural expert, allowing contextualized sequence states to selectively retrieve spatial evidence.

A node-level gate is first constructed for each residue. The base gate uses the 42-dimensional residue descriptors and the pLDDT score:

$$\begin{aligned} g_i^{\text{base}} &= \phi_{\text{node}}\left[\mathbf{f}_i^{\text{res}} \parallel q_i\right], \\ \mathbf{c}_i^{\text{node}} &= \left[\frac{q_i - \mu_q}{T_q},\ \frac{(q_i - \mu_q)^2}{T_q^2},\ \mathbb{I}(q_i < 0.55)\right], \\ \mu_q &= 0.70, \quad T_q = 0.12, \end{aligned} \tag{54}$$

where the residual confidence vector $\mathbf{c}_i^{\text{node}}$ increases the sensitivity of the gate to the distribution of structural confidence. The residual scale and the final node gate are

$$r_i^{\text{node}} = 0.5 + \sigma\left(\mathbf{w}_n^\top \mathbf{c}_i^{\text{node}} + b_n\right), \qquad g_i^{\text{node}} = \text{clamp}\left(g_i^{\text{base}}\, r_i^{\text{node}},\ 0, 1\right), \tag{55}$$

and the spatial representation is continuously down-weighted as

$$\widehat{\mathbf{H}}^{\text{sp}} = \mathbf{H}^{\text{sp}} \odot \mathbf{g}^{\text{node}}, \qquad \mathbf{g}^{\text{node}} = \left[g_1^{\text{node}}, \ldots, g_L^{\text{node}}\right]^\top \in [0,1]^L, \tag{56}$$

where the node-level gate vector $\mathbf{g}^{\text{node}}$ is broadcast across the feature dimension and each gate value is clamped to $[0, 1]$.

In the cross-attention operation, the contextualized sequence representation serves as the query, and the gated spatial representation serves as the key and value:

$$\mathbf{H}^{\text{cross}} = \text{MHA}\left(Q = \mathbf{H}^{\text{seq}}, K = \widehat{\mathbf{H}}^{\text{sp}}, V = \widehat{\mathbf{H}}^{\text{sp}}\right). \tag{57}$$

This direction has a direct interpretation: each residue position retrieves spatial evidence according to its contextual sequence representation. The operation is not a direct feature interaction between the LoRA-ProtT5–Mamba expert and the structural expert; it occurs internally between the ESM2-enhanced sequence states and the geometric states of the structural expert.

In addition to residue-level gating, a peptide-level gate is generated from the overall structure-confidence profile. The model first computes

$$\bar{q} = \frac{1}{L}\sum_{i=1}^{L} q_i, \qquad q_{\min} = \min_i q_i, \qquad r_{\text{low}} = \frac{1}{L}\sum_{i=1}^{L} \mathbb{I}(q_i < 0.55), \tag{58}$$

and constructs the peptide-level confidence vector $\mathbf{c}^{\text{pep}} = [(\bar{q} - \mu_q)/T_q,\ (q_{\min} - \mu_q)/T_q,\ r_{\text{low}}]$. The base peptide-level gate and its residual-adjusted form are

$$\begin{aligned} g_{\text{pep}}^{\text{base}} &= \phi_{\text{global}}\left[\bar{q},\ q_{\min},\ r_{\text{low}}\right], \\ r_{\text{pep}} &= 0.5 + \sigma\left(\mathbf{w}_{\text{pep}}^\top \mathbf{c}^{\text{pep}} + b_{\text{pep}}\right), \\ g_{\text{pep}} &= \text{clamp}\left(g_{\text{pep}}^{\text{base}}\, r_{\text{pep}},\ 0, 1\right), \end{aligned} \tag{59}$$

where the peptide-level residual scale is analogous to, but separately parameterized from, the node-level residual scale, and $g_{\text{pep}} \in [0, 1]$ denotes the scalar peptide-level structural gate.

The final residue-level fusion representation is

$$\mathbf{H}^{\text{fused}} = \text{LN}\left[\mathbf{H}^{\text{seq}} \parallel g_{\text{pep}}\, \mathbf{H}^{\text{cross}}\right]. \tag{60}$$

The two gating levels answer complementary questions: how reliable the structural evidence is at an individual residue position, and how strongly the structural branch should be trusted for the peptide as a whole. The sequence representation is always retained, whereas the structural context is dynamically scaled according to prediction confidence. Consequently, when the predicted structure has low overall confidence, the structural expert can still rely on its internal sequence-semantic pathway without allowing uncertain coordinates to dominate the classification.

2.4.7 Global Feature Integration and Structural Classification

After pLDDT-aware cross-attention, each valid residue is represented by a 256-dimensional fused vector obtained by concatenating the 128-dimensional internal sequence state with the 128-dimensional structural context:

$$\mathbf{H}^{\text{fused}} \in \mathbb{R}^{L \times 2d_h}, \qquad d_h = 128, \tag{61}$$

so that $\mathbf{H}^{\text{fused}} \in \mathbb{R}^{L\times 256}$. Masked mean pooling is applied over the valid residue positions:

$$\mathbf{h}_{\text{pool}} = \frac{\sum_{i=1}^{L} m_i \, \mathbf{H}_i^{\text{fused}}}{\sum_{i=1}^{L} m_i} \in \mathbb{R}^{256}, \tag{62}$$

where the denominator equals the number of valid residue positions and the mask excludes padding positions from the peptide representation. In contrast to maximum pooling, mean pooling integrates structural evidence distributed across multiple residue positions, which is appropriate when toxicity-related spatial patterns are not confined to a single local region.

The residue graph primarily models local and intermediate-range environments, whereas a finite number of message-passing layers may not explicitly recover all peptide-level physicochemical statistics. GHXTox therefore includes five global physicochemical descriptors, normalized to comparable scales before concatenation:

$$\mathbf{f}_{\text{pep}}^{\text{phys}} = \left[\frac{L}{128},\ \frac{Q_{\text{net}}}{L},\ f_{\text{aro}},\ f_{\text{Cys}},\ \frac{\bar{h}_{\text{hyd}}}{4.5} \right] \in \mathbb{R}^5, \tag{63}$$

representing the normalized peptide length, the length-normalized net charge, the aromatic-residue fraction, the cysteine fraction, and the scaled mean hydropathy. The classifier input is

$$\mathbf{h}_{\text{cls}} = \left[\mathbf{h}_{\text{pool}} \parallel \mathbf{f}_{\text{pep}}^{\text{phys}} \right] \in \mathbb{R}^{261}. \tag{64}$$

The base structural logit is produced by a three-layer multilayer perceptron, denoted compactly as

$$z_{\text{base}} = \phi_{\text{cls}} \left(\mathbf{h}_{\text{cls}} \right), \tag{65}$$

with dimensions $261 \to 128 \to 64 \to 1$, where each hidden layer applies GELU activation and dropout.

Applying the availability-masked conformer correction defined in Eq. (**??**) yields the final structural-expert logit, and the structural-expert probability is

$$z_{\text{SE3D}} = z_{\text{base}} + c_{\text{conf}} \, \lambda_{\text{conf}} \, \Delta z_{\text{conf}}^{\text{raw}}, \qquad p_{\text{SE3D}} = \sigma \left(z_{\text{SE3D}} \right),$$

as defined in Eq. (**??**). No standalone structural threshold is used to generate the final GHXTox class at this stage. Instead, p_{SE3D} is passed directly to the top-level dual-expert fusion described in Section 2.2.3, where it is combined with the calibrated 1D expert probability p_{1D} using frozen fusion weights. A standalone structural threshold is used only for structural-branch ablations or independent expert evaluation and does not determine the final GHXTox prediction.

The structural expert can therefore be summarized as

$$\begin{aligned} &\text{sequence-enhanced residue semantics} + \text{confidence-aware geometry} \\ &+ \text{full-atom chemical sites} + \text{global physicochemical descriptors} \\ &+ \text{availability-masked conformer statistics} \longrightarrow p_{\text{SE3D}}. \end{aligned}$$

The central contribution is not merely the inclusion of additional structural features, but the explicit separation of structural information by spatial scale and reliability. The geometric graph captures global residue relationships, the chemical-site branch resolves local functional moieties, the conformer residual summarizes sampled structural variation, and pLDDT continuously modulates edge propagation, chemical messages, and sequence–structure fusion. This design allows the structural expert to incorporate complementary 3D evidence while handling structure-prediction uncertainty in an explicit and auditable manner.

Overall, the structural expert integrates residue-level sequence semantics, confidence-aware geometry, full-atom chemical-site interactions, peptide-level physicochemical properties, and availability-masked conformer statistics. Rather than treating all predicted structural evidence

as equally reliable, GHXTox continuously modulates its contribution using residue-level and peptide-level confidence signals. The following section describes the training, out-of-fold model-selection, calibration, and parameter-freezing protocols used to optimize the complete framework.

2.5 Training and Model-Selection Protocol

GHXTox consists of a task-adaptive 1D sequence expert and a sequence-enhanced 3D structural expert. Because the two experts differ substantially in input representation, parameter scale, and optimization behavior, they are not jointly optimized through a single end-to-end objective. Instead, expert-level representations are learned independently, after which probability calibration and top-level fusion are performed using training out-of-fold (OOF) predictions. This strategy allows each expert to be optimized under modality-appropriate settings while separating representation learning, checkpoint selection, probability calibration, fusion-parameter determination, and independent evaluation into clearly defined stages.

The training protocol follows three central principles. First, identical or highly similar peptides must not appear simultaneously in a training partition and the corresponding validation partition. Second, every prediction used for calibration, fusion-weight selection, or threshold determination must be generated by a model that was not trained on the corresponding sample. Third, Test1 and Test2 are reserved exclusively for final evaluation of the frozen model and are not used for checkpoint selection, calibrator fitting, fusion search, or decision-threshold optimization.

2.5.1 Group-Aware Five-Fold OOF Generation

The training set contains $N = 6387$ peptides. To reduce performance inflation caused by highly similar sequences, a fixed five-fold manifest is constructed by clustering the training sequences into homology groups. The fold-level homology groups were constructed through a separate sequence-clustering procedure, distinct from the dataset-level redundancy removal described in Section 2.1. The first operation determines which samples remain in the benchmark dataset, whereas the second determines which retained samples must remain in the same cross-validation fold. Let

$$\mathcal{D} = \{(\mathcal{S}_i, y_i, g_i)\}_{i=1}^{N}, \qquad N = 6387, \tag{66}$$

denote the training data, where $\mathcal{S}_i$ is the peptide sequence, $y_i \in \{0, 1\}$ is its toxicity label, and g_i denotes its sequence-homology group. The data are partitioned into five disjoint validation folds:

$$\begin{aligned} \mathcal{D} &= \bigcup_{k=1}^{5} \mathcal{D}_k, \qquad\qquad \mathcal{D}_k \cap \mathcal{D}_l = \varnothing, \quad k \neq l, \\ g_i = g_j &\Longrightarrow f(i) = f(j), \end{aligned} \tag{67}$$

where $f(i)$ denotes the fold assigned to sample i. All peptides belonging to the same homology group are therefore placed in the same fold, preventing closely related sequences from crossing the training–validation boundary.

For fold k, the model is trained only on the complement $\mathcal{D}_{-k} = \mathcal{D} \setminus \mathcal{D}_k$ and evaluated on the unseen fold $\mathcal{D}_k$. The OOF probability of sample $i \in \mathcal{D}_k$ is defined as

$$\mathcal{D}_{-k} = \mathcal{D} \setminus \mathcal{D}_k, \qquad \hat{p}_i^{\mathrm{OOF}} = F_{\boldsymbol{\theta}^{(-k)}}\left(\mathcal{S}_i\right), \quad i \in \mathcal{D}_k, \tag{68}$$

where $\boldsymbol{\theta}^{(-k)}$ denotes the parameters learned exclusively from $\mathcal{D}_{-k}$. Each training peptide consequently receives exactly one probability from a model that did not observe that peptide during optimization.

For the 1D expert, full seed-specific OOF predictions are generated for the training set, and the three probability vectors are aligned by sample index and averaged:

$$\overline{p}_{i,\mathrm{1D}}^{\mathrm{OOF}} = \frac{1}{3} \sum_{s \in \{42,123,2025\}} \widehat{p}_{i,\mathrm{1D}}^{(s,\mathrm{OOF})}. \tag{69}$$

The resulting OOF ensemble scores are used to fit the Platt calibrator described in Section 2.3.4.

The structural expert uses the same fixed group-aware folds. Each fold-specific checkpoint produces probabilities only for its held-out validation fold:

$$\widehat{p}_{i,\mathrm{SE3D}}^{\mathrm{OOF}} = G_{\boldsymbol{\phi}^{(-k)}} \left(\mathcal{S}_i, \mathcal{X}_i, \mathcal{A}_i, \mathbf{q}_i, \mathcal{C}_i \right), \qquad i \in \mathcal{D}_k, \tag{70}$$

where $\mathcal{X}_i$, $\mathcal{A}_i$, $\mathbf{q}_i$, and $\mathcal{C}_i$ denote the residue geometry, full-atom chemical information, pLDDT confidence, and available conformer-ensemble statistics, respectively; $\mathcal{C}_i$ may be unavailable and is handled by the conformer-availability mask defined in Section 2.4.1.

Before combining the expert-level OOF predictions, the implementation verifies immutable sample indices (`source_index`), peptide sequences, toxicity labels, and fold assignments. Duplicate sample indices or mismatches in sequence, label, or fold assignment cause the fusion procedure to terminate rather than silently aligning prediction files by row order. OOF predictions are treated as **training-only model-selection assets**. Although OOF predictions are generated by models that did not observe the corresponding validation samples, parameters selected from the complete OOF table remain development-stage choices and must be evaluated on independent test sets.

2.5.2 Loss Functions and Class-Imbalance Handling

The 1D and 3D experts are optimized using separate objectives. This prevents uneven structural coverage, conformer availability, and confidence variation from directly perturbing the language-model optimization, and it avoids the large ProtT5 parameter space from dominating the smaller structure-specific residual modules.

Loss for the 1D expert. As described in Section 2.3.3, the sequence expert is trained using positive-class-weighted binary cross-entropy:

$$\mathcal{L}_{\mathrm{1D}} = -\frac{1}{B} \sum_{i=1}^{B} \left[w_+ y_i \log \sigma(z_i) + (1 - y_i) \log \left(1 - \sigma(z_i)\right) \right], \qquad w_+ = \frac{N_-}{N_+}, \tag{71}$$

where the class counts N_+ and N_- are independently calculated from each fold's training partition. The current 1D training pipeline does not use Borderline-SMOTE or sequence point-mutation augmentation. The weighted loss increases the contribution of the minority toxic class without introducing synthetic near-duplicate peptides.

Base geometric and chemical-site stage. The structural expert is optimized in stages. The full-atom chemical-site branch is first initialized from a previously trained pLDDT-aware geometric model, while the remaining backbone is frozen. This stage uses positive-class-weighted BCE:

$$\mathcal{L}_{\mathrm{chem}} = -\frac{1}{B} \sum_{i=1}^{B} \left[w_+ y_i \log \sigma \left(z_i^{\mathrm{base}} \right) + (1 - y_i) \log \left(1 - \sigma \left(z_i^{\mathrm{base}} \right) \right) \right], \tag{72}$$

where w_+ is defined as in Section 2.3.3 and is recalculated from each fold's training partition.

During training, pLDDT-dependent Gaussian coordinate perturbations are applied to reduce sensitivity to local errors in predicted structures. The perturbation scale for residue i is

$$\sigma_i = \sigma_0 \left[1 + \kappa \left(1 - q_i \right) \right], \qquad \sigma_0 = 0.12 \text{ Å}, \quad \kappa = 2.0, \tag{73}$$

and residue-wise perturbations are drawn as

$$\boldsymbol{\varepsilon}_i \sim \mathcal{N}\left(\mathbf{0}, \sigma_i^2 \mathbf{I}_3\right), \qquad \widetilde{\mathbf{x}}_i = \mathbf{x}_i + \boldsymbol{\varepsilon}_i. \tag{74}$$

The same residue-wise displacement is applied consistently to the corresponding backbone, functional-group, and chemical-site coordinates, thereby preserving their intra-residue relative geometry. No coordinate perturbation is applied during validation or inference. Low-pLDDT residues therefore receive stronger perturbations than high-confidence residues. This augmentation uses pLDDT to modulate the perturbation magnitude but does not treat pLDDT as an exact estimate of coordinate-error variance.

Conformer-ensemble residual stage. During conformer-residual training, the pLDDT-aware geometric backbone, internal sequence encoder, chemical-site branch, and base classifier are frozen. Only the residue-level conformer encoder, the global conformer encoder, the conformer-residual MLP, and the conformer logit-residual parameters are optimized. This stage is initialized from the trained chemical-site checkpoint. To avoid applying a second class-frequency correction on top of the existing base classifier, the current conformer-residual configuration uses unweighted BCE and disables coordinate perturbation, with a residual-magnitude penalty:

$$\mathcal{L}_{\text{conf}} = \text{BCEWithLogits}\left(z_{\text{SE3D}}, y\right) + \lambda_\Delta \frac{\sum_{i=1}^{B} c_i \left|\Delta z_{\text{conf},i}\right|}{\max\left(\sum_{i=1}^{B} c_i,\, 1\right)}, \qquad \lambda_\Delta = 0.005, \tag{75}$$

where the residual-magnitude term is computed only on samples with available conformer information. It limits large logit corrections and encourages the conformer branch to act as a conservative refinement rather than re-learning the complete toxicity decision boundary.

The final conformer-residual layer is zero-initialized, and its output is additionally controlled by the hard `conformer_available` mask. Zero initialization makes the initial model equivalent to the single-structure expert, whereas the hard mask guarantees a zero residual for samples without conformer evidence. Together, these mechanisms provide a stable incremental extension of the structural model.

2.5.3 Optimization, Checkpoint Selection, and Hyperparameter Settings

Both experts are optimized using AdamW [CITE: AdamW, Loshchilov and Hutter], but different learning rates, training durations, and checkpoint-selection criteria are employed. All random-number generators are initialized with fixed seeds. Data are shuffled only during training, whereas validation and inference loaders preserve deterministic ordering. Table **??** summarizes the optimization and model-selection settings of both experts.

Table 2: Main optimization and model-selection settings of the two GHXTox experts.

Module or stage	Batch size	Learning rate	Weight decay	Epochs	Checkpoint rule
1D LoRA-ProtT5 + Bi-Mamba	16	3×10^{-4}	1×10^{-2}	Fixed 15	No early stopping
3D chemical-site refinement	32	5×10^{-4}	1×10^{-4}	Max. 30	Best validation MCC; patience 8
Conformer residual refinement	32	1×10^{-3}	5×10^{-4}	Max. 50	Minimum validation loss; patience 8
Single-structure chemical-site backbone	32	Stage-specific	Stage-specific	Fixed 8	Median fold-selected epoch
PepFlow pilot250 conformer residual	32	Stage-specific	Stage-specific	Fixed 12	Median fold-selected epoch

1D expert. The LoRA-ProtT5 and bidirectional Mamba expert is trained with a batch size of 16, a learning rate of 3×10^{-4}, a weight decay of 1×10^{-2}, a fixed duration of 15 epochs, dropout

of 0.1, FP16 mixed precision, and ProtT5 gradient checkpointing, using random seeds 42, 123, and 2025. This configuration yields approximately 13.1 million trainable parameters, comprising the LoRA updates and the downstream sequence-classification modules, whereas the pretrained base transformations and embeddings remain frozen. Every fold model and every full-data model is trained for a fixed 15 epochs. Validation-based early stopping and a separate learning-rate scheduler are not used. A fixed training budget ensures consistency across folds and random seeds and avoids differences in training duration caused by noisy fold-level validation metrics. After cross-validation, three models are independently trained on the complete training set using the same configuration. The deployed sequence probability is obtained by averaging these three full-data models rather than selecting the seed with the highest validation performance.

3D chemical-site stage. The full-atom chemical-site refinement uses a batch size of 32, a learning rate of 5×10^{-4}, a weight decay of 1×10^{-4}, a maximum duration of 30 epochs, early-stopping patience of 8 epochs, base structural dropout of 0.22, and chemical-site dropout of 0.1. This stage is initialized from a pLDDT-aware geometric checkpoint, and only the chemical-site branch is made trainable. Training is terminated when the validation MCC does not improve for eight consecutive epochs, and the checkpoint with the highest validation MCC is retained.

Conformer-residual stage. The conformer-ensemble residual stage uses a batch size of 32, a learning rate of 1×10^{-3}, a weight decay of 5×10^{-4}, a maximum duration of 50 epochs, early-stopping patience of 8 epochs, conformer-residual dropout of 0.25, a conformer hidden dimension of 32, an initial conformer weight of 0.25, and a residual L1 coefficient of 0.005. Validation loss is used instead of training accuracy to select the conformer checkpoint, reducing sensitivity to threshold fluctuations arising from limited conformer coverage. Only conformer-related modules are optimized, whereas the geometric and chemical backbone remains frozen.

During structural-expert training, gradients of all trainable parameters are clipped to a maximum norm of 5.0 ($\|\nabla_\phi \mathcal{L}\|_2 \leq 5.0$), limiting unusually large gradients caused by local residual corrections or coordinate perturbations.

When a full-data structural checkpoint is required, the number of refitting epochs is not selected using either benchmark test set. Instead, a fixed epoch count is obtained from the median of the fold-specific selected epochs. For the single-structure chemical-site backbone, the recorded fold-level epochs are 8, 8, 14, 2, and 4, whose median is 8, and the full-data refit is trained for eight fixed epochs. The conformer-statistics residual is a separate stage trained only on the PepFlow pilot250 subset; its recorded fold-level epochs are 23, 18, 9, 12, and 1, whose median is 12, and the full pilot250 refit is trained for twelve fixed epochs.

2.5.4 OOF-Based Calibration, Fusion-Weight Selection, and Threshold Freezing

«««< HEAD

All calibration, fusion-weight, and threshold decisions are made exclusively on training out-of-fold (OOF) predictions generated under the fixed group-aware five-fold partition; Test1 and Test2 are never used for any parameter selection.

1D calibration. The OOF probabilities of the three seeds are averaged per sample, and a two-parameter Platt calibrator is fitted on these OOF ensemble scores (Eq. (**??**)); the fitted parameters are frozen and applied at inference.

Fusion-weight and threshold. For a grid of 1D weights $w \in [0, 1]$ (step 0.02), the fused OOF score $p = w\, p_{\mathrm{1D}} + (1 - w)\, p_{\mathrm{SE3D}}$ is thresholded and the Matthews correlation coefficient (MCC) on training OOF is computed; the weight–threshold pair maximizing OOF MCC is frozen as the deployed operating point ($w = 0.72$, threshold 0.4702).

Protocol note. In the original selection the 3D side of the OOF fusion used the previous-generation fused OOF (0.62× old ProtT5-TextCNN + 0.38× 3D expert). Re-selecting on the current 3D-expert OOF yields $w = 0.72$, threshold 0.4702, with held-out Test2 unchanged and Test1 BACC 0.9354 → 0.9323 (see `runs/lora_mamba_full/protocol_audit.json`). The deployed operating point is $w = 0.72$, threshold 0.4702. ======= After the expert-level OOF

predictions have been generated, model selection proceeds at the probability level. No ProtT5, Mamba, EGNN, chemical-site, or conformer-residual parameters are updated during this stage. Only the training OOF probabilities are used to determine the calibrator, fusion weight, and final decision threshold.

The three seed-specific 1D OOF probabilities are first averaged and calibrated using the monotonic Platt mapping described in Section 2.3.4:

$$p_{i,\mathrm{1D}}^{\mathrm{cal}} = \sigma\left[a\,\mathrm{logit}\left(\bar{p}_{i,\mathrm{1D}}^{\mathrm{OOF}}\right) + b\right], \qquad a = \exp(\eta) > 0, \tag{76}$$

where the scale is parameterized as a positive value, $a = \exp(\eta) > 0$, as described in Section 2.3.4. Platt calibration is applied only to the 1D ensemble. The structural-expert probability is not subjected to an additional top-level calibrator, and no new calibrator is fitted after the final fusion.

The calibrated sequence probability and the structural-expert probability are combined in probability space:

$$p_i(w) = w\,p_{i,\mathrm{1D}}^{\mathrm{cal}} + (1-w)\,p_{i,\mathrm{SE3D}}^{\mathrm{OOF}}, \qquad 0 \le w \le 1, \tag{77}$$

where w denotes the 1D expert weight and $1-w$ denotes the sequence-enhanced structural-expert weight. No additional stacking classifier or sample-specific routing network is fitted at this stage, reducing the risk of second-level overfitting to the finite OOF table.

For a candidate weight w and threshold τ, the predicted class is

$$\hat{y}_i(w,\tau) = \mathbb{I}\left[p_i(w) \ge \tau\right], \tag{78}$$

and the frozen parameters are selected according to

$$(w^*, \tau^*) = \arg\max_{w,\tau}\ \mathrm{MCC}\left(\mathbf{y}, \hat{\mathbf{y}}(w,\tau)\right). \tag{79}$$

MCC is used as the primary objective because of the pronounced class imbalance in the benchmark data, particularly in Test2. Balanced accuracy was used as the secondary selection criterion when candidate operating points produced identical MCC values under the evaluated search procedure.

The frozen values are

$$w_{\mathrm{1D}}^* = 0.62, \qquad w_{\mathrm{SE3D}}^* = 0.38, \qquad \tau^* = 0.4976932219075496 \approx 0.4977, \tag{80}$$

where the full-precision threshold is rounded to 0.4977 when reported in the final decision rule. The final probability and class prediction are therefore

$$p_{\mathrm{GHXTox}} = 0.62\,p_{1D}^{\mathrm{cal}} + 0.38\,p_{\mathrm{SE3D}}, \qquad \hat{y} = \mathbb{I}\left[p_{\mathrm{GHXTox}} \ge 0.4977\right]. \tag{81}$$

A second-level leave-one-fold-out analysis is additionally performed as a stability diagnostic. In each iteration, w and τ are selected using four OOF folds and applied to the remaining fold. This analysis assesses whether the fusion parameters are disproportionately dependent on a particular fold. However, because every upstream prediction stream is not fully regenerated within a separately nested outer loop, this diagnostic is not described as strict nested external validation.

The final values of 0.62/0.38 and 0.4977 are frozen from the complete training OOF table. The corresponding fused OOF metrics describe training-stage model selection rather than benchmark test-set performance. After freezing, the same calibration parameters, fusion weights, and threshold are applied unchanged to Test1 and Test2:

$$(a^*, b^*, w^*, \tau^*)_{\mathrm{Test}} = (a^*, b^*, 0.62, 0.4976932219075496)_{\mathrm{Training\ OOF}}. \tag{82}$$

Neither Test1 nor Test2 labels are used for recalibration or parameter adjustment. The frozen parameters, input prediction files, fusion space, and decision threshold are stored in machine-readable artifacts to permit auditing of the final evaluation protocol. »»»> cb384a004be5a3fb57bbb060fd858090f90efe12

2.6 Evaluation Metrics

To comprehensively evaluate GHXTox for peptide toxicity prediction, model performance is assessed from three complementary perspectives: classification performance at a fixed operating threshold, ranking ability based on continuous probability scores, and probabilistic calibration. Reliance on a single metric may conceal important differences in minority-class recognition, false-positive control, or probability reliability. We therefore jointly report confusion-matrix metrics, the area under the receiver operating characteristic curve (AUROC), the area under the precision–recall curve (AUPRC), the Brier score, and the expected calibration error (ECE).

Let the evaluation set contain N peptides. The ground-truth label of peptide i is

$$y_i \in \{0, 1\}, \qquad p_i = \mathbb{P}\left(y_i = 1 \mid \mathcal{S}_i\right), \tag{83}$$

where $y_i = 1$ denotes a toxic peptide, $y_i = 0$ denotes a non-toxic peptide, and $\mathcal{S}_i$ denotes the peptide sequence. The binary prediction is obtained using a fixed decision threshold τ:

$$\hat{y}_i = \mathbb{I}\left(p_i \geq \tau\right). \tag{84}$$

For the final GHXTox model, the threshold is frozen using the complete training OOF table, as described in Section 2.5.4. Its full-precision value is $\tau^* = 0.4976932219075496$, which is rounded to $\tau = 0.4977$ for presentation in the manuscript and result tables. The same frozen threshold is applied unchanged to Test1 and Test2, without dataset-specific retuning. Threshold-dependent metrics are calculated from $\hat{y}_i$, whereas AUROC, AUPRC, the Brier score, and ECE are calculated directly from the continuous probability p_i.

Because Test2 contains only 46 toxic peptides and 536 non-toxic peptides, its class distribution is strongly imbalanced. Accuracy alone may therefore provide an incomplete description of toxic-peptide recognition. Balanced accuracy (BACC) and the Matthews correlation coefficient (MCC) are emphasized as balanced summary measures; sensitivity (SN) and specificity (SP) are reported to expose the trade-off between missed toxic peptides and false alarms; and AUPRC and calibration metrics are reported together with AUROC.

2.6.1 Threshold-Dependent Classification Metrics

At a fixed decision threshold, the predictions can be summarized by four confusion-matrix counts:

$$\begin{aligned} \mathrm{TP} &= \sum_{i=1}^{N} \mathbb{I}\left(y_i = 1,\ \hat{y}_i = 1\right), \quad \mathrm{TN} = \sum_{i=1}^{N} \mathbb{I}\left(y_i = 0,\ \hat{y}_i = 0\right), \\ \mathrm{FP} &= \sum_{i=1}^{N} \mathbb{I}\left(y_i = 0,\ \hat{y}_i = 1\right), \quad \mathrm{FN} = \sum_{i=1}^{N} \mathbb{I}\left(y_i = 1,\ \hat{y}_i = 0\right), \end{aligned} \tag{85}$$

where TP denotes toxic peptides correctly identified as toxic, TN denotes non-toxic peptides correctly identified as non-toxic, FP denotes non-toxic peptides incorrectly predicted as toxic, and FN denotes toxic peptides incorrectly predicted as non-toxic.

Accuracy. Accuracy measures the proportion of correctly classified samples:

$$\mathrm{ACC} = \frac{\mathrm{TP} + \mathrm{TN}}{\mathrm{TP} + \mathrm{TN} + \mathrm{FP} + \mathrm{FN}}. \tag{86}$$

ACC provides an overall correctness measure but may be dominated by the majority class in strongly imbalanced datasets. A model biased toward non-toxic predictions may still achieve high ACC when non-toxic peptides greatly outnumber toxic peptides. ACC is therefore not used as the sole measure of predictive performance.

Sensitivity and specificity. Sensitivity, also referred to as recall or the true-positive rate, measures the fraction of toxic peptides correctly identified:

$$\mathrm{SN} = \frac{\mathrm{TP}}{\mathrm{TP} + \mathrm{FN}}, \qquad \mathrm{SP} = \frac{\mathrm{TN}}{\mathrm{TN} + \mathrm{FP}}. \tag{87}$$

A high SN indicates that relatively few toxic peptides are missed. In a toxicity-screening context, FN corresponds to potentially hazardous peptides that are not detected, making SN an important measure of toxic-class coverage. Specificity, or the true-negative rate, measures the fraction of non-toxic peptides correctly rejected. A high SP indicates that relatively few non-toxic candidates are falsely labeled as toxic. SN and SP should be interpreted jointly: lowering the decision threshold generally increases SN but may increase FP and reduce SP, whereas increasing the threshold may produce the opposite trade-off.

Precision and F1 score. Precision measures the proportion of predicted toxic peptides that are truly toxic:

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}, \qquad F_1 = \frac{2 \cdot \text{Precision} \cdot \text{SN}}{\text{Precision} + \text{SN}} = \frac{2\,\text{TP}}{2\,\text{TP} + \text{FP} + \text{FN}}. \tag{88}$$

Precision reflects the reliability of positive toxicity predictions. Because Precision depends on the prevalence of toxic peptides, comparisons across datasets with different class ratios should be interpreted together with the corresponding sample composition. The F1 score balances positive-prediction purity and toxic-peptide recall; however, it does not explicitly include TN and therefore does not fully describe performance on the non-toxic class.

Balanced accuracy. Balanced accuracy is the arithmetic mean of sensitivity and specificity:

$$\text{BACC} = \frac{\text{SN} + \text{SP}}{2}. \tag{89}$$

BACC assigns equal importance to the toxic and non-toxic classes, preventing the larger class from directly dominating the final score. A model performing well on one class but poorly on the other will therefore have a noticeably lower BACC than ordinary ACC.

Matthews correlation coefficient. The Matthews correlation coefficient incorporates all four elements of the confusion matrix:

$$\text{MCC} = \frac{\text{TP} \cdot \text{TN} - \text{FP} \cdot \text{FN}}{\sqrt{(\text{TP} + \text{FP})(\text{TP} + \text{FN})(\text{TN} + \text{FP})(\text{TN} + \text{FN})}}, \tag{90}$$

with $-1 \leq \text{MCC} \leq 1$. An MCC of 1 indicates perfect agreement, 0 indicates no overall correlation between predictions and labels, and -1 indicates complete disagreement. Because MCC jointly accounts for TP, TN, FP, and FN, it was used as the primary summary metric for fixed-threshold classification and as the primary objective for OOF fusion-parameter selection [CITE: Matthews correlation coefficient].

Numerical safeguards were applied when metric denominators were zero. All threshold-dependent metrics were calculated using the same OOF-frozen GHXTox decision threshold, consistent with the freezing protocol described in Section 2.5.4; no metric-specific or test-set-specific threshold optimization was performed.

2.6.2 Ranking and Probability-Calibration Metrics

Fixed-threshold metrics describe classification at one operating point but do not fully characterize sample ranking across all possible thresholds or determine whether the predicted probabilities have reliable numerical meaning. We therefore additionally report AUROC, AUPRC, the Brier score, and ECE-10. AUROC and AUPRC evaluate probability ranking, whereas the Brier score and ECE evaluate probabilistic error and calibration.

ROC curve and AUROC. For a varying probability threshold t, the true-positive rate and the false-positive rate are

$$\text{TPR}(t) = \frac{\text{TP}(t)}{\text{TP}(t) + \text{FN}(t)}, \qquad \text{FPR}(t) = \frac{\text{FP}(t)}{\text{FP}(t) + \text{TN}(t)}. \tag{91}$$

The ROC curve plots $\mathrm{TPR}(t)$ against $\mathrm{FPR}(t)$ over all thresholds, and its area is

$$\mathrm{AUROC} = \int_0^1 \mathrm{TPR}(u)\, du, \tag{92}$$

where u denotes the false-positive rate. AUROC measures the ability of the model to rank a randomly selected toxic peptide above a randomly selected non-toxic peptide. Values approaching one indicate strong ranking performance, whereas values near 0.5 generally indicate approximately random ranking. AUROC is independent of the fixed decision threshold and therefore complements the threshold-dependent metrics. Although AUROC is insensitive to class prevalence, it may underemphasize positive-class retrieval quality and the practical false-positive burden under severe class imbalance. AUPRC is therefore reported as a complementary ranking metric. Recent studies in peptide toxicity prediction commonly report ROC and PR analyses together [CITE: representative peptide-toxicity studies].

Precision–Recall curve and AUPRC. For threshold t, Precision and Recall are defined as

$$\mathrm{Precision}(t) = \frac{\mathrm{TP}(t)}{\mathrm{TP}(t) + \mathrm{FP}(t)}, \qquad \mathrm{Recall}(t) = \frac{\mathrm{TP}(t)}{\mathrm{TP}(t) + \mathrm{FN}(t)}. \tag{93}$$

The PR curve describes the trade-off between positive-prediction purity and toxic-peptide recall as the threshold varies. In the current implementation, AUPRC is calculated as average precision through `average_precision_score`. Let P_n and R_n denote Precision and Recall at the n-th score threshold after samples have been ranked in descending order; the reported value is

$$\mathrm{AUPRC}_{\mathrm{reported}} \coloneqq \mathrm{AP} = \sum_n (R_n - R_{n-1})\, P_n. \tag{94}$$

Throughout this study, the metric is reported as AUPRC, while its numerical value is computed using average precision. This definition weights Precision by the increase in Recall and is not necessarily identical to a trapezoidal numerical integral of the PR curve. AUPRC focuses on retrieval of the positive toxic class and is particularly informative when toxic peptides are relatively rare. Because the chance-level PR baseline is determined by the positive-class prevalence, AUPRC values for Test1 and Test2 should be interpreted within their respective class distributions rather than treated as directly comparable measures of dataset difficulty. AUROC and AUPRC are reported only when both classes are present in the evaluation subset; otherwise, the implementation returns an undefined value.

Brier score. The Brier score is the mean squared difference between the predicted probability and the binary ground-truth label [CITE: Brier 1950]:

$$\mathrm{Brier} = \frac{1}{N} \sum_{i=1}^{N} (p_i - y_i)^2 . \tag{95}$$

Its range is $0 \leq \mathrm{Brier} \leq 1$, with lower values indicating better probabilistic predictions. The Brier score penalizes both incorrect predictions and excessive confidence: assigning a probability of 0.01 to a truly toxic peptide incurs a larger Brier error than assigning a probability of 0.40. The Brier score reflects both probability calibration and discriminative performance and should not be interpreted as a pure calibration measure; it is therefore considered jointly with AUROC, AUPRC, and ECE.

Ten-bin expected calibration error. To further quantify the agreement between predicted confidence and observed toxicity frequency, we calculate the expected calibration error using ten equal-width probability bins, denoted ECE-10 [CITE: expected calibration error]. The interval $[0, 1]$ is divided into $M = 10$ bins, and for each non-empty bin the mean predicted

confidence and the observed toxic-peptide frequency are

$$\begin{aligned} \mathcal{B}_m &= \left\{ i : p_i \in \left[\frac{m-1}{M},\ \frac{m}{M} \right) \right\}, \quad m = 1, \ldots, M, \\ \mathrm{conf}\left(\mathcal{B}_m\right) &= \frac{1}{|\mathcal{B}_m|} \sum_{i \in \mathcal{B}_m} p_i, \\ \mathrm{freq}\left(\mathcal{B}_m\right) &= \frac{1}{|\mathcal{B}_m|} \sum_{i \in \mathcal{B}_m} y_i, \end{aligned} \tag{96}$$

with the final bin including $p_i = 1$. ECE-10 is defined as

$$\mathrm{ECE}_{10} = \sum_{m=1}^{10} \frac{|\mathcal{B}_m|}{N} \left| \mathrm{conf}\left(\mathcal{B}_m\right) - \mathrm{freq}\left(\mathcal{B}_m\right) \right|. \tag{97}$$

Values closer to zero indicate better agreement between predicted confidence and observed toxicity frequency; for example, a well-calibrated group of predictions near 0.8 should contain approximately 80% toxic peptides. Because ECE depends on the binning scheme, the number and boundaries of the bins remain fixed across models and datasets.

Joint interpretation of the metrics. No individual metric is sufficient to characterize peptide-toxicity prediction; the reported measures are therefore interpreted jointly. ACC summarizes overall correctness; SN and SP quantify toxic-peptide misses and non-toxic false positives, respectively; BACC evaluates class-balanced recognition; MCC provides a comprehensive correlation-based measure using all four confusion-matrix terms; AUROC and AUPRC assess ranking performance; and the Brier score and ECE-10 characterize probabilistic reliability. Exact numerical tables are used as the primary form of model comparison, with ROC and PR curves presented together. Radar charts, when included, are treated only as secondary summaries and do not replace exact metric tables or uncertainty analysis.

2.7 Robustness, Uncertainty, and Statistical Analysis

A single performance point estimate cannot fully characterize the reliability of a deep learning predictor. Model performance may be affected by random initialization, finite evaluation samples, class imbalance, predicted- structure quality, and distribution shift. GHXTox is therefore evaluated from five complementary perspectives: multi-seed reproducibility, class-stratified bootstrap confidence intervals, paired significance testing between frozen models, subgroup and structure-quality analysis, and frozen external-transfer evaluation.

All analyses in this section are conducted after the model architecture, checkpoints, probability-calibration parameters, fusion weights, and decision threshold have been frozen. No ProtT5, Mamba, EGNN, chemical-site, or conformer-residual parameters are updated during statistical evaluation, and the threshold is not modified according to the resulting confidence intervals or significance tests. This design explicitly separates model development from frozen-model evaluation.

Three sources of uncertainty are distinguished. Multi-seed analysis characterizes variation arising from stochastic optimization; bootstrap intervals quantify finite-sample uncertainty conditional on a frozen predictor; and subgroup analyses examine whether predictive performance is concentrated within particular sequence-length, physicochemical, or structure-confidence ranges. These analyses provide complementary evidence and should not be interpreted as interchangeable measures of uncertainty.

2.7.1 Multi-Seed Reproducibility and Prediction Dispersion

Neural-network training may vary because of parameter initialization, mini-batch ordering, dropout masks, and mixed-precision computation. To assess the sensitivity of the 1D expert

to these factors, three LoRA-ProtT5 and bidirectional Mamba models are trained using the random seeds $\mathcal{R} = \{42, 123, 2025\}$, while keeping the data partitions, architecture, training duration, and all hyperparameters unchanged. The current 1D expert uses an equal-weight probability average of the three full-data models rather than selecting the best-performing seed post hoc. The top-level model retains a single frozen 3D structural expert: the evaluated multi-checkpoint 3D ensemble did not satisfy the prespecified promotion criterion and was therefore not adopted in the current default GHXTox model.

For an evaluation metric M, let $M^{(s)}$ denote the result obtained using seed s. The multi-seed mean and the sample standard deviation are

$$\bar{M} = \frac{1}{S}\sum_{s=1}^{S} M^{(s)}, \quad \mathrm{SD}(M) = \sqrt{\frac{1}{S-1}\sum_{s=1}^{S}\left(M^{(s)} - \bar{M}\right)^2}, \qquad S = 3, \tag{98}$$

and seed-level reproducibility may therefore be reported as $\bar{M} \pm \mathrm{SD}(M)$. All seed-specific models must be evaluated using the same frozen threshold, or using thresholds selected without access to the corresponding test set; a test-specific optimal threshold must not be selected separately for each seed.

Prediction dispersion can also be quantified at the sample level. For peptide i, let $p_{i,1\mathrm{D}}^{(s)}$ denote the uncalibrated probability from seed s. The seed-averaged probability and the seed dispersion are

$$\bar{p}_{i,1\mathrm{D}}^{\mathrm{raw}} = \frac{1}{S}\sum_{s=1}^{S} p_{i,1\mathrm{D}}^{(s)}, \quad u_{i,\mathrm{seed}} = \sqrt{\frac{1}{S-1}\sum_{s=1}^{S}\left(p_{i,1\mathrm{D}}^{(s)} - \bar{p}_{i,1\mathrm{D}}^{\mathrm{raw}}\right)^2}, \tag{99}$$

where $\bar{p}_{i,1\mathrm{D}}^{\mathrm{raw}}$ denotes the uncalibrated three-seed average used at inference, which is distinguished from the training-time OOF average $\bar{p}_{i,1\mathrm{D}}^{\mathrm{OOF}}$ defined in Section 2.5.1. A large $u_{i,\mathrm{seed}}$ indicates that the prediction is sensitive to optimization randomness and may be used to flag boundary cases or expert-disagreement samples. It is, however, an empirical measure of training variability rather than a Bayesian posterior uncertainty estimate or a direct probability of prediction error.

The final 1D pathway follows the order defined in Section 2.3.4:

$$\left\{p_{i,1\mathrm{D}}^{(s)}\right\}_{s=1}^{3} \longrightarrow \bar{p}_{i,1\mathrm{D}}^{\mathrm{raw}} \longrightarrow \text{OOF-fitted Platt calibration} \longrightarrow p_{i,1\mathrm{D}}^{\mathrm{cal}}.$$

Seed-specific metrics characterize training stability, whereas the calibrated three-seed average is used for top-level 1D/3D fusion. The best individual seed is not substituted for the expected multi-seed result. The final calibrated ensemble prediction is a deterministic function of the three trained seed models; seed-level variability is summarized by $u_{i,\mathrm{seed}}$ rather than being treated as zero. Accordingly, variability is reported across the constituent seed models rather than by assigning a standard deviation of zero to their averaged prediction.

2.7.2 Class-Stratified Bootstrap Confidence Intervals

Performance metrics calculated on a finite test set are themselves estimates. This issue is particularly important for Test2, where a small number of changes in TP or FN can substantially alter SN, BACC, and MCC. We therefore use class-stratified percentile bootstrap resampling to calculate 95% confidence intervals [CITE: Efron and Tibshirani, bootstrap].

Let the positive- and negative-class index sets be

$$\begin{aligned}
&\mathcal{I}_+ = \{i : y_i = 1\}, && \mathcal{I}_- = \{i : y_i = 0\},\\
&\mathbf{i}_+^{(b)} \sim \mathrm{SampleWithReplacement}\left(\mathcal{I}_+,\ |\mathcal{I}_+|\right), && \mathbf{i}_-^{(b)} \sim \mathrm{SampleWithReplacement}\left(\mathcal{I}_-,\ |\mathcal{I}_-|\right),\\
&\mathbf{i}^{(b)} = \mathrm{Concat}\left(\mathbf{i}_+^{(b)},\ \mathbf{i}_-^{(b)}\right),
\end{aligned} \tag{100}$$

where the bootstrap index vectors preserve repeated indices. This procedure preserves the original number of positive and negative samples in every replicate, avoiding extreme class-ratio fluctuations or single-class replicates when the positive class is small. The validation implementation independently resamples the positive and negative index sets with replacement.

For metric M, the bootstrap estimate is

$$M^{(b)} = M\left(\mathbf{y}_{\mathbf{i}^{(b)}},\ \mathbf{p}_{\mathbf{i}^{(b)}}\right), \qquad b = 1, \ldots, B. \tag{101}$$

The primary test-set analysis used $B = 5000$ bootstrap replicates, whereas subgroup-difference analyses used 1000 replicates. The percentile confidence interval is

$$\mathrm{CI}_{95\%}(M) = \left[Q_{0.025}\left(\left\{M^{(b)}\right\}_{b=1}^{B}\right),\ Q_{0.975}\left(\left\{M^{(b)}\right\}_{b=1}^{B}\right)\right], \tag{102}$$

where Q_α is the empirical α-quantile.

For ACC, BACC, SN, SP, F1, and MCC, each bootstrap replicate uses the original frozen model threshold; the threshold is not reoptimized within any resampled data set. AUROC, AUPRC, and the Brier score are calculated directly from the resampled continuous probabilities.

These intervals quantify finite-sample uncertainty conditional on the frozen predictor and the observed evaluation distribution; they do not incorporate training-seed variability or distribution shift. Bootstrap uncertainty is therefore interpreted separately from the multi-seed analysis in Section 2.7.1 and the external-transfer analysis in Section 2.7.5.

2.7.3 Paired Bootstrap and Randomization Significance Testing

When the current GHXTox model is compared with the previous default or another frozen internal baseline, both models produce predictions for the same peptides; the sample-level predictions are therefore paired. Comparing two independent confidence intervals would ignore this dependence. We instead analyze the metric difference directly on aligned samples.

Let M_A and M_B denote the metric values of frozen models A and B, respectively, where B is the current model and A is the frozen baseline. The observed difference is

$$\Delta_M^{\mathrm{obs}} = M_B - M_A. \tag{103}$$

For BACC, SN, SP, F1, MCC, AUROC, and AUPRC, a positive difference favors model B; for lower-is-better measures such as the Brier score and ECE, a negative difference indicates improvement.

Paired class-stratified bootstrap. For every bootstrap replicate, the same class-stratified index vector $\mathbf{i}^{(b)}$ defined in Section 2.7.2 is applied to both models:

$$\Delta_M^{(b)} = M\left(\mathbf{y}_{\mathbf{i}^{(b)}},\ \mathbf{p}_{B,\mathbf{i}^{(b)}}\right) - M\left(\mathbf{y}_{\mathbf{i}^{(b)}},\ \mathbf{p}_{A,\mathbf{i}^{(b)}}\right), \tag{104}$$

where using identical indices preserves the paired sample structure. The 95% percentile interval is

$$\mathrm{CI}_{95}\left(\Delta_M\right) = \left[Q_{0.025}\left(\left\{\Delta_M^{(b)}\right\}_{b=1}^{B}\right),\ Q_{0.975}\left(\left\{\Delta_M^{(b)}\right\}_{b=1}^{B}\right)\right]. \tag{105}$$

For a higher-is-better metric, an interval entirely above zero supports a consistent positive difference; for a lower-is-better metric such as the Brier score, improvement corresponds to an interval entirely below zero. Using a metric-direction coefficient s_M, where $s_M = +1$ for higher-is-better metrics and $s_M = -1$ for lower-is-better metrics, the bootstrap probability of improvement is

$$P_{\mathrm{boot}}^{\mathrm{improve}} = \frac{1}{B}\sum_{b=1}^{B}\mathbb{I}\left(s_M\,\Delta_M^{(b)} > 0\right). \tag{106}$$

This quantity is the proportion of bootstrap replicates in which the current model outperforms the baseline; it is not a classical hypothesis-test p-value and should not be reported using an undifferentiated P label.

Paired randomization test. A within-sample exchange randomization test is additionally used to evaluate the null hypothesis that the two frozen model outputs are exchangeable for each peptide [CITE: paired randomization test]. For randomization replicate r, $z_i^{(r)} \sim \text{Bernoulli}(0.5)$ is independently drawn for each sample; if $z_i^{(r)} = 1$, the probabilities and frozen-threshold decisions of models A and B are exchanged for sample i, and otherwise they remain unchanged. The resulting null difference is

$$\Delta_{M,0}^{(r)} = M_B^{(r)} - M_A^{(r)}. \tag{107}$$

A two-sided paired randomization test was performed by comparing the absolute randomized metric differences with the absolute observed difference:

$$p_{\text{rand}} = \frac{1 + \sum_{r=1}^{R} \mathbb{I}\left(\left|\Delta_{M,0}^{(r)}\right| \geq \left|\Delta_M^{\text{obs}}\right|\right)}{R+1}. \tag{108}$$

The primary paired analysis uses $B = 5000$ and $R = 5000$ replicates with a fixed seed of 2026. The implementation exchanges both continuous scores and the corresponding frozen-threshold decisions within each sample.

MCC and BACC are treated as prespecified primary summary measures, whereas SN, SP, AUROC, AUPRC, and the Brier score provide complementary evidence. Because several correlated metrics are examined for the same model comparison, secondary p-values are interpreted descriptively rather than as multiple independent discoveries.

Finally, Test1 and Test2 have been repeatedly observed during the historical development of the project. Paired confidence intervals and randomization p-values on these sets therefore provide retrospective evidence for differences between frozen models, rather than fully independent prospective confirmation; this limitation is explicitly recorded by the project validation implementation.

2.7.4 Subgroup and Structure-Quality Analysis

2.7.5 Frozen External Generalization Evaluation

2.8 Interpretability Analysis Protocol

2.8.1 Residue Masking and Integrated-Gradient Attribution

2.8.2 Chemical-Site Deletion Analysis

2.8.3 Expert Agreement and Conflict Analysis

3 RESULTS AND DISCUSSION

3.1 Overall Predictive Performance on the Benchmark Test Sets

3.1.1 Comparison with Existing Peptide-Toxicity Predictors

Table 3: Performance comparison on the benchmark Test1 and Test2 sets.

3.1.2 Discrimination, Calibration, and Decision Characteristics

Figure 3: Overall discrimination and calibration performance of GHXTox. (A, B) Test1 ROC and PR curves; (C, D) Test2 ROC and PR curves; (E, F) Test1 and Test2 reliability diagrams.

3.2 Complementarity of the 1D and 3D Experts

3.2.1 Performance of the Individual Experts

Table 4: Performance of the individual experts and the final probability-level fusion.

Figure 4: Complementarity and decision changes induced by expert fusion. (A) scatter of 1D vs SE3D probabilities; (B) error-overlap diagram; (C) probability shifts; (D) corrected/regressed/unchanged counts; (E, F) representative corrected cases.

Table 5: Ablation analysis of the task-adaptive 1D sequence expert.

Table 6: Ablation and computational analysis of the 3D structural expert.

Figure 5: Module-level ablation results for the 1D and 3D experts (A–F).

Table 7: Bootstrap confidence intervals and paired statistics on Test1 and Test2.

3.2.2 Gain from OOF-Frozen Probability Fusion

3.2.3 Expert Agreement, Disagreement, and Error Correction

3.3 Analysis of the Task-Adaptive 1D Sequence Expert

3.3.1 Contribution of LoRA-Based ProtT5 Adaptation

3.3.2 Contribution of Bidirectional Mamba Modeling

3.3.3 Effects of Multi-Seed Ensembling and OOF Calibration

3.4 Analysis of the pLDDT-Aware Multi-Scale 3D Structural Expert

3.4.1 Contribution of pLDDT-Aware Geometric Encoding

3.4.2 Contribution of Full-Atom Chemical-Site Modeling

3.4.3 Role of Sequence–Structure Cross-Attention and Confidence Gating

3.4.4 Conformer Residual and Exact-Fallback Behavior

3.4.5 Model Complexity and Computational Cost

3.5 Robustness, Statistical Uncertainty, and Applicability Analysis

3.5.1 Multi-Seed Reproducibility

3.5.2 Bootstrap Confidence Intervals

3.5.3 Paired Comparison with the Previous Model

3.5.4 Length and Structure-Quality Stratification

3.5.5 External Evidence and Generalization Boundary

3.6 Interpretability and Representative Case Studies

3.6.1 Residue-Level Interpretation of the 1D Expert

3.6.2 Structural and Chemical-Site Interpretation

3.6.3 Expert Agreement and Conflict Interpretation

3.6.4 Representative Conformer Cases

3.7 Limitations and Future Directions

3.7.1 Dataset and Evaluation Limitations

3.7.2 Structural and Conformer Limitations

3.7.3 Modeling and Interpretability Limitations

3.7.4 Future Directions

4 CONCLUSIONS

Data and Software Availability

The source code, configuration files, fold manifests, and inference scripts used in this study are available at [repository]. The manuscript results correspond to commit [HASH] and release

Figure 6: Stratified performance by sequence length, structure quality, and chemical-site coverage (A–F).

Figure 7: Representative interpretability cases for the 1D expert, the 3D expert, and the fused prediction.

[VERSION]. Frozen model parameters, calibration coefficients, fusion weights, the full-precision decision threshold, and sample-level prediction files are provided in [archive/release]. Raw peptide records were obtained from the public databases described in Section 2.1. Where redistribution is restricted by the original database terms, accession lists and preprocessing scripts are provided instead of redistributing the source records.

Supporting Information

Supporting Information is available and includes detailed dataset audits, fold-wise results, hyperparameter settings, additional ablation experiments, subgroup analyses, statistical outputs, and extended interpretability case studies.

CRediT Authorship Contribution Statement

Acknowledgements

Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.