

MPAS-URBAN QUICKSTART | GUIDE 2 OF 3

# Initialize the HRAIN2025 case

---

*Use the public 30 km–500 m grid or optionally regenerate it, then create static and initial-condition files.*

**OUTCOME** You will have the static, initial-condition, and 112-task decomposition files needed to run the HRAIN2025 case.

**AUTHOR** LIU Zhuo

**AFFILIATION** The Hong Kong University of Science and Technology (HKUST)

## Before you begin

Complete Guide 1 and the recommended official MPAS tutorial first. Keep `init_atmosphere_model`, the standard MPAS static data, and the CGLC-LCZ dataset available.

**CASE DESCRIPTION - INTERCOMPARISON GUIDELINES V1.1**

**Event:** The 2025 Black Rainstorm Event - HRAIN2025

**Timespan:** August 2-5, 2025, with the peak on August 5

**Observation highlights:** 358.8 mm on August 5 (355.7 mm at HKO headquarters), the highest single-day August rainfall since 1884; fourth black rainstorm warning in eight days; more than 9,600 cloud-to-ground lightning strikes between 05:00 and 12:00; peak rainfall near 90 mm h<sup>-1</sup>

**Reported impacts:** at least 2 deaths and more than 140 injuries; 42 elevator entrapments, 175 fire-alarm activations, 36 fallen trees, 7 landslides and 69 flooding cases; about 20% of flights cancelled and more than 400 delayed

**Common simulation period:** 2025-08-03 00:00 UTC to 2025-08-06 00:00 UTC (3 days)

**GFS initialization used in this guide:** 2025-08-03\_00:00:00

For a first run, use the public grid and GFS intermediate file. Regenerating the global variable-resolution mesh is optional and requires JIGSAW, METIS, `mpas_tools`, GeoPandas, NumPy, xarray, SciPy, Shapely, and a high-memory compute node.

## Step 1 | Download the ready grid and GFS input

### RECOMMENDED BEGINNER PATH

```
mkdir -p "$HOME/HRAIN2025_INPUT"
cd "$HOME/HRAIN2025_INPUT"

curl -fL -O https://github.com/Liuzh223/HRAIN2025/releases/download/v1.0/MPAS-
Urban_HRAIN2025_30km-to-500m_grid-and-GFS2025080300_v1.0.tar.gz

echo "45fcfab80a3ecb5f8db558a4582d8910d1cac236f202ab499bb2b5e8e0e8143d MPAS-
Urban_HRAIN2025_30km-to-500m_grid-and-GFS2025080300_v1.0.tar.gz" | sha256sum -c -

tar -xzf MPAS-Urban_HRAIN2025_30km-to-500m_grid-and-GFS2025080300_v1.0.tar.gz

ls -lh 30km_500m.grid.nc GFS:2025-08-03_00
```

The archive contains only 30km\_500m.grid.nc and GFS:2025-08-03\_00. The GFS file is already in WPS intermediate format; do not run ungrib.exe on it again.

## Step 2 | Optional: regenerate the Hong Kong mesh

Skip this step when using the public grid. Use it only when you want to change the refinement region or independently reproduce the mesh-generation workflow.

### CHECK THE MESH ENVIRONMENT

```
command -v python
command -v gpmets
python -c "import geopandas, numpy, xarray, scipy, shapely, mpas_tools"
```

### GET THE CASE SOURCE

```
cd "$HOME"
git clone https://github.com/Liuzh223/HRAIN2025.git
cd HRAIN2025

curl -fL https://raw.githubusercontent.com/pedrospeixoto/MPAS-
BR/master/grids/utilities/jigsaw/jigsaw_util.py -o mesh/jigsaw_util.py
```

Download the Hong Kong boundary through the Aliyun DataV area selector and save the exact file as mesh/hongkong.geojson: [https://datav.aliyun.com/portal/school/atlas/area\\_selector](https://datav.aliyun.com/portal/school/atlas/area_selector). This is the source used by the case author. Aliyun DataV is a third-party service and is not an official Hong Kong SAR Government boundary source. Archive the exact GeoJSON for reproducibility, check its terms before redistribution, and note that another boundary can change the generated mesh.

### GENERATE AND PARTITION

```
python mesh/generate_hk_500m_mesh.py --geojson mesh/hongkong.geojson --jigsaw-util
mesh/jigsaw_util.py --output-dir generated_mesh --partitions 112

ls -lh generated_mesh/hk_hull_500m.mpas.nc
ls -lh generated_mesh/hk_hull_500m_graph.info.part.112
```

The generated hk\_hull\_500m.mpas.nc is an MPAS mesh file. The extension is only a filename convention. To use the same filename as the ready case:

```
cp generated_mesh/hk_hull_500m.mpas.nc generated_mesh/30km_500m.grid.nc
```

**MEMORY NOTE** The default global sampling field is memory intensive. A failure caused by insufficient memory is not evidence that the ready Release grid is invalid; use the ready grid for the beginner workflow.

## Step 3 | Create the case directory

### COPY AND LINK THE REQUIRED FILES

```
export MPAS_SRC="$HOME/MPAS/HKUST-MPAS"
# For the optional cutoff build, use instead:
# export MPAS_SRC="$HOME/MPAS/HKUST-MPAS-NTDK"

export HRAIN_REPO="$HOME/HRAIN2025"
export HRAIN_INPUT="$HOME/HRAIN2025_INPUT"
export CASE="$HOME/MPAS_CASES/HRAIN2025_30km_500m"

mkdir -p "$CASE"
cd "$CASE"

ln -sf "$MPAS_SRC/init_atmosphere_model" .
cp "$HRAIN_REPO/config/namelist.init_atmosphere" .
cp "$MPAS_SRC/streams.init_atmosphere" .
ln -sf "$HRAIN_INPUT/30km_500m.grid.nc" .
ln -sf "$HRAIN_INPUT/GFS:2025-08-03_00" .
cp "$HRAIN_REPO/mesh/hk_hull_500m_graph.info.part.112" .
ln -sf "$MPAS_SRC/vertical_levels" .
```

**PATH NOTE** The custom urban vertical-level file referenced by the case namelist must exist under the linked vertical\_levels directory. The Release archive does not contain this file.

## Step 4 | Create the reusable static file

Create a separate static-stage copy before editing. The HRAIN2025 reference namelist below is configured for meteorological initialization, so do not overwrite the only copy.

### REFERENCE NAMELIST

[https://github.com/Liuzh223/HRAIN2025/blob/main/config/namelist.init\\_atmosphere](https://github.com/Liuzh223/HRAIN2025/blob/main/config/namelist.init_atmosphere)

**FILE TO EDIT** Copy namelist.init\_atmosphere to namelist.init.static, then edit namelist.init.static for this step.

**CHANGE 1** - &data\_sources/config\_geog\_data\_path: replace the example relative path with the real absolute directory containing the standard MPAS data and mpas\_cgic\_lcz.

**CHANGE 2** - &data\_sources/config\_landuse\_data: select 'CGLC\_LCZ' for the urban static interpolation.

**CHANGE 3** - &preproc\_stages: use the official tutorial static-stage block below. Enable static and native-GWD processing, disable vertical-grid and meteorological interpolation, keep config\_input\_sst = false, and set config\_frac\_seaice = false.

## ESSENTIAL SETTINGS

```

&nhyd_model
  config_init_case = 7
/

&data_sources
  config_geog_data_path = '/home/USER/MPAS_DATA/mpas_static/'
  config_landuse_data   = 'CGLC_LCZ'
/

&preproc_stages
  config_static_interp   = true
  config_native_gwd_static = true
  config_vertical_grid   = false
  config_met_interp      = false
  config_input_sst       = false
  config_frac_seaice     = false
/

```

FILE TO EDIT `streams.init_atmosphere`. Set the input stream to the grid and the output stream to a new static file:

```

<streams>
<immutable_stream name="input"
  type="input"
  filename_template="30km_500m.grid.nc"
  input_interval="initial_only" />
<immutable_stream name="output"
  type="output"
  filename_template="30km_500m.static.nc"
  packages="initial_conds"
  output_interval="initial_only" />
</streams>

```

## RUN

```

cd "$CASE"
mpiexec -n 1 ./init_atmosphere_model
tail -n 40 log.init_atmosphere.0000.out
ls -lh *.static.nc

```

## Step 5 | Create the initial condition

Restore a fresh copy of the linked HRAIN2025 namelist for meteorological initialization. Edit the fields below before running; do not reuse the static-stage flags.

## REFERENCE NAMELIST

[https://github.com/Liuzh223/HRAIN2025/blob/main/config/namelist.init\\_atmosphere](https://github.com/Liuzh223/HRAIN2025/blob/main/config/namelist.init_atmosphere)

CHANGE 1 - `&nhyd_model`: `config_start_time` and `config_stop_time` must both be 2025-08-03\_00:00:00.

CHANGE 2 - `&data_sources`: `config_met_prefix` = 'GFS' must match GFS:2025-08-03\_00.

CHANGE 3 - `&vertical_grid`: `config_specified_zeta_levels` must point to an existing `vertical_levels/urban_ZR_75.txt`.

CHANGE 4 - `&preproc_stages`: use the complete meteorological-initialization block below. Switch off static and native-GWD generation, switch on vertical-grid and GFS interpolation, and keep `config_input_sst` = false and `config_frac_seaice` = true.

CHANGE 5 - &decomposition: keep the prefix `hk_hull_500m_graph.info.part.` so that 112 tasks select the supplied `.part.112` file.

#### ESSENTIAL SETTINGS

```
&nhyd_model
  config_init_case = 7
  config_start_time = '2025-08-03_00:00:00'
  config_stop_time = '2025-08-03_00:00:00'
/

&data_sources
  config_met_prefix = 'GFS'
/

&preproc_stages
  config_static_interp = false
  config_native_gwd_static = false
  config_vertical_grid = true
  config_met_interp = true
  config_input_sst = false
  config_frac_seaice = true
/

&decomposition
  config_block_decomp_file_prefix =
    'hk_hull_500m_graph.info.part.'
/
```

FILE TO EDIT `streams.init_atmosphere`. Use the static file as input and choose the initial-condition output:

```
<streams>
<immutable_stream name="input"
  type="input"
  filename_template="30km_500m.static.nc"
  input_interval="initial_only" />
<immutable_stream name="output"
  type="output"
  filename_template="30km_500m.init.nc"
  packages="initial_conds"
  output_interval="initial_only" />
</streams>
```

#### RUN WITH THE MATCHING PARTITION

```
export OMP_NUM_THREADS=1
mpiexec -n 112 ./init_atmosphere_model
tail -n 50 log.init_atmosphere.0000.out
ls -lh *.init.nc
```

CHECK The MPI task count must match the `.part.112` suffix. Do not use the single GFS file for another initialization time.

## If you need another date

Follow the official MPAS/WPS tutorial to download the matching GFS GRIB2 files and run WPS `ungrib.exe`. Use the prefix `GFS` and provide every valid time required by the intended initialization. The HRAIN2025 Release file is only for 2025-08-03\_00:00:00.

This HRAIN2025 mesh is global with variable resolution, so the beginner workflow does not create limited-area lateral boundary files.

## Ready for Guide 3

- The static file exists and is non-empty.
- The 2025-08-03\_00:00:00 initial-condition file exists and is non-empty.
- The decomposition file ends in .part.112 and the planned run uses 112 MPI tasks.

## Primary references

- Intercomparison Guidelines v1.1: Sections 2.2.2 and 3.1 (supplied project PDF)
- HRAIN2025: <https://github.com/Liuzh223/HRAIN2025>
- Official MPAS tutorial: <https://mpas-dev.github.io/atmosphere/tutorial.html>
- Hong Kong boundary used by this case (third-party, not an official Hong Kong SAR Government source): [https://datav.aliyun.com/portal/school/atlas/area\\_selector](https://datav.aliyun.com/portal/school/atlas/area_selector)