

MPAS-URBAN QUICKSTART | GUIDE 3 OF 3

Run the HRAIN2025 case

Prepare the run directory, apply the 500 m mesh setting, and optionally use the HRAIN2025 NTDK cutoff modification.

OUTCOME You will launch the three-day HRAIN2025 atmosphere experiment and understand which settings are standard, case-specific, or required only for comparison with existing historical results.

AUTHOR LIU Zhuo

AFFILIATION The Hong Kong University of Science and Technology (HKUST)

Before you begin

Complete the recommended official MPAS tutorial and Guides 1–2. Confirm that the initial-condition file and `hk_hull_500m_graph.info.part.112` exist.

Choose the executable deliberately: standard `hkust-dev` for normal MPAS-Urban learning and new experiments, or the verified HRAIN2025 case-specific commit

`57b42fa1d7649117bbf28a69c47697ea8756d268` for direct historical-result comparison and the optional 10 km CU cutoff. The latter also includes the HRAIN2025 ZT compatibility setting.

Step 1 | Prepare the run directory

Guide 2 created an independent case under `$HOME/MPAS`. Select the same compiled build used for initialization, then link all runtime files from that build into the existing case.

SELECT THE SAME COMPILED BUILD

```
export MPAS_ROOT="$HOME/MPAS"
export MPAS_BUILD="$MPAS_ROOT/HKUST-MPAS"
```

```
test -x "$MPAS_BUILD/atmosphere_model"
```

For the verified HRAIN2025 comparison/cutoff build, replace `MPAS_BUILD` with `$MPAS_ROOT/HKUST-MPAS-NTDK`. Do not mix files from the two builds.

ENTER THE EXISTING CASE

```
export HRAIN_REPO="$MPAS_ROOT/HRAIN2025"
export CASE="$MPAS_ROOT/HRAIN2025_30km_500m"
```

```
test -d "$CASE"
cd "$CASE"
test -s 30km_500m.init.nc
test -s hk_hull_500m_graph.info.part.112
```

COPY THE RUN CONFIGURATION

```
cp "$HRAIN_REPO/config/namelist.atmosphere" ./namelist.atmosphere
cp "$MPAS_BUILD/streams.atmosphere" ./streams.atmosphere
```

LINK ALL RUNTIME FILES FROM THE SELECTED BUILD

```
ln -sf "$MPAS_BUILD/atmosphere_model" ./atmosphere_model
ln -sf "$MPAS_BUILD"/default_inputs/stream_list.atmosphere.* .
ln -sf "$MPAS_BUILD"/src/core_atmosphere/physics/physics_wrf/files/*TBL .
ln -sf "$MPAS_BUILD"/src/core_atmosphere/physics/physics_wrf/files/*DATA* .
ln -sf "$MPAS_BUILD"/src/core_atmosphere/physics/physics_noahmp/parameters/*TBL .
```

FINAL FILE CHECK

```
ls -lh atmosphere_model
ls -lh namelist.atmosphere streams.atmosphere
ls -lh 30km_500m.init.nc hk_hull_500m_graph.info.part.112
```

BUILD CONSISTENCY NOTE The executable, streams file, stream lists, physics tables, and data links must all come from the same MPAS_BUILD. Do not relink a case after it has produced output; use a separate case directory when comparing source versions.

Step 2 | Set the case time and mesh scale

REFERENCE NAMELIST

<https://github.com/Liuzh223/HRAIN2025/blob/main/config/namelist.atmosphere>

FILE TO EDIT namelist.atmosphere. Copy the repository version into the run directory and verify the following fields before launch.

CHANGE 1 - config_start_time: the first model time is 2025-08-03_00:00:00.

CHANGE 2 - config_run_duration: 3_00:00:00 covers the complete three-day case; the commented three-hour value is only a smoke test.

CHANGE 3 - config_dt: 6 seconds is the dynamics time step used by this experiment.

CHANGE 4 - config_len_disp: explicitly set 500.0 here in the running namelist. This is the first point in the tutorial where this case parameter is introduced.

NAMELIST.ATMOSPHERE

```
&nhyd_model
  config_start_time = '2025-08-03_00:00:00'
  config_run_duration = '3_00:00:00'
  config_dt         = 6
  config_len_disp   = 500.0
/
```

REQUIRED CASE SETTING Keep config_len_disp = 500.0. It explicitly records the 500 m minimum mesh spacing used by this experiment and should not be omitted even when the mesh contains nominalMinDc.

Step 3 | Set the physics schemes and optional cutoff

FILE TO EDIT Continue editing the &physics group in namelist.atmosphere. The following suite is the explicit HRAIN2025 case configuration; verify every value rather than relying on source-tree defaults.

Physics suite used by HRAIN2025

The case uses WSM6 microphysics, New Tiedtke cumulus, Noah-MP land surface, YSU boundary layer and gravity-wave-drag options, cloud fraction, RRTMG longwave and shortwave radiation, the revised Monin-Obukhov surface layer, and MPAS-Urban. Use the same suite with either source tree; the standard hkust-dev build omits config_cu_disable_dx.

```
&physics
  config_microp_scheme      = 'mp_wsm6'
  config_convection_scheme = 'cu_ntiedtke'
  config_lsm_scheme        = 'sf_noahmp'
  config_pbl_scheme        = 'bl_ysu'
  config_gwdo_scheme       = 'bl_ysu_gwdo'
  config_radt_cld_scheme   = 'cld_fraction'
  config_radt_lw_scheme    = 'rrtmg_lw'
  config_radt_sw_scheme    = 'rrtmg_sw'
  config_sfclayer_scheme   = 'sf_monin_obukhov_rev'
  config_urban_physics     = true
/
```

Optional HRAIN2025 cutoff derivative

Use the following only when atmosphere_model was compiled from the verified HRAIN2025 case-specific commit 57b42fa1d7649117bbf28a69c47697ea8756d268 on Liuzh223/HKUST-MPAS-Official branch ntdk-grid-cutoff.

```
&physics
  config_convection_scheme = 'cu_ntiedtke'
  config_cu_disable_dx     = 10000.0
/
```

The value 10000.0 is a 10 km grid-spacing threshold. New Tiedtke convection is disabled where the local mesh spacing is below 10 km. The option default is 0.0, which leaves the cutoff disabled.

SOURCE NOTE ntdk-grid-cutoff is a case-author derivative, not the official HKUST-MPAS main branch. The verified case commit is <https://github.com/Liuzh223/HKUST-MPAS-Official/commit/57b42fa1d7649117bbf28a69c47697ea8756d268>. There is no separate shell command named cutoff.

Step 4 | Check the decomposition and streams

CHANGE 1 - namelist.atmosphere/&decomposition: use the prefix hk_hull_500m_graph.info.part. and launch 112 MPI tasks.

```
&decomposition
  config_block_decomp_file_prefix =
    'hk_hull_500m_graph.info.part.'
/
```

Use 112 MPI tasks so that the prefix resolves to hk_hull_500m_graph.info.part.112. In streams.atmosphere, point the input stream to the initial-condition file created in Guide 2 and select the desired output interval.

FILE TO EDIT `streams.atmosphere`. Set the input filename to `30km_500m.init.nc`, choose the history filename and output interval, and verify that all relative paths are resolved from the run directory.

Step 5 | Run and monitor

RUN

```
cd "$CASE"
export OMP_NUM_THREADS=1

mpiexec -n 112 ./atmosphere_model
```

CHECK

```
tail -n 60 log.atmosphere.0000.out
ls -lh history.*.nc 2>/dev/null || ls -lh *.nc
```

For an inexpensive first check, temporarily use a short `config_run_duration`, confirm that output is created, and then restore the intended three-day duration. Do not describe the short smoke test as the HRAIN2025 experiment result.

Final note | Comparing with existing HRAIN2025 results

The HRAIN2025 historical experiment results have not yet been publicly released. This section is needed only for a future direct comparison with those existing results. It is not required for learning MPAS or for a new independent simulation.

Use the verified HRAIN2025 case-specific source commit: <https://github.com/Liuzh223/HKUST-MPAS-Official/commit/57b42fa1d7649117bbf28a69c47697ea8756d268>. This single source contains both the 10 km CU cutoff and the HRAIN2025 ZT compatibility setting; the rainfall branch is not required.

SOURCE FILE

```
src/core_atmosphere/physics/physics_wrf/module_sf_urban.F
```

Inside `SFCDIF_URB`, the case-specific source has two active ZT updates: one after USTAR is calculated and one inside the stability iteration. The behavior originates from upstream HKUST-MPAS commit `562bdb4e5ef63527496b6374d52def06a01a84a0`: <https://github.com/HKUST-MPAS/HKUST-MPAS/commit/562bdb4e5ef63527496b6374d52def06a01a84a0>. Z0 is the momentum roughness length and ZT is the thermal roughness length; this setting does not redefine or recalculate Z0.

```
ZT = 0.1 * Z0
```

The verified case-specific commit already includes both active `ZT = 0.1 * Z0` assignments, so no manual source edit is needed. Check out the exact commit and rebuild `atmosphere_model`. Do not confuse this with `ZOHC_TBL = 0.1 * ZOC_TBL`, which is a different calculation.

For a new independent experiment, keep the ZT implementation supplied by the selected HKUST-MPAS version and record the repository, branch, and commit. Do not modify ZT merely to complete the tutorial.

Completion checklist

- `config_start_time` is 2025-08-03_00:00:00.
- `config_run_duration` is 3_00:00:00 for the full experiment.
- `config_len_disp` is explicitly 500.0.
- `config_cu_disable_dx` is present only for a verified cutoff-capable build and is 10000.0 for this case.
- The MPI task count matches `.part.112`.
- For direct comparison with existing HRAIN2025 results, use the exact case-specific commit above; no rainfall-branch checkout or manual source edit is required.

Primary references

- [Official MPAS-A tutorial](#)
- [MPAS-A Quick Start Guide](#)
- [HKUST-MPAS hkust-dev](#)
- [HRAIN2025](#)