

Get inferred AI Models for a Library Track

GET https://rest-api.cyanite.ai/v1/library-tracks/:id/models

Retrieve a list of desired and available inferred AI Models of a Library Track.

Request

PATH PARAMETERS

id Library Track Id

REQUIRED

Possible values: Value must match regular expression `^libtr_`

The unique identifier of a track in your Cyanite Library. Every track has its own id that no other track has.

Example: `libtr_01KFGMPCN97HQYHQR6`

QUERY PARAMETERS

model string[]

REQUIRED

Possible values: `[AiMusicDetectionV1, AudioFileInfoV1, AugmentedKeywordsV3, AutoDescriptionV2, BpmV2, CharacterV2, FreeGenreV3, InstrumentsV2, KeyV2, MainGenreV2, MoodAdvancedV2, MoodSimpleV2, MovementV2, MusicalEraV2, MusicForV1, RepresentativeSegmentV2, SubgenreV2, TempoV1, TimeSignatureV2, ValenceArousalV2, VocalStyleV1, VocalsV2, VoiceoverV2]`

The Cyanite AI Model type to filter by.

Responses

200401403404429

A collection of inferred Cyanite AI Models of a given library track.

APPLICATION/JSON

SchemaExample (auto)

SCHEMA

items object[]

AUTHORIZATION: X-API-KEY

name: x-api-key

type: apiKey

in: header

description: The standard way of authenticating with the Cyanite API. Your client acts on behalf of your Cyanite account.

CURL

JAVASCRIPT

PYTHON

PHP

CURL

```
1 curl -L 'https://rest-api.cyanite.ai/v1/library-tracks/:id/models?
   model=AudioFileInfoV1' \
2 -H 'Accept: application/json' \
3 -H 'x-api-key: <x-api-key>'
```

REQUEST

COLLAPSE ALL

Base URL

https://rest-api.cyanite.ai/v1

Auth

ApiKeyAuth

ApiKeyAuth

Parameters

id — path **REQUIRED**

The unique identifier of a track in your Cyanite Library. Every track has

model — query **REQUIRED**

AiMusicDetectionV1

AudioFileInfoV1

AugmentedKeywordsV3

AutoDescriptionV2

BpmV2

CharacterV2