CS3103 Assignment 4: LiveRecall

Aw Ming Xuan, Kosolpattanadurong Thitiwat, Lee Zhao Rui, Wong Ji Kean

1 Architecture and Protocol

Our system has two parts: the solution server (`solution_server.py`) and the browser client (`client/app.js`). The server has two main components: a `CaptionStore`, which holds the captions received from the caption source, and a set of `Client` objects, each holding one client's WebSocket connection and its send queue.

When a WebSocket connects, the server reads the `type` of its first message to tell the caption source (`SOURCE_HELLO`) from a viewer (`CLIENT_HELLO`) and dispatches it to the matching handler (`handle_source` or `handle_client`). The following sections describe how each handler works internally.

1.1 Server: storing captions

The `CaptionStore` (`server/store.py`) holds the server's view of the last `keep_seconds` of the transcript. It keeps a deque `order` of segment numbers, in order, and a hashmap from segment number to an `Entry` holding the segment's `source_ts` (source timestamp), revision, finality and text.

When our backend receives a `CAPTION_UPDATE` message from the caption server, we parse and validate it into an `Entry` (malformed messages are counted and dropped), then call `store.apply(entry)`, which returns `STALE`, `DUP_FINAL`, `TOO_OLD` or `ACCEPTED` based on our **revision semantics**.

Result	Condition	Action
`STALE`	Segment held and `new.revision <= cur.revision`	Drop; a delayed packet never rolls a caption back
`DUP_FINAL`	Segment is *already-final*[1] (held as final, or at/below `contig_final`)	Drop; a final is never replaced
`TOO_OLD`	Segment older than the oldest one on the deque (already pruned)	Drop
`ACCEPTED`	Otherwise (new segments are appended; the deque is re-sorted in the rare out-of-order case)	Replace entry, prune, broadcast

For every `ACCEPTED` update, we update the store and then broadcast. Keeping the store current and consistent matters because a reconnecting client asks for the segments it lacks, which are served from the store by `get_history()`. While updating, we also prune outdated segments (those whose `source_ts` is older than `latest_ts - keep_seconds`, where `latest_ts` is the newest source timestamp seen) to bound the size of our deque. We use `keep_seconds = 120` and additionally cap the deque at `max_items = 500` entries in case timestamps misbehave.

After an update is accepted, `broadcast(segment)` (`solution_server.py`) hands only the *segment number* (not the text) to every connected client and returns immediately, without waiting for any network send. Each client's background sender then reads the latest text from the store when it is ready to send. How each client queues and paces these updates is described in the next section.

Recovery semantics

On reconnect (or late join, with `last_segment = 0`), the client sends `CLIENT_HELLO` with its resume state (`last_segment`, `last_revision`, `history_seconds`). `get_history()` returns, in order, the finalized segments it lacks within the last `history_seconds` (clamped to $[0, 60]$; invalid fields fall back to defaults). This `HISTORY` is

[1] Checking *already-final* is tricky: since pruning removes segments from memory, we cannot simply look a segment up to know if it was finalized. We therefore keep `contig_final`, the highest N such that segments $1..N$ are all final. As such, a late update for a segment at or below `contig_final` is rejected as `DUP_FINAL`.

queued before the client joins the broadcast set, so it precedes live updates; any overlap is deduplicated by the client's revision rule.

1.2 Server: Sending to clients

When a client connects (`CLIENT_HELLO`), the server queues its initial history from the store (see Recovery semantics) and spawns a background sender task, `unicast(client)`. This task takes segment ids from the client's queue, reads their latest text from the store and sends them according to our protocol, which went through several versions during optimization. The table below summarizes how the sending path evolved from v0 to v6; each version retains all previous functionality. The submitted `solution_server.py` is v6.

Mechanism	What it does	Problem addressed
v0 Naive broadcast	Sends each update to every client; the source awaits all sends.	One slow client stalls the source and all others.
v1 Per-client dirty set[2]	Each client has a FIFO queue of segment ids. `broadcast()` appends the segment id to the back of each client's queue (if already queued, it keeps its place, so repeated edits coalesce into one entry) and wakes that client's sender. The sender pops from the front and reads the segment's latest text from the store at send time. Close the client if its queue reaches 100 segments.	Backlog bounded by segments, not edits; slow readers block no one. *Issue:* `send()` returns once data is in the OS socket buffer, so the queue drains instantly and stays near zero; the real backlog hides in socket/client buffers, invisible to the server.
v2 Ping flow control	Ping after each send; wait for pong up to `PONG_WAIT` = 1 s. This ensures that the client has read every earlier message off the socket.	It solves the queue draining problem. We also use pong RTT for further optimizations (e.g., detecting client read rates).
v3 Lag-window disconnect	Forcing client to disconnect when the oldest dirty entry is greater than `MAX_LAG_WINDOW` = 10 s.	Bounds staleness; client recovers via `HISTORY`.
v4 Lag mode (for slow clients)	Enter this mode if dirty age > 0.5 s or a pong > 0.3 s. Under lag mode, we send the missing finals oldest first. We only send the newest provisional messages after `LAG_PROV_GAP` = 4 s idle. Exiting lag mode requires 3 fast pongs and a 3-second minimum duration.	For slow clients, finals never delayed; unreadable intermediate revisions skipped. *Issue:* fast pongs only show the client is reading quickly *now*, not that it has caught up; it can leave lag mode with stale messages still in its receive buffer, fall behind again and oscillate between modes.
v5 **Buffer-aware lag exit**	Fast pongs are no longer enough to exit: the server also estimates whether the client's receive buffer has drained (estimated reads > messages sent in lag + 36; see Receive buffer estimation). Soft-pong threshold lowered to 0.2 s.	Fixes the v4 issue: no premature return to full updates, so no oscillation; also earlier lag detection. *Issue:* the lag-mode sender polls every 0.1 s and waits for a pong after every message, so a new final can sit for up to one poll interval plus a full RTT, and on a high-latency link throughput is capped at one message per RTT.
v6 Event-driven pacing	Lag-mode sender sleeps on an event (woken by `broadcast()`) instead of polling every 0.1 s; a final that arrives while a pong is outstanding is sent at once; in lag mode it pings once every 2 messages (`PING_EVERY_N` = 2) rather than after each one.	Fixes the v5 issue: new finals go out as soon as they arrive instead of waiting for the next poll, and halving the pings roughly doubles lag-mode throughput on a high-latency link.

Receive buffer estimation

The server cannot see a client's receive buffer, i.e. the messages the client's WebSocket library has received but the client has not yet processed. A fast pong shows the client is reading quickly *now*, not that the buffer is empty, so from v5 onwards the server estimates the backlog conservatively before letting a client leave lag mode:

1. **Assume the buffer was full when lag began.** `LAG_QUEUE_GUESS` = 32 messages, a deliberately high guess.
2. **Estimate the per-message read time** `iv_est` from pong RTTs during lag. While the buffer is full, each pong returns about one read interval after the previous one. We keep the largest value seen (capped at `IV_CAP` = 1 s), since overestimating is the safe direction. The initial estimate is the RTT of the pong that triggered lag mode (at least 0.1 s).
3. **Count reads.** Estimated reads = time in lag / `iv_est`. The client must work through the 32 assumed messages plus every message sent during lag (`lag_sent`).
4. **Exit only once it has caught up:** `reads - lag_sent >= LAG_QUEUE_GUESS + LAG_EXIT_MARGIN` (32 + 2), and the latest pong was fast (`LAG_CALM_PONGS` = 1, RTT $\leq$ 0.2 s). On exit, every in-progress (non-final) segment is marked dirty again so the client immediately receives their latest text.

For example, a client reading one message every 0.5 s that has been sent 10 messages in lag needs about 44 reads (~22 s) before it may exit. Overestimating the buffer only delays the exit slightly, while underestimating would send the client back into lag almost immediately. (v5 originally used a margin of 4, `IV_CAP` = 2 s and 3 fast pongs; we relaxed these so clients leave lag mode sooner once they recover.)

Putting the pieces together, each client's sender is a small two-state machine, in normal mode (every update, one pong per message) or lag mode (finals first, rationed provisionals). The transitions between the two states are the core of our backpressure policy and are summarised below.

Normal → Lag. The server switches a client to lag mode as soon as it looks like the client cannot keep up: its oldest unsent update is older than 0.5 s (`LAG_AGE_ENTER`), or a single pong takes longer than 0.2 s (`LAG_PONG_SOFT`) or times out after 1 s. Its dirty set is cleared (the store and the client's final cursor now determine what to send), and from then on it sends only what matters: missing finals oldest first, never paced, plus the latest provisional after 4 s without a send.
Lag → Normal. The client returns to normal mode once its latest pong is fast again *and* the receive-buffer estimate says its backlog has drained. Its in-progress segments are then re-queued so it receives full updates again.

Addressing the two advanced challenges

Challenge 1: Slow-reader semantic backpressure. Each client's backlog is bounded by its dirty set (at most 100 segments) and the 10 s lag window (v1, v3), so it does not grow with the edit rate. Since repeated edits to a segment coalesce into one entry, superseded provisionals are never queued, and in lag mode only the newest provisional is sent (v4). Because `broadcast()` never waits and every client has its own sender task, a slow reader cannot delay the source or other clients. Finals are still sent oldest first in lag mode, and a client that gets cut off recovers them through `HISTORY`.

Challenge 2: Constrained-bandwidth semantic delivery. We use ping/pong flow control (v2) to detect the bottleneck: when the link is congested, pongs come back slowly, which puts the client into lag mode (v4, v5). The remaining bandwidth then goes to missing finals first, then the latest provisional, while intermediate revisions are skipped instead of building a stale backlog. Once pongs are fast again and the client's queue has drained, it returns to normal mode and receives full updates again.

1.3 Client (`app.js`)

The browser client opens a WebSocket, sends `CLIENT_HELLO`, and renders every `CAPTION_UPDATE` and `HISTORY` item through one `append()` path in `FrontEndRenderer`, which maps each segment to a DOM row holding its `revision_id`, `source_ts` and `is_final`. A message updates its row only if `msg.revision > row.revision_id`, replacing the text in place so each segment appears once with its latest text; `is_final` is sticky, and rows are re-sorted by segment when updates arrive out of order. Since `HISTORY` items pass through the same check, overlap with live updates is deduplicated for free. The client keeps finals for `KEEP_MESSAGE_WINDOW = 90` s (above the required 60 s), pruning once a second, while the 15/30/60 s recall view only hides rows, so switching windows needs no server request. On close, the client reconnects with `last_segment`, `last_revision` and `history_seconds =`

[2] Dirty set is a dictionary that maps segment id to the time it first became dirty. A segment is dirty for a client when its content has changed in the server's store but that client hasn't been sent the new version yet. Each client has its own dirty set.

60 under a stable client_id from sessionStorage, so a client disconnected as too slow (close code 1013) recovers its missing finals through HISTORY; only a 1008 close (protocol violation, e.g. an invalid hello) is shown to the user instead of triggering a reconnect.

2 Results

The before/after comparison uses v5 (from solution_server copy.py) as the baseline, with per-client queues, ping flow control, lag mode and the buffer-aware lag exit, against the submitted v6 (solution_server.py), which replaces lag-mode polling with event-driven wake-up, pings every 2 messages in lag mode, and uses the relaxed lag-exit constants. Each of the 24 public tests was run 3 times per version and we report the median.

3 Discussion

4 Conclusion

A Raw data

B ASR Bonus: Real-Lecture Caption Source

B.1 Integration

The ASR path is a third, optional component: bonus_asr/asr_source.py replaces caption_source.py as the caption source. It connects to the same solution_server.py over WebSocket, sends SOURCE_HELLO, then CAPTION_UPDATE messages, and finally SOURCE_DONE. **Neither solution_server.py nor the browser client was modified**; the server cannot tell the ASR source from the deterministic source, so every mechanism described in the main report (revision semantics, history, backpressure, lag mode, recovery) applies unchanged to ASR captions.

Pipeline

1) ffmpeg (lecture audio / mic (default), 16 kHz mono s16le)
2) reader thread (1 s chunks, bounded queue (of size 30 chunks))
3) faster-whisper base.en (CPU, int8, 4 threads, VAD filter)
4) CAPTION_UPDATE
5) solution_server.py
6) browser client.

Protocol field	How the ASR source sets it
segment	One segment per fixed 5 s window of audio (SEGMENT_TIMING_SEC = 5); incremented only if the window produced text, so silent windows do not create empty segments.
revision	Each new 1 s chunk re-transcribes the whole window buffered so far and sends the result as the next revision. The first revision waits for 2 s of audio (FIRST_REVISION_SEC = 2), giving up to 3 provisional revisions and 1 final per segment.
final	true once the window reaches 5 s, and for the partial window flushed on shutdown.
text	The full transcript of the window, not a delta, so the client's replace-by-revision rule shows the newest hypothesis even when Whisper rewrites earlier words.
source_ts	Wall-clock time at which the newest audio chunk was read.

How to run it

Installing the required dependencies:

```
sudo apt install ffmpeg
python3 -m venv asr-venv
asr-venv/bin/pip install -r bonus_asr/requirements-asr.txt
```

Running it (from the repository root, one terminal each and in the same order):

```
venv/bin/python solution_server.py --port 8765
python3 -m http.server 8000 -d client
asr-venv/bin/python bonus_asr/asr_source.py
```

- Note the first run will download the `base.en` model (Around 150 MB)

B.2 Limitations

- **Fixed-time segmentation.** Windows end every 5 s regardless of speech, so sentences and occasionally words are split across segments, and each window is transcribed without the previous one as context, which lowers accuracy at boundaries. Pause-based segmentation (using the VAD) would align segments with sentences.
- **Re-transcription cost.** Each revision re-transcribes the whole window (2–5 s of audio), so the work per window grows with each revision. If the transcription timing exceeds the 1 s chunk interval, audio queues up.
- **Overload drops audio to bound delay.** The audio queue is bounded at 30 chunks (30 s). When transcription falls behind, the oldest queued chunk is dropped and logged, so caption delay is capped at roughly 30 s instead of growing without limit, at the cost of permanently lost words. The dropped chunk can also leave a gap inside a window.
- **No source reconnect or session reset.** Segment numbers restart at 1 on every run, while the server rejects updates for segments it already holds as final (DUP_FINAL) and an open browser ignores revisions lower than the ones it already shows, so the server must be restarted and the browser reloaded before each ASR run. The ASR source also does not reconnect if the server connection drops; it must be started again.
- **Clock assumption.** `source_ts` uses the source machine's clock, and the client's recall window compares it with the browser's clock. This holds when both run on the same machine.
- **Accuracy not tuned.** `base.en` on CPU was chosen for real-time speed. Accuracy and model size are not graded and were not optimised.