



Front idlers / Tensioners



Hardware and extra info on last page



Dept.	Technical reference	Created by DutchDude	21/03/2021	Approved by
		Document type	Document status	
		Title Experimental Front Towers	DWG No.	
		Rev.	Date of issue	Sheet 1/5

Front idler parts


Hardware and extra info on last page



Dept.	Technical reference	Created by DutchDude 21/03/2021	Approved by	
		Document type	Document status	
		Title Experimental Front Towers	DWG No.	
			Rev.	Date of issue
			Sheet 2/5	

Front idler parts Top view


Hardware and extra info on last page



Dept.	Technical reference	Created by J Paassen	21/03/2021	Approved by
		Document type	Document status	
		Title Experimental Front Towers	DWG No.	
		Rev.	Date of issue	Sheet 3/5

Front idler parts Back view

Hardware and extra info on last page




Dept.	Technical reference	Created by J Paassen	21/03/2021	Approved by
		Document type	Document status	
		Title Experimental Front Towers	DWG No.	
		Rev.	Date of issue	Sheet 4/5

- HARDWARE FOR BOTH FRONT IDLERS
- 2 - M5X30 DOWELL PIN (FOR FLANGE BEARINGS)
 - 2 - M5X20 BOLTS (INTO T-NUTS)
 - 2 - M3X25 BOLTS (USED TO TENSION)
 - 2 - T-NUTS (FOR EXTRUSION)
 - 4 - M5 1MM SPACER (CHECK PAGE 2 FLANGE STACK)
 - 4 - 625RS 5*16*5mm (FLANGE BEARING)

EXTRA INFO

With an afterburner we suggest to tension the belts to about 110hz using spectroid (app on your phone) to meassure.

When tensioning the belts, losen the two M5X20 bolts. Tighten or losen



the M3X25 bolts to tension, once you're happy, tighten the M5X20

Dept.	Technical reference	Created by J Paassen	21/03/2021	Approved by
		Document type	Document status	
		Title Experimental Front Towers	DWG No.	
		Rev.	Date of issue	Sheet 5/5