

Carga de archivo en Bucket

✔ Se ha realizado la carga correctamente
Para obtener más información, consulte la tabla Archivos y carpetas.

Ruta: https://housing-data-lake.s3.us-east-2.amazonaws.com/house_data_aws.csv

Configuración de base de datos y Glue

1-Data base creada dentro de Glue

☐ [housing_db_glue](#)

2-Create Crawler dentro de Glue

Crawlers

Name

housing_crawler

Add data source

Data source

Choose the source of data to be c

S3

S3 path

Browse for or enter an existing S3 path.

Q s3://housing-data-lake



View

Browse S3

Creando roles **AWSGlueServiceRole** & **AmazonS3FullAccess**

✔ Se creó el rol AWSGlueServiceRoleDefault.

Configure security settings

IAM role [Q help](#)

Existing IAM role

AWSGlueServiceRoleDefault


Set output and scheduling

Output configuration [Q help](#)

Target database

housing_db_glue

Creando Crawler



Ejecutar Crawler

Tabla generada al correr el Crawler

Tables (1)

View and manage all available tables.

☐	Name	Database	Location	Classification
☐	housing_data_lake	housing_db_glue	s3://housing-data-lake/	CSV

Verificación en ATENA

Origen de datos

AwsDataCatalog

Catálogo

Ningún elemento

Base de datos

housing_db_glue

Tablas y vistas Cre

▼ **Tablas (1)**

☒ housing_data_lake

Explorador d... + Agregar

- ▼ Catálogos
 - ▼ AwsDataCatalog
 - ▼ housing_db_glue
 - ▼ tablas (1)

Ejecutar todo AwsDataCatalog, housing_db_glue Athena (SQL)

☐ Límite de 100 #1

```
1 SELECT COUNT(*) FROM housing_db_glue.housing_data_lake;
```

_col0
21613

```
2 DESCRIBE housing_data_lake;
```

col_name	data_type
id	bigint
date	string
price	bigint
bedrooms	bigint

Creando un directorio donde se guarde una tabla

```
CREATE TABLE housing_clean
WITH (
  format = 'PARQUET'
)
AS
SELECT
  id,
  TRY(date_parse(date, '%d/%m/%Y')) AS date_parsed,
  price,
  bedrooms,
  bathrooms,
  sqft_living,
  sqft_lot,
  floors,
  waterfront,
  condition,
  grade,
  sqft_basement,
  yr_built,
  yr_renovated,
  zipcode,
  lat,
  long
FROM housing_data_lake;
```

✔ La consulta se ejecutó correctamente

▶ | ☒ Límite de 100 #1

```
1 SELECT AVG(price) AS precio_promedio_2014
2 FROM housing_clean
3 WHERE year(date_parsed) = 2014;
```

Precio Promedio de las casas durante el 2014

precio_promedio_2014
160855.0655021834

Verificar que la eliminación de duplicados funcionó

```
CREATE TABLE housing_final
WITH (
  format = 'PARQUET'
)
AS
SELECT
  id,
  date_parsed,
  price,
  bedrooms,
  bathrooms,
  sqft_living,
  sqft_lot,
  floors,
  waterfront,
  condition,
  grade,
  sqft_basement,
  yr_built,
  yr_renovated,
  zipcode,
  lat,
  long
FROM (
  SELECT *,
    ROW_NUMBER() OVER (PARTITION BY id ORDER BY id) AS rn
  FROM housing_clean
) t
WHERE rn = 1;
```

▶ ☒ Límite de 100 #1	precio_promedio_2014
1 SELECT AVG(price) AS precio_promedio_2014	160935.71115973743
2 FROM housing_final	
3 WHERE year(date_parsed) = 2014;	