

Introduction to programming for data science

STAT 201

Arvind Krishna

9/20/22

Table of contents

Preface	6
I Python	7
1 Introduction to Jupyter Notebooks and programming in python	8
1.1 Jupyter notebook	8
1.1.1 Introduction	8
1.1.2 Writing and executing code	9
1.1.3 Saving and loading notebooks	9
1.1.4 Rendering notebook as HTML	10
1.2 In-class exercise	10
1.3 Python libraries	10
1.4 Debugging and errors	11
1.5 Terms used in programming	11
2 Variables, expressions and statements	12
2.0.1 Practice exercise 1	12
2.1 Constants and Variables	13
2.1.1 Variable names	14
2.1.2 Practice exercise 2	15
2.2 Assignment statements	15
2.3 Expressions	16
2.3.1 Practice exercise 3	16
2.4 Converting datatypes	17
2.5 User input	18
2.5.1 Practice exercise 4	19
2.6 Commenting code	19
2.6.1 Practice exercise 5	19
2.7 Programming errors	19
2.7.1 Syntax errors	20
2.7.2 Run-time errors	20
2.7.3 Semantic errors	20
2.7.4 Practice exercise 6	21
2.8 Practice exercise 7	21

3	Control flow statements	22
3.0.1	Comparison operators	22
3.0.2	Logical operators	23
3.0.3	if-elif-else statement	23
3.0.4	Practice exercise 1	24
3.0.5	Try-except	25
3.0.6	Practice exercise 2	25
3.1	Loops	27
3.1.1	for loop	27
3.1.2	while loop	29
3.1.3	Practice exercise 3	30
3.2	break statement	32
3.2.1	Practice exercise 4	33
3.3	continue statement	33
3.3.1	Practice exercise 5:	34
3.4	Loops with strings	35
3.4.1	Practice exercise 6	36
4	Functions	38
4.1	Defining a function	38
4.2	Parameters and arguments of a function	39
4.2.1	Function with a parameter	39
4.2.2	Function with a parameter having a default value	40
4.2.3	Function with multiple parameters	41
4.2.4	Practice exercise 1	41
4.3	Functions that return objects	42
4.4	Global and local variables with respect to a function	43
4.5	Built-in python functions	43
4.6	Python libraries	44
4.6.1	Practice exercise 2	45
5	Data structures	46
5.0.1	Practice exercise 1	47
5.0.2	Concatenating tuples	47
5.0.3	Unpacking tuples	47
5.0.4	Practice exercise 2	48
5.0.5	Tuple methods	49
5.1	List	50
5.1.1	Adding and removing elements in a list	50
5.1.2	List comprehensions	52
5.1.3	Practice exercise 3	53
5.1.4	Concatenating lists	53
5.1.5	Sorting a list	54

5.1.6	Slicing a list	54
5.1.7	Practice exercise 4	56
5.2	Dictionary	58
5.2.1	Adding and removing elements in a dictionary	58
5.2.2	Iterating over elements of a dictionary	60
5.2.3	Practice exercise 5	60
5.3	Functions	61
5.3.1	Global and local variables with respect to a function	62
5.3.2	Practice exercise 6	62
5.4	Practice exercise 7	63

Appendices 64

A Assignment A 65

A.1	Alarm clock	65
A.1.1	When does the alarm go off?	65
A.1.2	User-friendly alarm clock	66
A.2	Finding prime factors	66
A.2.1	Prime or not	66
A.2.2	Factors	66
A.2.3	Prime factors	66
A.2.4	User-friendly prime factor calculator	67
A.3	Number of words in a sentence	67
A.4	Survival of rabbits	67
A.4.1	Number of rabbits and foxes	68
A.4.2	How long can 100 rabbits survive?	69
A.4.3	Saving rabbits from extinction	69

B Assignment B 71

B.1	Sentence analysis	71
B.1.1	Word count	71
B.1.2	Max word count	72
B.2	Prime factors	72
B.2.1	Prime	72
B.2.2	Factor	72
B.2.3	Prime Factors	73
B.3	Binary search	73
B.3.1	Word search	73
B.3.2	Iterations to find the word	74
B.3.3	Index of word	74
B.3.4	Maximum iterations	74

Preface

This book is currently being written for the course STAT201.

Part I

Python

1 Introduction to Jupyter Notebooks and programming in python

This chapter is a very brief introduction to python and Jupyter notebooks. We only discuss the content relevant for applying python to analyze data.

Anaconda: If you are new to python, we recommend downloading the [Anaconda installer](#) and following the instructions for installation. Once installed, we'll use the Jupyter Notebook interface to write code.

Quarto: We'll use Quarto to publish the `**ipynb*` file containing text, python code, and the output. Download and install Quarto from [here](#).

1.1 Jupyter notebook

1.1.1 Introduction

Jupyter notebook is an interactive platform, where you can write code and text, and make visualizations. You can access Jupyter notebook from the Anaconda Navigator, or directly open the Jupyter Notebook application itself. It should automatically open up in your default browser. The figure below shows a Jupyter Notebook opened with Google Chrome. This page is called the *landing page* of the notebook.

<IPython.core.display.Image object>

To create a new notebook, click on the **New** button and select the **Python 3** option. You should see a blank notebook as in the figure below.

<IPython.core.display.Image object>

1.1.2 Writing and executing code

Code cell: By default, a cell is of type *Code*, i.e., for typing code, as seen as the default choice in the dropdown menu below the *Widgets* tab. Try typing a line of python code (say, `2+3`) in an empty code cell and execute it by pressing *Shift+Enter*. This should execute the code, and create an new code cell. Pressing *Ctrl+Enter* for *Windows* (or *Cmd+Enter* for *Mac*) will execute the code without creating a new cell.

Commenting code in a code cell: Comments should be made while writing the code to explain the purpose of the code or a brief explanation of the tasks being performed by the code. A comment can be added in a code cell by preceding it with a `#` sign. For example, see the comment in the code below.

Writing comments will help other users understand your code. It is also useful for the coder to keep track of the tasks being performed by their code.

```
#This code adds 3 and 5
3+5
```

8

Markdown cell: Although a comment can be written in a code cell, a code cell cannot be used for writing headings/sub-headings, and is not appropriate for writing lengthy chunks of text. In such cases, change the cell type to *Markdown* from the dropdown menu below the *Widgets* tab. Use any markdown cheat sheet found online, for example, [this one](#) to format text in the markdown cells.

Give a name to the notebook by clicking on the text, which says ‘Untitled’.

1.1.3 Saving and loading notebooks

Save the notebook by clicking on **File**, and selecting **Save as**, or clicking on the **Save and Checkpoint** icon (below the **File** tab). Your notebook will be saved as a file with an extension *ipynb*. This file will contain all the code as well as the outputs, and can be loaded and edited by a Jupyter user. To load an existing Jupyter notebook, navigate to the folder of the notebook on the *landing page*, and then click on the file to open it.

1.1.4 Rendering notebook as HTML

We'll use Quarto to print the `**ipynb*` file as HTML. Check the procedure for rendering a notebook as HTML [here](#). You have several options to format the file.

You will need to open the command prompt, navigate to the directory containing the file, and use the command: `quarto render filename.ipynb --to html`.

1.2 In-class exercise

1. Create a new notebook.
2. Save the file as `In_class_exercise_1`.
3. Give a heading to the file - `First HTML file`.
4. Print `Today is day 1 of my programming course`.
5. Compute and print the number of seconds in a day.

The HTML file should look like the picture below.

<IPython.core.display.Image object>

1.3 Python libraries

There are several [built-in functions](#) in python like `print()`, `abs()`, `max()`, `sum()` etc., which do not require importing any library. However, these functions will typically be insufficient for analyzing data. Some of the popular libraries in data science and their primary purposes are as follows:

1. NumPy: Performing numerical operations and efficiently storing numerical data.
2. Pandas: Reading, cleaning and manipulating data.
3. Matplotlib, Seaborn: Visualizing data.
4. SciPy: Performing scientific computing such as solving differential equations, optimization, statistical tests, etc.
5. Scikit-learn: Data pre-processing and machine learning, with a focus on prediction.
6. Statsmodels: Developing statistical models with a focus on inference

A library can be imported using the `import` keyword. For example, a NumPy library can be imported as:

```
import numpy as np
```

Using the `as` keyword, the NumPy library has been given the name `np`. All the functions and attributes of the library can be called using the `'np.'` prefix. For example, let us generate a sequence of whole numbers upto 10 using the NumPy function `arange()`:

```
np.arange(8)
```

```
array([0, 1, 2, 3, 4, 5, 6, 7])
```

Generating random numbers is very useful in python for performing simulations (we'll see in later chapters). The library `random` is used to generate random numbers such as integers, real numbers based on different probability distributions, etc.

Below is an example of using the `randint()` function of the library for generating random numbers in `[a, b]`, where `a` and `b` are integers.

```
import random as rm
rm.randint(5,10) #This will generate a random number in [5,10]
```

7

1.4 Debugging and errors

Read sections 1.3 - 1.6 from http://openbookproject.net/thinkcs/python/english3e/way_of_the_program.html

1.5 Terms used in programming

Read section 1.11 from http://openbookproject.net/thinkcs/python/english3e/way_of_the_program.html

2 Variables, expressions and statements

Some of the commonly used objects in python are numbers - integer and float, strings and bool (true/false). The data type of the object can be identified using the in-built python function `type()`. For example, see the following objects and their types:

```
type(4)
```

int

```
type(4.4)
```

float

```
type('4')
```

str

```
type(True)
```

bool

2.0.1 Practice exercise 1

What is the datatype of the following objects?

1. 'This is False'
2. "This is a number"
3. 1000
4. 65.65
5. False

2.1 Constants and Variables

A constant is a value that cannot be changed. It may be a number, string or any other datatype. Below are some examples of printing a constant:

```
print(4)
```

4

```
print("This is a string and also a constant")
```

This is a string and also a constant

```
print(False)
```

False

A variable is an object whose value can be changed. For example, consider the object below:

```
x = 2
```

In the above code the variable `x` has been assigned a value of 2. However, the value of `x` can be changed:

```
x = 3  
print("x =", x)
```

x = 3

Thus, the object `x` in the above code is a variable that refers to a memory location storing the constant value of 3.

2.1.1 Variable names

There are a some rules for naming variables:

1. A variable name must start with a letter or underscore `_`
2. A variable name may consist of letters, numbers, and underscores only

For example, some of the valid variable names are `*salary`, `text10`, `__varname`. *Some of the invalid variable names are `salary% 10text`, `varname)*`*

3. Variable names are case-sensitive. For example, the variable `Varname` will be different from `varname`.
4. There are certain *reserved words* in python that have some meaning, and cannot be used as variable names. These reserved words are:

```
<IPython.core.display.Image object>
```

Best coding practice: Variables should be named such that they are informative of the value they are storing. For example, suppose we wish to compute the income tax a person has to pay based on their income and tax rate. Below are two ways of naming variables to do this computation:

```
income = 80000
tax_rate = 0.15
print("Income tax = ",income*tax_rate)
```

```
Income tax = 12000.0
```

```
a = 80000
b = 0.15
print("Income tax = ",a*b)
```

```
Income tax = 12000.0
```

The former code chunk is better than the latter one as it makes the code easy to read and understand.

2.1.2 Practice exercise 2

2.1.2.1 Variables or constants?

In the statements below, classify the objects as variables or constants?

1. `value = "name"`
2. `constant = 7`
3. `another_const = "variable"`
4. `True_False = True`

2.1.2.2 Valid variable names?

Which of the following variable names are valid?

1. `var.name`
2. `var9name`
3. `__varname`
4. `varname*`

2.2 Assignment statements

Values are assigned to variables with the assignment statement (`=`). An assignment statement may have a constant or an expression on the right hand side of the (`=`) sign, and a variable name on the left hand side.

For example, the code lines below are assignment statements

```
var = 2
var = var + 3
```

2.3 Expressions

The mathematical operations and their corresponding operators are as follows:

1. Exponent: `**`
2. Remainder: `%`
3. Multiplication: `*`
4. Division: `/`
5. Addition: `+`
6. Subtraction: `-`

The operators above are in decreasing order of precedence, i.e., an exponent will be evaluated before a remainder, a remainder will be evaluated before a multiplication, and so on.

For example, check the precedence of operators in the computation of the following expression:

```
2+3%4*2
```

8

In case an expression becomes too complicated, use of parenthesis may help clarify the precedence of operators. Parenthesis takes precedence over all the operators listed above. For example, in the expression below, the terms within parenthesis are evaluated first:

```
2+3%(4*2)
```

5

2.3.1 Practice exercise 3

Which of the following statements is an assignment statement:

1. `x = 5`
2. `print(x)`
3. `type(x)`
4. `x + 4`

What will be the result of the following expression:

```
1%2**3*2+1
```

2.4 Converting datatypes

Sometimes a value may have a datatype that is not suitable for using it. For example, consider the variable called *annual_income* in the code below:

```
annual_income = "80000"
```

Suppose we wish to divide *annual_income* by 12 to get the monthly income. We cannot use the variable *monthly_income* directly as its datatype is a string and not a number. Thus, numerical operations cannot be performed on the variable *annual_income*.

We'll need to convert *annual_income* to an integer. For that we will use the python's in-built `int()` function:

```
annual_income = int(annual_income)
monthly_income = annual_income/12
print("monthly income = ", monthly_income)
```

```
monthly income = 6666.666666666667
```

Similarly, datatypes can be converted from one type to another using in-built python functions as shown below:

```
#Converting integer to string
str(9)
```

```
'9'
```

```
#Converting string to float
float("4.5")
```

```
4.5
```

```
#Converting bool to integer
int(True)
```

1

Sometimes, conversion of a value may not be possible. For example, it is not possible to convert the variable *greeting* defined below to a number:

```
greeting = "hello"
```

However, in some cases, mathematical operators such as `+` and `*` can be applied on strings. The operator `+` concatenates multiple strings, while the operator `*` can be used to concatenate a string to itself multiple times:

```
"Hi" + " there!"
```

```
'Hi there!'
```

```
"5" + '3'
```

```
'53'
```

```
"5"*8
```

```
'55555555'
```

2.5 User input

Python's in-built `input()` function can be used to accept an input from the user. For example, suppose we wish the user to onput their age:

```
age = input("Enter your age:")
```

```
Enter your age:34
```

The entered value is stored in the variable `age` and can be used for computation.

2.5.1 Practice exercise 4

Ask the user to input their year of birth, and print their age.

2.6 Commenting code

The `#` symbol can be used to comment the code. Anything after the `#` sign is ignored by python. Commenting a code may have several purposes, such as:

- Describe what is going to happen in a sequence of code
- Document who wrote the code or other ancillary information
- Turn off a line of code - perhaps temporarily

For example, below is code with a comment to describe the purpose of the code:

```
#Computing number of hours of lecture in this course  
print("Total lecture hours of STAT201=",10*3*(5/6))
```

Total lecture hours of STAT201= 25.0

2.6.1 Practice exercise 5

Which of the following lines is a comment:

1. `#this is a comment`
2. `##this may be a comment`
3. `A comment#`

2.7 Programming errors

There are 3 types of errors that can occur in a program - syntax errors, run-time errors, and semantic errors.

2.7.1 Syntax errors

Syntax errors occur if the code is written in a way that it does not comply with the rules / standards / laws of the language (python in this case). For example, suppose a values is assigned to a variable as follows:

```
9value = 2
```

The above code when executed will indicate a syntax error as it violates the rule that a variable name must not start with a number.

2.7.2 Run-time errors

Run-time errors occur when a code is syntactically correct, but there are other issues with the code such as:

- Misspelled or incorrectly capitalized variable and function names
- Attempts to perform operations (such as math operations) on data of the wrong type (ex. attempting to subtract two variables that hold string values)
- Dividing by zero
- Attempts to use a type conversion function such as int on a value that can't be converted to an int

For example, suppose a number is multiplied as follws:

```
multiplication_result = x * 4
```

The above code is syntactically correct. However, it will generate an error as the variable `x` has not been defined as a number.

2.7.3 Semantic errors

Semantic errors occur when the code executes without an error being indicated by the compiler. However, it does not work as inteded by the user. For example, consider the following code of mutiplying the number 6 by 3:

```
x = '6'  
x * 3
```

```
'666'
```

If it was intended to multiply the number 6, then the variable `x` should have been defined as `x=6` so that `x` has a value of type `integer`. However, in the above code `6` is a `string` type value. When a `string` is multiplied by an integer, say n , it concatenates with itself n times.

2.7.4 Practice exercise 6

Suppose we wish to compute tax using the income and the tax rate. Identify the type of error from amongst syntax error, semantic error and run-time error in the following pieces of code.

```
income = 2000
tax = .08 * Income
print("tax on", income, "is:", tax)
```

```
income = 2000
tax = .08 x income
print("tax on", income, "is:", tax)
```

```
income = 2000
tax = .08 ** income
print("tax on", income, "is:", tax)
```

2.8 Practice exercise 7

The formula for computing final amount if one is earning compound interest is given by:

$$A = P \left(1 + \frac{r}{n} \right)^{nt},$$

where:

P = Principal amount (initial investment),

r = annual nominal interest rate,

n = number of times the interest is computed per year,

t = number of years

Write a Python program that assigns the principal amount of \$10000 to variable P , assign to n the value 12, and assign to r the interest rate of 8%. Then have the program prompt the user for the number of years t that the money will be compounded for. Calculate and print the final amount after t years.

What is the amount if the user enters t as 4 years?

3 Control flow statements

A [control flow statement](#) in a computer program determines the individual lines of code to be executed and/or the order in which they will be executed. In this chapter, we'll learn about 3 types of control flow statements:

1. if-elif-else
2. for loop
3. while loop

The first type of control flow statement is **if-elif-else**. This statement helps with conditional execution of code, i.e., the piece of code to be executed is selected based on certain condition(s).

3.0.1 Comparison operators

For testing if conditions are true or false, first we need to learn the operators that can be used for comparison. For example, suppose we want to check if two objects are equal, we use the `==` operator:

```
5==6
```

False

```
x = "hi"  
y = "hi"  
x==y
```

True

Below are the python comparison operators and their meanings.

Python code	Meaning
<code>x==y</code>	Produce True if ... x is equal to y
<code>x != y</code>	... x is not equal to y
<code>x > y</code>	... x is greater than y
<code>x < y</code>	... x is less than y
<code>x >= y</code>	... x is greater than or equal to y
<code>x <= y</code>	... x is less than or equal to y

3.0.2 Logical operators

Sometimes we may need to check multiple conditions simultaneously. The logical operator **and** is used to check if all the conditions are true, while the logical operator **or** is used to check if either of the conditions is true.

```
#Checking if both the conditions are true using 'and'
5==5 and 67==68
```

False

```
#Checking if either condition is true using 'or'
x = 6; y = 90
x<0 or y>50
```

True

3.0.3 if-elif-else statement

The **if-elif-else** statements can check several conditions, and execute the code corresponding to the condition that is true. Note that there can be as many **elif** statements as required.

Syntax: Python uses indentation to identify the code to be executed if a condition is true. All the code indented within a condition is executed if the condition is true.

Example: Input an integer. Print whether it is positive or negative.

```
number = input("Enter a number:") #Input an integer
number_integer = int(number)      #Convert the integer to 'int' datatype
if number_integer>0:              #Check if the integer is positive
    print("Number is positive")
```

```
else:
    print("Number is negative")
```

Enter a number:-9
Number is negative

In the above code, note that anything entered by the user is taken as a string datatype by python. However, a string cannot be positive or negative. So, we converted the number input by the user to integer to check if it was positive or negative.

There may be multiple statements to be executed if a condition is true. See the example below.

Example: Input a number. Print whether it is positive, negative or zero. If it is negative, print its absolute value.

```
number = input("Enter a number:")
number_integer = int(number)
if number_integer>0:
    print("Number is positive")
elif number_integer==0:
    print("Number is zero")
else:
    print("Number is negative")
    print("Absolute value of number = ", abs(number_integer))
```

Enter a number:0
Number is zero

3.0.4 Practice exercise 1

Input a number. Print whether its odd or even.

Solution:

```
num = int(input("Enter a number: "))
if num%2==0:                #Checking if the number is divisible by 2
    print("Number is even")
else:
    print("Number is odd")
```



```
Enter a number: 5
Number is odd
```

3.0.5 Try-except

If we suspect that some lines of code may produce an error, we can put them in a **try** block, and if an error does occur, we can use the **except** block to instead execute an alternative piece of code. This way the program will not stop if an error occurs within the **try** block, and instead will be directed to execute the code within the **except** block.

Example: Input an integer from the user. If the user inputs a valid integer, print whether it is a multiple of 3. However, if the user does not input a valid integer, print a message saying that the input is invalid.

```
num = input("Enter an integer:")

#The code lines within the 'try' block will execute as long as they run without error
try:
    #Converting the input to integer, as user input is a string
    num_int = int(num)

    #checking if the integer is a multiple of 3
    if num_int%3==0:
        print("Number is a multiple of 3")
    else:
        print("Number is not a multiple of 3")

#The code lines within the 'except' block will execute only if the code lines within the '
except:
    print("Input must be an integer")
```

```
Enter an integer:hi
Input must be an integer
```

3.0.6 Practice exercise 2

3.0.6.1

Ask the user to enter their exam score. Print the grade based on their score as follows:

Score	Grade
(90,100]	A
(80,90]	B
[0,80]	C

If the user inputs a score which is not a number in [0,100], print invalid entry.

Solution:

```
score = input("Enter exam score:")
try:

    #As exam score can be a floating point number (such as 90.65), we need to use 'float'
    score_num = float(score)
    if score_num>90 and score_num<=100:
        print("Grade: A")
    elif score_num>80 and score_num<=90:
        print("Grade: B")
    elif score_num>=0 and score_num<=80:
        print("Grade: C")
    else:
        print("Invalid score")           #If a number is less than 0 or more than 100
except:
    print("Invalid input")              #If the input is not a number
```

Enter exam score:90

Grade: B

3.0.6.2

Nested if-elif-else statements: This question will lead you to create nested if statements, i.e., an if statement within another if statement.

Think of a number in [1,5]. Ask the user to guess the number.

- If the user guesses the number correctly, print “Correct in the first attempt!”, and stop the program. Otherwise, print “Incorrect! Try again” and give them another chance to guess the number.
- If the user guesses the number correctly in the second attempt, print “Correct in the second attempt”, otherwise print “Incorrect in both the attempts, the correct number is:”, and print the correct number.

Solution:

```
#Let us say we think of the number. Now the user has to guess the number in two attempts.
rand_no = 3
guess = input("Guess the number:")
if int(guess)==rand_no:
    print("Correct in the first attempt!")

#If the guess is incorrect, the program will execute the code block below
else:
    guess = input("Incorrect! Try again:")
    if int(guess)==rand_no:
        print("Correct in the second attempt")
    else:
        print("Incorrect in the both the attempts, the correct number was:", rand_no)
```

3.1 Loops

With loops, a piece of code can be executed repeatedly for a fixed number of times or until a condition is satisfied.

3.1.1 for loop

With a **for** loop, a piece of code is executed a fixed number of times.

We typically use **for** loops with an in-built python function called **range()** that supports **for** loops. Below is its description.

range(): The **range()** function returns a sequence of evenly-spaced integer values. It is commonly used in **for** loops to define the sequence of elements over which the iterations are performed.

Below is an example where the **range()** function is used to create a sequence of whole numbers upto 10. Ignore the **list()** function in the code below, as it will be introduced later.

```
print(list(range(10)))
```

[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]

Note that the last element is one less than the integer specified in the `range()` function.

Using the `range()` function, the `for` loop can iterate over a sequence of numbers. See the example below.

Example: Print the first n elements of the [Fibonacci sequence](#), where n is an integer input by the user, such that $n > 2$. In a fibonacci sequence, each number is the sum of the preceding two numbers, and the sequence starts from 0,1. The sequence is as follows:

0,1,1,2,3,5,8,13,....

```
n=int(input("Enter number of elements:"))

#Initializing the sequence to start from 0, 1
n1=0;n2=1

#Printing the first two numbers of the sequence
print(n1)
print(n2)

for i in range(n-2): #Since two numbers of the sequence are already printed, n-2 numbers

    #Computing the next number of the sequence as the summation of the previous two number
    n3 = n1+n2
    print(n3)

    #As 'n3' is already printed, it is no longer the next number of the sequence.
    #Thus, we move the values of the variables n1 and n2 one place to the right to compute
    n1 = n2
    n2 = n3

print("These are the first", n, "elements of the fibonacci series")
```

Enter number of elements:6

0
1
1
2
3
5

These are the first 6 elements of the fibonacci series

As in the `if-elif-else` statement, the `for` loop uses indentation to indicate the piece of code to be run repeatedly.

Note that we have used an in-built python function

3.1.2 while loop

With a **while** loops, a piece of code is executed repeatedly until certain condition(s) hold.

Example: Print all the elements of the [Fibonacci sequence](#) less than n , where n is an integer input by the user, such that $n > 2$. In a fibonacci sequence, each number is the sum of the preceding two numbers, and the sequence starts from 0,1. The sequence is as follows:

0,1,1,2,3,5,8,13,....

```
n=int(input("Enter the value of n:"))

#Initializing the sequence to start from 0, 1
n1=0;n2=1

#Printing the first number of the sequence
print(n1)

while n2<n:

    #Print the next number of the sequence
    print(n2)

    #Computing the next number of the sequence as the summation of the previous two number
    n3 = n1+n2

    #As n2 is already printed, assigning n2 to n3, so that the next number of the sequence
    #Assigning n1 to n2 as n1 has already been used to compute the next number of the sequence
    n1 = n2
    n2 = n3
print("These are all the elements of the fibonacci series less than", n)
```

Enter the value of n:50

0
1
1
2
3
5
8

13
21
34

These are all the elements of the fibonacci series less than 50

3.1.3 Practice exercise 3

3.1.3.1

Write a program that identifies whether a number input by the user is prime or not.

Solution:

```
number = int(input("Enter a positive integer:"))

#Defining a variable that will have a value of 0 if there are no divisors
num_divisors=0

#Checking if the number has any divisors from 2 to half of the number
for divisor in range(2,int(number/2+1)):
    if number%divisor==0:

        #If the number has a divisor, setting num_divisors to 1, to indicate that the
        num_divisors = 1

        #If a divisor has been found, there is no need to check if the number has more
        #Even if the number has a single divisor, it is not prime. Thus, we 'break' out
        #If you don't 'break', your code will still be correct, it will just do some u
        break

#If there are no divisors of the number, it is prime, else not prime
if num_divisors==0:
    print("Prime")
else:
    print("Not prime")
```

Enter a positive integer:97
Prime

3.1.3.2

Update the program above to print the prime numbers starting from 2, and less than n where n is a positive integer input by the user.

Solution:

```
n = int(input("Enter a positive integer:"))

#Defining a variable - number_iterator. We will use this variable to iterate over all integers
#While iterating over each integer from 2 to n, we will check if the integer is prime or not
number_iterator = 2

print(number_iterator) #Since '2' is a prime number, we can print it directly (without checking)

#Continue to check for prime numbers until n (but not including n)
while(number_iterator<n):

    #After each check, increment the number_iterator to check if the next integer is prime
    number_iterator=number_iterator+1

    #Defining a variable that will have a value of 0 if there are no divisors
    num_divisors=0

    #Checking if the integer has any divisors from 2 to half of the integer being checked
    for divisor in range(2,int(number_iterator/2+1)):
        if number_iterator%divisor==0:

            #If the integer has a divisor, setting num_divisors to 1, to indicate that the integer is not prime
            num_divisors=1

            #If a divisor has been found, there is no need to check if the integer has more divisors
            #Even if the integer has a single divisor, it is not prime.
            #Thus, we 'break' out of the loop that checks for divisors
            break

    #If there are no divisors of the integer being checked, the integer is a prime number,
    if num_divisors==0:
        print(number_iterator)
```

```
Enter a positive integer:100
2
```

3
5
7
11
13
17
19
23
29
31
37
41
43
47
53
59
61
67
71
73
79
83
89
97

3.2 break statement

The `break` statement is used to unconditionally exit the innermost loop.

For example, suppose we need to keep asking the user to input year of birth and compute the corresponding age, until the user enters 1900 as the year of birth.

```
#The loop will continue to run indefinitely as the condition 'True' is always true
while True:
    year = int(input("Enter year of birth:"))
    if year==1900:
        break          #If the user inputs 1900, then break out of the loop
    else:
        print("Age = ",2022-year)    #Otherwise compute and print the age
```

Enter year of birth:1987


```
Age = 35
Enter year of birth:1995
Age = 27
Enter year of birth:2001
Age = 21
Enter year of birth:1900
```

3.2.1 Practice exercise 4

Write a program that finds and prints the largest factor of a number input by the user. Check the output if the user inputs 133.

Solution:

```
num = int(input("Enter an integer:"))

#Looping from the half the integer to 0 as the highest factor is likely to be closer to half
for i in range(int(num/2)+1,0,-1):
    if num%i==0:
        print("Largest factor = ",i)

        #Exiting the loop if the largest integer is found
        break
```

```
Enter an integer:133
Largest factor = 19
```

3.3 continue statement

The `continue` statement is used to continue with the next iteration of the loop without executing the lines of code below it.

For example, consider the following code:

```
for i in range(10):
    if i%2==0:
        continue
    print(i)
```

1
3
5
7
9

When the control flow reads the statement `continue`, it goes back to the beginning of the `for` loop, and ignores the lines of code below the statement.

3.3.1 Practice exercise 5:

Write a program that asks the user the question, “How many stars are in the Milky Way (in billions)?”. If the user answers 100, the program should print correct, and stop. However, if the user answers incorrectly, the program should print “incorrect”, and ask them if they want to try again. The program should continue to run until the user answers correctly, or they want to stop trying.

```
#Defining an infinite while loop as the loop may need to run indefinitely if the user keeps trying
while True:
    answer = input("How many stars are there in the Milky Way? ")
    if answer=='100':
        print("Correct")

        #Exiting the loop if the user answers correctly
        break
    else:
        print("Incorrect")
        try_again = input("Do you want to try again? (Y/N) ")
        if try_again=='Y':

            #Continuing with the infinite loop if the user wants to try again
            continue
        else:

            #Exiting the infinite loop if the user wants to stop trying
            break
```

```
How many stars are there in the Milky Way? 101
Incorrect
Do you want to try again? (Y/N) Y
How many stars are there in the Milky Way? 7
```

```
Incorrect
Do you want to try again? (Y/N) Y
How many stars are there in the Milky Way? 5
Incorrect
Do you want to try again? (Y/N) Y
How many stars are there in the Milky Way? 100
Correct
```

3.4 Loops with strings

Loops can be used to iterate over a string, just like we used them to iterate over a sequence of integers.

Consider the following string:

```
sentence = "She sells sea shells on the sea shore"
```

The i^{th} character of the string can be retrieved by its index. For example, the first character of the string `sentence` is:

```
sentence[0]
```

```
'S'
```

Slicing a string:

A part of the string can be sliced by passing the starting index (say `start`) and the stopping index (say `stop`) as `start:stop` to the index operator `[]`. This is called slicing a string. For a string `S`, the characters starting from the index `start` upto the index `stop`, but not including `stop`, can be sliced as `S[start:stop]`.

For example, the slice of the string `sentence` from index 4 to index 9, but not including 9 is:

```
sentence[4:9]
```

```
'sells'
```

Example:

Input a string, and count and print the number of “*t*”s.

```

string = input("Enter a sentence:")

#Initializing a variable 'count_t' which will store the number of 't's in the string
count_t = 0

#Iterating over the entire length of the string.
#The length of the string is given by the len() function
for i in range(len(string)):

    #If the ith character of the string is 't', then we count it
    if string[i]=='t':
        count_t = count_t+1

print("Number of 't's in the string = ",count_t)

```

Enter a sentence:Getting a tatto is not a nice experience
Number of 't's in the string = 6

3.4.1 Practice exercise 6

Write a program that asks the user to input a string, and print the number of “*the*”s in the string.

```

string = input("Enter a sentence:")

#Defining a variable to store the count of the word 'the'
count_the = 0

#Looping through the entire length of the string except the last 3 letters.
#As we are checking three letters at a time starting from the index 'i', the last 3 letter
for i in range(len(string)-3):

    #Slicing 3 letters of the string and checking if they are 'the'
    if string[i:(i+3)]=='the':

        #Counting the words that are 'the'
        count_the = count_the+1
print("Number of 'the's in the string = ",count_the)

```

Enter a sentence:She sells the sea shells on the sea shore in the spring

Number of 'the's in the string = 3

4 Functions

As the words suggests, *functions* are a piece of code that have a specific function or purpose. As an analogy, if a human is a computer program, then the mind can be considered to be a function, which has purpose of thinking, eyes can be another function, which have a purpose of seeing. These functions are called upon by the human when needed.

Similarly, in case of a computer program, functions are a piece of code, that perform a specific task, when called upon by the program. Instead of being defined as a function, the piece of code can also be used directly whenever it is needed in a program. However, defining a frequently-used piece of code as a function has the following benefits:

1. It reduces the number of lines of code, as the lines of code need to be written just once in the function definition. Thereafter, the function is called by its name, wherever needed in the program. This makes the code compact, and enhances readability.
2. It makes the process of writing code easier, as the user needs to just type the name of the function, wherever it is needed, instead of pasting lines of code.
3. It can be used in different programs, thereby saving time in writing other programs.

To put it more formally, a function is a piece of code that takes arguments (if any) as input, performs computations or tasks, and then returns a result or results.

4.1 Defining a function

Look at the function defined below. It asks the user to input a number, and prints whether the number is odd or even.

```
#This is an example of a function definition

#A function definition begins with the 'def' keyword followed by the name of the function.
#Note that 'odd_even()' is the name of the function below.
def odd_even():
    num = int(input("Enter an integer:"))
    if num%2==0:
        print("Even")
```

```

    else:
        print("Odd")    #Function definition ends here

print("This line is not a part of the function as it is not indented") #This line is not a

```

This line is not a part of the function as it is not indented

Note that the function is defined using the `def` keyword. All the lines within the function definition are indented. The indentation shows the lines of code that belong to the function. When the indentation stops, the function definition is considered to have ended.

Whenever the user wishes to input a number and print whether it is odd or even, they can call the function defined above by its name as follows:

```
odd_even()
```

```

Enter an integer:5
Odd

```

4.2 Parameters and arguments of a function

Note that the function defined above needs no input when called. However, sometimes we may wish to define a function that takes input(s), and performs computations on the inputs to produce an output. These input(s) are called parameter(s) of a function. When a function is called, the value(s) of these parameter(s) must be specified as argument(s) to the function.

4.2.1 Function with a parameter

Let us change the previous example to write a function that takes an integer as an input argument, and prints whether it is odd or even:

```

#This is an example of a function definition that has an argument
def odd_even(num):
    if num%2==0:
        print("Even")
    else:
        print("Odd")

```

We can use the function whenever we wish to find a number is odd or even. For example, if we wish to find that a number input by the user is odd or even, we can call the function with the user input as its argument.

```
number = int(input("Enter an integer:"))
odd_even(number)
```

```
Enter an integer:6
Even
```

Note that the above function needs an argument as per the function definition. It will produce an error if called without an argument:

```
odd_even()
```

```
TypeError: odd_even() missing 1 required positional argument: 'num'
```

4.2.2 Function with a parameter having a default value

To avoid errors as above, sometimes is a good idea to assign a default value to the parameter in the function definition:

```
#This is an example of a function definition that has an argument with a default value
def odd_even(num=0):
    if num%2==0:
        print("Even")
    else:
        print("Odd")
```

Now, we can call the function without an argument. The function will use the default value of the parameter specified in the function definition.

```
odd_even()
```

```
Even
```


4.2.3 Function with multiple parameters

A function can have as many parameters as needed. Multiple parameters/arguments are separated by commas. For example, below is a function that inputs two strings, concatenates them with a space in between, and prints the output:

```
def concat_string(string1, string2):  
    print(string1+' '+string2)
```

```
concat_string("Hi", "there")
```

Hi there

4.2.4 Practice exercise 1

Write a function that prints prime numbers between two real numbers - **a** and **b**, where **a** and **b** are the parameters of the function. Call the function and check the output with **a = 60**, **b = 80**.

Solution:

```
def prime_numbers (a,b=100):  
    num_prime_nos = 0  
  
    #Iterating over all numbers between a and b  
    for i in range(a,b):  
        num_divisors=0  
  
        #Checking if the ith number has any factors  
        for j in range(2, i):  
            if i%j == 0:  
                num_divisors=1;break;  
  
        #If there are no factors, then printing and counting the number as prime  
        if num_divisors==0:  
            print(i)  
prime_numbers(60,80)
```

61

67

71
73
79

4.3 Functions that return objects

Until now, we saw functions that print text. However, the functions did not **return** any object. For example, the function `odd_even` prints whether the number is odd or even. However, we did not save this information. In future, we may need to use the information that whether the number was odd or even. Thus, typically, we return an object from the function definition, which consists of the information we may need in the future.

The example `odd_even` can be updated to return the text “odd” or “even” as shown below:

```
#This is an example of a function definition that has an argument with a default value, and
def odd_even(num=0):
    if num%2==0:
        return("Even")
    else:
        return("Odd")
```

The function above returns a string “Odd” or “Even”, depending on whether the number is odd or even. This result can be stored in a variable, which can be used later.

```
response=odd_even(3)
response
```

'Odd'

The variable `response` now refers to the object where the string “Odd” or “Even” is stored. Thus, the result of the computation is stored, and the variable can be used later on in the program. Note that the control flow exits the function as soon as the first **return** statement is executed.

Figure 4.1 below shows the terminology associated with functions.

<IPython.core.display.Image object>

Figure 4.1: Terminology associated with functions

4.4 Global and local variables with respect to a function

A variable defined within a function is local to that function, while a variable defined outside the function is global with respect to that function. In case a variable with the same name is defined both outside and inside a function, it will refer to its global value outside the function and local value within the function.

The example below shows a variable with the name `var` referring to its local value when called within the function, and global value when called outside the function.

```
var = 5
def sample_function(var):
    print("Local value of 'var' within 'sample_function()' = ",var)

sample_function(4)
print("Global value of 'var' outside 'sample_function()' = ",var)
```

```
Local value of 'var' within 'sample_function()' = 4
Global value of 'var' outside 'sample_function()' = 5
```

4.5 Built-in python functions

So far we have seen user-defined functions in this chapter. These functions were defined by us, and are not stored permanently in the python compiler. However, there are some functions that come built-in with python and we can use them directly without defining them. These built-in functions can be seen [here](#). For example the built-in function `max()` computes the max of numeric values:

```
max(1,2,3)
```

3

Another example is the `round()` function that rounds up floating point numbers:

```
round(3.7)
```

4

4.6 Python libraries

Other than the built-in functions, python has hundreds of thousands of libraries that contain several useful functions. These libraries are contributed by people around the world as python is an open-source platform. Some of the libraries popular in data science, and their purposes are the following:

1. NumPy: Performing numerical operations and efficiently storing numerical data.
2. Pandas: Reading, cleaning and manipulating data.
3. Matplotlib, Seaborn: Visualizing data.
4. SciPy: Performing scientific computing such as solving differential equations, optimization, statistical tests, etc.
5. Scikit-learn: Data pre-processing and machine learning, with a focus on prediction.
6. Statsmodels: Developing statistical models with a focus on inference

A library can be imported using the `import` keyword. For example, a NumPy library can be imported as:

```
import numpy as np
```

Using the `as` keyword, the NumPy library has been given the name `np`. All the functions and attributes of the library can be called using the `'np.'` prefix. For example, let us generate a sequence of whole numbers upto 10 using the NumPy function `arange()`:

```
np.arange(8)
```

```
array([0, 1, 2, 3, 4, 5, 6, 7])
```

Generating random numbers is very useful in python for performing simulations (we'll see in later chapters). The library `random` is used to generate random numbers such as integers, real numbers based on different probability distributions, etc.

Below is an example of using the `randint()` function of the library for generating random numbers in `[a, b]`, where `a` and `b` are integers.

```
import random as rm
rm.randint(5,10) #This will generate a random number in [5,10]
```

4.6.1 Practice exercise 2

Generate a random number between $[-5,5]$. Do this 10,000 times. Find the mean of all the 10,000 random numbers generated.

Solution:

```
import random as rm
counter = 0
for i in range(10000):
    counter = counter + rm.uniform(-5,5)
print("Mean is:", counter/10000)
```

Mean is: 0.061433810226516616

5 Data structures

In this chapter we'll learn about the python data structures that are often used or appear while analyzing data.

Tuple is a sequence of python objects, with two key characteristics: (1) the number of objects are fixed, and (2) the objects are immutable, i.e., they cannot be changed.

Tuple can be defined as a sequence of python objects separated by commas, and enclosed in rounded brackets (). For example, below is a tuple containing three integers.

```
tuple_example = (2,7,4)
```

We can check the data type of a python object using the *type()* function. Let us check the data type of the object *tuple_example*.

```
type(tuple_example)
```

tuple

Elements of a tuple can be extracted using their index within square brackets. For example the second element of the tuple *tuple_example* can be extracted as follows:

```
tuple_example[1]
```

7

Note that an element of a tuple cannot be modified. For example, consider the following attempt in changing the second element of the tuple *tuple_example*.

```
tuple_example[1] = 8
```

TypeError: 'tuple' object does not support item assignment

The above code results in an error as tuple elements cannot be modified.

5.0.1 Practice exercise 1

USA's GDP per capita from 1960 to 2021 is given by the tuple T in the code cell below. The values are arranged in ascending order of the year, i.e., the first value is for 1960, the second value is for 1961, and so on. Print the years in which the GDP per capita of the US increased by more than 10%.

```
T = (3007, 3067, 3244, 3375, 3574, 3828, 4146, 4336, 4696, 5032, 5234, 5609, 6094, 6726, 7226, 78
```

5.0.2 Concatenating tuples

Tuples can be concatenated using the + operator to produce a longer tuple:

```
(2,7,4) + ("another", "tuple") + ("mixed","datatypes",5)
```

```
(2, 7, 4, 'another', 'tuple', 'mixed', 'datatypes', 5)
```

Multiplying a tuple by an integer results in repetition of the tuple:

```
(2,7,"hi") * 3
```

```
(2, 7, 'hi', 2, 7, 'hi', 2, 7, 'hi')
```

5.0.3 Unpacking tuples

If tuples are assigned to an expression containing multiple variables, the tuple will be unpacked and each variable will be assigned a value as per the order in which it appears. See the example below.

```
x,y,z = (4.5, "this is a string", (("Nested tuple",5)))
```

```
x
```

```
4.5
```

```
y
```

```
'this is a string'
```

```
z
```

```
('Nested tuple', 5)
```

If we are interested in retrieving only some values of the tuple, the expression `*_` can be used to discard the other values. Let's say we are interested in retrieving only the first and the last two values of the tuple:

```
x,*_,y,z = (4.5, "this is a string", (("Nested tuple",5)), "99",99)
```

```
x
```

```
4.5
```

```
y
```

```
'99'
```

```
z
```

```
99
```

5.0.4 Practice exercise 2

USA's GDP per capita from 1960 to 2021 is given by the tuple T in the code cell below. The values are arranged in ascending order of the year, i.e., the first value is for 1960, the second value is for 1961, and so on.

Write a function that has two parameters:

1. Year : which indicates the year from which the GDP per capita are available in the second parameter
2. Tuple of GDP per capita's: Tuple consisting of GDP per capita for consecutive years starting from the year mentioned in the first parameter.

The function should return a tuple of length two, where the first element of the tuple is the number of years when the increase in GDP per capita was more than 5%, and the second element is the most recent year in which the GDP per capita increase was more than 5%.

Call the function to find the number of years, and the most recent year in which the GDP per capita increased by more than 5%, since the year 2000. Assign the **number of years** returned by the function to a variable named **num_years**, and assign the most recent year to a variable named **recent_year**. Print the values of **num_years** and **recent_year**.

```
T = (3007, 3067, 3244, 3375, 3574, 3828, 4146, 4336, 4696, 5032, 5234, 5609, 6094, 6726, 7226, 78
```

5.0.5 Tuple methods

A couple of useful tuple methods are **count**, which counts the occurrences of an element in the tuple and **index**, which returns the position of the first occurrence of an element in the tuple:

```
tuple_example = (2, 5, 64, 7, 2, 2)
```

```
tuple_example.count(2)
```

3

```
tuple_example.index(2)
```

0

Now that we have an idea about tuple, let us try to think where it can be used.

<IPython.core.display.HTML object>

5.1 List

List is a sequence of python objects, with two key characteristics that differentiates it from tuple: (1) the number of objects are variable, i.e., objects can be added or removed from a list, and (2) the objects are mutable, i.e., they can be changed.

List can be defined as a sequence of python objects separated by commas, and enclosed in square brackets []. For example, below is a list consisting of three integers.

```
list_example = [2,7,4]
```

5.1.1 Adding and removing elements in a list

We can add elements at the end of the list using the *append* method. For example, we append the string 'red' to the list *list_example* below.

```
list_example.append('red')
```

```
list_example
```

```
[2, 7, 4, 'red']
```

Note that the objects of a list or a tuple can be of different datatypes.

An element can be added at a specific location of the list using the *insert* method. For example, if we wish to insert the number 2.32 as the second element of the list *list_example*, we can do it as follows:

```
list_example.insert(1,2.32)
```

```
list_example
```

```
[2, 2.32, 7, 4, 'red']
```

For removing an element from the list, the *pop* and *remove* methods may be used. The *pop* method removes an element at a particular index, while the *remove* method removes the element's first occurrence in the list by its value. See the examples below.

Let us say, we need to remove the third element of the list.

```
list_example.pop(2)
```

7

```
list_example
```

```
[2, 2.32, 4, 'red']
```

Let us say, we need to remove the element 'red'.

```
list_example.remove('red')
```

```
list_example
```

```
[2, 2.32, 4]
```

```
#If there are multiple occurrences of an element in the list, the first occurrence will be removed
list_example2 = [2,3,2,4,4]
list_example2.remove(2)
list_example2
```

```
[3, 2, 4, 4]
```

For removing multiple elements in a list, either `pop` or `remove` can be used in a `for` loop, or a `for` loop can be used with a condition. See the examples below.

Let's say we need to remove integers less than 100 from the following list.

```
list_example3 = list(range(95,106))
list_example3
```

```
[95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105]
```

```
#Method 1: For loop with remove
list_example3_filtered = list(list_example3) #
```

```

for element in list_example3:
    if element<100:
        list_example3_filtered.remove(element)
print(list_example3_filtered)

```

[100, 101, 102, 103, 104, 105]

Q1: What's the need to define a new variable `list_example3_filtered` in the above code?

A1: Replace `list_example3_filtered` with `list_example3` and identify the issue.

```

#Method 2: For loop with condition
[element for element in list_example3 if element>100]

```

[101, 102, 103, 104, 105]

5.1.2 List comprehensions

List comprehension is a compact way to create new lists based on elements of an existing list or other objects.

Example: Create a list that has squares of natural numbers from 5 to 15.

```

sqrt_natural_no_5_15 = [(x**2) for x in range(5,16)]
print(sqrt_natural_no_5_15)

```

[25, 36, 49, 64, 81, 100, 121, 144, 169, 196, 225]

Example: Create a list of tuples, where each tuple consists of a natural number and its square, for natural numbers ranging from 5 to 15.

```

sqrt_natural_no_5_15 = [(x,x**2) for x in range(5,16)]
print(sqrt_natural_no_5_15)

```

[(5, 25), (6, 36), (7, 49), (8, 64), (9, 81), (10, 100), (11, 121), (12, 144), (13, 169), (14, 196)]

5.1.3 Practice exercise 3

Below is a list consisting of responses to the question: “At what age do you think you will marry?” from students of the STAT303-1 Fall 2022 class.

```
exp_marriage_age=['24','30','28','29','30','27','26','28','30+','26','28','30','30','30','
```

Use list comprehension to:

5.1.3.1

Remove the elements that are not integers - such as *‘probably never’*, *‘30+’*, etc. What is the length of the new list?

Hint: The built-in python function of the `str` class - `isdigit()` may be useful to check if the string contains only digits.

5.1.3.2

Cap the values greater than 80 to 80, in the clean list obtained in (1). What is the mean age when people expect to marry in the new list?

5.1.3.3

Determine the percentage of people who expect to marry at an age of 30 or more.

5.1.4 Concatenating lists

As in tuples, lists can be concatenated using the `+` operator:

```
import time as tm

list_example4 = [5,'hi',4]
list_example4 = list_example4 + [None,'7',9]
list_example4
```

```
[5, 'hi', 4, None, '7', 9]
```

For adding elements to a list, the **extend** method is preferred over the **+** operator. This is because the **+** operator creates a new list, while the **extend** method adds elements to an existing list. Thus, the **extend** operator is more memory efficient.

```
list_example4 = [5,'hi',4]
list_example4.extend([None, '7', 9])
list_example4
```

```
[5, 'hi', 4, None, '7', 9]
```

5.1.5 Sorting a list

A list can be sorted using the **sort** method:

```
list_example5 = [6,78,9]
list_example5.sort(reverse=True) #the reverse argument is used to specify if the sorting i
list_example5
```

```
[78, 9, 6]
```

5.1.6 Slicing a list

We may extract or update a section of the list by passing the starting index (say **start**) and the stopping index (say **stop**) as **start:stop** to the index operator **[]**. This is called *slicing* a list. For example, see the following example.

```
list_example6 = [4,7,3,5,7,1,5,87,5]
```

Let us extract a slice containing all the elements from the the 3rd position to the 7th position.

```
list_example6[2:7]
```

```
[3, 5, 7, 1, 5]
```

Note that while the element at the **start** index is included, the element with the **stop** index is excluded in the above slice.

If either the **start** or **stop** index is not mentioned, the slicing will be done from the beginning or until the end of the list, respectively.

```
list_example6[:7]
```

```
[4, 7, 3, 5, 7, 1, 5]
```

```
list_example6[2:]
```

```
[3, 5, 7, 1, 5, 87, 5]
```

To slice the list relative to the end, we can use negative indices:

```
list_example6[-4:]
```

```
[1, 5, 87, 5]
```

```
list_example6[-4:-2:]
```

```
[1, 5]
```

An extra colon (':') can be used to slice every ith element of a list.

```
#Selecting every 3rd element of a list  
list_example6[::3]
```

```
[4, 5, 5]
```

```
#Selecting every 3rd element of a list from the end  
list_example6[::-3]
```

```
[5, 1, 3]
```

```
#Selecting every element of a list from the end or reversing a list  
list_example6[::-1]
```

```
[5, 87, 5, 1, 7, 5, 3, 7, 4]
```

5.1.7 Practice exercise 4

Start with the list [8,9,10]. Do the following:

5.1.7.1

Set the second entry (index 1) to 17

5.1.7.2

Add 4, 5, and 6 to the end of the list

5.1.7.3

Remove the first entry from the list

5.1.7.4

Sort the list

5.1.7.5

Double the list (concatenate the list to itself)

5.1.7.6

Insert 25 at index 3

The final list should equal [4,5,6,25,10,17,4,5,6,10,17]

Now that we have an idea about lists, let us try to think where it can be used.

<IPython.core.display.HTML object>

Now that we have learned about lists and tuples, let us compare them.

Q2: A list seems to be much more flexible than tuple, and can replace a tuple almost everywhere. Then why use tuple at all?

A2: The additional flexibility of a list comes at the cost of efficiency. Some of the advantages of a tuple over a list are as follows:

1. Since a list can be extended, space is over-allocated when creating a list. A tuple takes less storage space as compared to a list of the same length.
2. Tuples are not copied. If a tuple is assigned to another tuple, both tuples point to the same memory location. However, if a list is assigned to another list, a new list is created consuming the same memory space as the original list.
3. Tuples refer to their element directly, while in a list, there is an extra layer of pointers that refers to their elements. Thus it is faster to retrieve elements from a tuple.

The examples below illustrate the above advantages of a tuple.

```
#Example showing tuples take less storage space than lists for the same elements
tuple_ex = (1, 2, 'Obama')
list_ex = [1, 2, 'Obama']
print("Space taken by tuple =",tuple_ex.__sizeof__()," bytes")
print("Space taken by list =",list_ex.__sizeof__()," bytes")
```

Space taken by tuple = 48 bytes

Space taken by list = 64 bytes

```
#Examples showing that a tuples are not copied, while lists can be copied
tuple_copy = tuple(tuple_ex)
print("Is tuple_copy same as tuple_ex?", tuple_ex is tuple_copy)
list_copy = list(list_ex)
print("Is list_copy same as list_ex?",list_ex is list_copy)
```

Is tuple_copy same as tuple_ex? True

Is list_copy same as list_ex? False

```
#Examples showing tuples takes lesser time to retrieve elements
import time as tm
tt = tm.time()
list_ex = list(range(1000000)) #List containinig whole numbers upto 1 million
```

```

a=(list_ex[::-2])
print("Time take to retrieve every 2nd element from a list = ", tm.time()-tt)

tt = tm.time()
tuple_ex = tuple(range(1000000)) #tuple containinig whole numbers upto 1 million
a=(tuple_ex[::-2])
print("Time take to retrieve every 2nd element from a tuple = ", tm.time()-tt)

```

```

Time take to retrieve every 2nd element from a list = 0.03579902648925781
Time take to retrieve every 2nd element from a tuple = 0.02684164047241211

```

5.2 Dictionary

A dictionary consists of key-value pairs, where the keys and values are python objects. While values can be any python object, keys need to be immutable python objects, like strings, integers, tuples, etc. Thus, a list can be a value, but not a key, as elements of list can be changed. A dictionary is defined using the keyword `dict` along with curly braces, colons to separate keys and values, and commas to separate elements of a dictionary:

```
dict_example = {'USA':'Joe Biden', 'India':'Narendra Modi', 'China':'Xi Jinping'}
```

Elements of a dictionary can be retrieved by using the corresponding key.

```
dict_example['India']
```

```
'Narendra Modi'
```

5.2.1 Adding and removing elements in a dictionary

New elements can be added to a dictionary by defining a key in square brackets and assigning it to a value:

```

dict_example['Japan'] = 'Fumio Kishida'
dict_example['Countries'] = 4
dict_example

```

```
{'USA': 'Joe Biden',
 'India': 'Narendra Modi',
 'China': 'Xi Jinping',
 'Japan': 'Fumio Kishida',
 'Countries': 4}
```

Elements can be removed from the dictionary using the `del` method or the `pop` method:

```
#Removing the element having key as 'Countries'
del dict_example['Countries']
```

```
dict_example
```

```
{'USA': 'Joe Biden',
 'India': 'Narendra Modi',
 'China': 'Xi Jinping',
 'Japan': 'Fumio Kishida'}
```

```
#Removing the element having key as 'USA'
dict_example.pop('USA')
```

```
'Joe Biden'
```

```
dict_example
```

```
{'India': 'Narendra Modi', 'China': 'Xi Jinping', 'Japan': 'Fumio Kishida'}
```

New elements can be added, and values of existing keys can be changed using the `update` method:

```
dict_example = {'USA': 'Joe Biden', 'India': 'Narendra Modi', 'China': 'Xi Jinping', 'Countries': 3}
dict_example
```

```
{'USA': 'Joe Biden',
 'India': 'Narendra Modi',
 'China': 'Xi Jinping',
 'Countries': 3}
```

```
dict_example.update({'Countries':4, 'Japan':'Fumio Kishida'})
```

```
dict_example
```

```
{'USA': 'Joe Biden',  
 'India': 'Narendra Modi',  
 'China': 'Xi Jinping',  
 'Countries': 4,  
 'Japan': 'Fumio Kishida'}
```

5.2.2 Iterating over elements of a dictionary

The `items()` attribute of a dictionary can be used to iterate over elements of a dictionary.

```
for key,value in dict_example.items():  
    print("The Head of State of",key,"is",value)
```

```
The Head of State of USA is Joe Biden  
The Head of State of India is Narendra Modi  
The Head of State of China is Xi Jinping  
The Head of State of Countries is 4  
The Head of State of Japan is Fumio Kishida
```

5.2.3 Practice exercise 5

The GDP per capita of USA for most years from 1960 to 2021 is given by the dictionary D given in the code cell below.

Find:

1. The GDP per capita in 2015
2. The GDP per capita of 2014 is missing. Update the dictionary to include the GDP per capita of 2014 as the average of the GDP per capita of 2013 and 2015.
3. Impute the GDP per capita of other missing years in the same manner as in (2), i.e., as the average GDP per capita of the previous year and the next year. Note that the GDP per capita is not missing for any two consecutive years.
4. Print the years and the imputed GDP per capita for the years having a missing value of GDP per capita in (3).

```
D = {'1960':3007,'1961':3067,'1962':3244,'1963':3375,'1964':3574,'1965':3828,'1966':4146,'
```

5.3 Functions

If an algorithm or block of code is being used several times in a code, then it can be separately defined as a function. This makes the code more organized and readable. For example, let us define a function that prints prime numbers between **a** and **b**, and returns the number of prime numbers found.

```
#Function definition
def prime_numbers (a,b=100):
    num_prime_nos = 0

    #Iterating over all numbers between a and b
    for i in range(a,b):
        num_divisors=0

        #Checking if the ith number has any factors
        for j in range(2, i):
            if i%j == 0:
                num_divisors=1;break;

        #If there are no factors, then printing and counting the number as prime
        if num_divisors==0:
            print(i)
            num_prime_nos = num_prime_nos+1

    #Return count of the number of prime numbers
    return num_prime_nos
```

In the above function, the keyword **def** is used to define the function, **prime_numbers** is the name of the function, **a** and **b** are the arguments that the function uses to compute the output.

Let us use the defined function to print and count the prime numbers between 40 and 60.

```
#Printing prime numbers between 40 and 60
num_prime_nos_found = prime_numbers(40,60)
```

41
43
47
53
59

```
num_prime_nos_found
```

5

If the user calls the function without specifying the value of the argument **b**, then it will take the default value of 100, as mentioned in the function definition. However, for the argument **a**, the user will need to specify a value, as there is no value defined as a default value in the function definition.

5.3.1 Global and local variables with respect to a function

A variable defined within a function is local to that function, while a variable defined outside the function is global to that function. In case a variable with the same name is defined both outside and inside a function, it will refer to its global value outside the function and local value within the function.

The example below shows a variable with the name **var** referring to its local value when called within the function, and global value when called outside the function.

```
var = 5
def sample_function(var):
    print("Local value of 'var' within 'sample_function()' = ",var)

sample_function(4)
print("Global value of 'var' outside 'sample_function()' = ",var)
```

```
Local value of 'var' within 'sample_function()' = 4
Global value of 'var' outside 'sample_function()' = 5
```

5.3.2 Practice exercise 6

The object **deck** defined below corresponds to a deck of cards. Estimate the probability that a five card hand will be a **flush**, as follows:

1. Write a function that accepts a hand of 5 cards as argument, and returns whether the hand is a flush or not.
2. Randomly pull a hand of 5 cards from the deck. Call the function developed in (1) to determine if the hand is a flush.
3. Repeat (2) 10,000 times.

4. Estimate the probability of the hand being a flush from the results of the 10,000 simulations.

You may use the function `shuffle()` from the `random` library to shuffle the deck everytime before pulling a hand of 5 cards.

```
deck = [{'value':i, 'suit':c}
for c in ['spades', 'clubs', 'hearts', 'diamonds']
for i in range(2,15)]
```

5.4 Practice exercise 7

The code cell below defines an object having the nutrition information of drinks in starbucks. Assume that the manner in which the information is structured is consistent throughout the object.

```
, 'value': 1}, {'starbucks_typek_nutrition':{'value':10},'starbucks_ref_desk_pos_sever_age_nutr':['it's not right on: type c
```

Use the object above to answer the following questions:

5.4.1

What is the datatype of the object?

5.4.1.1

If the object in (1) is a dictionary, what is the datatype of the values of the dictionary?

5.4.1.2

If the object in (1) is a dictionary, what is the datatype of the elements within the values of the dictionary?

5.4.1.3

How many calories are there in Iced Coffee?

5.4.1.4

Which drink(s) have the highest amount of protein in them, and what is that protein amount?

5.4.1.5

Which drink(s) have a fat content of more than 10g, and what is their fat content?

A Assignment A

1. You may talk to a friend, discuss the questions and potential directions for solving them. However, you need to write your own solutions and code separately, and not as a group activity.
2. Do not write your name on the assignment.
3. Write your code in the *Code* cells of the Jupyter notebook. Ensure that the solution is written neatly enough to understand and grade.
4. Use [Quarto](#) to print the *.ipynb* file as HTML. You will need to open the command prompt, navigate to the directory containing the file, and use the command: `quarto render filename.ipynb --to html`. Submit the HTML file.
5. There are 5 points for cleanliness and organization. The breakdown is as follows:
 - Must be an HTML file rendered using Quarto (1.5 pts).
 - There aren't excessively long outputs of extraneous information (e.g. no printouts of unnecessary results without good reason, there aren't long printouts of which iteration a loop is on, there aren't long sections of commented-out code, etc.) (1 pt)
 - There is no piece of unnecessary / redundant code, and no unnecessary / redundant text (1 pt)
 - The code should be commented and clearly written with intuitive variable names. For example, use variable names such as `number_input`, `factor`, `hours`, instead of `a,b,xyz`, etc. (1.5 pts)
6. The assignment is worth 100 points, and is due on **13th April 2023 at 11:59 pm**.

A.1 Alarm clock

A.1.1 When does the alarm go off?

You look at the clock and it is exactly 2pm. You set an alarm to go off in 510 hours. At what time does the alarm go off? If the answer is say, 4 pm, then your code should print - "The alarm goes off at 4 pm".

(2 points)

A.1.2 User-friendly alarm clock

Write a program to solve the general version of the above problem. Ask the user for - (1) the time now (in hours), and (2) the number of hours for the alarm to go off. Your program should output the time at which the alarm goes off. Both the user inputs must be in $\{0, 1, 2, \dots, 22, 23\}$. If the answer is, say 14:00 hours, then your program should print - “The alarm goes off at 14:00 hours.

Show the output of your program when the user inputs 7 as the current time, and 95 as the number of hours for the alarm to go off.

(4 points)

A.2 Finding prime factors

A.2.1 Prime or not

Write a program that checks if a positive integer is prime or not. Show the output when the program is used to check if 89 is prime or not.

(2 points)

A.2.2 Factors

Prompt the user to input a positive integer. Write a program that prints the **factors** of the positive integer input by the user. Show the output of the program if the user inputs 190.

(2 points)

A.2.3 Prime factors

Prompt the user to input a positive integer. Update the program in 2(b) to print the **prime factors** of the positive integer input by the user. Show the output of the program if the user inputs 190.

(8 points)

A.2.4 User-friendly prime factor calculator

Update the program in 2(c), so that it prints “Incorrect input, please enter positive integer” if the user does not enter a positive integer, and then prompts the user to input a positive integer. The program should continue to prompt the user to enter a positive integer until the user successfully enters a positive integer. Show the output of the program if the user enters "seventy" in the first attempt, "#70" in the second attempt, and 70 in the third attempt.

(12 points)

A.3 Number of words in a sentence

Prompt the user to input an english sentence. Write a program that counts and prints the number of words in the sentence input by the user. The program should continue to run until the user inputs the sentence - “end program”. Show the output of the program if the user enters "this is the time to sleep" in the first attempt, "this is too much work for a day" in the second attempt, and "end program" in the third attempt.

Hint: Count the number of spaces

(10 points)

A.4 Survival of rabbits

In many environments, two or more species compete for the available resources. Classic predator–prey equations have been used to simulate or predict the dynamics of biological systems in which two species interact, one as a predator and the other as prey. You will use a simplified version of the [Lotka-Volterra equations](#) for modeling fox/rabbit populations, described below.

Let the following variables be defined as:

r_t : The number of prey (rabbits) at time t , where t corresponds to a certain year.

f_t : The number of predators (foxes) at time t , where t corresponds to a certain year.

α : The birth rate of prey.

β : The death rate of prey (depends on predator population).

γ : The birth rate of predators (depends on prey population).

δ : The death rate of predators.

Then, we can define the populations of the next time period or the next year ($t + 1$) using the following system of equations:

$$r_{t+1} = r_t + \alpha r_t - \beta r_t f_t,$$

$$f_{t+1} = f_t + \gamma f_t r_t - \delta f_t$$

A.4.1 Number of rabbits and foxes

Write a program that uses the following parameter values, and calculates and prints the populations of the rabbits and foxes for each year up to the next 14 years. Since the number of rabbits and foxes cannot be floating-point numbers, use the in-built python function `round()` to round-off the calculated values to integers. Also, we cannot have negative rabbits or negative foxes, so if the population values are ever negative, consider the population to be zero instead.

$$r_0 = 500$$

$$f_0 = 1$$

$$\alpha = 0.2$$

$$\beta = 0.005$$

$$\gamma = 0.001$$

$$\delta = 0.2$$

The output of the program should be as follows:

```
At time t = 0, there are 500 rabbits, and 1 foxes
At time t = 1, there are 598 rabbits, and 1 foxes
At time t = 2, there are 713 rabbits, and 2 foxes
At time t = 3, there are 849 rabbits, and 3 foxes
At time t = 4, there are 1007 rabbits, and 5 foxes
At time t = 5, there are 1186 rabbits, and 8 foxes
At time t = 6, there are 1375 rabbits, and 16 foxes
At time t = 7, there are 1538 rabbits, and 35 foxes
At time t = 8, there are 1573 rabbits, and 83 foxes
At time t = 9, there are 1237 rabbits, and 196 foxes
```

At time $t = 10$, there are 270 rabbits, and 400 foxes

At time $t = 11$, there are 0 rabbits, and 428 foxes

At time $t = 12$, there are 0 rabbits, and 342 foxes

At time $t = 13$, there are 0 rabbits, and 274 foxes

At time $t = 14$, there are 0 rabbits, and 219 foxes

(10 points)

A.4.2 How long can 100 rabbits survive?

Suppose at $t = 0$, there are 100 rabbits, i.e., $r_0 = 100$. How many foxes should be there at $t = 0$ (i.e., what should be f_0), such that the rabbit species survives (i.e., $r_{t_{max}} > 0$) for the maximum possible number of years (t_{max}) before becoming extinct (i.e., $r_{t_{max}+1} = 0$). Also, find the maximum possible number of years (i.e., t_{max}) the rabbit species will survive.

Modify the program in the previous question to compute the answers to the above questions, and print the following statement, with the blanks filled:

If there are ___ foxes at $t = 0$, the rabbit species will survive for ___ years, which is the maximum possible number of years they can survive.

Note: Use the same values of α , β , γ , and δ as in the previous question.

Hint:

1. Consider values of f_0 starting from 1, and upto a large number, say 1000.
2. For each value of f_0 , find the number of years for which the rabbit species survives.
3. Find the value of f_0 and t for which the rabbit species survives the maximum number of years, i.e., $t = t_{max}$.

(20 points)

A.4.3 Saving rabbits from extinction

What must be the minimum number of rabbits, and the corresponding number of foxes at $t = 0$, such that the rabbit and fox species never become extinct.

Note: Use the same values of α , β , γ , and δ as in the previous question.

Hint:

1. Consider $r_0 = 1$, and then keep increasing r_0 by 1 if it's not possible for the rabbit species to survive with the value of r_0 under consideration.

2. For each r_0 , consider number of foxes starting from $f_0 = 1$, and upto a large number, say $f_0 = 200$.
3. As soon as you find a combination of r_0 and f_0 , such that there is no change in r_t and f_t for 2 consecutive years, you have found the values of r_0 and f_0 , such that both the species maintain their numbers and never become extinct. At this point, print the result, and stop the program (*break out of all loops*).

Modify the program in the previous question to answer the above question, and print the following statement with the blanks filled:

For ___ foxes, and ___ rabbits at $t = 0$, the fox and rabbit species will never be extinct.

(25 points)

B Assignment B

1. You may talk to a friend, discuss the questions and potential directions for solving them. However, you need to write your own solutions and code separately, and not as a group activity.
2. Do not write your name on the assignment.
3. Write your code in the *Code* cells of the Jupyter notebook. Ensure that the solution is written neatly enough to understand and grade.
4. Use [Quarto](#) to print the *.ipynb* file as HTML. You will need to open the command prompt, navigate to the directory containing the file, and use the command: `quarto render filename.ipynb --to html`. Submit the HTML file.
5. There are 5 points for cleanliness and organization. The breakdown is as follows:
 - Must be an HTML file rendered using Quarto (1.5 pts).
 - There aren't excessively long outputs of extraneous information (e.g. no printouts of unnecessary results without good reason, there aren't long printouts of which iteration a loop is on, there aren't long sections of commented-out code, etc.) (1 pt)
 - There is no piece of unnecessary / redundant code, and no unnecessary / redundant text (1 pt)
 - The code should be commented and clearly written with intuitive variable names. For example, use variable names such as `number_input`, `factor`, `hours`, instead of `a,b,xyz`, etc. (1.5 pts)
6. The assignment is worth 100 points, and is due on **Friday, 21st April 2023 at 11:59 pm**.

B.1 Sentence analysis

B.1.1 Word count

Write a function that accepts a word, and a sentence as arguments, and returns the number of times the word occurs in the sentence.

Call the function, and print the returned value if the word is “*sea*”, and the sentence is “*She sells sea shells on the sea shore when the sea is calm.*” Note that this is just an example to check your function. Your function should work for any word and sentence.

(10 points)

B.1.2 Max word count

Ask the user to input a sentence. Use the function in B.1.1 to find the word that occurs the maximum number of times in the sentence. Print the word and its number of occurrences. If multiple words occur the maximum number of times, then you can print any one of them.

Check your program when the user inputs the sentence, “*She sells sea shells on the sea shore when the sea is calm.*”. Your program must print, “*The word with the maximum number of occurrences is ‘sea’ and it occurs 3 times.*” Note that this is just an example to check your program. Your program must work for any sentence. If multiple words occur the most, you can print any of them.

(20 points)

B.2 Prime factors

B.2.1 Prime

Write a function that checks if an integer is prime. The function must accept the integer as an argument, and return **True** if the integer is prime, otherwise it must return **False**.

Call your function with the argument as 197.

(4 points)

B.2.2 Factor

Write a function that checks if an integer is a factor of another integer. The function must accept both the integers as arguments, and return **True** if the integer is a factor, otherwise it must return **False**.

Call your function with the arguments as (19,85).

(3 points)

B.2.3 Prime Factors

Prompt the user to input a positive integer. Use the functions in B.2.1 and B.2.2 to print the prime factors of the integer. Your program should be no more than 4 lines (excluding the comments)

Check your program is the user inputs 190

(8 points)

B.3 Binary search

B.3.1 Word search

The tuple below named as `tuple_of_words` consists of words. Write a function that accepts a word, say `word_to_search` and the `tuple_of_words` as arguments, and finds if the `word_to_search` occurs in the `tuple_of_words` or not. This is very simple to do with the code `word_to_search in tuple_of_words`. However, this code is unfortunately very slow.

As the words in the `tuple_of_words` are already sorted in alphabetical order, we can search using a faster way, called binary search. To implement binary search in a function, start by comparing `word_to_search` with the middle entry in the `tuple_of_words`. If they are equal, then you are done and the function should return `True`. On the other hand, if the `word_to_search` comes before the middle entry, then search the first half of `tuple_of_words`. If it comes after the middle entry, then search the second half of `tuple_of_words`. Then repeat the process on the appropriate half of the `tuple_of_words` and continue until the word is found or there is nothing left to search, in which case the function should return `False`. The `<` and `>` operators can be used to alphabetically compare two strings.

You may write just one function or multiple functions to solve this problem.

Check your function if the `word_to_search` is: 1. 'rocket' 2. 'rest' 3. 'ambush'

(25 points)

```
tuple_of_words=('abacus', 'abdomen', 'abdominal', 'abide', 'abiding', 'ability', 'ablaze',  
               'cattishly', 'cattle', 'catty', 'catwalk', 'caucasian', 'caucus', 'causal',  
               'directly', 'directory', 'direness', 'dirtiness', 'disabled', 'disagree', 'disallow',  
               'freemason', 'freeness', 'freestyle', 'freeware', 'freeway', 'freewill', 'freezable',  
               'laurel', 'lavender', 'lavish', 'laxative', 'lazily', 'laziness', 'lazy', 'lecturer',  
               'payee', 'payer', 'paying', 'payment', 'payphone', 'payroll', 'pebble', 'pebbly', 'pec',  
               'rift', 'rigging', 'rigid', 'rigor', 'rimless', 'rimmed', 'rind', 'rink', 'rinse', 'ri',  
               'stoneware', 'stonework', 'stoning', 'stony', 'stood', 'stooge', 'stool', 'stoop', 'st
```

```
'unscented', 'unscrew', 'unsealed', 'unseated', 'unsecured', 'unseeing', 'unseemly', '
```

B.3.2 Iterations to find the word

Update the function in 3(a) to also print the number of iterations it took to find the `word_to_search` or fail in finding the `word_to_search`.

Check your function if the `word_to_search` is: 1. 'rocket' 2. 'rest' 3. 'amendable'

(10 points)

B.3.3 Index of word

Update the function in 3(b) to also print the index of `word_to_search` in `tuple_of_words` if the word is found in the tuple. For example, the index of 'abacus' is 0, the index of 'abdomen' is 1, and so on.

Check your function if the '`word_to_search`' is: 1. 'rocket' 2. 'rest' 3. 'ambush'

(10 points)

B.3.4 Maximum iterations

What is the maximum number of iterations it may take for your function to search or fail in searching the `word_to_search`. You may either write a program to answer this question, or answer it analytically.

(5 points)

C Assignment templates and Datasets

Assignment templates and datasets used in the book can be found [here](#)