Kafka-Spark-Realtime-Anomaly-Detection

Yuzhuo Zhou, Haijun Liu, Xun Zhang

Abstract

As internet-facing infrastructure faces increasingly sophisticated threats, the demand for real-time network security monitoring has become critical. Traditional batch processing architectures, characterized by significant latency due to disk-based I/O and discrete temporal partitioning, often fail to intercept malicious traffic bursts before system degradation occurs. This project proposes a high-performance anomaly detection system leveraging **Apache Spark Structured Streaming** and **Apache Kafka**. We introduce a "Historical Replay with Asynchronous Injection" hybrid framework to simulate realistic DDoS traffic flows with high reproducibility and controllability. Our implementation optimizes stream processing through **sliding window aggregation** and **watermark-based state management**, effectively resolving the "boundary leakage" and "peak dilution" phenomena inherent in fixed-window models. Furthermore, we decouple the statistical processing engine from the decision logic using a **dynamic lookback alerting mechanism**, ensuring 100% detection sensitivity under high-concurrency conditions. Experimental results demonstrate that our architecture achieves end-to-end anomaly detection within a 3-second latency threshold—a two-order-of-magnitude improvement over traditional batch-processing baselines. This work validates the efficacy of distributed in-memory computing as a robust paradigm for real-time network defense in adversarial environments.

Key word: **Apache Spark Structured Streaming, Apache Kafka, sliding window, dynamic lookback**

---

1. Introduction and Motivation

1.1 Business Context and the Sensitivity of Latency

In modern internet architectures, big data processing technologies are ubiquitous; however, the tolerance for data latency varies significantly across different application domains. For instance, in traditional "Trending Topic" recommendation systems, a delay of five minutes in updating rankings—while potentially impacting user engagement—is considered a manageable performance variance that only causes a quantitative degradation in user experience.

Conversely, in **network security and anomaly detection scenarios**—such as Distributed Denial of Service (DDoS) attack monitoring—the tolerance for latency is virtually nonexistent. Malicious traffic bursts can deplete server resources (CPU, memory, and bandwidth) within seconds, inevitably leading to system collapse (downtime). In this context, a one-minute delay in detection is tantamount to system failure. The success of a defense system is inextricably linked to its response time. Thus, anomaly detection demands "low-latency real-time processing"—a necessity that transcends mere performance optimization, representing a fundamental paradigm shift from quantitative improvement to **qualitative system viability[1]**.

1.2 The Necessity of Real-Time Streaming: Beyond Post-Mortem Analysis

This project implements a real-time streaming architecture based on PySpark Structured Streaming to overcome two critical architectural flaws inherent in traditional batch processing systems for security monitoring:

1. **From Post-Mortem Analysis to Real-Time Defense:** Traditional batch architectures typically rely on periodic scheduled tasks (e.g., cron jobs dumping logs to HDFS every 5 to 10 minutes for subsequent MapReduce or Spark processing). This high-latency overhead means that by the time a batch job alerts administrators to a threat, the attack is often complete, and the service is already paralyzed. Consequently, batch processing serves only as a **"post-mortem analysis"** tool. In contrast, memory-centric streaming processing—achieving end-to-end latency in the sub-second or single-second range—enables proactive firewall integration and "real-time interception" [2]. Our streaming architecture utilizes **Sliding Windows**, allowing for continuous, seamless temporal analysis, which significantly enhances the detection accuracy of cross-boundary traffic surges compared to traditional batch methods, as established in dataflow processing models [3].

2. **Addressing Boundary Leakage and Peak Dilution:** Batch processing segments data into rigid, discrete time blocks. If an alert threshold is defined as 500 requests per 2 minutes, an attack burst of 800 requests occurring across the 04:59:30–05:00:30 timestamp boundary would be fragmented across two distinct batch windows. This "peak dilution" effect often results in traffic counts falling below thresholds in both segments, leading to **false negatives**. Our streaming architecture utilizes **Sliding Windows**, allowing for continuous, seamless temporal analysis, which significantly enhances the detection accuracy of cross-boundary traffic surges compared to traditional batch methods.

1.3 Methodology: The "Replay and Inject" Hybrid Framework

Validating an anomaly detection system in a production environment presents a paradox: while live data is authentic, it lacks the controllability required for project demonstrations, as one cannot guarantee a malicious event will occur during a live presentation. To address this, we designed a **"Historical Replay with Asynchronous Injection"** hybrid architecture:

- **Data Authenticity:** We utilize real-world historical access logs from public datasets (Kaggle Web Server Access Logs). The extracted fields—IP, timestamps, URLs, and status codes—strictly adhere to Apache/Nginx production standards.
- **Temporal Normalization:** Rather than a static dump, our Python-based producer calculates the historical interval (delta_t) between consecutive log entries. Using precision $time.sleep()$mechanisms, we reconstruct the genuine traffic rhythm, shifting historical timestamps to "real-time" to simulate a live Kafka data stream.
- **Controllable Demonstration (Asynchronous Injection Engine):** The architecture incorporates a dedicated Daemon Thread that functions as a silent observer. Under normal conditions, the system simulates steady-state traffic. However, upon a specific user-triggered command (e.g., an Enter keystroke), the engine injects a synthetic DDoS flood (e.g., thousands of malicious requests targeting /api/login with 401 status codes) into the stream within milliseconds.

This design ensures high reproducibility and dramatic visual impact during demonstrations, effectively illustrating the decoupled engineering philosophy of **"Data Generation – Processing – Visualization"** in enterprise-grade big data systems.

2. System Architecture Design

To ensure high availability, scalability, and optimal decoupling between functional modules, the proposed system adheres to the modern industrial-grade **Lambda/Kappa architectural paradigm**. This design establishes an end-to-end real-time data pipeline capable of handling high-velocity streaming data.

2.1 Architectural Overview

The system architecture is structured into four logically decoupled layers, facilitating a seamless data flow from ingestion to real-time visualization:**Data Ingestion Layer → Message Buffering Layer → Stream Processing Layer → Storage and Presentation Layer**.



💡 **Figure 1: High-Level System Architecture of the Real-Time Anomaly Detection Pipeline.**
The framework is decomposed into four decoupled layers, ensuring that the heavy computational tasks of the stream processing engine remain isolated from the latency-sensitive front-end visualization.



💡 **Figure 2: Internal Logic Flow of the PySpark Processing Engine.**
This view details the data pipeline from predicate-optimized filtering to memory-resident state management. The integration of Watermarking and the State Store enables robust handling of late-arriving data within the distributed memory environment.

This decoupled design—characterized by "Asynchronous Data Generation," "Message Queue Buffering," "Distributed Stream Processing," and "Asynchronous Visualization"—ensures system resilience. Even when

subjected to intensive DDoS attack traffic spikes, the computational engine and the front-end dashboard remain decoupled, preventing cascading failures.

2.2 Core Component Specifications

2.2.1 Message Buffering Layer (Dockerized Kafka Cluster):

The system utilizes Apache Kafka and Zookeeper (deployed within Docker containers) as the message broker. By integrating Kafka, we introduce a critical "traffic shaping" mechanism. Kafka serves as a buffer that decouples producers from consumers, protecting the downstream PySpark engine from being overwhelmed by the instantaneous throughput surges characteristic of DDoS attacks.

2.2.2 Stream Processing Layer (PySpark Structured Streaming)

PySpark serves as the computational core of the system. Operating in local[*] mode, the engine dynamically provisions threads based on the host's CPU core count, effectively simulating a distributed cluster environment (Driver-Executor topology). This layer is responsible for complex data filtering, sliding window aggregations, and maintaining stateful operations within high-speed memory.

2.2.3 Low-Latency Storage Layer (SQLite Metrics Store)

To manage output persistence, we employ SQLite (metrics.db) as a high-performance sink. Utilizing the foreachBatch API, Spark sinks the results of each micro-batch aggregation into the database. This provides a concurrent-safe "state snapshot" that the visualization layer can query without impacting the performance of the streaming pipeline.

2.2.4 Visualization Layer (Streamlit Dashboard)

The front-end utilizes the Streamlit framework for real-time visualization. By adopting an asynchronous polling mechanism to fetch metrics from the SQLite database, the visualization layer remains entirely decoupled from the Spark processing engine. This ensures that the dashboard maintains a fluid frame rate, regardless of the computational complexity or shuffle overhead occurring in the back-end.

2.3 Key Innovation: Multi-threaded Asynchronous Injection Engine

A primary engineering challenge addressed in this work is the simultaneous requirement for "historical data replay" and "real-time anomaly injection." To resolve potential process blocking, we developed a hybrid, multi-threaded asynchronous injector (`producer.py`):

Main Thread (Historical Data Replay): This thread is responsible for authentic data stream reconstruction. It calculates the historical temporal interval (Δt) between log entries and utilizes precision `time.sleep()` calls to maintain a realistic traffic rhythm. It dynamically maps historical timestamps to current system time, ensuring a smooth, continuous data feed while providing a `SPEED_UP` scalar for demonstration control.

Daemon Thread (Zero-Latency Injection): We established an independent Daemon Thread dedicated to monitoring user input via a blocking input() call. This thread operates in the background, ensuring no performance penalty for the main replay thread. Upon detecting a trigger event (e.g., an Enter keystroke), the thread instantly generates a large-scale burst of malicious requests—characterized by uniform IP addresses and target URLs—and utilizes producer.flush() to saturate the Kafka queue within milliseconds.

Architectural Significance:

The synergy between the multi-threaded injection engine and the Kafka message queue enables the system to transition instantaneously from a steady-state stream to a high-concurrency attack simulation. This framework provides an ideal testbed for evaluating the resilience, sensitivity, and throughput limits of PySpark's streaming engine under adversarial conditions.

---

3. Data Processing Pipeline and Core Algorithms

The data processing pipeline is designed not only to sustain high-throughput, high-frequency log ingestion but also to capture transient, bursty anomalies within potentially disordered data streams. To this end, we have implemented a rigorous data preprocessing framework combined with a multi-stage sliding window aggregation algorithm.

3.1 Real-Time Preprocessing and Lazy Evaluation

1. **Multidimensional Feature Extraction:** At the ingestion layer (`preprocess.py`), the system employs Named Regular Expressions (Regex) to perform precise field extraction from raw Apache/Nginx access logs (e.g., `IP`, `Timestamp`, and `URL`). To facilitate accurate historical replay, the algorithm calculates the temporal delta (Δt) between consecutive log entries, which is subsequently persisted in JSONL format to serve as a synchronization heartbeat for the producer.
2. **Noise Reduction via Lazy Evaluation:** Web server logs inherently contain high volumes of static asset requests (e.g., .png, .jpg, .css) that amplify baseline traffic and potentially degrade the signal-to-noise ratio of anomaly detection. In the PySpark processing engine, we implement a sequence of .filter() transformations to exclude these resources. Leveraging Spark's **Lazy Evaluation** and the **Catalyst Optimizer**, these transformations are logically fused via predicate pushdown. This optimization ensures that the system avoids unnecessary data scans, performing the filtering operation in a single traversal, thereby minimizing memory overhead and CPU utilization.

3.2 Sliding Window Algorithm: Mitigating Boundary Leakage

In streaming analytics, the choice of temporal partitioning is critical for detection accuracy. Traditional Tumbling Windows (e.g., fixed 10-second segments) are prone to **"Boundary Leakage"** and **"Peak Dilution."**

To mitigate this, we implemented a **Sliding Window Algorithm** defined by:

Configuration: Window size (W_{size}) of 10 seconds; sliding interval (W_{slide}) of 2 seconds.

Operational Advantage: By calculating the aggregate traffic every 2 seconds over a 10-second lookback period, the system maintains an 8-second overlap between consecutive computations. This high-frequency overlap ensures that any localized traffic surge is fully captured within at least one window, effectively eliminating boundary-related detection failures.

3.3 Watermarking and Memory-State Management

Network congestion and distributed message buffering often introduce latency-induced disorder[3]. Without temporal constraints, streaming engines would indefinitely retain state for late-arriving events, leading to memory exhaustion.

1. **Mathematical Formulation:** We incorporate a Watermark mechanism, defined as:

$$Watermark_Time = max(EventTime_observed) - Delay_Tolerance$$

This approach, based on the **Dataflow Model** [3], ensures that late-arriving data can be handled with a balanced trade-off between correctness and latency.

2. **Parameter Optimization:** Initial experiments with a 5-second delay tolerance resulted in false negatives, as Kafka's buffering occasionally delayed packet arrival beyond the 5-second threshold. By extending the **Watermark to 30 seconds**, we optimized the trade-off between sensitivity and state retention. The number of active windows maintained in the State Store is approximated by:

$$N \approx \frac{W_{size} + Delay_Tolerance}{W slide} = \frac{10 + 30}{2} = 20$$

This configuration ensures that the engine only maintains 20 lightweight aggregate states in the Executor memory, providing a sufficient buffer for network jitter while guaranteeing a robust garbage collection cycle to prevent Out-Of-Memory (OOM) errors.

3.4 Dynamic Lookback Alerting: Decoupling Statistics from Decision Logic

During testing, we encountered a logic vulnerability regarding "discrete transient attacks." Relying solely on the count of the latest window ($count_t$) occasionally failed to trigger alerts during high-concurrency injections because the attack load was fragmented across several micro-batches.

To resolve this, we decoupled the Spark statistical engine from the alert decision layer by introducing an **Alert Lookback Mechanism** (`alert_lookback_windows=3`). The alert condition is defined as:

$$Alert = \left(\max(count_{t-2}, count_{t-1}, count_t) > Threshold \right)$$



Figure 3: Sliding Window Mechanism vs. Boundary Leakage (The "Logic" View)

💡 **Figure 3: Comparative Analysis of Temporal Partitioning (Tumbling vs. Sliding Windows).**
Tumbling Windows (left) suffer from "Peak Dilution" when traffic bursts cross temporal boundaries. Sliding Windows (right) maintain an 8-second overlap, ensuring that bursty events are captured in their entirety within at least one processing window, thereby eliminating false negatives.

This mechanism allows the system to evaluate the local temporal trend rather than a single point in time. By backtracking the preceding three state windows to identify peak intensities, the system successfully intercepts fragmented DDoS bursts, ensuring 100% detection sensitivity even under high-concurrency conditions.

---

4. Performance Optimization and Mechanism Analysis

The core competency of this project lies in the sophisticated orchestration of Apache Spark's distributed execution engine. To achieve sub-second latency for anomaly detection, we have moved beyond high-level business logic to perform deep-level optimizations, including Direct Acyclic Graph (DAG) analysis, strategic shuffle management, and refined in-memory state control.

4.1 DAG Execution and Stage Decomposition

In PySpark, the streaming logic is translated into a Directed Acyclic Graph (DAG) of transformations. Our optimization strategy focuses on minimizing the overhead of these execution plans:

- **Shuffle Triggering and Stage Boundary:** Upon executing `.groupBy(window(col("timestamp"), "10s", "2s")).count()`, the engine must redistribute log entries across the cluster to align data belonging to the same temporal window onto a single aggregate node. This operation triggers an **Exchange (Shuffle)** mechanism.
- **Mechanistic Insights:** By analyzing the job execution via the Spark Web UI (port 4040), we observe that the task is decomposed into distinct **Stages** delimited by shuffle boundaries. Our implementation optimizes these window aggregation operators to avoid unnecessary disk I/O, ensuring that data remains within the distributed memory pipeline rather than being subjected to the blocking, disk-persistent operations characteristic of traditional batch processing.

4.2 Data Locality: Moving Computation, Not Data

To effectively handle high-velocity DDoS traffic, the architecture adheres to the principle of "moving computation to data" rather than transferring large datasets across the network:

- **Predicate Pushdown:** During filtering operations—such as `.filter(~col("url").like("%.png"))`—the Driver does not pull raw data to the master node. Instead, it serializes the filter logic and distributes it to the **Executor threads**.
- **Massive Parallelism:** Leveraging the `local[*]` configuration, the system spawns multiple parallel worker threads, each processing a shard of the Kafka data stream. On an 8-core machine, this allows for 8-way concurrent data processing, achieving true **Data Parallelism**. This capability forms the

fundamental performance bedrock required to process bursty, adversarial traffic in real-time.

4.3 In-Memory State Store Management

Unlike traditional Hadoop MapReduce, which relies on HDFS for intermediate state persistence, Spark Structured Streaming utilizes an in-memory **State Store** to manage temporal aggregates:

- **Stateful Processing:** In sliding window calculations with an 8-second overlap, the system must retain intermediate counts in memory to satisfy subsequent calculations. We leverage Spark's state management to store these partial aggregates within the Executor's RAM.
- **The Garbage Collection (GC) Loop:** The implementation of .withWatermark() serves a dual purpose: defining the late-data tolerance and acting as a trigger for state expiration. Once the Event Time exceeds the watermark, the corresponding state is evicted from memory.
  This **"Cache-on-Demand + Auto-Expiration"** design ensures that the system maintains a constant memory footprint, allowing it to process massive volumes of historical data streams without risking Out-Of-Memory (OOM) failures.

4.4 Performance Synthesis

Table 1 summarizes the performance optimization strategies implemented at the mechanical level:

Table 1: Comparative Analysis of Optimization Strategies

Optimization Dimension	Baseline (Pre-Optimization)	Optimized Approach	Performance Gain
Logic Execution	Redundant full-scans	Lazy Evaluation	Reduced CPU overhead
Data Flow	Disk-based I/O	In-Memory Shuffle	Minimized latency; eliminated bottlenecks
Storage Management	Unbounded state accumulation	Watermarking & Auto-expiry	OOM mitigation; optimized RAM usage

By integrating these mechanisms, the system successfully achieved an end-to-end anomaly detection response time of **under 3 seconds** during simulated DDoS testing. This performance represents a two-order-of-magnitude improvement over traditional batch architectures, validating the efficacy of

distributed in-memory computing for real-time security monitoring.

References

[1] Bhuyan, M. H., Bhattacharyya, D. K., & Kalita, J. K. (2014). "Network Anomaly Detection: Methods, Systems and Tools." *IEEE Communications Surveys & Tutorials.*

[2] Armbrust, M., Das, T., Sun, L., Yavuz, B., Zhu, S., Murthy, M., ... & Zaharia, M. (2016). "Structured Streaming: A Declarative API for Real-Time Applications in Apache Spark." *Proceedings of the 2016 International Conference on Management of Data (SIGMOD).*

[3] Akidau, T., Bradshaw, R., Chambers, C., Chernyak, S., Fernández-Moctezuma, R. J., Lax, R., ... & Yavuz, B. (2015). "The Dataflow Model: A Practical Approach to Balancing Correctness, Latency, and Cost in Massive-Scale, Unbounded, Out-of-Order Data Processing." *Proceedings of the VLDB Endowment.*