
Ljunggren Audio – Roll Your Own Bills of material AMPMIX 1.3

COMPONENTS



TYPE	PART	VALUE	PCS	NOTE
Resistor	R3	10K	1	Ca 3.5mm long resistor
Resistor	R13, R14, R15, R16	330R	4	Ca 3.5mm long resistor
Resistor	R5, R6, R7, R8, R9, R10, R11, R12, R17, R18, R19, R20, R21, R22, R23, R24, R25, R26, R27, R28, R29, R30, R31	22K, 1%	23	1% tolerance. Ca 3.5mm long resistor
Resistor	R1, R2	10R	2	Ca 7mm long resistor
Diode	D1, D2	SB130	2	Or 1N5818. Power polarity protection.
Capacitor	C9, C10, C11, C16	68pF	4	Ceramic 2.5mm
Capacitor	C1, C2, C7, C8, C12, C13, C14, C15	100nF	8	Ceramic X7R 2.5mm
IC Socket	IC1	8 pin	1	
Opamp	IC1	TL072	1	Or TL082
IC Socket	IC2, IC3	14 pin	2	
Opamp	IC2, IC3	TL084	2	Or TL074
Electrolytic	C3, C4, C6	10uF	3	2mm pin pitch, 5mm dia, 5mm height
Volt ref.	D3	LM4040 2.5V	1	
Power header	POWER	10 pin	1	boxed and keyed euro power header
Jack	IN1, IN2, IN3, IN4, OUT1, OUT2, OUT3, OUT4	3.5mm	8	PJ301BM
Potentiometer	POT1, POT2, POT3, POT4	22K linear	4	Or 25K. Snap in 9mm metal shaft.

OTHER

TYPE	PART	VALUE	PCS_	NOTE
Faceplate		8hp	1	PCB material (FR4), black, 2mm
PCB			1	
Power cable		IDC	1	16pin – 10pin
Mounting screws			2	M3x6 black pozi