Power header Socket strip 1x8 Pin strip 1x8 Socket strip 1x1 Pin strip 1x1 Resistor 249 Resistor 22k Resistor 10k Resistor 10k Resistor 430 MLCC / disc 15p MLCC / disc 4.7r MLCC 100 Electrolytic 10u Electrolytic 10u Diode 1N4 Diode 1N5 IC Socket DIP CD4xxx 401 Comparator LM3 IC Socket DIP CD4xxx 451	x8pin x10pin x10pin x49R .3k .3k .2k .0k .00k .0R .30R .5pF .7nF .00nF .0uF .0uF .0uF .0uF .0uF .0uF .0uF	1 3 3 1 1 1 5 7 7 8 8 10 19 2 2 8 1 2 2 1 1 12	All parts POWER CON1-PCB1, CON2-PCB1, CON3-PCB1 CON3-PCB1 CON1-PCB2, CON2-PCB2, CON4-PCB3 CON4-PCB3 CON4-PCB2 R3, R4, R5, R6, R32 R29, R30, R31, R37, R38, R39, R40 R11, R12, R13, R14, R19, R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41 R42 R43 R47 R52 R13, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	Description Euro power connector. 8 pin female connector. 0.1in/2.54mm 8 pin male connector. 0.1in/2.54mm 10 pin female connector. 0.1in/2.54mm 10 pin male connector. 0.1in/2.54mm Ca 3.5mm long body / LED resistors Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 7mm long body Ca 7mm long body Ca 7mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V 2.5mm pin pitch, 6.3mm dia, max 9mm height,	PCB1 qty 3 5 7 5 4	PCB1 parts CON1-PCB1, CON2-PCB1, CON3-PCB1 R3, R4, R5, R6, R32 R11, R12, R13, R14, R53, R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56 C7, C8, C9, C10, C22, C25		PCB2 parts POWER CON1-PCB2, CON2-PCB2, CON3-PCB2 CON4-PCB2 R21, R22 R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14, C15, C16, C23, C24, C26	PCB3 qty 1 1 7 1 1 2 5	PCB3 parts CON4-PCB3 R29, R30, R31, R37, R38, R39, R40 R19 R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27 C12, C17, C18, C19, C20
Neader	x8pin x8pin x10pin x10pin x49R .3sk .2k .0k .0ok .0R .30R .5pF .7nF .00nF .0uF .0uF .0uF .0uF .0uF .0uF .0uF .0u	3 1 1 5 7 8 10 19 2 8 1 2 21 1	CON1-PCB1, CON2-PCB1, CON3-PCB1 CON3-PCB2, CON2-PCB2, CON3-PCB2 CON4-PCB3 CON4-PCB2 R3, R4, R5, R6, R32 R29, R30, R31, R37, R38, R39, R40 R11, R12, R13, R14, R19, R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41, R42 R43, R47, R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C22, C23, C24, C25, C26 C3, C4	8 pin female connector. 0.1in/2.54mm 8 pin male connector. 0.1in/2.54mm 10 pin female connector. 0.1in/2.54mm 10 pin male connector. 0.1in/2.54mm Ca 3.5mm long body / LED resistors Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 7mm long body Ca 7mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch	7 5 4	PCB1, CON3-PCB1 R3, R4, R5, R6, R32 R11, R12, R13, R14, R53, R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56	2 4 2 8 1 10	CON1-PCB2, CON2- PCB2, CON3-PCB2 CON4-PCB2 R21, R22 R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14,	1 3 11 2 2	R29, R30, R31, R37, R38, R39, R40 R19 R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27
Name	x8pin x10pin x10pin x10pin x10pin x49R3k2k	3 1 1 5 7 8 10 19 2 8 1 2 21 1	CON3-PCB1 CON1-PCB2, CON2-PCB2, CON3-PCB2 CON4-PCB3 CON4-PCB3 CON4-PCB2 R3, R4, R5, R6, R32 R29, R30, R31, R37, R38, R39, R40 R11, R12, R13, R14, R19, R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41, R42 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	8 pin male connector. 0.1in/2.54mm 10 pin female connector. 0.1in/2.54mm 10 pin male connector. 0.1in/2.54mm Ca 3.5mm long body / LED resistors Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 7mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch	7 5 4	PCB1, CON3-PCB1 R3, R4, R5, R6, R32 R11, R12, R13, R14, R53, R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56	2 4 2 8 1 1 10	PCB2, CON3-PCB2 CON4-PCB2 R21, R22 R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14,	1 3 11 2 2	R29, R30, R31, R37, R38, R39, R40 R19 R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27
Socket strip	x10pin x10pin x10pin 149R .33k .22k .00k .00k .0R .30R .5pF .7nF .00nF	1 1 1 5 7 8 10 19 2 8 1 2 2 1	CON3-PCB2 CON4-PCB3 CON4-PCB3 R3, R4, R5, R6, R32 R29, R30, R31, R37, R38, R39, R40 R11, R12, R13, R14, R19, R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41 R42 R43 R47 R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C16, C19, C20, C22, C23, C24, C25, C26 C3, C4 C5	10 pin female connector. 0.1in/2.54mm 10 pin male connector. 0.1in/2.54mm Ca 3.5mm long body / LED resistors Ca 3.5mm long body Ca 7mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch	7 5 4	R11, R12, R13, R14, R53, R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56	2 4 2 8 1 1 10	PCB2, CON3-PCB2 CON4-PCB2 R21, R22 R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14,	1 3 11 2 2	R29, R30, R31, R37, R38, R39, R40 R19 R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27
Pin strip	x10pin 49R .3k .3k 0k 00k 00R 30R 5pF .7nF 00nF	7 8 10 19 2 8 1 2 21 2 1	CON4-PCB2 R3, R4, R5, R6, R32 R29, R30, R31, R37, R38, R39, R40 R11, R12, R13, R14, R19, R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41 R42 R43 R47 R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4 C5	10 pin male connector. 0.1in/2.54mm Ca 3.5mm long body / LED resistors Ca 3.5mm long body Ca 7mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch	7 5 4	R11, R12, R13, R14, R53, R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56	2 8 1	R21, R22 R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11	1 3 11 2 2	R29, R30, R31, R37, R38, R39, R40 R19 R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27
Resistor 249 Resistor 3.34 Resistor 10k Resistor 10k Resistor 100 Resistor 430 Resistor 430 MLCC / disc 15p MLCC / disc 4.7r MLCC / disc 100 Electrolytic 10u Electrolytic 10u Diode 1N4 Diode 1N5 IC Socket DIP CD4xxx 401 CD4xxx 401 COmparator LM3 IC Socket DIP CD4xxx 451	00k 00k 00R 30R 5pF .7nF 00nF 00uF N4148	7 8 10 19 2 8 1 2 21 2 1	R3, R4, R5, R6, R32 R29, R30, R31, R37, R38, R39, R40 R11, R12, R13, R14, R19, R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41 R42 R43 R47 R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	Ca 3.5mm long body / LED resistors Ca 3.5mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V	7 5 4	R11, R12, R13, R14, R53, R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56	2 8 1	R21, R22 R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11	1 3 11 2 2	R39, R40 R19 R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27
Resistor 3.3 Resistor 22k Resistor 10k Resistor 10k Resistor 10k Resistor 10k Resistor 430 MLCC / disc 15p MLCC / disc 4.7r MLCC 100 Electrolytic 10u Electrolytic 10u Electrolytic 10u Diode 1N4 Diode 1N5 IC Socket DIP CD4xxx 401 COmparator LM3 IC Socket DIP CD4xxx 451 CD4	.3k .2k .0k .00k .00R .30R .5pF .7nF .00nF .00uF .00uF .00uF .00uF .00uF .00uF	7 8 10 19 2 8 1 2 21 2 1	R29, R30, R31, R37, R38, R39, R40 R11, R12, R13, R14, R19, R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41, R42, R43, R47, R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26	Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch	7 5 4	R11, R12, R13, R14, R53, R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56	2 8 1	R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14,	1 3 11 2 2	R39, R40 R19 R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27
Resistor 22k	0k 00k 00R 30R 5pF .7nF 00nF 00uF N4148	10 19 2 8 1 2 21 2 1	R39, R40 R11, R12, R13, R14, R19, R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41, R42 R43 R47 R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C22, C23, C24, C25, C26 C3, C4 C5	Ca 3.5mm long body Ca 3.5mm long body Ca 3.5mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch	5	R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56	2 8 1	R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14,	1 3 11 2 2	R39, R40 R19 R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27
Resistor	0k 0R 30R 5pF .7nF 00nF 0uF 00uF N4148	10 19 2 8 1 2 21 2 1	R53, R57, R58 R15, R16, R17, R18, R21, R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41 R42 R43 R47 R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C22, C23, C24, C25, C26 C3, C4 C5	Ca 3.5mm long body Ca 3.5mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V	5	R57, R58 R15, R16, R17, R18, R54 R7, R10, R55, R56	2 8 1	R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14,	11	R44, R45, R46 R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59 C21, C27
Resistor	00k 0R 30R 5pF .7nF 00nF 00uF N4148	19 2 8 1 2 21 2 1	R22, R44, R45, R46, R54 R7, R8, R9, R10, R20, R23, R24, R25, R26, R27, R28, R41 R42 R43 R47 R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	Ca 3.5mm long body Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V	4	R7, R10, R55, R56	2 8 1	R23, R24, R25, R26 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14,	11	R8, R9, R20, R27, R28, R41, R42, R43, R47, R52, R59
Resistor	0R 30R 5pF .7nF 00nF 0uF 0uF N4148	2 8 1 2 21 2 1	R24, R25, R26, R27, R28, R41 R42 R43 R47 R52 R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	Ca 7mm long body. Min 0.25W Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V			2 8 1	R1, R2 R33, R34, R35, R36, R48, R49, R50, R51 C11	2	R41, R42, R43, R47, R52, R59
Marcol M	30R 5pF .7nF 00nF 0uF 00uF N4148	2 21 1 12	R33, R34, R35, R36, R48, R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	Ca 7mm long body. Min 0.35W. 410-470R 2.5-2.54mm pin pitch 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V	6	C7, C8, C9, C10, C22, C25	1 10	R33, R34, R35, R36, R48, R49, R50, R51 C11 C1, C2, C6, C13, C14,		+ '
MLCC / disc	5pF .7nF 00nF 0uF 0uF N4148	1 2 21 2 1	R49, R50, R51 C11 C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	2.5-2.54mm pin pitch 2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V	6	C7, C8, C9, C10, C22, C25	10	R49, R50, R51 C11 C1, C2, C6, C13, C14,		+ '
MLCC / disc 4.77 MLCC 100 Electrolytic 100 Electrolytic 100 Diode 1N4 Diode 1N5 IC Socket DIP CD4xxx 408 CD4xxx 401 OpAmp TL0 Comparator LM3 IC Socket DIP CD4xxx 451	00nF 00uF 00uF N4148 N5818	2 1 1 12	C21, C27 C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	2.5-2.54mm pin pitch X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V	6	C7, C8, C9, C10, C22, C25	10	C1, C2, C6, C13, C14,		+ '
Electrolytic 10u Electrolytic 10u Diode 1N4 Diode 1N5 IC Socket DIP CD4xxx 401 OpAmp TL0 Comparator LM3 IC Socket DIP CD5xxx 401 CD6xxx 401	00nF 0uF 00uF N4148 N5818	2 1 1 12	C1, C2, C6, C7, C8, C9, C10, C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4 C5	X7R 2.5-2.54mm pin pitch 2.5mm pin pitch, 5mm dia, max 9mm height, min 25V	6	C7, C8, C9, C10, C22, C25				+ '
Electrolytic 10u Electrolytic 100 Diode 1N4 Diode 1N5 IC Socket DIP CD4xxx 401 OpAmp TL0 Comparator LM3 IC Socket DIP CD4xxx 451	0uF 00uF N4148 N5818	1 12	C12, C13, C14, C15, C16, C17, C18, C19, C20, C22, C23, C24, C25, C26 C3, C4	2.5mm pin pitch, 5mm dia, max 9mm height, min 25V	6	C7, C8, C9, C10, C22, C25			5	C12, C17, C18, C19, C20
Electrolytic 100 Diode 1N4 Diode 1N5 IC Socket DIP CD4xxx 408 CD4xxx 401 OpAmp TL0 Comparator LM3 IC Socket DIP CD4xxx 451	00uF N4148 N5818	1	C5	min 25V						1
Diode 1N4 Diode 1N5 IC Socket DIP CD4xxx 408 CD4xxx 401 OpAmp TL0 Comparator LM3 IC Socket DIP CD4xxx 451	N4148 N5818			2.5mm pin pitch, 6.3mm dia max 9mm height			2	C3, C4		
Diode 1N5 IC Socket DIP CD4xxx 408 CD4xxx 401 OpAmp TL0 Comparator LM3 IC Socket DIP CD4xxx 451	N5818			min 16V			1	C5		
IC Socket DIP		-	D3, D4, D5, D6, D7, D8, D9, D10, D11, D12, D13, D14		6	D3, D4, D5, D6, D7, D8	2	D9, D10	4	D11, D12, D13, D14
CD4xxx	ND44	2	D1, D2	1N5817-1N5819			2	D1, D2		
CD4xxx 401 OpAmp TL0 Comparator LM3 IC Socket DIP CD4xxx 451	л г 14	5	IC1, IC2, IC3, IC4, IC8		2	IC1, IC2	1	IC3	2	IC4, IC8
OpAmp TL0 Comparator LM3 IC Socket DIP CD4xxx 451	081N	1	IC1	DIP14	1	IC1				
Comparator LM3 IC Socket DIP CD4xxx 451	0106N	2	IC2, IC3	DIP14	1	IC2	1	IC3		
IC Socket DIP CD4xxx 451	L084	1	IC4	DIP14, alt: TL074					1	IC4
CD4xxx 451	.M339	1	IC8	DIP14			ļ		1	IC8
OB-AAA		5	IC5, IC6, IC7, IC9, IC10				4	IC5, IC6, IC7, IC9	1	IC10
Switch IC I DG.		1	IC5	DIP16			1	IC5		<u> </u>
		2	IC6, IC7	DIP16			2	IC6, IC7		
52 1300X	052N 043N	1	IC9	DIP16			1	IC9	_	IC10
	.5mm	12	FWD, HLD, I/O1, I/O2, I/O3, I/O4, O/I1, O/I2, O/I3, O/I4, RES, REV	DIP16 PJ301M-12 / Thonkiconn / Inline	12	FWD, HLD, I/O1, I/O2, I/O3, I/O4, O/I1, O/I2, O/I3, O/I4, RES, REV			1	1010
Transister F"	JN3303R	3	Q1, Q2, Q3		3	Q1, Q2, Q3	 		+	+
			RG1		۲	w:, wz, wo	1	RG1	\vdash	+
Toggle SPE	SPDT on/off/on	1	SW2		1	SW2		iko:		
Toggle SPE	SPDT on/on	1	SW1		1	SW1				
	SPST off/(on)	2	SW3, SW6	C&K D6R 00/white	2	SW3, SW6				
	SPST off/(on)	2	SW4, SW5	C&K D6R 40/red	2	SW4, SW5				
Switch LED gree	reen	2	L1, L4	3mm	2	L1, L4	\vdash		 	+
		6	L2, L3, L5, L6, L7, L8	3mm	6	L2, L3, L5, L6, L7, L8	 		-	<u> </u>
	0pin – 16pin	1	,,,,,,		Ĺ	,,,,,,,,				
		2								
PCB		3	PCB1, PCB2, PCB3			†	<u> </u>		<u> </u>	1
	CB material	1	,,							
	1mm	2				†	†	1	†	1
000000		2								1
screws for	or spacers	2		1	1		T .		1	