

BREAK INTO AEROSPACE

5cm0.6pt

In-Space Propulsion Engineering

Subdomain Interview Preparation Guide

Targeted for the 2025–2026 Recruitment Cycle

What This Document Covers: In-space propulsion engineering covers every system that moves, points, or controls a spacecraft once it has left the launch vehicle. It is a discipline that spans chemical monopropellant and bipropellant thrusters operating at millinewtons of thrust for attitude control, to electric propulsion systems delivering micronewtons of thrust over months-long primary orbit-raising missions, to cold gas systems providing the precise impulsive control authority needed to separate two spacecraft by a controlled fraction of a metre per second during rendezvous operations. The engineering challenges across this range are profoundly different — the bipropellant apogee engine designer works in combustion thermodynamics and pressure-fed feed system hydraulics; the Hall thruster engineer works in plasma physics and electromagnetic field design; the cold gas system engineer works in compressed gas thermodynamics and precision valve actuation — but they share a common mission: every gram of propellant is precious, every watt consumed is subtracted from the payload, and the system must function correctly at the first ignition command after years of storage in the thermal and radiation environment of deep space, with no opportunity for repair.

The field is experiencing its most significant structural expansion since the 1990s. The proliferation of commercial satellite constellations — Starlink, Kuiper, OneWeb, and their successors — has created demand for high-volume, cost-reduced electric propulsion systems in the 200–500W range that must be manufacturable at rates of hundreds per month rather than the handful per year that characterised heritage GEO satellite propulsion. The new-space spacecraft manufacturing model — SpaceX Starship upper stages, Rocket Lab Photon, Exoplanet Engineering, Isar Aerospace upper stages — requires propulsion systems designed for the manufacturing cadence of a product company rather than the heritage pace of a government programme. And the deep space mission portfolio at NASA, ESA, and JAXA is increasingly electric — the DART mission used a NEXT-C ion engine for orbit maintenance, Europa Clipper carries a NEXT-C for trajectory correction, and ESA's JUICE mission uses the RIT-2X ion thruster. Engineers who understand the physics and engineering of in-space propulsion across both electric and chemical modalities are in persistent demand across all of these simultaneously.

The employer landscape spans heritage propulsion suppliers (Aerojet Rocketdyne — now L3Harris Propulsion, Moog, Bradford ECAPS, Nammo, Safran Spacecraft Propulsion, ArianeGroup), dedicated electric propulsion companies (Busek, Exoplanet Engineering, Phase Four, Accion Systems, ThrusterCo, Apollo Fusion now part of Aerojet, Sitael, ThrustMe, Enpulsion), spacecraft prime contractors with propulsion responsibility (Airbus DS propulsion systems, Thales Alenia Space, Maxar, ISRO LPSC, JAXA ISAS), government research facilities (NASA Glenn Research Center, NASA JPL, ESA ESTEC, DLR Stuttgart, ONERA DPHY), and a growing set of university research groups with strong electric propulsion research programmes (Georgia Tech, Michigan, Stanford, Southampton, Delft, Tohoku). The technical vocabulary is shared; the application context, technology maturity level, and interview culture differ substantially between a heritage government supplier building flight-qualified chemical thrusters and a new-space EP startup trying to reduce unit cost by an order of magnitude.

PART I: WHAT IN-SPACE PROPULSION ACTUALLY LOOKS FOR

By Level

Intern / Graduate

At entry level, in-space propulsion employers are not screening for thruster-specific knowledge — they are screening for the physical intuition that makes someone able to learn propulsion engineering quickly: thermodynamics at the level of the Rocket Equation and the specific impulse definition (what it measures and why it matters), plasma physics at the level of charge-to-mass ratio and the $E \times B$ drift that governs Hall thruster operation, and the ability to reason quantitatively about the constraints that make in-space propulsion fundamentally different from launch propulsion (mass, volume, and power are all precious and compete with the payload).

The question that most reliably distinguishes strong from weak graduates is not “what is specific impulse?” but “a 100 kg satellite needs to raise its orbit by 2,000 m/s of Δv — compare the propellant mass required for three specific impulse levels: 220s (monopropellant hydrazine), 320s (bipropellant MMH/NTO), and 1,600s (Hall thruster). What does the result tell you about why electric propulsion is used for orbit-raising on large GEO satellites despite its much lower thrust level?” The candidate who can apply the Tsiolkovsky equation, produce numbers in the right order of magnitude, reason about the impact on satellite dry mass fraction, and then explain why the long mission time of electric propulsion becomes acceptable in exchange for the mass savings is demonstrating the quantitative systems-level reasoning that in-space propulsion requires.

Graduate interviews at heritage propulsion suppliers and government facilities typically include a technical screen covering thermodynamics (isentropic expansion in a nozzle, specific impulse, thrust coefficient), plasma physics basics (Debye length, Bohm criterion, magnetic field configurations), and basic spacecraft propulsion system design (feed system pressure regulation, propellant management). At new-space EP startups, the interview is typically more direct — a hardware problem to solve, a simulation to run, or a dataset to interpret — because the pace of development does not permit lengthy technical theory discussion.

What distinguishes graduate candidates is evidence of genuine propulsion hardware engagement: a thesis involving a thruster or feed system test, participation in a university CubeSat project where the propulsion system was a real engineering responsibility, a personal project involving a cold gas or monopropellant thruster built and tested, or significant engagement with the published literature from AIAA Joint Propulsion Conference or the International Electric Propulsion Conference (IEPC). The AIAA EP technical committee publishes openly accessible papers from every IEPC; reading five recent papers on the specific propulsion technology the employer develops is specific preparation that most candidates do not do.

Mid-Level (Engineer, Senior Engineer, ~3–8 years)

At mid-level, propulsion interviews become technology-specific and problem-oriented. The interviewer is assessing whether you can diagnose a thruster anomaly from telemetry data, design a feed system that meets the required inlet pressure range across the full propellant load range, identify the dominant life-limiting failure mode for a specific thruster technology, or assess whether a proposed propellant loading is within the safe operating envelope for the propellant combination.

Technical interviews at chemical propulsion suppliers probe the feed system architecture — the difference between pressure-regulated and blowdown operation, how the feed system pressure affects specific impulse and thrust, what the waterhammer risk is from a fast valve actuation, and what the materials compatibility requirements are for the propellant combination being used. Electric propulsion interviews probe thruster plasma physics — what the Hall parameter is and why it matters for electron confinement in a Hall thruster, what the double-grid spacing in an ion engine determines, what the sputtering mechanism responsible for thruster erosion is and what it implies for useful life — and the power processing unit design, which is the power electronics system that conditions spacecraft bus power for the thruster’s specific voltage and current requirements.

Senior (Principal Engineer, Technical Lead, Chief Engineer)

At senior level, in-space propulsion interviews assess the ability to make system architecture decisions — selecting the right propulsion technology for a mission, designing the propellant management system for a complex multi-mode operation, managing the interfaces between the propulsion system and the spacecraft structure, thermal control, and power system — and to own the qualification and flight demonstration of a propulsion system that has not flown before. The distinguishing credential is having taken a propulsion system through environmental qualification and flight — having seen what the acoustic and vibration environment of launch does to a thruster that has only ever operated in the thermal and vacuum environment of ground test, and having understood the surprises.

Hands-On Experience and Domain Knowledge Treated as Strong Signals

- The Tsiolkovsky Rocket Equation and its derivatives** — mass fraction, Δv , and the specific impulse trade. The Tsiolkovsky equation ($\Delta v = I_{sp} \times g_0 \times \ln(m_0/m_f)$) is the foundational equation of all in-space propulsion. Every propulsion system selection decision begins here: given the mission Δv budget, what propellant mass is required at each specific impulse level, and what does this imply for the spacecraft mass budget? Engineers who can apply this equation fluently — who can compute the propellant mass fraction for a range of I_{sp} values and a specified Δv , reason about why high I_{sp} is more valuable for high- Δv missions than for low- Δv missions, and explain what the practical limits on I_{sp} are for each propulsion technology (thermodynamic limits for chemical propulsion, power-to-thrust ratio limits for electric propulsion) — are demonstrating the quantitative propulsion systems thinking that every in-space propulsion employer requires from their first day.
- Electric propulsion fundamentals** — the I_{sp} advantage, the thrust-power relationship, and the mission time trade-off. Electric propulsion decouples the energy source (electric power from solar panels or a nuclear reactor) from the propellant. This allows specific impulses of 1,000–10,000s, compared to the 150–460s achievable with chemical propulsion, dramatically reducing the propellant mass for high- Δv missions. The constraint is thrust: the thrust of an electric thruster is $T = 2\eta P / (I_{sp} \times g_0)$, where η is the thruster efficiency and P is the input power. At practical spacecraft power levels (100W to 5kW for commercial satellites, up to 40kW for deep space missions), this produces thrusts of millinewtons to a few hundred millinewtons — compared to the tens to thousands of newtons from chemical thrusters. The consequence: orbit raising with electric propulsion takes months to years rather than hours. Understanding this trade — why electric propulsion is economically and technically optimal for missions with high Δv requirements and low time constraints, and why chemical propulsion is optimal for impulsive manoeuvres where time matters — is the propulsion technology selection literacy that every mission design and propulsion systems role requires.
- Hall effect thruster operating principles** — electron confinement, the $E \times B$ drift, and the ionisation process. The Hall thruster is the dominant electric propulsion technology for commercial GEO and LEO constellation satellites. Its operation depends on three key physical processes: the application of a radial magnetic field perpendicular to the axial electric field to trap electrons in an azimuthal $E \times B$ drift (the Hall current) while allowing ions to be accelerated out of the thruster by the axial electric field; the ionisation of the propellant (typically xenon or krypton) by electron impact; and the neutralisation of the ion beam by an external cathode (the hollow cathode neutraliser) that emits electrons at the same rate as ions are emitted. Understanding why the magnetic field must confine electrons but not ions (electron gyroradius must be much smaller than the thruster channel, while ion gyroradius is much larger), what the Hall parameter is (the ratio of electron cyclotron frequency to electron-neutral collision frequency, which must be $\gg 1$ for efficient electron confinement), and what the role of the propellant flow rate is in setting the operating point are the Hall thruster physics fundamentals that every EP engineer must have.
- Ion engine principles** — the grid system, beamlet optics, and the life-limiting erosion mechanism. The gridded ion engine — used on NASA's Dawn mission, the Hayabusa missions, ESA's SMART-1 and Rosetta, and currently on Europa Clipper and JUICE — uses electron bombardment or radio frequency excitation to ionise propellant in a discharge chamber, then extracts and accelerates the ions through a multi-grid system (screen grid, accelerator grid, and in some designs a decelerator grid). The double-grid spacing determines the ion beam energy and therefore the specific impulse: a closer spacing produces a higher electric field per unit voltage, enabling smaller voltages for the same I_{sp} . The life-limiting failure mode for gridded ion engines is grid erosion — the sputtering of grid material by ion bombardment, particularly from ions with trajectories that strike the accelerator grid rather than passing through the aperture. Understanding what limits the thruster life (typically the accelerator grid erosion rate, measured by electron backstreaming onset), how this is characterised through wear testing, and what the design features (charge-exchange ion trajectories, accel grid negative bias voltage) affect the erosion rate are the ion engine engineering fundamentals that NASA and ESA deep space mission teams require.
- Chemical monopropellant systems** — hydrazine catalytic decomposition, the catalyst bed, and green alternatives. Hydrazine (N_2H_4) monopropellant systems are the most widely deployed in-space propulsion technology in the heritage satellite fleet — used for attitude control (ADCS) and small Δv manoeuvres.

vres on hundreds of spacecraft. The thruster operates by passing hydrazine through a heated catalyst bed (typically Shell 405 catalyst — iridium-impregnated alumina granules) where the catalytic decomposition produces hot nitrogen, hydrogen, and ammonia gases that expand through the nozzle. Understanding the specific impulse achievable (220–240s in vacuum), the chamber pressure range, the catalyst bed preheat requirement (catalyst beds must be preheated to ensure reliable ignition at low temperatures), and the pulse performance versus steady-state performance trade are the hydrazine monopropellant engineering competencies that attitude control system designers require. Green propellant alternatives — HPGP (High Performance Green Propellant, specifically AF-M315E / ASCENT propellant), LMP-103S, and Aerojet's AF-M315E variants — offer higher I_{sp} (250–260s) and lower toxicity at the cost of higher operating temperature and different catalyst requirements.

- **Bipropellant systems** — hypergolic ignition, the MMH/NTO system, LOX/ethanol, and the main engine application. Bipropellant propulsion systems use two propellants that react spontaneously on contact (hypergolic) or require ignition. The MMH (monomethylhydrazine) / NTO (nitrogen tetroxide) propellant combination is hypergolic, storable at room temperature, and has been used for spacecraft main engines and attitude control thrusters on hundreds of satellites and deep space probes (the Space Shuttle OMS, the Cassini spacecraft, the Mars Science Laboratory descent stage). Understanding the advantages of bipropellant propulsion — I_{sp} of 300–330s in vacuum, high thrust for impulsive manoeuvres — and the disadvantages — toxicity of both propellants requiring hazmat handling infrastructure, complexity of a dual feed system, and the hypergolic ignition risk — is the bipropellant engineering baseline required for spacecraft prime contractor propulsion teams and heritage thruster manufacturers. The trend toward green bipropellants (LOX/ethanol or LOX/methane for spacecraft applications) is driven by the same toxicity concerns as the green monopropellant transition.
- **Cold gas propulsion** — the simplest in-space propulsion system, its specific applications, and its limitations. Cold gas thrusters store a pressurant gas (typically nitrogen, argon, or recently R236fa for CubeSats) and expel it through a nozzle without combustion. They offer extremely simple, reliable, low-contamination propulsion at the cost of very low specific impulse (50–80s) and correspondingly high propellant mass. Cold gas systems are used where propellant mass is not the primary constraint and simplicity and cleanliness are — attitude control on spacecraft with sensitive optical surfaces that cannot tolerate propellant contamination, separation systems for rideshare satellites where the Δv requirement is small, and proximity operations where the thrust plume must not contaminate adjacent spacecraft. Understanding when cold gas is the right choice (small Δv , simplicity and reliability required, cleanliness critical) and when it is not (any mission where propellant mass is significant relative to spacecraft mass) is the propulsion selection competence that spacecraft systems engineers require.
- **Propellant feed system design** — pressure-regulated versus blowdown, flow control valves, and the propellant management device. The feed system delivers propellant from the tank to the thruster at the required inlet pressure and flow rate throughout the mission. Pressure-regulated systems use a regulator to maintain constant thruster inlet pressure as the tank empties, producing constant thrust and I_{sp} throughout the mission at the cost of system complexity (pressure regulator, latch valve, pyrotechnic isolation valve). Blowdown systems allow the tank pressure to drop as propellant is expelled, producing decreasing thrust and I_{sp} but simpler and lighter feed systems — acceptable for attitude control applications where the total Δv is small and the performance variation is tolerable. The propellant management device (PMD) — the screen, vane, or surface tension device that ensures gas-free propellant delivery to the thruster in zero-gravity — is a critical and often underestimated component that has caused mission failures when its design assumptions were not met. Engineers who understand the PMD design methodology (the Bond number criterion for screen PMDs, the capillary pressure margin requirement) are demonstrating the feed system depth that qualifies them for propulsion systems integration roles.
- **Thruster qualification and environmental testing** — vibration, thermal vacuum, and the life test. In-space propulsion systems must survive the launch environment (acoustic and random vibration, shock from pyrotechnic events) and then operate reliably in the space environment (vacuum, thermal cycling between sun and shadow, radiation). The environmental qualification programme — vibration testing to the launch vehicle's random vibration spectrum, thermal cycling in a vacuum chamber, qualification life test for the specified number of operating hours or pulse cycles — is the test programme that every flight propulsion system must pass. Understanding what the environmental qualification sequence

is (typically: vibration → thermal vacuum → functional performance test at each stage), what the test conditions are (the qualification levels are typically 3–6 dB above the expected flight levels to provide qualification margin), and what the failure modes most commonly revealed during qualification (structural failures under vibration, thermal interface failures under temperature cycling, valve seal degradation under repeated actuation) are the propulsion qualification engineering competencies that flight programme engineers must demonstrate.

- **Power Processing Units for electric propulsion** — the PPU architecture, efficiency, and the regulation challenge. The Power Processing Unit (PPU) is the power electronics system that converts spacecraft bus power (typically 28V or 50V regulated DC for small satellites, 100V for medium satellites) to the specific voltages and currents required by the electric thruster. For a Hall thruster, the PPU must supply the discharge voltage (typically 200–400V at 1–10A for the main beam), the anode flow controller, the cathode heater and keeper supply, and the electromagnet current. The efficiency of the PPU — the ratio of power delivered to the thruster to power drawn from the spacecraft bus — directly affects the total power requirement and therefore the solar array size. Understanding the PPU's boost converter and inverter architecture, what limits PPU efficiency (switching losses in the power MOSFETs or IGBTs, magnetic core losses in the transformers), and how the PPU regulates the discharge voltage against a variable thruster impedance (which changes with operating condition) are the power electronics fundamentals that EP system engineers require.

How In-Space Propulsion Interviews Differ from Launch Propulsion and from Generic Spacecraft Engineering

- **I_{sp} matters in a way that is qualitatively different from launch propulsion.** In launch propulsion, specific impulse is one important performance parameter among several (chamber pressure, turbopump reliability, manufacturing cost). In in-space propulsion, I_{sp} is the governing design constraint — because every kilogram of propellant saved through higher I_{sp} is a kilogram available for payload, and the relationship between I_{sp} and propellant mass fraction is exponential through the Tsiolkovsky equation. An in-space propulsion engineer who cannot apply the Tsiolkovsky equation fluently and reason about the mass fraction implications of I_{sp} choices at different Δv levels is missing the analytical lens through which every propulsion system selection decision is made.
- **Electric and chemical propulsion require fundamentally different physical intuitions.** The chemical propulsion engineer thinks in thermodynamics, combustion, and fluid mechanics. The electric propulsion engineer thinks in plasma physics, electromagnetic fields, and atomic collision cross-sections. These are not small differences — an experienced chemical propulsion engineer and an experienced EP engineer share the Tsiolkovsky equation and the thruster qualification test sequence, but their daily technical vocabulary, their failure mode intuition, and their problem-solving approach are substantially different. Interviews in each area probe the relevant physical intuition specifically: a Hall thruster interview that produces only thermodynamic answers signals that the candidate has studied chemical propulsion and is attempting to transfer into EP without understanding the underlying physics change.
- **The integration of the propulsion system with the spacecraft is as important as the thruster itself.** In-space propulsion systems do not operate in isolation — they interact with the spacecraft's power system (every watt consumed by the thruster is subtracted from the payload power budget), the thermal control system (thrusters radiate heat into the spacecraft structure and propellant tanks that must be managed), the attitude determination and control system (every thruster firing is a torque input to the spacecraft that the ADCS must compensate), and the structural system (the thruster must be mounted to withstand launch loads without misalignment). Engineers who understand these interfaces — who can describe what happens to the spacecraft angular momentum when a Hall thruster fires, what the thermal consequence of a monopropellant thruster firing next to a temperature-sensitive optical instrument is, and what the feed system pressure fluctuation means for attitude control thruster repeatability — are demonstrating the systems integration depth that spacecraft prime contractor propulsion roles require.
- **The space environment is a design constraint, not a background condition.** In-space propulsion systems must operate after years of exposure to an environment that is hostile to almost every material used in their construction. Radiation — from the Van Allen belts, solar particle events, and galactic cosmic rays — degrades the semiconductor devices in the PPU through total ionising dose (TID) and single-

event effects (SEEs). Atomic oxygen in LEO — highly reactive monatomic oxygen at orbital altitudes between 200–700 km — oxidises metals and polymers exposed on the spacecraft exterior, degrading thruster nozzle coatings, propellant line polymer seals, and thruster body materials. Thermal cycling — as the spacecraft alternates between sunlit and eclipse periods at orbital frequency — stresses every joint, seal, and bonded interface through differential thermal expansion. And propellant contamination — from the plumes of adjacent thrusters depositing on solar arrays, optical surfaces, or thruster insulators — is a cross-contamination problem that thruster designers and spacecraft integration engineers manage jointly.

- **New-space pace and heritage reliability culture are genuinely different environments.** A Hall thruster qualification programme at a heritage government supplier (Aerojet, Moog, VACCO) follows a rigorous qualification sequence that may take three to five years from design through flight. A similar programme at a new-space EP startup (Phase Four, Accion Systems, ThrustMe) may target flight qualification in 18 months using a test-fail-fix approach and extensive in-orbit demonstration rather than comprehensive ground qualification. Both approaches have their specific failure modes, and candidates who understand the trade-offs — what heritage qualification provides that accelerated new-space qualification does not, and what in-orbit demonstration reveals that ground testing cannot — are demonstrating the programme engineering awareness that senior roles in both environments require.

PART II: 20 SPECIFIC PREP TASKS

INTERN / GRADUATE

1. Apply the Tsiolkovsky Rocket Equation across the full in-space propulsion technology range — from cold gas to ion engine 4–5 hours

Skill: The foundational propellant mass calculation that every in-space propulsion technology selection begins with

Why the field cares: The Tsiolkovsky equation is to in-space propulsion what the balanced field length calculation is to aircraft performance engineering — the foundational quantitative tool that connects the mission requirement to the hardware specification, and that every engineer in the field must apply fluently. A candidate who cannot compute the propellant mass for a specified mission Δv at three different specific impulse levels, reason about the mass fraction implications, and compare the results to a realistic spacecraft mass budget is missing the analytical foundation of the discipline. This is specifically tested in every in-space propulsion interview, because the inability to apply it fluently is the clearest signal that a candidate has studied propulsion from textbooks without engaging with the quantitative design problem it governs.

Done signal: You can compute the propellant mass fraction for a spacecraft requiring 2,500 m/s of Δv at I_{sp} values of 220s (hydrazine monopropellant), 320s (bipropellant), 1,600s (Hall thruster), and 3,000s (ion engine). You can reason about what the resulting propellant fraction implies for each technology at a realistic spacecraft wet mass, explain why the mass savings from electric propulsion justify the longer mission time for large Δv requirements, and identify the Δv threshold below which the mass savings from electric propulsion no longer justify its complexity. You can explain why the relevant I_{sp} comparison for a LEO constellation orbit maintenance manoeuvre is different from the relevant comparison for a GEO orbit-raising manoeuvre.

2. Understand Hall thruster operating principles — electron confinement, Hall current, ionisation, and the role of the hollow cathode 5–6 hours

Skill: The plasma physics of the dominant commercial electric propulsion technology

Why the field cares: Hall thrusters produce more than half of all electric propulsion thrust currently operating in space. Understanding how they work — at the level of the electron confinement mechanism (the radial magnetic field creates an $E \times B$ drift that traps electrons in the azimuthal Hall

5–6 hours

current while ions are accelerated axially by the electric field), the ionisation process (electron impact ionisation of the propellant, typically xenon or krypton), and the role of the hollow cathode (emitting electrons to neutralise the ion beam and sustaining the discharge) — is the EP physics baseline that every Hall thruster engineer and every spacecraft propulsion system engineer working with Hall thrusters must have. The specific question that distinguishes physical understanding from rote description: “why does the Hall thruster magnetic field need to be radial rather than axial?” The answer requires understanding that the $E \times B$ drift must be azimuthal (to create the Hall current and confine electrons) which requires B to be radial and E to be axial.

Done signal: You can explain the $E \times B$ drift mechanism and why it confines electrons but not ions in the Hall thruster channel. You can describe the role of the external magnetic field in setting the operating point — specifically how the magnetic field strength affects the ionisation efficiency, the Hall current magnitude, and the electron-ion recombination rate. You can explain why the hollow cathode is necessary (the neutraliser function), how it operates (thermionic emission from the cathode insert, sustained by the keeper discharge), and what happens if the cathode fails (the spacecraft charges positively, the thruster cannot sustain the discharge, and thrust is lost). You can sketch the cross-section of a Hall thruster and label the key components.

4–5 hours

3. Understand the specific impulse of chemical propulsion systems — what limits I_{sp} in chemical systems and why electric propulsion exceeds this limit

Skill: The thermodynamic basis of chemical propulsion performance and the physical reason electric propulsion exceeds it

Why the field cares: The specific impulse of a chemical propulsion system is limited by the temperature achievable in the combustion chamber (or decomposition reaction), which is bounded by the energy available in the chemical bonds of the propellant. The maximum achievable temperature for practical chemical propellants — approximately 3,500–4,000K for the highest-energy bipropellant combinations — combined with the molecular weight of the combustion products sets a thermodynamic ceiling on I_{sp} of approximately 460s (for LOX/LH2). Electric propulsion bypasses this limit by using electrical energy to accelerate propellant to velocities far beyond what thermodynamic expansion can achieve: a Hall thruster operating at 300V discharge voltage accelerates xenon ions to approximately 20,000 m/s, corresponding to an I_{sp} of approximately 2,000s. Understanding this physical distinction — and being able to derive the approximate exit velocity from the ion beam energy ($\frac{1}{2}mv^2 = qV$ for an ion of charge q accelerated through voltage V) — is the cross-domain propulsion physics that every in-space propulsion interview probes when the candidate has a chemical propulsion background.

Done signal: You can derive the maximum theoretical exhaust velocity for a chemical propulsion system from the thermodynamic energy available in the propellant combination, and explain why this limits chemical I_{sp} to approximately 460s regardless of how the combustion products are expanded. You can derive the ion exhaust velocity for a Hall thruster operating at a specified discharge voltage (using $\frac{1}{2}mv^2 = qV$) and compute the resulting specific impulse. You can explain why electric propulsion is described as decoupling the energy source from the propellant, and what the constraint on this decoupling is (the available power, which limits thrust through the thrust-power relationship $T = 2\eta P/v$).

2–3 hours

4. Prepare behavioural answers that demonstrate systems integration thinking and comfort with novel hardware challenges

Skill: STAR stories with the cross-system interface and first-hardware emphasis in-space propulsion employers probe

Why the field cares: In-space propulsion employers — particularly at new-space EP companies and spacecraft prime contractor propulsion teams — probe how candidates respond when the thruster interacts with another spacecraft system in an unexpected way: the Hall thruster plume that deposits sputtered material on the solar array, the monopropellant thruster firing that shifts the spacecraft's

2–3 hours

attitude more than the ADCS expected because of a higher-than-nominal impulse bit, or the PPU switching transient that creates an EMI environment that disrupts the spacecraft's C-band communications downlink. These are not hypothetical — every in-space propulsion programme has stories of exactly these interactions, and they are the failure modes that textbooks do not prepare engineers for. Candidates who have encountered any cross-system interaction — even in a student CubeSat project — and can describe the investigation and resolution are demonstrating the interdisciplinary hardware awareness that propulsion system integration requires.

Done signal: Four STAR stories covering: a situation where a propulsion system or thruster component interacted with another system in an unexpected way; a hardware test that produced a result different from the analytical prediction; a situation where you had to make an engineering decision based on incomplete data; and a failure in your own analysis or simulation that you identified before it affected a design decision. At least two stories involve real propulsion or electrical hardware, even at model or student scale.

3–4 hours

5. Understand cold gas and monopropellant systems — operating principles, performance limits, and typical spacecraft applications

Skill: The two most widely deployed heritage in-space propulsion technologies

Why the field cares: Cold gas and hydrazine monopropellant systems power the attitude control and station-keeping of a large fraction of the operational satellite fleet. Understanding the operating principles (cold gas: stored gas expanded through a nozzle with no energy addition; monopropellant: exothermic catalytic decomposition providing enthalpy before nozzle expansion), the performance limits (cold gas: I_{sp} 50–80s, limited by gas molecular weight and temperature; monopropellant: I_{sp} 220–240s for hydrazine, limited by decomposition temperature and molecular weight), the typical applications (cold gas: CubeSats, separation systems, clean-room safe systems; monopropellant: attitude control on medium and large spacecraft, Δv manoeuvres up to a few hundred m/s), and the key design considerations for each (cold gas: gas storage pressure, valve C_v , flow-metering precision; monopropellant: catalyst bed preheat, thermal management, propellant management device) are the heritage propulsion knowledge baseline that every spacecraft propulsion system engineer must have before engaging with the more technically novel electric propulsion systems.

Done signal: For cold gas and monopropellant hydrazine systems, you can state: the typical I_{sp} range and what limits it, the typical thrust range, the key components of a complete flight system (from tank to thruster nozzle), the primary application context where each technology is the preferred choice, and one specific spacecraft mission that used each system. You can explain why hydrazine requires a preheated catalyst bed for reliable cold-start ignition and what the failure mode is if the catalyst bed temperature is below the operating threshold when the thruster is commanded to fire.

6–8 hours

6. Get hands-on with propulsion system analysis — build a blowdown or pressure-regulated feed system model and analyse its performance across the propellant load range

Skill: Quantitative feed system analysis as the practical foundation of propulsion system design

Why the field cares: Feed system analysis — computing the propellant inlet pressure to the thruster as a function of the remaining propellant load, for either a blowdown or pressure-regulated system — is a routine engineering task in spacecraft propulsion that requires combining the ideal gas law (for the pressurant gas behaviour as the tank empties), the liquid propellant hydrostatic column (for the propellant head contribution to inlet pressure), and the thruster inlet pressure requirement (which sets the constraint on minimum acceptable tank pressure). A candidate who has built this model in Python, MATLAB, or even a spreadsheet — who has computed the inlet pressure versus propellant mass expended curve for a blowdown system and identified at what remaining propellant fraction the inlet pressure falls below the thruster's minimum operating pressure — is demonstrating the quantitative propulsion system engineering that textbook study alone cannot provide.

Done signal: You have built a quantitative model of a blowdown or pressure-regulated monopropel-

lant feed system — computing the pressurant gas pressure as propellant is expelled (using the ideal gas law or a more accurate real gas model), the thruster inlet pressure as a function of remaining propellant mass, and the resulting variation in thruster thrust and I_{sp} across the blowdown range. You can identify the minimum tank pressure that maintains the thruster above its minimum inlet pressure specification, and compute the corresponding fraction of the initial propellant load that represents the practical usable propellant. You can explain why the blowdown ratio (ratio of initial to final tank pressure) is typically 2:1 to 4:1 for attitude control systems.

6–8 hours

MID-LEVEL (Engineer, Senior Engineer, ~3–8 years)

All graduate tasks still apply. Technical stories must come from professional or serious research contexts involving real propulsion hardware or flight programme experience.

7. Build thorough working knowledge of Hall thruster performance characterisation — the operating map, efficiency decomposition, and the I_{sp} -thrust trade

5–6 hours

Skill: The thruster performance engineering knowledge that connects design parameters to mission capability

Why the field cares: Hall thruster performance — thrust, specific impulse, and efficiency as functions of discharge voltage, discharge current, and propellant flow rate — is not fixed. The thruster operates across a range of conditions defined by the thruster's throttle map, and the operating point is selected to match the available spacecraft power, the required thrust level, and the mission's I_{sp} requirement. Understanding how thrust scales with discharge current (approximately linearly, since thrust is proportional to ion mass flow rate which is proportional to discharge current for a fixed voltage), how I_{sp} scales with discharge voltage (approximately as the square root of voltage, since ion velocity scales as $\sqrt{2qV/m}$), and how the thruster efficiency depends on the operating point (the ratio of beam power to input power, degraded by neutral propellant utilisation losses, divergence losses, and discharge losses) are the Hall thruster performance engineering fundamentals that thruster development engineers and spacecraft propulsion system engineers work with daily. The ability to read a thruster throttle table, identify the operating conditions for a specified power and I_{sp} requirement, and estimate the resulting thrust level is the performance engineering competency that connects the thruster to the mission.

Done signal: You can describe the Hall thruster performance map — how thrust, I_{sp} , and efficiency vary with discharge voltage and current — and explain the physical reasons for each trend. You can compute the approximate thrust and I_{sp} for a Hall thruster at a specified operating condition (discharge voltage, current, propellant flow rate) using simplified analytical models. You can explain the concept of thrust efficiency decomposition — separating the total efficiency into propellant utilisation efficiency, current utilisation efficiency, and beam divergence efficiency — and identify which loss mechanism typically dominates at each operating regime. You can explain what the thrust-to-power ratio implies for the time required to raise a spacecraft's orbit using electric propulsion at a specified power level.

8. Understand ion engine grid system design — beam optics, perveance, and the erosion life model

5–6 hours

Skill: The gridded ion engine's defining technical challenge — precision ion beam optics and lifetime management

Why the field cares: Gridded ion engines achieve the highest specific impulse of any operational in-space propulsion technology (3,000–10,000s for deep space missions) but require precision ion beam optics to extract and accelerate the ion beam while minimising accelerator grid erosion. The perveance of the grid system — a measure of the grid's ability to pass current at the space-charge-limited flow rate — determines whether the beam is correctly focused: operating above the perveance limit causes beam defocusing and increased grid impingement; operating below it wastes voltage

5–6 hours

across the accel grid without improving beam quality. Understanding the perveance scaling law ($J/V^{3/2} = \text{const}$ for a given grid geometry), what happens when the spacing changes due to thermal expansion, and how the erosion rate of the accelerator grid is modelled — using sputtering yield data from laboratory measurements and numerical simulations of the charge-exchange ion trajectories — are the ion engine design engineering competencies that deep space EP teams require.

Done signal: You can explain what perveance is, write the Child-Langmuir space-charge limited current density formula, and explain how it constrains the grid voltage and spacing for a specified beam current density. You can explain what charge-exchange (CEX) ion production is — the process by which a fast beam ion transfers its charge to a slow neutral atom, producing a slow ion that is then accelerated in the wrong direction by the grid potential — and describe why CEX ions are the dominant source of accelerator grid erosion. You can describe how the thruster's useful life is defined (when the accelerator grid erosion reaches a specified fraction of the grid thickness or when electron backstreaming onset occurs), and what the typical life of a qualified ion engine is in operating hours.

2 hours

9. Prepare a technically specific story about a propulsion hardware test anomaly — what the telemetry showed, what you hypothesised, and how it was resolved

Skill: Applied propulsion engineering judgement with real hardware at professional depth

Why the field cares: In-space propulsion systems have failure modes that simulations rarely predict — a Hall thruster that oscillates in a mode not seen in ground testing because the vacuum chamber's background pressure is orders of magnitude higher than in-space vacuum; a monopropellant thruster that shows anomalous impulse bits because the catalyst bed temperature was lower than nominal due to a thermal interface resistance not captured in the thermal model; a bipropellant thruster that produces pressure spikes during ignition because the mixture ratio deviated during the valve actuation transient. Engineers who have diagnosed a real propulsion hardware anomaly — who can describe the telemetry signature, the hypothesis formation, the diagnostic test, and the root cause — are demonstrating the applied propulsion engineering judgement that simulation-only experience cannot provide.

Done signal: You have a story about a propulsion hardware test anomaly from professional or serious research experience — naming the thruster or system, the test campaign, the anomaly in the telemetry data (a pressure spike, an unexpected oscillation, a performance shortfall, or a valve anomaly), the hypothesis you formed, the diagnostic test you designed, and the root cause you identified. The story includes specific measured values and ends with a specific corrective action — a design change, an operating procedure modification, or an updated test procedure.

4–5 hours

10. Understand the propellant management device — design principles, the Bond number criterion, and failure modes

Skill: The zero-gravity propellant delivery challenge that has caused multiple mission failures

Why the field cares: In zero gravity, propellant in a spacecraft tank is not guaranteed to settle near the outlet — surface tension forces and residual accelerations distribute it throughout the tank volume, potentially allowing pressurant gas to enter the propellant line and reach the thruster (gas ingestion causes thruster malfunction and potentially loss of function). The propellant management device — a system of screens, vanes, or surface-tension structures that uses surface tension to guarantee propellant at the tank outlet regardless of orientation — is the engineering solution. The design criterion is the Bond number: $Bo = \Delta P r g / \sigma$ where ΔP is the pressure differential across the screen, r is the pore radius, g is the acceleration, and σ is the propellant surface tension. A properly designed PMD maintains $Bo < 1$ throughout the mission (surface tension forces dominate over acceleration forces), ensuring gas-bubble-free propellant delivery. PMD design failures — PMDs that allowed gas ingestion because the acceleration environment was higher than expected (during a large Δv burn or a spacecraft manoeuvre) — have contributed to spacecraft propulsion failures, and the engineering analysis that characterises the PMD's operating envelope is specifically tested in propulsion system design interviews.

4–5 hours

Done signal: You can explain what a propellant management device is and why it is needed in zero gravity. You can state the Bond number criterion for PMD design ($Bo \ll 1$ for surface tension dominance) and explain what each parameter in the Bond number represents. You can describe three common PMD architectures (screen, vane, and sponge/porous liner types) and explain what determines the choice between them. You can describe the failure mode when a PMD is undersized — the specific operational scenario that causes gas ingestion — and explain what the consequence is for thruster operation.

4–5 hours

11. Understand the Power Processing Unit for Hall thrusters — the architecture, efficiency drivers, and the thruster-PPU interface

Skill: The power electronics system that determines the total power draw of the electric propulsion system

Why the field cares: The PPU is the component that converts spacecraft bus power to the specific voltages and currents required by the Hall thruster, and its efficiency directly affects the total power the spacecraft must provide to operate the propulsion system. For a Hall thruster with 1,000W of beam power at 60% thruster efficiency, the PPU must deliver 1,667W of processed power; if the PPU itself is 90% efficient, the total spacecraft power consumption is 1,852W — significantly more than the 1,000W the thruster is producing in thrust. Understanding the PPU architecture (boost converters for the high-voltage discharge supply, inverters for the electromagnet supply, regulated supplies for the cathode heater and keeper), what the dominant sources of efficiency loss are (MOSFET switching losses, transformer core losses, and the difficulty of regulating against the thruster's negative impedance characteristic at the discharge supply output), and what the thruster-PPU interface requirements are (electromagnetic compatibility — the PPU must not inject noise into the spacecraft's DC power bus at levels that disrupt other systems) are the PPU engineering fundamentals that EP system engineers must have.

Done signal: You can describe the PPU's main functional blocks for a Hall thruster application — discharge power supply, electromagnet supply, cathode heater and keeper supply, flow controller, and telemetry/command interface. You can explain why the discharge supply must handle negative impedance (as discharge current increases, discharge voltage tends to decrease, creating the equivalent of a negative resistance) and what the control approach is to maintain stability. You can estimate the PPU efficiency requirement for a specified system power budget, and describe what the consequence is of a 5% reduction in PPU efficiency for a spacecraft with a 5kW EP system operating for 6 months of orbit-raising.

4–5 hours

12. Understand the thruster qualification — the environmental test sequence, acceptance test philosophy, and the delta-qualification concept

Skill: The test programme that produces a flight-qualified propulsion system

Why the field cares: A flight-qualified propulsion system is not simply one that has been shown to operate correctly in the laboratory — it is one that has been demonstrated to survive the launch environment (vibration, shock, acoustic loading) and then operate reliably through its full specified life in the space environment (vacuum, thermal cycling, radiation, atomic oxygen). The qualification test sequence — typically vibration at qualification levels, thermal cycling in vacuum, functional performance tests at each stage, and finally a life test at the specified number of operating hours or pulse cycles — is the engineering programme that demonstrates this. Understanding what qualification levels are (typically a specified margin above the expected flight levels, defined in the launch vehicle user's guide), what acceptance test philosophy is (every flight unit is tested at reduced levels to verify workmanship without consuming qualification life), and what the delta-qualification concept means (when an existing qualified thruster is modified, a delta-Q test programme demonstrates that the modification does not affect the qualified characteristics) are the qualification engineering fundamentals that propulsion programme engineers must demonstrate.

Done signal: You can describe the standard qualification test sequence for a flight thruster — identi-

4–5 hours

fying the test types (random vibration, thermal vacuum, leak test, functional performance, life test), the typical qualification margin above expected flight levels for vibration (typically 3–6 dB), and the rationale for the specific sequence (vibration before thermal vacuum to identify latent structural weaknesses, functional tests after each environmental test to detect induced failures). You can explain the difference between qualification test levels and acceptance test levels, and describe why every flight unit requires an acceptance test rather than relying on the qualification data. You can define what a delta-qualification programme is and give one example of a modification that would and one that would not require a delta-qualification.

4–6 hours

13. Prepare for a propulsion system sizing problem under interview conditions — technology selection, propellant mass, and power budget

Skill: Structured in-space propulsion system design under time pressure

Why the field cares: Mid-level and senior in-space propulsion interviews frequently include a live or take-home problem: “a 500 kg GEO communication satellite needs to raise its orbit from a GTO insertion point to GEO — approximately 1,800 m/s of Δv — using its onboard propulsion. Available spacecraft power at GTO is 2 kW, rising to 8 kW at GEO. Compare a bipropellant apogee engine approach versus a Hall thruster approach in terms of propellant mass, orbit-raising time, and power system impact.” The candidate who can apply the Tsiolkovsky equation, estimate the Hall thruster orbit-raising time from the thrust-power relationship, compare the propellant mass fraction for both systems, and reason about the spacecraft mass budget implications is demonstrating the quantitative propulsion systems design competency that connects the physics to a real mission decision.

Done signal: You can work through a complete propulsion system comparison for a specified orbit-raising scenario in under 45 minutes — applying the Tsiolkovsky equation for each technology, computing the orbit-raising time from the EP thrust-power relationship, estimating the mass saving from electric propulsion relative to chemical, and reasoning about the power system impact. You can identify the key assumptions (thruster efficiency, PPU efficiency, solar array specific power, operational power margin during orbit-raising) and discuss how varying each assumption changes the comparison. You have practised this for at least two different mission scenarios.

SENIOR LEVEL (Principal Engineer, Technical Lead, Chief Engineer)

All mid-level tasks still apply. Thruster physics knowledge must extend to design and test experience, not just operational understanding. System integration knowledge must include direct experience with propulsion-spacecraft interface management on a real programme.

4–6 hours

14. Prepare to walk through the complete development and qualification of a propulsion system — from requirements through flight demonstration

Skill: End-to-end propulsion system development ownership at the level a senior engineer must demonstrate

Why the field cares: Senior in-space propulsion engineers at heritage suppliers and at advanced new-space companies are expected to have personally owned a significant thread of a complete propulsion system development — from the mission requirements that drove the propulsion selection, through the design and analysis, through the hardware build, through the environmental qualification, through the flight launch and in-orbit commissioning, and through the correlation of in-orbit performance against pre-launch predictions. This is genuinely rare experience: the number of new spacecraft propulsion systems that have completed qualification and flown in the past decade is small. Engineers who have it are immediately distinguishable by the specificity and honesty of their account — the qualification anomaly they did not expect, the in-orbit performance that did not match the ground calibration, and the analysis they did to close the discrepancy.

Done signal: For one propulsion system or major component you personally owned a development thread for — a thruster, a feed system, a PPU, or a complete propulsion module — you can dis-

4–6 hours

cuss without notes: the mission requirement that drove the design (Δv budget, power constraint, I_{sp} target), the key design trade-off you made, the most significant anomaly found during qualification testing, the root cause investigation, the corrective action, the qualification closure argument, and the first in-orbit performance data. You can quantify the qualification anomaly and the in-orbit versus ground performance comparison.

4–5 hours

15. Prepare a technically grounded position on one active frontier in in-space propulsion — krypton propellants, electrospray thrusters, or nuclear electric propulsion

Skill: Forward-looking technical awareness at senior engineering depth

Why the field cares: In-space propulsion in 2025–2026 has several genuine technical frontiers where the engineering challenges are real and the solutions are not settled. Krypton as a Hall thruster propellant — offering lower cost and greater terrestrial availability than xenon at the cost of slightly lower performance (lower atomic mass, higher ionisation energy) — is now operational on Starlink satellites but raises questions about thruster design optimisation (different magnetic field configuration optimal for krypton versus xenon) and cathode compatibility (different sputtering characteristics). Electrospray (colloid) thrusters — which emit charged droplets of ionic liquid from electrically stressed Taylor cones at the tips of needles or capillaries — offer extremely fine thrust resolution at sub-millinewton levels and near-zero plume contamination, making them attractive for precision pointing and proximity operations, but their specific impulse variability (from ~ 100 s to ~ 2000 s depending on the operating mode) and their sensitivity to propellant contamination are engineering challenges that are not fully resolved. Nuclear electric propulsion for deep space missions — combining a fission reactor with high-power ion engines to enable rapid transit to the outer solar system — is under active development at NASA (the Fission Surface Power programme and the NASA NEP concept studies). Senior engineers who can engage at technical depth with any of these frontiers are demonstrating the forward-looking perspective that senior roles require.

Done signal: You have a prepared 3-minute technical discussion covering one specific engineering challenge on one frontier — named specifically: the magnetic field topology optimisation for krypton propellant in a Hall thruster and why the xenon-optimised design is suboptimal for krypton; the Taylor cone stability limit in an electrospray thruster and what operating conditions cause the cone to collapse, interrupting thrust; or the reactor shielding mass trade in a nuclear electric propulsion system and what mass limit makes NEP competitive with solar electric propulsion for a specific deep space mission trajectory. Your position identifies the specific unresolved engineering problem.

4–5 hours

16. Prepare to lead a propulsion architecture trade-off for a specified mission — electric versus chemical, and the governing constraints

Skill: Architectural decision-making at senior engineering speed

Why the field cares: Senior in-space propulsion engineers are the technical authority for propulsion system selection at spacecraft prime contractors and mission design organisations. “A 250 kg LEO Earth observation satellite needs 500 m/s of Δv for drag makeup and orbit maintenance over a 5-year mission — compare a green monopropellant system, a Hall thruster operating at 200W, and a cold gas system, and recommend the preferred approach for this mission” requires reasoning through the propellant mass for each technology, the power impact on the spacecraft, the volume and mass of the complete system, the qualification and reliability heritage, and the specific mission constraints (contamination sensitivity of the optical payload, power availability, cost). The senior interview tests whether you can structure this reasoning live and arrive at a specific recommendation with explicit trade-offs.

Done signal: You have worked through at least three in-space propulsion architecture trade-off problems spanning at least two mission types — a LEO constellation satellite, a GEO communication satellite, or a deep space mission. For each, you state the governing constraint (power, mass, mission time, contamination, cost), the two or three credible technology options, the key performance comparison, and your recommendation with explicit trade-offs. You can do this in under 10 minutes per

scenario, conversationally, without reference to notes.

4–5 hours

17. Understand the space environment effects on propulsion systems — radiation, atomic oxygen, thermal cycling, and contamination

4–5 hours

Skill: The environmental design requirements that govern propulsion material selection and qualification

Why the field cares: In-space propulsion systems must survive years of exposure to an environment that is hostile to almost every material used in their construction. Radiation — from the Van Allen belts, solar particle events, and galactic cosmic rays — degrades the semiconductor devices in the PPU through total ionising dose (TID) and single-event effects (SEEs). Atomic oxygen in LEO — highly reactive monatomic oxygen at orbital altitudes between 200–700 km — oxidises metals and polymers exposed on the spacecraft exterior, degrading thruster nozzle coatings, propellant line polymer seals, and thruster body materials. Thermal cycling — as the spacecraft alternates between sunlit and eclipse periods at orbital frequency — stresses every joint, seal, and bonded interface through differential thermal expansion. And propellant contamination — from the plumes of adjacent thrusters depositing on solar arrays, optical surfaces, or thruster insulators — is a cross-contamination problem that thruster designers and spacecraft integration engineers manage jointly. Engineers who understand these environmental effects at the level of material selection criteria and qualification test requirements are demonstrating the in-space propulsion environmental engineering depth that every programme requires.

Done signal: For radiation, atomic oxygen, thermal cycling, and plume contamination: you can describe the physical mechanism of each effect, identify the propulsion system component most susceptible to each effect, state the typical design margin or material selection criterion used to address it, and describe how it is addressed in the qualification test programme. You can explain what total ionising dose means for a PPU semiconductor device, and what radiation hardening approaches are used for the MOSFET switches in the discharge supply.

18. Build quantitative estimation fluency for in-space propulsion — propellant mass, orbit-raising time, thrust, and power — without simulation

4–5 hours

Skill: Senior-speed first-principles reasoning about propulsion system feasibility

Why the field cares: Senior propulsion engineers are expected to sanity-check propulsion budgets, estimate whether a proposed technology selection meets the mission constraints before the detailed analysis is complete, and recognise physically implausible performance claims from suppliers. The estimation problems are tractable: applying the Tsiolkovsky equation to compute propellant mass; computing the approximate I_{sp} of a Hall thruster from the ion exhaust velocity at a specified discharge voltage; estimating the orbit-raising time from the thrust-power ratio and the initial orbit Δv requirement; estimating the propellant tank volume from the propellant mass and density with a specified ullage volume. These are order-of-magnitude estimates that experienced propulsion engineers can produce in minutes, and they are what allow a quick sanity check on a supplier's claim or a junior engineer's analysis before committing time to a detailed review.

Done signal: You have worked through five in-space propulsion estimation problems covering at least two of: propellant mass from Tsiolkovsky at specified I_{sp} and Δv ; Hall thruster I_{sp} from discharge voltage using the ion exhaust velocity formula; orbit-raising time from thrust level and Δv requirement; EP system propellant mass versus chemical equivalent for a specified mission; and propellant tank volume from mass and density with ullage. You state assumptions before numbers, give order-of-magnitude answers with stated uncertainty, and identify the most load-bearing assumption in each.

ALL LEVELS

19. Prepare a specific answer to "Why in-space propulsion — and why this specific technology area?" that reflects genuine technical engagement

1–2 hours

Skill: Technically specific motivation that distinguishes propulsion-committed candidates from spacecraft engineers who happen to be interested in thrusters

Why the field cares: In-space propulsion employers — particularly at EP startups and deep space mission teams — are looking for engineers who are genuinely drawn to the specific technical challenges of the field: the combination of plasma physics, thermodynamics, materials science, and spacecraft systems integration that makes every propulsion system a small-scale physics experiment with a very tight weight and power budget. The expected answer in 2025–2026 engages with one of: the Hall thruster magnetic field optimisation challenge for krypton propellant; the electrospray thruster Taylor cone stability limit and its implications for precision thrust control; the propellant management device design challenge for electric propulsion in a spinning or maneuvering spacecraft; the power processing unit switching loss challenge for high-power EP systems; or the specific propulsion challenge of the programme the candidate is applying to work on. The answer must name one specific engineering challenge and connect the candidate's background to contributing to its solution.

Done signal: You have a 90-second answer that names your target in-space propulsion technology (Hall thruster, ion engine, monopropellant, bipropellant, cold gas, electrospray, or a specific hybrid), identifies one specific active engineering challenge in that technology area, explains what makes it technically hard (the specific plasma physics, thermodynamics, or materials challenge), and connects your engineering background to contributing to its solution. The answer cannot be given unchanged to a candidate for a launch propulsion or aircraft propulsion role.

20. Map your technical background to a specific propulsion technology, mission class, and employer type — and understand the heritage versus new-space culture divide

1–2 hours

Skill: Precise self-positioning in a field that spans government deep space missions to commercial constellation propulsion

Why the field cares: The in-space propulsion employer landscape spans organisations whose engineering cultures, development timescales, qualification philosophies, and career trajectories differ more than in almost any other aerospace subdomain. An engineer at NASA Glenn Research Center working on ion engine development for a deep space mission operates on a ten-year programme timeline, with a qualification standard that requires demonstration of the full design life in ground testing before flight. An engineer at ThrustMe or Phase Four working on a Hall thruster for a commercial LEO constellation customer operates on an 18-month development cycle, with a test philosophy that combines abbreviated ground qualification with in-orbit demonstration as the primary reliability evidence. An engineer at Moog or Bradford ECAPS working on a green monopropellant thruster for a medium satellite operates in the heritage supplier culture that prioritises heritage qualification data and customer-proven designs. A candidate who cannot identify which of these cultures their engineering background positions them for — and why — is mismatching their experience to the employer's expectation.

Done signal: You can state in under 60 seconds: the in-space propulsion technology you are most experienced in or targeting, the mission class most relevant to your background (LEO constellation, GEO commercial, science deep space, or planetary exploration), the development culture you are most experienced in (government research, heritage prime contractor, or new-space startup), the analysis and simulation tools you work in fluently, and two specific technical contributions your background makes to the target role. You have read at least three recent AIAA Joint Propulsion Conference or IEPC papers from the employer you are targeting, and you can describe one specific technical challenge from those papers that connects to your background.

SUMMARY REFERENCE TABLE

#	Task Description	Target Level	Effort
1	Tsiolkovsky Rocket Equation across full I_{sp} range — cold gas to ion engine	All	4–5 h
2	Hall thruster physics — $E \times B$ drift, electron confinement, ionisation, hollow cathode	All	5–6 h
3	Chemical I_{sp} thermodynamic limit and why electric propulsion exceeds it	All	4–5 h
4	STAR stories — cross-system interaction, hardware anomaly, incomplete data, own error	All	2–3 h
5	Cold gas and monopropellant systems — principles, performance, applications	All	3–4 h
6	Blowdown or pressure-regulated feed system model — inlet pressure vs propellant mass	All	6–8 h
7	Hall thruster performance characterisation — operating map, efficiency decomposition	Mid+	5–6 h
8	Ion engine grid system — perveance, CEX erosion, life model	Mid+	5–6 h
9	Propulsion hardware anomaly story — telemetry, hypothesis, root cause, resolution	Mid+	2 h
10	Propellant management device — Bond number, PMD architectures, gas ingestion failure mode	Mid+	4–5 h
11	Power Processing Unit — architecture, efficiency, thruster-PPU interface	Mid+	4–5 h
12	Thruster qualification — environmental test sequence, acceptance philosophy, delta-Q	Mid+	4–5 h
13	Propulsion system sizing problem — technology selection, propellant mass, orbit-raising time	Mid+	4–6 h
14	Complete propulsion system development story — requirements through flight demonstration	Senior	4–6 h
15	One active frontier — krypton Hall thrusters, electrospray, or nuclear electric	Senior	4–5 h
16	Propulsion architecture trade-off — technology selection for specified mission constraints	Senior	4–5 h
17	Space environment effects — radiation, atomic oxygen, thermal cycling, contamination	Senior	4–5 h
18	Quantitative estimation — propellant mass, orbit-raising time, thrust, power	Senior	4–5 h
19	"Why in-space propulsion — why this technology area?" — technically specific	All	1–2 h
20	Technology / mission class / employer culture self-positioning	All	1–2 h

THE STRUCTURAL REALITY THAT MAKES IN-SPACE PROPULSION DIFFERENT

In-space propulsion is the discipline where the mission begins where the launch vehicle ends — and where every gram of propellant consumed in the wrong direction, at the wrong efficiency, or at the wrong moment represents an irreversible reduction in mission capability that no ground team can reverse. The satellite that burns two kilograms of extra hydrazine correcting a navigation error is not two kilograms lighter for the next manoeuvre — it is two kilograms of life subtracted from a fixed budget that was balanced to the kilogram when the spacecraft was designed.

This conservation imperative — every propellant molecule is precious, every watt consumed by the thruster is taken from the payload, and every ignition consumes an irreplaceable portion of the spacecraft's useful life — creates an engineering culture that is unusual in aerospace. In most aerospace engineering, consuming more resource than planned is a cost problem or a schedule problem. In in-space propulsion, consuming more propellant than planned is a mission life problem, and the mission cannot be refuelled. This is why in-space propulsion engineers are, as a professional culture, more conservative than launch propulsion engineers and more mass-focused than spacecraft power or communications engineers: their resource budget has a hard, physical floor that no additional investment can change.

It is also the reason that the discipline's technical frontiers — higher I_{sp} through electric propulsion, lighter propellant management devices, more efficient power processing, green propellants that replace the toxic chemistry of hydrazine — are all ultimately in the service of the same goal: doing more with the same mass. Every drag count of I_{sp} improvement has a calculable benefit in propellant mass saved per Δv unit. Every watt of PPU efficiency improvement has a calculable benefit in solar array mass avoided per kilowatt of EP power. These are not abstract engineering improvements — they are propellant mass budgets that translate directly into spacecraft lifetime, payload mass fraction, or mission capability.

The engineers who succeed in this field are those who hold the mission constraint and the physical mechanism simultaneously — who understand that the Hall parameter must be greater than approximately 10 in the region of maximum ionisation because the magnetic field configuration determines the electron confinement, which determines the discharge efficiency, which determines how much power is wasted as heat in the discharge chamber walls rather than going into ion beam power, which determines how much solar array area the spacecraft needs, which determines the spacecraft mass, which determines how much propellant is available, which determines the mission lifetime. This chain of consequence — from plasma physics to mission lifetime — is the specific intellectual texture of in-space propulsion engineering, and it is what every senior interview in the field is ultimately assessing whether the candidate can hold.

BREAK INTO AEROSPACE
