

Package [exception](#)

Class UnauthorizedException

[java.lang.Object](#)
 [java.lang.Throwable](#)
 [java.lang.Exception](#)
 [java.lang.RuntimeException](#)
 [exception.UnauthorizedException](#)

All Implemented Interfaces:

[Serializable](#)

```
public class UnauthorizedException
extends RuntimeException
```

Excepción lanzada cuando un usuario no está autenticado Mapea a código HTTP 401 Unauthorized

See Also:

[Serialized Form](#)

Constructor Summary

Constructors
Constructor
Description
UnauthorizedException (String message)
Constructor simple
UnauthorizedException (String message, String reason)
Constructor con razón personalizada

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method	Description
	String	
	getReason ()	
Methods inherited from class java.lang.Throwable		
addSuppressed , fillInStackTrace , getCause , getLocalizedMessage , getMessage , getStackTrace , getSuppressed , initCause , printStackTrace , printStackTrace , printStackTrace , setStackTrace , toString		
Methods inherited from class java.lang.Object		
clone , equals , finalize , getClass , hashCode , notify , notifyAll , wait , wait , wait		

Constructor Details

UnauthorizedException
<pre>public UnauthorizedException(String message)</pre>
Constructor simple
Parameters:

message - mensaje de error

UnauthorizedException

```
public UnauthorizedException(String message,
                             String reason)
```

Constructor con razón personalizada

Parameters:

message - mensaje de error

reason - razón por la que no está autenticado

Method Details

getReason

```
public String getReason()
```