Package model

Enum Class AuditAction

java.lang.Object
    java.lang.Enum<AuditAction>
        model.AuditAction

All Implemented Interfaces:
Serializable, Comparable<AuditAction>, Constable

---

public enum **AuditAction**
extends Enum<AuditAction>

Enum que define los tipos de acciones auditadas en la plataforma.

Nested Class Summary

Nested classes/interfaces inherited from class java.lang.*Enum*

Enum.EnumDesc<E extends Enum<E>>

Enum Constant Summary

Enum Constants

Enum Constant
Description
CREATE
DELETE
DISABLE_ACCOUNT
UPDATE

Method Summary

All Methods	Static Methods	Concrete Methods

Modifier and Type
Method
Description
static **AuditAction**
valueOf(String name)
Returns the enum constant of this class with the specified name.
static **AuditAction**[]
values()
Returns an array containing the constants of this enum class, in the order they are declared.

Methods inherited from class java.lang.*Enum*

clone, compareTo, describeConstable, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.*Object*

Enum Constant Details

CREATE

`public static final AuditAction CREATE`

UPDATE

`public static final AuditAction UPDATE`

DELETE

`public static final AuditAction DELETE`

DISABLE_ACCOUNT

`public static final AuditAction DISABLE_ACCOUNT`

Method Details

values

`public static AuditAction[] values()`

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:
an array containing the constants of this enum class, in the order they are declared

valueOf

`public static AuditAction valueOf(String⌗ name)`

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:
name - the name of the enum constant to be returned.

Returns:
the enum constant with the specified name

Throws:
IllegalArgumentException⌗ - if this enum class has no constant with the specified name

NullPointerException⌗ - if the argument is null