

**Package** [exception](#)

## Class UnauthorizedException

[java.lang.Object](#)  
  [java.lang.Throwable](#)  
    [java.lang.Exception](#)  
      [java.lang.RuntimeException](#)  
        [exception.UnauthorizedException](#)

**All Implemented Interfaces:**

[Serializable](#)

```
public class UnauthorizedException
extends RuntimeException
```

Excepción lanzada cuando un usuario no está autenticado Mapea a código HTTP 401 Unauthorized

**See Also:**

[Serialized Form](#)

### Constructor Summary

Constructors
Constructor
Description
<a href="#">UnauthorizedException</a> ( <a href="#">String</a> message)
Constructor simple
<a href="#">UnauthorizedException</a> ( <a href="#">String</a> message, <a href="#">String</a> reason)
Constructor con razón personalizada

### Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method	Description
	<a href="#">String</a>	
	<a href="#">getReason</a> ()	
Methods inherited from class <a href="#">java.lang.Throwable</a>		
<a href="#">addSuppressed</a> , <a href="#">fillInStackTrace</a> , <a href="#">getCause</a> , <a href="#">getLocalizedMessage</a> , <a href="#">getMessage</a> , <a href="#">getStackTrace</a> , <a href="#">getSuppressed</a> , <a href="#">initCause</a> , <a href="#">printStackTrace</a> , <a href="#">printStackTrace</a> , <a href="#">printStackTrace</a> , <a href="#">setStackTrace</a> , <a href="#">toString</a>		
Methods inherited from class <a href="#">java.lang.Object</a>		
<a href="#">clone</a> , <a href="#">equals</a> , <a href="#">finalize</a> , <a href="#">getClass</a> , <a href="#">hashCode</a> , <a href="#">notify</a> , <a href="#">notifyAll</a> , <a href="#">wait</a> , <a href="#">wait</a> , <a href="#">wait</a>		

### Constructor Details

UnauthorizedException
<pre>public UnauthorizedException(<a href="#">String</a> message)</pre>
Constructor simple
<b>Parameters:</b>

message - mensaje de error

### UnauthorizedException

```
public UnauthorizedException(String message,
                             String reason)
```

Constructor con razón personalizada

**Parameters:**

message - mensaje de error

reason - razón por la que no está autenticado

### Method Details

#### getReason

```
public String getReason()
```