

Project Configuration Report

bt_cs_soc_initiator

Target Device:

Target Part: EFR32MG24B210F1536IM48

Boards:

Target SDK

Simplicity SDK Suite v2025.6.0: Bluetooth 10.0.0, Bluetooth Mesh 9.0.0, Connect 4.1.0.0, EmberZNet 8.2.0.0, Micrium OS Kernel 5.18.00, OpenThread 2.7.0.0 (GitHub-fb0446f53), Platform 5.2.0.0, RAIL 2.19.0, Silicon Labs Matter 2.6.0-1.4, USB 1.5.0.0, Wi-Fi SDK 3.5.0, Wi-SUN 2.6.0.0, Z-Wave SDK 7.24.0.0
SDK Version: 2025.6.0

Extensions

- WiSeConnect 3 3.5.0
- Silicon Labs Matter 2.6.0

Project Generators

- Simplicity IDE Project

Installed Software Components:

- Application
 - Utility
 - Assert**
Configurable: true
Configs: app_assert_config.h
 - Log**
Sources: app_log.c
Configurable: true
Configs: app_log_config.h
- Bluetooth
 - Application
 - Miscellaneous
 - BLE Peer Manager Central**
Sources: ble_peer_manager_central.c
Configurable: true
Configs: ble_peer_manager_central_config.h
 - BLE Peer Manager Common**
Sources: ble_peer_manager_connections.c
Configurable: true

Configs: ble_peer_manager_common_config.h

BLE Peer Manager Filter

Sources: ble_peer_manager_filter.c

Configurable: true

Configs: ble_peer_manager_filter_config.h

CS Antenna

Sources: cs_antenna.c

Configurable: false

CS Initiator

Sources: cs_initiator_extract.c, cs_initiator_state_machine.c, cs_initiator_client.c, cs_initiator_estimate.c, cs_initiator.c, cs_initiator_error.c

Configurable: true

Configs: cs_initiator_config.h

CS Initiator Display

Sources: cs_initiator_display.c, cs_initiator_display_core.c, cs_initiator_display_stubs.c

Configurable: true

Configs: cs_initiator_display_config.h

IO Stream interface over BGAPI Trace

Sources: iostream_bgapi_trace.c

Configurable: false

- Bluetooth Host (Stack)

Bluetooth Core

Sources: sl_bt_stack_init.c

Configurable: true

Configs: sl_bluetooth_config.h

Static GATT Database and Configuration

Configurable: true

Configs: gatt_configuration.btconf

• Additional Features

BGAPI Trace utility

Sources: sli_bgapi_trace.c

Configurable: true

Configs: sl_bgapi_trace_config.h

- Features with Commands and Events

Device filtering with Bluetooth controller's Filter Accept List

Configurable: true

Configs: sl_bt_accept_list_config.h

GAP

Configurable: false

Security Manager

Configurable: false

System

Configurable: false

- Bluetooth LE Controller (Link Layer)

- Additional Features

Bluetooth controller anchor selection

Configurable: true

Configs: sl_btctrl_anchor_selection_config.h

- Features with Commands and Events

Connection in the Central role

Configurable: false

Scanner for extended advertisements

Configurable: false

- Platform

- Board

Board Control

Sources: sl_board_control_gpio.c, sl_board_control_stub.c, sl_board_init.c

Configurable: true

Configs: sl_board_control_config.h

- Board Drivers

Configuration Over SWO

Sources: sl_cos.c

Configurable: false

MX25 Flash Shutdown with eusart

Sources: sl_mx25_flash_shutdown.c

Configurable: true

Configs: sl_mx25_flash_shutdown_eusart_config.h

- Device

- EFR32MG24

EFR32MG24B210F1536IM48

Sources: startup_efr32mg24.c, system_efr32mg24.c

Configurable: true

Configs: device.yaml

- Driver

- LED

Simple LED

Configurable: true

Configs: sl_simple_led_led1_config.h, sl_simple_led_led0_config.h

- SPI

SPIDRV EUSART

Configurable: true

Configs: sl_spidrv_eusart_inst_config.h

- Peripheral

- EMLIB

IADC

Sources: em_iadc.c

Configurable: false

- HAL

IADC

Sources: sl_hal_iadc.c

Configurable: false

- Security

- Mbed TLS

- Authenticated Encryption

CCM

Sources: ccm.c

Configurable: false

- Memory Protection Unit

Simple MPU

Sources: sl_mpu_s3.c, sl_mpu_s2.c

Configurable: false

- PSA Crypto

- Signatures

Deterministic ECDSA

Configurable: false

- Toolchain

GCC Toolchain

Configurable: false

- Utilities

Component Catalog

Configurable: false

• **Services**

- Clock Manager

Clock Manager

Sources: sl_clock_manager_init.c

Configurable: true

Configs: sl_clock_manager_oscillator_config.h, sl_clock_manager_ext_flash_config.h,
sl_clock_manager_tree_config.h

- Device Initialization

Automatic Device Initialization

Configurable: false

- IO Stream

IO Stream: Recommended Stream

Configurable: false

• **Driver**

IO Stream: USART

Configurable: true

Configs: sl_iostream_usart_vcom_config.h

- System Setup

System Setup (sl_main)

Configurable: true

Configs: sl_main_start_task_config.h

Pins:

Peripherals:

Peripheral	Software Component	Custom Peripheral Name
ACMP0		
ACMP1		
CMU	Clock Manager	
EUSART0	SPIDRV EUSART (inst)	
EUSART1	SPIDRV EUSART (inst)	
GPIO	SWO Debug	

HFXO0		
I2C0		
I2C1		
IADC0		
KEYSCAN		
LETIMER0		
LFXO		
MODEM		
PCNT0		
PRS Channel ASYNCH0		
PRS Channel ASYNCH1		
PRS Channel ASYNCH10		
PRS Channel ASYNCH11		
PRS Channel ASYNCH12		
PRS Channel ASYNCH13		
PRS Channel ASYNCH14		
PRS Channel ASYNCH15		
PRS Channel ASYNCH2		
PRS Channel ASYNCH3		
PRS Channel ASYNCH4		
PRS Channel ASYNCH5		
PRS Channel ASYNCH6		
PRS Channel ASYNCH7		
PRS Channel ASYNCH8		
PRS Channel ASYNCH9		
PRS Channel SYNCH0		
PRS Channel SYNCH1		
PRS Channel SYNCH2		
PRS Channel SYNCH3		
PTI		
TIMER0		
TIMER1		
TIMER2		
TIMER3		
TIMER4		
USART0	IO Stream: USART (vcom)	
VDAC0		
VDAC1		