



Swagger Petstore

## Overview

This is a sample server Petstore server.

Learn about [Swagger](#) or join the IRC channel [#swagger](#) on [irc.freenode.net](#).

For this sample, you can use the api key [special-key](#) to test the authorization filters

## Version information

*Version* : 1.0.0

## Contact information

*Contact* : [apiteam@swagger.io](mailto:apiteam@swagger.io)

## License information

*License* : Apache 2.0

*License URL* : <http://www.apache.org/licenses/LICENSE-2.0.html>

*Terms of service* : <http://helloverb.com/terms/>

## URI scheme

*Host* : petstore.swagger.io

*BasePath* : /v2

*Schemes* : HTTP

## Tags

- pet : Pet resource
- store : Store resource
- user : User resource

## Paths

### Add a new pet to the store

POST /pets

#### Parameters

Type	Name	Description	Schema
Body	<b>body</b> <i>optional</i>	Pet object that needs to be added to the store	<a href="#">Pet</a>

#### Responses

HTTP Code	Description	Schema
405	Invalid input	No Content

#### Consumes

- `application/json`
- `application/xml`

#### Produces

- `application/json`
- `application/xml`

#### Tags

- pet

#### Security

Type	Name	Scopes
oauth2	<a href="#">petstore_auth</a>	write_pets,read_pets

#### Example HTTP request

## Request path

```
/pets
```

## Request body

```
{
  "id" : 0,
  "category" : {
    "id" : 0,
    "name" : "FoobarCategory"
  },
  "name" : "doggie",
  "photoUrls" : [ "string" ],
  "tags" : [ {
    "id" : 0,
    "name" : "string"
  } ],
  "status" : "string"
}
```

## Update an existing pet

PUT /pets

### Parameters

Type	Name	Description	Schema
Body	<b>body</b> <i>optional</i>	Pet object that needs to be added to the store	<a href="#">Pet</a>

### Responses

HTTP Code	Description	Schema
400	Invalid ID supplied	No Content
404	Pet not found	No Content
405	Validation exception	No Content

### Consumes

- `application/json`
- `application/xml`

### Produces

- `application/json`
- `application/xml`

### Tags

- pet

### Security

Type	Name	Scopes
oauth2	<a href="#">petstore_auth</a>	write_pets,read_pets

### Example HTTP request

## Request path

```
/pets
```

## Request body

```
{
  "id" : 0,
  "category" : {
    "id" : 0,
    "name" : "FoobarCategory"
  },
  "name" : "doggie",
  "photoUrls" : [ "string" ],
  "tags" : [ {
    "id" : 0,
    "name" : "string"
  } ],
  "status" : "string"
}
```

## Finds Pets by status

GET /pets/findByStatus

### Description

Multiple status values can be provided with comma seperated strings

### Parameters

Type	Name	Description	Schema
Query	<b>status</b> <i>optional</i>	Status values that need to be considered for filter	< string > array(multi)

### Responses

HTTP Code	Description	Schema
200	successful operation <b>Headers :</b> <b>X-Rate-Limit-Limit</b> (integer) : The number of allowed requests in the current period. <b>X-Rate-Limit-Remaining</b> (integer) : The number of remaining requests in the current period. <b>X-Rate-Limit-Reset</b> (integer) : The number of seconds left in the current period.	< <a href="#">Pet</a> > array
400	Invalid status value	No Content

### Produces

- [application/json](#)
- [application/xml](#)

### Tags

- pet

### Security

Type	Name	Scopes
oauth2	<a href="#">petstore_auth</a>	write_pets,read_pets

## Example HTTP request

### Request path

```
/pets/findByStatus
```

### Request query

```
{  
  "status" : "string"  
}
```

## Example HTTP response

### Response 200

```
"array"
```



## Finds Pets by tags

GET /pets/findByTags

### Description

Multiple tags can be provided with comma separated strings. Use tag1, tag2, tag3 for testing.

### Parameters

Type	Name	Description	Schema
Query	<b>tags</b> <i>optional</i>	Tags to filter by	< string > array(multi)

### Responses

HTTP Code	Description	Schema
200	successful operation <b>Headers :</b> <b>X-Rate-Limit-Limit</b> (integer) : The number of allowed requests in the current period. <b>X-Rate-Limit-Remaining</b> (integer) : The number of remaining requests in the current period. <b>X-Rate-Limit-Reset</b> (integer) : The number of seconds left in the current period.	< <a href="#">Pet</a> > array
400	Invalid tag value	No Content

### Produces

- [application/json](#)
- [application/xml](#)

### Tags

- pet

### Security

Type	Name	Scopes
oauth2	<a href="#">petstore_auth</a>	write_pets,read_pets

## Example HTTP request

### Request path

```
/pets/findByTags
```

### Request query

```
{  
  "tags" : "string"  
}
```

## Example HTTP response

### Response 200

```
"array"
```

## Updates a pet in the store with form data

POST /pets/{petId}

### Parameters

Type	Name	Description	Schema
Path	<b>petId</b> <i>required</i>	ID of pet that needs to be updated	string
FormData	<b>name</b> <i>required</i>	Updated name of the pet	string
FormData	<b>status</b> <i>required</i>	Updated status of the pet	string

### Responses

HTTP Code	Description	Schema
405	Invalid input	No Content

### Consumes

- `application/x-www-form-urlencoded`

### Produces

- `application/json`
- `application/xml`

### Tags

- pet

### Security

Type	Name	Scopes
oauth2	<a href="#">petstore_auth</a>	write_pets,read_pets

### Example HTTP request

### Request path

```
/pets/string
```

### Request formData

```
"string"
```

## Find pet by ID

```
GET /pets/{petId}
```

### Description

Returns a pet when ID < 10. ID > 10 or nonintegers will simulate API error conditions

### Parameters

Type	Name	Description	Schema
Path	<b>petId</b> <i>required</i>	ID of pet that needs to be fetched	integer(int64)

### Responses

HTTP Code	Description	Schema
200	successful operation <b>Headers :</b> <b>X-Rate-Limit-Limit</b> (integer) : The number of allowed requests in the current period. <b>X-Rate-Limit-Remaining</b> (integer) : The number of remaining requests in the current period. <b>X-Rate-Limit-Reset</b> (integer) : The number of seconds left in the current period.	<a href="#">Pet</a>
400	Invalid ID supplied	No Content
404	Pet not found	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- pet

### Security

Type	Name	Scopes
apiKey	<a href="#">api_key</a>	
oauth2	<a href="#">petstore_auth</a>	write_pets,read_pets

## Example HTTP request

### Request path

```
/pets/0
```

## Example HTTP response

### Response 200

```
{
  "id" : 0,
  "category" : {
    "id" : 0,
    "name" : "FoobarCategory"
  },
  "name" : "doggie",
  "photoUrls" : [ "string" ],
  "tags" : [ {
    "id" : 0,
    "name" : "string"
  } ],
  "status" : "string"
}
```

## Deletes a pet

```
DELETE /pets/{petId}
```

### Parameters

Type	Name	Description	Schema
Header	<b>api_key</b> <i>required</i>		string
Path	<b>petId</b> <i>required</i>	Pet id to delete	integer(int64)

### Responses

HTTP Code	Description	Schema
400	Invalid pet value	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- pet

### Security

Type	Name	Scopes
oauth2	<b>petstore_auth</b>	write_pets,read_pets

### Example HTTP request

#### Request path

```
/pets/0
```

#### Request header

"string"



## Place an order for a pet

POST /stores/order

### Parameters

Type	Name	Description	Schema
Body	<b>body</b> <i>optional</i>	order placed for purchasing the pet	<a href="#">Order</a>

### Responses

HTTP Code	Description	Schema
200	successful operation <b>Headers :</b> <b>X-Rate-Limit-Limit</b> (integer) : The number of allowed requests in the current period. <b>X-Rate-Limit-Remaining</b> (integer) : The number of remaining requests in the current period. <b>X-Rate-Limit-Reset</b> (integer) : The number of seconds left in the current period.	<a href="#">Order</a>
400	Invalid Order	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- store

### Example HTTP request

#### Request path

/stores/order

#### Request body

```
{
  "id" : 0,
  "petId" : 0,
  "quantity" : 10,
  "shipDate" : "string",
  "status" : "string",
  "complete" : true
}
```

## Example HTTP response

### Response 200

```
{
  "id" : 0,
  "petId" : 0,
  "quantity" : 10,
  "shipDate" : "string",
  "status" : "string",
  "complete" : true
}
```

## Find purchase order by ID

```
GET /stores/order/{orderId}
```

### Description

For valid response try integer IDs with value  $\leq 5$  or  $> 10$ . Other values will generated exceptions

### Parameters

Type	Name	Description	Schema
Path	<b>orderId</b> <i>required</i>	ID of pet that needs to be fetched	string

### Responses

HTTP Code	Description	Schema
200	successful operation <b>Headers :</b> <b>X-Rate-Limit-Limit</b> (integer) : The number of allowed requests in the current period. <b>X-Rate-Limit-Remaining</b> (integer) : The number of remaining requests in the current period. <b>X-Rate-Limit-Reset</b> (integer) : The number of seconds left in the current period.	Order
400	Invalid ID supplied	No Content
404	Order not found	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- store

### Example HTTP request

#### Request path

```
/stores/order/string
```

## Example HTTP response

### Response 200

```
{  
  "id" : 0,  
  "petId" : 0,  
  "quantity" : 10,  
  "shipDate" : "string",  
  "status" : "string",  
  "complete" : true  
}
```

## Delete purchase order by ID

```
DELETE /stores/order/{orderId}
```

### Description

For valid response try integer IDs with value < 1000. Anything above 1000 or nonintegers will generate API errors

### Parameters

Type	Name	Description	Schema
Path	<b>orderId</b> <i>required</i>	ID of the order that needs to be deleted	string

### Responses

HTTP Code	Description	Schema
400	Invalid ID supplied	No Content
404	Order not found	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- store

### Example HTTP request

#### Request path

```
/stores/order/string
```

## Create user

POST /users

### Description

This can only be done by the logged in user.

### Parameters

Type	Name	Description	Schema
Body	<b>body</b> <i>optional</i>	Created user object	User

### Responses

HTTP Code	Description	Schema
default	successful operation	No Content

### Produces

- application/json
- application/xml

### Tags

- user

### Example HTTP request

#### Request path

/users

#### Request body

```
{  
  "id" : 0,  
  "username" : "string",  
  "firstName" : "string",  
  "lastName" : "string",  
  "email" : "string",  
  "password" : "string",  
  "phone" : "string",  
  "userStatus" : 0  
}
```

## Creates list of users with given input array

POST /users/createWithArray

### Parameters

Type	Name	Description	Schema
Body	<b>body</b> <i>optional</i>	List of user object	< <a href="#">User</a> > array

### Responses

HTTP Code	Description	Schema
default	successful operation	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- user

### Example HTTP request

#### Request path

/users/createWithArray

#### Request body



```
[ {  
  "id" : 0,  
  "username" : "string",  
  "firstName" : "string",  
  "lastName" : "string",  
  "email" : "string",  
  "password" : "string",  
  "phone" : "string",  
  "userStatus" : 0  
} ]
```

## Creates list of users with given input array

POST /users/createWithList

### Parameters

Type	Name	Description	Schema
Body	<b>body</b> <i>optional</i>	List of user object	< <a href="#">User</a> > array

### Responses

HTTP Code	Description	Schema
default	successful operation	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- user

### Example HTTP request

#### Request path

/users/createWithList

#### Request body

```
[ {  
  "id" : 0,  
  "username" : "string",  
  "firstName" : "string",  
  "lastName" : "string",  
  "email" : "string",  
  "password" : "string",  
  "phone" : "string",  
  "userStatus" : 0  
} ]
```

## Logs user into the system

GET /users/login

### Parameters

Type	Name	Description	Schema
Query	<b>password</b> <i>optional</i>	The password for login in clear text	string
Query	<b>username</b> <i>optional</i>	The user name for login	string

### Responses

HTTP Code	Description	Schema
200	successful operation <b>Headers :</b> <b>X-Rate-Limit-Limit</b> (integer) : The number of allowed requests in the current period. <b>X-Rate-Limit-Remaining</b> (integer) : The number of remaining requests in the current period. <b>X-Rate-Limit-Reset</b> (integer) : The number of seconds left in the current period.	string
400	Invalid username/password supplied	No Content

### Produces

- application/json
- application/xml

### Tags

- user

### Example HTTP request

#### Request path

/users/login

### Request query

```
{  
  "password" : "string",  
  "username" : "string"  
}
```

### Example HTTP response

#### Response 200

```
"string"
```

## Logs out current logged in user session

GET /users/logout

### Responses

HTTP Code	Description	Schema
default	successful operation	No Content

### Produces

- application/json
- application/xml

### Tags

- user

### Example HTTP request

#### Request path

/users/logout

## Get user by user name

```
GET /users/{username}
```

### Parameters

Type	Name	Description	Schema
Path	<b>username</b> <i>required</i>	The name that needs to be fetched. Use user1 for testing.	string

### Responses

HTTP Code	Description	Schema
200	successful operation <b>Headers :</b> <b>X-Rate-Limit-Limit</b> (integer) : The number of allowed requests in the current period. <b>X-Rate-Limit-Remaining</b> (integer) : The number of remaining requests in the current period. <b>X-Rate-Limit-Reset</b> (integer) : The number of seconds left in the current period.	User
400	Invalid username supplied	No Content
404	User not found	No Content

### Produces

- application/json
- application/xml

### Tags

- user

### Example HTTP request

#### Request path

```
/users/string
```

## Example HTTP response

### Response 200

```
{
  "id" : 0,
  "username" : "string",
  "firstName" : "string",
  "lastName" : "string",
  "email" : "string",
  "password" : "string",
  "phone" : "string",
  "userStatus" : 0
}
```



## Updated user

```
PUT /users/{username}
```

### Description

This can only be done by the logged in user.

### Parameters

Type	Name	Description	Schema
Path	<b>username</b> <i>required</i>	name that need to be deleted	string
Body	<b>body</b> <i>optional</i>	Updated user object	<a href="#">User</a>

### Responses

HTTP Code	Description	Schema
400	Invalid user supplied	No Content
404	User not found	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- user

### Example HTTP request

#### Request path

```
/users/string
```

#### Request body

```
{  
  "id" : 0,  
  "username" : "string",  
  "firstName" : "string",  
  "lastName" : "string",  
  "email" : "string",  
  "password" : "string",  
  "phone" : "string",  
  "userStatus" : 0  
}
```

## Delete user

```
DELETE /users/{username}
```

### Description

This can only be done by the logged in user.

### Parameters

Type	Name	Description	Schema
Path	<b>username</b> <i>required</i>	The name that needs to be deleted	string

### Responses

HTTP Code	Description	Schema
400	Invalid username supplied	No Content
404	User not found	No Content

### Produces

- `application/json`
- `application/xml`

### Tags

- user

### Example HTTP request

#### Request path

```
/users/string
```

## Definitions

### Category

Name	Description	Schema
<b>id</b> <i>optional</i>	<b>Example :</b> 0	integer(int64)
<b>name</b> <i>optional</i>	The name of the category <b>Default :</b> "DefaultCategory" <b>Length :</b> 0 - 255 <b>Pattern :</b> "[A-Za-zäöüÄÖÜß]{0,255}" <b>Example :</b> "FoobarCategory"	string

### Order

Name	Description	Schema
<b>complete</b> <i>optional</i>	<b>Example :</b> true	boolean
<b>id</b> <i>optional</i>	<b>Example :</b> 0	integer(int64)
<b>petId</b> <i>optional</i>	<b>Example :</b> 0	integer(int64)
<b>quantity</b> <i>optional</i>	<b>Default :</b> 0 <b>Minimum value :</b> 0 <b>Maximum value :</b> 10000 <b>Example :</b> 10	integer(int32)
<b>shipDate</b> <i>optional</i>	<b>Example :</b> "string"	string(date-time)
<b>status</b> <i>optional</i>	Order Status <b>Example :</b> "string"	enum (Ordered, Cancelled)

### Pet

Name	Description	Schema
<b>category</b> <i>optional</i>	<b>Example :</b> "Category"	Category
<b>id</b> <i>optional</i>	<b>Example :</b> 0	integer(int64)
<b>name</b> <i>required</i>	<b>Example :</b> "doggie"	string
<b>photoUrls</b> <i>required</i>	<b>Example :</b> [ "string" ]	< string > array

Name	Description	Schema
<b>status</b> <i>optional</i>	pet status in the store, <b>Example :</b> <code>"string"</code>	enum (Dead, Alive)
<b>tags</b> <i>optional</i>	<b>Example :</b> <code>[ "Tag" ]</code>	< <code>Tag</code> > array

## Tag

Name	Description	Schema
<b>id</b> <i>optional</i>	<b>Example :</b> <code>0</code>	integer(int64)
<b>name</b> <i>optional</i>	<b>Example :</b> <code>"string"</code>	string

## User

Name	Description	Schema
<b>email</b> <i>optional</i>	<b>Example :</b> <code>"string"</code>	string
<b>firstName</b> <i>optional</i>	<b>Example :</b> <code>"string"</code>	string
<b>id</b> <i>optional</i>	<b>Example :</b> <code>0</code>	integer(int64)
<b>lastName</b> <i>optional</i>	<b>Example :</b> <code>"string"</code>	string
<b>password</b> <i>optional</i>	<b>Example :</b> <code>"string"</code>	string
<b>phone</b> <i>optional</i>	<b>Example :</b> <code>"string"</code>	string
<b>userStatus</b> <i>optional</i>	User Status <b>Example :</b> <code>0</code>	integer(int32)
<b>username</b> <i>optional</i>	<b>Example :</b> <code>"string"</code>	string

## Security

### petstore\_auth

Type : oauth2

Flow : implicit

Token URL : <http://petstore.swagger.io/api/oauth/dialog>

Name	Description
write_pets	modify pets in your account
read_pets	read your pets

### api\_key

Type : apiKey

Name : api\_key

In : HEADER