

Install Oracle AI Database 26ai (23.26.1) for Linux x86-64

Pre-requisites already been taken care like memory, swap, kernel parameters, add groups, profile and users...etc

Table of Contents

1. Hardware Requirements
2. Verify OS version
3. Download 19c db software
4. Oracle Installation Prerequisites
5. Unzip
6. Invoke ./runInstaller
7. Verify

1. Hardware Requirements

The first thing we need to verify the hardware requirements

– Check Physical RAM.

```
[root@lxicborasgv01 ~]# grep MemTotal /proc/meminfo
MemTotal:          17516840 kB
[root@lxicborasgv01 ~]#
```

– Check Swap Space.

```
[root@lxicborasgv01 ~]# grep SwapTotal /proc/meminfo
SwapTotal:         8253436 kB
[root@lxicborasgv01 ~]#
```

-- Check space available in /tmp

```
[root@lxicborasgv01 ~]# df -h /tmp
```

```
Filesystem      Size  Used Avail Use% Mounted on
/dev/mapper/ol_10-root 62G  7.2G   54G  12% /
[root@lxicborasgv01 ~]#
```

-- Check space for Oracle Software and pre-configured database.

```
[root@lxicborasgv01 ~]# df -h /u01
Filesystem      Size  Used Avail Use% Mounted on
/dev/mapper/ol_10-home 30G  246M   30G   1% /u01
[root@lxicborasgv01 ~]#
```

-- Check CPU

```
[root@lxicborasgv01 ~]# lscpu | grep -i "CPU(s):" | head -n 1
CPU(s) :                4
[root@lxicborasgv01 ~]#
```

2. Verify OS version

```
[root@lxicborasgv01 ~]# cat /etc/redhat-release
Red Hat Enterprise Linux release 9.6 (Plow)
[root@lxicborasgv01 ~]#

[root@lxicborasgv01 ~]# cat /etc/hosts | grep -i lxicborasgv01
192.168.2.52 lxicborasgv01
[root@lxicborasgv01 ~]#
```

3. Download Software

Download the Oracle software from OTN or MY ORACLE SUPPORT (MOS).

<https://www.oracle.com/database/technologies/oracle26ai-linux-downloads.html>

4. Oracle Installation Prerequisites

[root@lxicborasgv01 ~]# **dnf install -y oracle-ai-database-preinstall-26ai**
Last metadata expiration check: 0:44:40 ago on Wed 28 Jan 2026 06:14:51 PM.
Dependencies resolved.

Package	Size	Architecture	Version
Repository			
Installing:			
oracle-ai-database-preinstall-26ai		x86_64	1.0-1.el9
ol9_appstream	34 k		
Installing dependencies:			
compat-openssl11		x86_64	1:1.1.1k-5.el9_6.1
ol9_appstream	1.5 M		

Transaction Summary

Install 2 Packages

Total download size: 1.5 M
Installed size: 3.8 M
Downloading Packages:
(1/2): oracle-ai-database-preinstall-26ai-1.0-1.el9.x86_64.rpm
295 kB/s | 34 kB 00:00
(2/2): compat-openssl11-1.1.1k-5.el9_6.1.x86_64.rpm
3.4 MB/s | 1.5 MB 00:00

Total
3.4 MB/s | 1.5 MB 00:00
Running transaction check
Transaction check succeeded.
Running transaction test
Transaction test succeeded.
Running transaction
Preparing :
1/1
Installing : compat-openssl11-1:1.1.1k-5.el9_6.1.x86_64
1/2
Installing : oracle-ai-database-preinstall-26ai-1.0-1.el9.x86_64
2/2
Running scriptlet: oracle-ai-database-preinstall-26ai-1.0-1.el9.x86_64
2/2

```
Verifying      : compat-openssl11-1:1.1.1k-5.el9_6.1.x86_64
1/2
Verifying      : oracle-ai-database-preinstall-26ai-1.0-1.el9.x86_64
2/2

Installed:
  compat-openssl11-1:1.1.1k-5.el9_6.1.x86_64                oracle-ai-database-preinstall-26ai-1.0-1.el9.x86_64

Complete!
[root@lxicborasgv01 ~]#

[root@lxicborasgv01 ~]# id oracle
uid=54321(oracle) gid=54321(oinstall) groups=54321(oinstall),54322(dba),54323(oper),54324(backupdba),54325(dgdba),54326(kmdba),54330(racdba)
[root@lxicborasgv01 ~]#
```

5. Unzip Software

NOTE: During installation using OUI, you cannot manually edit the Oracle Home location. The installer automatically detects the ORACLE_HOME from the directory where the database binaries are unzipped. Therefore, make sure to unzip the binaries directly inside the intended ORACLE_HOME directory before running ./runInstaller.

Also note that after unzipping, the files will not be placed under a single directory as in Oracle 10g, 11g, and 12c.

```
[root@lxicborasgv01 ~]# mkdir -p /u01/app/oracle/product/23.26.1/dbhome_1
[root@lxicborasgv01 ~]# chown -R oracle:oinstall /u01
[root@lxicborasgv01 ~]# chmod -R 775 /u01
[root@lxicborasgv01 ~]#

[root@lxicborasgv01 ~]# passwd oracle
Changing password for user oracle.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: all authentication tokens updated successfully.
[root@lxicborasgv01 ~]#

[oracle@lxicborasgv01 ~]$ cd /u01/app/oracle/product/23.26.1/dbhome_1/
[oracle@lxicborasgv01 dbhome_1]$ ls -ltr
total 2349668
-rw-r--r--. 1 oracle oinstall 2406058543 Jan 28 12:25 LINUX.X64_2326100_db_home.zip
[oracle@lxicborasgv01 dbhome_1]$
```

```
[oracle@lxicborasgv01 dbhome_1]$ unzip LINUX.X64_2326100_db_home.zip
Archive:  LINUX.X64_2326100_db_home.zip
  inflating: META-INF/MANIFEST.MF
  inflating: META-INF/ORACLE_C.SF
  inflating: META-INF/ORACLE_C.RSA
    creating: OPatch/
  inflating: OPatch/README.txt
    creating: OPatch/auto/
..
..
  rdbms/mesg/ocius.msg   -> ./oraus.msg
  rdbms/mesg/ocizhs.msb -> orazhs.msb
  rdbms/mesg/ocizht.msb -> orazht.msb
[oracle@lxicborasgv01 dbhome_1]$
```





6. Invoke `./runInstaller`



Start the Oracle Universal Installer (OUI) by issuing the following command.

```
[oracle@lxicborasgv01 ~]$ cd /u01/app/oracle/product/23.26.1/dbhome_1/
```

```
[oracle@lxicborasgv01 dbhome_1]$ ./runInstaller
```

Launching Oracle AI Database Setup Wizard...





```
[root@lxicborasgv01 ~]# /u01/app/oraInventory/orainstRoot.sh
Changing permissions of /u01/app/oraInventory.
Adding read,write permissions for group.
Removing read,write,execute permissions for world.

Changing groupname of /u01/app/oraInventory to oinstall.
The execution of the script is complete.
[root@lxicborasgv01 ~]#
[root@lxicborasgv01 ~]# /u01/app/oracle/product/23.26.1/dbhome_1/root.sh
```

Performing root user operation.

The following environment variables are set as:

ORACLE_OWNER= oracle

ORACLE_HOME= /u01/app/oracle/product/23.26.1/dbhome_1

Enter the full pathname of the local bin directory: [/usr/local/bin]:

Copying dbhome to /usr/local/bin ...

Copying oraenv to /usr/local/bin ...

Copying coraenv to /usr/local/bin ...

Creating /etc/oratab file...

Entries will be added to the /etc/oratab file as needed by

Database Configuration Assistant when a database is created

Finished running generic part of root script.

Now product-specific root actions will be performed.

[root@lxicborasgv01 ~]#

7. Verify

```
[oracle@lxicborasgv01 ~]$ export ORACLE_HOME=/u01/app/oracle/product/23.26.1/dbhome_1
[oracle@lxicborasgv01 ~]$ export PATH=$ORACLE_HOME/bin:$PATH
[oracle@lxicborasgv01 ~]$ which sqlplus
/u01/app/oracle/product/23.26.1/dbhome_1/bin/sqlplus
[oracle@lxicborasgv01 ~]$
[oracle@lxicborasgv01 ~]$ sqlplus /nolog
```

```
SQL*Plus: Release 23.26.1.0.0 - Production on Wed Jan 28 21:15:21 2026
Version 23.26.1.0.0
```

```
Copyright (c) 1982, 2025, Oracle. All rights reserved.
```

```
SQL>
```

Caution: *Your use of any information or materials on this website is entirely at your own risk. It is provided for educational purposes only. It has been tested internally, however, we do not guarantee that it will work for you. Ensure that you run it in your test environment before using.*

Thank you,

Rajasekhar Amudala

Email: br8dba@gmail.com

WhatsApp : +

Linkedin: <https://www.linkedin.com/in/rajasekhar-amudala/>