

Sheet: /MCU/
File: MCU.kicad_sch

Title:


Size: A4 Date:


KiCad E.D.A. 9.0.4

Rev:

Id: 2/8

BMS Protection Board for 3S Battery Pack
In/Out: min voltage: 9.6 V, nominal voltage: 11.1 V, max voltage: 12.6 V
Output: 20A continuous discharge current
Min Each Cell set to 3.2 V, Max Each Cell set to 4.2 V





Sheet: /Motor Control Board/
File: Motor Control Board.kicad_sch

Title:


Size: A4

Date:

KiCad E.D.A. 9.0.4

Rev:


Id: 5/8




Id: 6/8

(1) Red	motor power (connects to one motor terminal)
(2) Black	motor power (connects to the other motor terminal)
(3) Green	encoder GND
(4) Blue	encoder Vcc (3.5 – 20 V)
(5) Yellow	encoder A output
(6) White	encoder B output

- TP13○ ENC_GND
- TP14○ MOTOR1_TERMINAL1
- TP15○ MOTOR1_TERMINAL2
- TP16○ ENCODER1_OUTPUT1_5V
- TP17○ ENCODER1_OUTPUT2_5V
- TP18○ MOTOR2_TERMINAL1
- TP19○ MOTOR2_TERMINAL2
- TP20○ ENCODER2_OUTPUT1_5V
- TP21○ ENCODER2_OUTPUT2_5V
- TP22○ ENCODER1_OUTPUT1
- TP23○ ENCODER1_OUTPUT2
- TP24○ ENCODER2_OUTPUT1
- TP25○ ENCODER2_OUTPUT2



Input has to be 5V, output has to be 3V3



Sheet: /Motor Control Board/Optical Encoder Headers/
File: Optical Encoder Headers.kicad_sch

Title:


Size: A4

Date:

Rev:

KiCad E.D.A. 9.0.4

Id: 7/8




Sheet: /Motor Control Board/Motor Drivers/
File: Motor Drivers.kicad_sch

Title:

Size: A4
KiCad E.D.A. 9.0.4

Date:

Rev:
Id: 8/8



Id: 9/8