LocoManiLab: A Unified Testbed for Data, Policies, Controllers, and Deployment in Humanoid Loco-Manipulation

Dewei Wang[1,2,*,§], **Jinrui Han**[1,3,*,§], **Jiyuan Shi**[1,*], **Chenyun Zhang**[1], **Xianbo Lu**[1,4], **Jiabao Wu**[5], **Jiqin Feng**[1,2], **Jipeng Kong**[6], **Ping Luo**[3], **Chenjia Bai**[1,7,†], **Xuelong Li**[1,†]

[1]Institute of Artificial Intelligence (TeleAI), China Telecom
[2]University of Science and Technology of China
[3]The University of Hong Kong
[4]Zhejiang University
[5]Shanghai Jiao Tong University
[6]ShanghaiTech University
[7]Gamma Robotics
[*]Equal contribution [§]Co-project leaders [†]Corresponding authors

Humanoid robots must coordinate locomotion and manipulation in everyday environments, yet progress is difficult to assess across differing policies, controllers, and task settings. LocoManiLab provides an integrated testbed spanning data collection and generation, policy training, evaluation, and physical deployment. Its task suite covers 234 atomic and compositional tasks across five household scene categories, supported by 51.5 hours of simulated teleoperation. The evaluation covers twelve policies with a shared controller across task and scene splits and perturbation levels, two policies across five controllers, and studies of demonstration scale and data-source mixtures. Success rates fall on unseen tasks and scenes and generally decline as visual perturbations increase, with differences in generalization and robustness across policies. For data generation, a humanoid motion generation model is fine-tuned for loco-manipulation to study the alignment of its outputs with task execution requirements and its integration into the data generation pipeline. Three simulated loco-manipulation tasks closely match real-world setups, enabling evaluation of three policies in both domains. Similar policy rankings support the reliability of simulation-based evaluation.

Date: October 20, 2026
Project: https://locomanilab.github.io/

Keywords. Humanoid Robots, Imitation Learning, Performance Evaluation and Benchmarking, Humanoid Loco-Manipulation.

1 Introduction

Humanoid robots combine navigation, posture changes, and manipulation to act throughout human environments. Most systems use a high-level policy to map vision and language to intermediate commands (Wei et al., 2026a; Shi et al., 2026; Hu et al., 2026; Jiang et al., 2026), which a whole-body controller realizes under balance, contact, and actuator constraints (Luo et al., 2026; Li et al., 2025a; Shi et al., 2025; Liu et al., 2026). Evaluated behavior consequently depends on the policy–controller pairing, its command interface, and the data used to train it. Evaluating humanoid loco-manipulation across different policy–controller pairings requires a large, diverse set of humanoid-specific tasks and a comprehensive evaluation platform with standardized protocols.

Existing work has advanced humanoid evaluation through broader task coverage (Sferrazza et al., 2024; Wei et al., 2026b), demonstration generation (Lin et al., 2026a), physical deployment (Hu et al., 2026), and transfer



Figure 1 Overview of the benchmark. Scene categories span kitchens, living rooms, bedrooms, bathrooms, and offices, with affordances including articulated appliances, drawers, object placement, and desk interactions. Data collection combines teleoperation with controller-executed motion generation, while dedicated interfaces connect policies to compatible controllers. Evaluation measures task completion and execution quality on seen tasks, unseen tasks and scenes, and under domain randomization, with a shared workflow.

across controllers (Wang et al., 2026b). However, these complementary efforts leave a need for a unified framework that assesses performance across a large and diverse set of tasks and execution quality while accounting for policy, controller, and demonstration choices. Similar task-success rates can conceal differences in stability and effort, while performance on familiar tasks alone does not establish generalization to new tasks or scenes. Household tasks provide a representative setting for such evaluation because they closely couple navigation, posture adaptation, and manipulation. Opening a drawer, for example, requires the robot to approach the handle, establish a suitable stance, and maintain stable contact during manipulation. Long-horizon tasks further require skills to compose through the physical states left by preceding actions. Successful navigation can still leave the robot poorly positioned for the subsequent reach or manipulation. These demands make household tasks well suited to evaluating both individual skills and their composition, together with the motion quality arising from policy–controller coordination. Motivated by these requirements, LocoManiLab provides a comprehensive humanoid loco-manipulation testbed that combines diverse household tasks with standardized evaluation protocols to study policies, their execution interfaces between controllers, and their dependence on demonstrations. Fig. 1 summarizes the testbed. Its four main contributions are as follows.

Unified testbed. The testbed provides a large and diverse suite of humanoid loco-manipulation tasks. A shared episode format and controller-specific adapters integrate data collection and generation, policy training, controller execution, and evaluation across simulation and hardware.

Policy and controller. Twelve policies, including vision-language-action (VLA) models, world-action models (WAMs), and an imitation-learning baseline, are evaluated under a shared whole-body controller. A complementary study evaluates two VLA models across five whole-body controllers, assessing both task completion and execution quality.

Tasks and demonstrations. The task suite comprises 234 atomic and compositional tasks across five household scene categories, supported by 51.5 hours of simulated teleoperation. Motion synthesis and trajectory augmentation provide additional demonstration sources, whose downstream utility is evaluated separately from data generator adaptation.

Benchmarking and deployment. Evaluation distinguishes familiar tasks, unseen task definitions, unseen scenes,

Table 1 Comparison of humanoid loco-manipulation systems.

System	Sim data (h)	Real data (h)	Sim tasks	Policies	Controllers	Data-gen.	Hardware deployment
HumanoidBench (Sferrazza et al., 2024)	–	–	27	–	–	–	–
SIMPLE (Wei et al., 2026b)	3.0	7.9	60	9	2	✓	✓
HumanoidArena (Wang et al., 2026b)	∼5.0	–	7	4	2	–	–
OpenHLM (Hu et al., 2026)	–	–	–	3	2	–	✓
LocoManiLab	51.5	9.0	234	12	5	✓	✓

and visual randomization, with dedicated studies of demonstration scale and source mixtures. Three policies are evaluated on three matched tasks in simulation and the real world.

The results show that policy rankings on familiar tasks largely hold on unseen tasks and scenes, whereas absolute success drops sharply under these shifts. Policy rankings can change with perturbation level and controller choice, while higher task success does not necessarily imply better motion quality. The benefits of additional demonstrations and mixed data sources vary across policies and tasks, while fine-tuning the motion generator improves motion generation and task success. These findings motivate evaluating generalization, execution quality, and data utility as distinct but connected dimensions. Table 1 compares LocoManiLab with existing simulation-based humanoid loco-manipulation evaluation platforms across key dimensions, including demonstration scale, task suite, policy and controller coverage, data generation, and hardware deployment.

2 Related Work

2.1 Humanoid Whole-Body Controllers

Whole-body controllers enable pose-based teleoperation (He et al., 2025b,c), decoupled locomotion and manipulation (Li et al., 2025a; Shi et al., 2025), and general motion tracking through diverse training references and architectures (Chen et al., 2025b; Han et al., 2025; Luo et al., 2026; Liu et al., 2026; Zeng et al., 2026). Recent work also distills specialist skills into a vision-based generalist locomotion policy (Wang et al., 2026a). Related studies investigate whole-body bilateral teleoperation and learning task priorities from demonstrations for humanoid loco-manipulation (Ramos and Kim, 2018; Silvério et al., 2019), as well as object-aware mobile manipulation with a wheeled humanoid (Baek et al., 2026). Across these systems, command interfaces range from velocity and arm targets to full-body references and learned motion tokens, shaping both policy training and execution. These interfaces determine how motion decisions are divided between the policy and controller. Velocity commands delegate gait control to the controller, whereas control through reference motions requires denser and richer control signals. Comparing these systems therefore requires reporting command representations alongside task success and motion quality. LocoManiLab makes these interfaces explicit and supports policy evaluation with five whole-body controllers.

2.2 Humanoid Whole-Body Loco-Manipulation

Motion-driven methods acquire humanoid loco-manipulation skills from human motions and interaction demonstrations (Weng et al., 2025; Wang et al., 2025; Lin et al., 2026b). Physics-aware whole-body control also supports dynamic humanoid–object interaction such as skateboarding (Han et al., 2026). Generation-based approaches predict whole-body motion for execution through tracking controllers (Wang et al., 2026c), while planning-based methods construct loco-manipulation trajectories for policy learning (Lin et al., 2026a). General-purpose VLAs transfer visual and language representations to robot action (Black et al., 2025; NVIDIA et al., 2025; Shukor et al., 2025; Zheng et al., 2026; Chen et al., 2025a). Humanoid VLA systems extend this approach to whole-body loco-manipulation, including learning from egocentric human video (Wei et al., 2026a; Shi et al., 2026; Jiang et al., 2026). WAMs offer another route to general-purpose control by jointly learning visual dynamics and actions (Ye et al., 2026b; Yuan et al., 2026). Despite these advances, comprehensive evaluation of VLA and WAM-based humanoid loco-manipulation systems remains limited. LocoManiLab systematically evaluates policies under shared task protocols, assessing task success, generalization, and execution quality across controller and training data configurations.

2.3 Benchmarks for Manipulation and Loco-Manipulation

Manipulation benchmarks provide reusable task suites, diverse scenes, and protocols for evaluating generalization (James et al., 2020; Liu et al., 2023; Nasiriany et al., 2024; Tao et al., 2025; Nasiriany et al., 2026). Cross-embodiment datasets and simulation–hardware comparisons highlight the importance of explicit data and evaluation conventions (Open X-Embodiment Collaboration, 2024; Li et al., 2025b), while benchmark audits show that model rankings can depend on action representation and environment (Guruprasad et al., 2024). Complementary studies develop simulation-to-real evaluation protocols for contact-rich visuotactile manipulation and use imperfect simulation to reduce the physical trials required for policy tuning (Chen et al., 2024; He et al., 2025a). For humanoid robots, HumanoidBench (Sferrazza et al., 2024) covers locomotion and whole-body manipulation, SIMPLE (Wei et al., 2026b) evaluates multiple policy families, including imitation-learning baselines, and HumanoidArena (Wang et al., 2026b) examines controller-dependent transfer. OpenHLM (Hu et al., 2026) further evaluates policies and controllers on hardware. Together, these studies highlight the need to report both task coverage and the execution configurations underlying benchmark scores. LocoManiLab brings policy coverage, controller-dependent execution, and demonstration choices into a shared evaluation framework.

3 LocoManiLab

3.1 Overview

LocoManiLab provides a unified testbed for humanoid loco-manipulation, connecting demonstration acquisition, policy learning, controller execution, and evaluation. The task suite covers both atomic and compositional behaviors, supported by teleoperated demonstrations, motion synthesis, and trajectory augmentation. Shared data workflows and policy–controller adapters connect these demonstration sources to training and deployment while accommodating different observation and action representations. The benchmark compares twelve policies spanning VLAs, WAMs, and an imitation-learning baseline under a shared whole-body controller, complemented by a study of two VLA policies across five controllers. Evaluation measures both task completion and motion quality, examining generalization to unseen tasks and scenes, robustness to visual perturbations, and the influence of controller choice on execution. Further studies investigate demonstration scale, data-source mixtures, and motion generator fine-tuning, while corresponding simulation and real-world tasks provide evidence of policy performance across both domains. Together, these components support systematic comparisons of humanoid loco-manipulation systems and the data and execution choices underlying their performance. To support these evaluations, the benchmark includes simulated household environments with diverse room layouts and interactive objects. The scenes run in MuJoCo (Todorov et al., 2012) and combine objects and fixtures from RoboCasa (Nasiriany et al., 2024) and Objaverse (Deitke et al., 2023) with room layouts from MolmoSpaces' iTHOR-derived scenes (Kim et al., 2026) and Holodeck offices (Yang et al., 2024).

3.2 Policies and Controllers

LocoManiLab evaluates twelve policies across three categories, comprising ten pretrained VLAs such as $\pi_{0.5}$ (Black et al., 2025), WAMs such as Fast-WAM (Yuan et al., 2026), and an imitation-learning baseline based on Diffusion Policy (Chi et al., 2025). Table 2 lists all evaluated policies. Each policy is trained separately for atomic and compositional tasks, with model adaptations, training configurations, and preprocessing detailed in Appendix B.

Policies use egocentric RGB observations and G1 proprioception where supported to predict action chunks for a compatible whole-body controller. Adapters connect policy inference to controller execution by handling observation processing, action representations, and normalization for each pairing. The main comparison uses SONIC motion tokens and finger targets, while the controller study trains policies for the respective controller interfaces. A shared driver delivers commands at 50 Hz, allowing policies to specify the intended behavior while controllers realize coordinated body motion. The supported controllers differ in how they represent these commands, ranging from base and arm targets to whole-body references and learned motion tokens.

The testbed integrates five whole-body controllers with complementary control strategies:

- AMO (Li et al., 2025a) coordinates learned locomotion and torso control with arm-motion control, allowing manipulation while maintaining balance.
- SONIC (Luo et al., 2026) learns a shared motion representation through large-scale motion tracking, supporting diverse whole-body behaviors with a unified control policy.
- HEFT (Liu et al., 2026) learns robust whole-body tracking from noisy teleoperation references using privileged motion guidance and a payload curriculum.
- ALMI (Shi et al., 2025) coordinates lower-body locomotion and upper-body motion imitation through adversarial training between the two policies.
- ScaleBFM (Zeng et al., 2026) scales whole-body motion tracking through diverse reference data and a Humanoid Transformer architecture.

Observations and commands are recorded at 50 Hz for all five controllers, with finger targets handled alongside the body-control interface. The recorded state contains 43 measured joint positions for SONIC, HEFT, ALMI, and ScaleBFM. AMO uses a 32-entry layout containing 28 measured arm-and-hand joints and four previous torso-command entries. Appendix B-B describes the policy-specific selection of recorded state fields and the corresponding controller command layouts.

3.3 Task Design

The task suite spans kitchen, living-room, bedroom, bathroom, and office scenes, with 13 scene instances and 234 instructed tasks. Its 102 atomic tasks isolate skills including navigation, articulated-object interaction, picking, placing, and object reorientation. The 132 compositional tasks combine two to four primitives into longer episodes, often linking manipulation through navigation. Most compositional tasks combine atomic tasks, extending evaluation from individual skills to their coordination and long-horizon execution. For the main benchmark, policies are trained separately on two 50-task lists, each covering all five scene categories. Each checkpoint is evaluated on seen tasks, unseen tasks in training scenes, and unseen tasks in held-out scenes, testing both familiar-task execution and generalization to new tasks and environments. Split assignments are defined separately for the atomic and compositional checkpoints, with task counts reported in Table 2. Task success is determined by physical predicates, while stage annotations support demonstration collection and analysis.

3.4 Dataset

LocoManiLab combines three demonstration sources for policy learning and data-source comparisons. Teleoperation captures human-guided execution in simulation and on the physical robot, while motion synthesis produces demonstrations by executing task-conditioned whole-body motions. Trajectory augmentation adapts existing demonstrations to perturbed initial conditions and retains successful simulated executions as additional training data. The teleoperated corpus includes 51.5 hours of simulation data across five controllers and approximately 9.0 hours of real-robot data, complemented by synthesized and augmented demonstrations for selected tasks. Fig. 2 summarizes the simulated teleoperation corpus by scene, controller, trajectory duration, and body-motion patterns, characterizing its scale and behavioral diversity.

3.4.1 Data Collection

Human operators use a virtual-reality (VR) headset and hand controllers to teleoperate the humanoid through its whole-body controller, collecting task demonstrations in simulation and on the physical robot. Each episode records controller commands, measured robot states, and egocentric RGB images, with image resolutions of 320×240 in simulation and 640×480 on hardware. Simulation episodes end automatically when predefined task-specific success conditions are satisfied, while real-robot episodes are ended by the operator upon judging task completion. At the start of each simulated episode, the initial horizontal positions of the robot and movable task objects are perturbed within 5 cm and 2 cm of their nominal locations, respectively.

3.4.2 Data Generation

Motion generator adaptation. The motion generation model Kimodo (Rempe et al., 2026) is fine-tuned for task-oriented data generation. As the motion diffusion model (MDM) in Fig. 1, it generates whole-body motion chunks by iteratively denoising a motion sequence conditioned on action text, an initial motion prefix, and root or wrist targets. Kimodo is paired with a frozen whole-body controller that executes the generated references during fine-tuning and data generation. During fine-tuning, spatial commands specify a planar root-position target and a target end-effector (EEF) position represented at the wrist. Fine-tuning combines randomly sampled spatial conditions with conditions extracted from benchmark task stages in equal proportions. Random conditions sample palm goals around the robot and derive corresponding root and wrist targets. Task-derived conditions obtain navigation goals and manipulation waypoints from task definitions and scene geometry, with navigation stages using root targets alone. The denoiser is adapted using proximal policy optimization (PPO) (Schulman et al., 2017), following diffusion-policy optimization (Black et al., 2024). Each stochastic denoising transition defines a Gaussian distribution over the next motion estimate, allowing the sampled transition to be evaluated under the old and updated models. The clipped objective uses per-transition probability ratios and advantages obtained by normalizing execution rewards across motions sampled under the same condition. Rewards are computed from controller execution in an uncluttered simulator. Palm-reaching rewards depend on sustained target proximity when achieved and terminal palm-target distance otherwise, while approach rewards use terminal root-target distance with torso and waist inclination penalties. The adaptation study compares low-rank adaptation (LoRA) (Hu et al., 2022) with full denoiser fine-tuning (Full), keeping the controller and non-denoiser Kimodo components frozen.

Scene-level generation. Task demonstrations are generated by pairing the fine-tuned Kimodo model with the frozen controller in a loop that alternates motion generation and physical execution. Kimodo generates each motion chunk from current spatial targets and a prefix of the robot's executed motion, while the controller tracks the resulting reference motion in the scene. The executed motion then conditions the next chunk, with reference smoothing at chunk boundaries to support continuous execution.

For navigation, A* (Hart et al., 1968) plans a route to a standing region on an occupancy map that accounts for body and arm clearance, and the route is converted into root waypoints that preserve turns. The route is replanned from the robot's current position when drift or stalls occur. For manipulation, the pipeline uses object positions and shapes to construct a sequence of wrist targets that guide the hand toward the object, establish contact or a grasp, perform the required object motion, and release it. Contact and grasp feedback determine when to advance through this sequence and when to close or open the fingers. A language model can assist by selecting the operating hand and an interaction location from task and scene descriptions, after which geometric rules determine the wrist targets. Generation uses hand choices determined in advance and wrist targets computed from object geometry or task-specific manual annotations, without querying a language model during rollout. Successful rollouts are retained as demonstrations, with additional physical and motion-quality filtering in some collection stages.

Trajectory augmentation. Trajectory augmentation uses a single teleoperated demonstration as a motion prior for execution from perturbed initial conditions. An optional large language model (LLM) planner receives task information, initialization offsets, and feedback from previous attempts. Its structured output selects wrist-target compensation, motion-generation text and keyframe spacing, and the allowed deviation from the demonstration. A frozen controller executes the candidate motions, and task-completion and physical-validity checks determine which recordings are retained. The data-source experiment uses a fixed augmentation routine that varies the timing of body and finger commands together and perturbs robot and object initial positions, without online LLM planning.

3.4.3 Data Statistics

Fig. 2 summarizes 14,160 simulated teleoperation episodes and 51.5 hours of motion across five controllers. SONIC provides the largest collection, with atomic and compositional demonstrations across all five household scene categories. The other four controllers contribute demonstrations on ten shared bathroom tasks for comparisons across control interfaces. The SONIC recordings show increasing median episode duration and a wider spread of durations as task chains grow longer. Atomic demonstrations primarily capture object interactions with little base movement, while compositional demonstrations more frequently involve walking,




Figure 2 Teleoperation data statistics. Panels (a)–(c) describe the SONIC corpus by scene category, task-chain duration, and body motion. Duration is shown by median, interquartile range, and 5th–95th percentile. Panel (d) compares recorded execution time for 50 demonstrations per task on ten shared bathroom tasks, totaling 500 episodes per controller. Stacked segments separate atomic and compositional tasks, and bar labels give total hours.

turning, and bimanual manipulation. These motion patterns reflect the combination of navigation and object interaction in compositional tasks. For the controller comparison in Fig. 2(d), 50 demonstrations per task are selected for each controller on the same ten bathroom tasks. At this equal episode count, shorter recorded durations indicate more efficient data collection. The largest differences arise in compositional tasks, showing that the execution-time cost of collecting longer demonstrations varies across controllers.

3.5 Randomization and Real-Robot Validation

Domain randomization composes appearance, camera, and distractor perturbations separately from reset configuration. Low changes textures and lighting. Mid adds camera and material-shading changes, while High also enables distractors, lens distortion, and robot-color changes. Parameters can be overridden, so presets specify combinations rather than independent visual, geometric, and dynamics severity scales. Episode-derived seeds control sampling. Each DR episode applies the same reset randomization and seed as the corresponding episode without DR; when distractors are added, the robot and task objects are first returned to their distractor-free nominal placements before the randomization is applied. These perturbations retain task definitions while changing visual context. They complement unseen task and scene evaluation by examining appearance sensitivity separately from performance on new activities and layouts.

Three real-world tasks are designed to evaluate policy performance on a Unitree G1 humanoid, with matching tasks in simulation used to examine whether simulation-based evaluation reflects policy performance on the physical robot. The simulated tasks reproduce the corresponding activities and approximate the real-world scene layouts. Policies use the same training and inference configurations in both settings, with real teleoperation replacing simulated demonstrations for real-world training. Task completion on the physical robot is judged by a human. The comparison examines consistency in policy performance across the two settings, while differences in scene geometry and success criteria limit direct comparisons of absolute success rates.

4 Experiments

In this section, we evaluate the performance and generalization of humanoid loco-manipulation policies through systematic experiments on LocoManiLab in simulation and the real world. The main experiment compares twelve policies on seen and unseen tasks and scenes, followed by a robustness test under visual perturbations. Studies of controller choice, demonstration scale, and data sources then examine how training and execution settings affect task success and motion quality. Kimodo adaptation is evaluated through executed motion accuracy and task completion, and corresponding simulation and real-robot tasks provide a final comparison of policy performance across the two environments.

4.1 Experimental Setup

4.1.1 Policies and training

The main experiment evaluates the twelve policies introduced in Sec. 3.2, including VLA and WAM models and the Diffusion Policy baseline. All use the SONIC controller and are trained separately on an atomic task list and a compositional task list, each containing 50 tasks with ten from each scene category. Appendix A summarizes these datasets and their evaluation splits.

Each policy retains its original observation, preprocessing, action-chunk length, and optimization schedule. Every configuration uses one training run, and the main benchmark evaluates the model obtained at the end of its training budget without validation-based or test-score-based selection. The controller, demonstration scale, and data-source studies focus on GR00T N1.7 and $\pi_{0.5}$, with the task sets and training budgets specified in their respective subsections.

4.1.2 Task splits

The main benchmark evaluates 102 atomic and 132 compositional tasks. Seen-task evaluation uses the training task suite and scenes with evaluation initial states, while unseen-task evaluation introduces new tasks in familiar scenes. The unseen-scene split includes both new scenes and new task definitions, so it tests their combined effect. Splits are defined separately for the atomic and compositional checkpoints, allowing a scene to be familiar to one checkpoint and unseen by the other. Domain randomization (DR) tests robustness on seen tasks, while the controller, demonstration scale, and data-source studies evaluate the tasks and scenes used for their own training.

4.1.3 Metrics

Success rate (SR) measures completion according to each task's recorded success predicate, with aggregation weights specified for each experiment. The controller comparison also reports absolute mechanical output power, foot slip during contact, changes in body-joint targets, fall rate, and relative completion time. SR uses all evaluation episodes, while the other five metrics describe successful episodes only. Slip and action-rate calculations additionally exclude invalid motion signals. Action rate measures the magnitude of changes in commanded body-joint targets per unit time, and relative time compares completion times against a task- and policy-specific reference shared across controllers. These measures therefore characterize how successful tasks are executed, although the set of solved tasks may differ between controllers. Appendix C gives the definitions, normalization, and aggregation rules.

4.2 Main Results: Generalization and Domain Randomization

4.2.1 Seen and unseen evaluation

Table 2 compares all twelve policies without DR, using the same tasks for every policy. Atomic and compositional columns follow the semantic task labels, while each task retains the checkpoint trained on its original task list. Evaluation uses 20 trials per seen task and 10 per unseen task or scene. Scores are calculated from recorded success counts and weight tasks equally, including when combining the separately trained atomic and compositional checkpoints. Overall Avg. averages over all evaluated tasks across the three

Table 2 Success rate (%) with SONIC and no DR. Averages weight tasks equally. Bold and underlined values mark the best and second best in each column.

Policy	Seen task			Unseen task			Unseen scene			Overall Avg.
Tasks	Atom. 50	Comp. 50	Avg. 100	Atom. 46	Comp. 77	Avg. 123	Atom. 6	Comp. 5	Avg. 11	234
XR-1 (Xiaomi Robotics Team et al., 2026)	<u>85.2</u>	**75.1**	**80.2**	**23.7**	**26.1**	**25.2**	0.0	18.0	8.2	**47.9**
DM0.5 (Dexmal Team, 2026)	**90.1**	<u>65.7</u>	<u>77.9</u>	<u>16.3</u>	<u>16.8</u>	<u>16.6</u>	0.0	**34.0**	**15.5**	<u>42.7</u>
$\pi_{0.5}$ (Black et al., 2025)	84.4	51.0	67.7	12.6	13.6	13.3	<u>1.7</u>	<u>24.0</u>	<u>11.8</u>	36.5
GR00T N1.7 (NVIDIA, 2026)	82.3	54.1	68.2	11.3	11.7	11.5	<u>1.7</u>	12.0	6.4	35.5
InternVLA-A1.5 (Ma et al., 2026)	70.7	36.7	53.7	11.5	9.9	10.5	0.0	18.0	8.2	28.8
SmolVLA (Shukor et al., 2025)	73.9	17.4	45.7	6.7	2.5	4.1	<u>1.7</u>	6.0	3.6	21.8
Fast-WAM (Yuan et al., 2026)	52.8	28.6	40.7	7.8	4.2	5.5	<u>1.7</u>	4.0	2.7	20.4
PRTS (Zhang et al., 2026)	37.0	34.3	35.7	3.5	7.0	5.7	<u>1.7</u>	4.0	2.7	18.4
Ψ_0 (Wei et al., 2026a)	55.1	9.0	32.1	8.0	1.7	4.1	0.0	0.0	0.0	15.8
X-VLA (Zheng et al., 2026)	54.5	6.0	30.3	5.2	2.9	3.7	<u>1.7</u>	4.0	2.7	15.0
StarVLA-α (Ye et al., 2026a)	47.6	13.5	30.6	6.7	1.2	3.3	**5.0**	0.0	2.7	14.9
Diffusion Policy (Chi et al., 2025)	27.6	1.8	14.7	4.1	0.0	1.5	0.0	0.0	0.0	7.1

splits, and the rows are ordered by this score. The task counts in the table determine each split's contribution to the overall average.

Compositional tasks separate policies with similar atomic performance. DM0.5, XR-1, $\pi_{0.5}$, and GR00T N1.7 achieve similar success on seen atomic tasks, but XR-1 and DM0.5 have a larger advantage on compositional tasks. SmolVLA and PRTS illustrate a different change in ordering. SmolVLA performs better on atomic tasks, while PRTS performs better on compositional tasks. Atomic task rankings therefore do not fully describe performance when navigation and manipulation must be combined across several stages. Together, atomic and compositional evaluations assess both the execution of individual skills and the coordination of navigation and manipulation across multiple stages.

High seen-task success leaves many unseen tasks unsolved. All policies lose substantial performance on unseen tasks. Even XR-1, which leads both unseen atomic and compositional tasks, drops from 80.2% on seen tasks to 25.2% on unseen tasks. $\pi_{0.5}$ and GR00T N1.7 also decline sharply, and their advantage over InternVLA-A1.5 becomes much smaller on unseen tasks despite a clear gap on seen tasks. SmolVLA achieves a higher seen-task average than PRTS but falls below it on unseen tasks, showing that familiar-task rankings do not fully predict performance on new tasks. These results highlight the need to evaluate unseen-task generalization separately from proficiency on training tasks.

Generalization to unseen scenes remains limited. This split combines new task definitions with scenes excluded from training, requiring policies to handle changes in both task goals and the surrounding environment. Success remains low across all evaluated policies, with DM0.5 achieving the highest average of only 15.5%. XR-1 and InternVLA-A1.5 show a similar difference between the two categories, whereas Diffusion Policy records no successes in either category. The relatively higher success on compositional tasks may reflect the richer training experience provided by compositional demonstrations. By combining navigation and manipulation, these demonstrations expose policies to more varied viewpoints, robot configurations, and intermediate interaction states, which may help them apply learned skills in unfamiliar scenes.

4.2.2 Domain randomization on seen tasks

Table 3 evaluates the same twelve policies with SONIC on seen tasks under Low, Mid, and High perturbations. Each policy performs 20 evaluation rollouts per task at each perturbation level. As in Table 2, atomic and compositional categories follow the semantic task labels, while each task retains the checkpoint trained on its original task list. The overall score weights tasks equally and averages the three DR levels equally. The perturbation combinations are defined in Sec. 3.5 and Appendix A-A, and the comparison measures robustness during evaluation rather than the effect of training with randomization.

Stronger perturbations reduce success, but policies differ in robustness. Average success across all evaluated policies decreases at each level in both task categories. XR-1 leads both task categories at Low, but DM0.5

Table 3 Seen-task success rate (%) across DR levels. Bold marks the best value and underlining marks the second best.

Policy	Atomic			Compositional			Overall Avg.
	Low	Mid	High	Low	Mid	High	
Tasks	50	50	50	50	50	50	100
DM0.5 (Dexmal Team, 2026)	89.3	**86.9**	**83.0**	60.8	**58.5**	**42.5**	**70.2**
XR-1 (Xiaomi Robotics Team et al., 2026)	**90.0**	85.4	70.5	**71.1**	57.7	39.5	69.0
$\pi_{0.5}$ (Black et al., 2025)	83.5	81.7	78.8	44.1	40.7	34.1	60.5
GR00T N1.7 (NVIDIA, 2026)	80.1	75.3	59.8	47.6	41.6	20.7	54.2
InternVLA-A1.5 (Ma et al., 2026)	67.5	65.4	61.6	31.2	27.2	22.1	45.8
SmolVLA (Shukor et al., 2025)	68.5	66.9	58.0	15.7	13.5	8.9	38.6
Ψ_0 (Wei et al., 2026a)	48.3	43.4	38.4	8.1	6.0	4.8	24.8
Fast-WAM (Yuan et al., 2026)	36.7	28.8	28.0	19.4	15.2	15.2	23.9
StarVLA-α (Ye et al., 2026a)	41.2	32.7	25.4	11.0	9.0	3.0	20.4
PRTS (Zhang et al., 2026)	30.9	36.3	32.3	4.1	3.6	2.4	18.3
X-VLA (Zheng et al., 2026)	39.4	32.7	27.9	2.1	2.4	1.9	17.7
Diffusion Policy (Chi et al., 2025)	10.0	10.5	9.7	0.2	0.1	0.0	5.1




Figure 3 Controller comparison at 50 demonstrations per task. Each controller panel shows GR00T N1.7 and $\pi_{0.5}$ on atomic profiles with solid lines and filled circles, and compositional profiles with dashed lines and hollow diamonds. SR uses all episodes and other metrics use successful episodes only. Radial ticks show normalized values, with outward values better. Shared raw ranges, rounded to three decimals, are SR 5–79%, power 13.795–317.734 W, slip 0.093–20.911 cm/s, action rate 3.048–45.392 rad/s, falls 0–22.785%, and relative time 0.873–1.859. SR and falls use linear scales and other metrics use logarithmic scales.

loses less performance as perturbations increase and ranks first in both categories at Mid and High. On atomic tasks, $\pi_{0.5}$ also declines less than XR-1 and surpasses it at High. A policy that performs best under mild perturbations therefore need not retain its lead under stronger changes. The combined presets assess how well policies maintain task success under simultaneous changes in scene appearance, lighting, and camera conditions.

4.3 Multi-Controller Evaluation

The multi-controller evaluation compares GR00T N1.7 and $\pi_{0.5}$ with SONIC, AMO, HEFT, ALMI, and ScaleBFM on five atomic and five compositional bathroom tasks. Each policy is trained for the corresponding

controller's command representation, using separate atomic and compositional checkpoints and 50 demonstrations per task. These are the same configurations evaluated at the shared 50-demonstration budget in the demonstration scale experiment. Figure 3 shows task success and motion metrics for each policy, controller, and task category. The metrics use shared normalization ranges across all profiles, with larger radii indicating better values on each axis.

The controller with the highest success need not produce the best motion. For GR00T N1.7 on atomic tasks, ALMI achieves the highest SR but has more falls among its successful episodes than SONIC. SONIC uses the least mechanical output power during successful execution for both policies and task categories, yet other controllers achieve higher SR in several of these comparisons. These results show that task completion alone is insufficient for choosing an execution controller, as configurations with comparable success can differ in power use, stability, and motion quality. Since each policy is trained with controller-specific demonstrations and action targets, the comparison describes the resulting policy–controller pairs, including their training data and command representations.

4.4 Demonstration Scale Study

The demonstration scale study examines how the number of demonstrations used for post-training affects GR00T N1.7 and $\pi_{0.5}$ across all five controllers. The task set is the same as in the multi-controller experiment, and atomic and compositional checkpoints are trained separately. Figure 4 compares 10, 30, and 50 demonstrations per task, using nested subsets shared by the two policies within each controller. SONIC additionally includes 100 demonstrations per task, while the mean panel compares only the budgets available for all five controllers.



Figure 4 Success rate versus demonstrations per task. Atomic and compositional checkpoints are trained separately, with 100 evaluation episodes per checkpoint. SONIC additionally includes 100 demonstrations per task, with shading highlighting this budget extension. The mean panel weights the five controllers equally at their shared budgets.

Each checkpoint is evaluated on its five training tasks with 20 trials per task, and the mean panel gives each controller equal weight. The 50-demonstration results also form the controller comparison in Fig. 3. Training uses the model configurations of the main experiment in Sec. 4.2, with the number of training updates increasing in proportion to the demonstration count. Appendix D-A specifies the training schedules and normalization settings.

More demonstrations and training improve most configurations. Success increases from 10 to 50 demonstrations per task for most combinations of policy, controller, and task category. For example, GR00T N1.7's mean atomic SR rises from 33.0% to 69.8%, while $\pi_{0.5}$ improves on average in both task categories from a weaker starting point.

The benefit depends on the controller and task category. GR00T N1.7 improves substantially on atomic tasks with HEFT and ScaleBFM, whereas SONIC already performs well at the smallest budget and shows little improvement by 50 demonstrations. Controller rankings therefore change with the available training data. The atomic and compositional results also follow different trends. Between 30 and 50 demonstrations, GR00T N1.7's mean compositional SR levels off, with small decreases for three controllers, while its mean atomic SR continues to rise. Over the same interval, $\pi_{0.5}$ improves on average in both categories. Additional demonstrations and training therefore do not benefit all policy–controller pairs or both task categories equally. The SONIC extension shows that gains can also stop beyond the shared budget range. Increasing the demonstration count from 50 to 100 per task further improves $\pi_{0.5}$ on atomic tasks, with a slight decrease in compositional success.

4.5 Data Generation

The data-generation experiments examine how synthesized and augmented demonstrations affect downstream policy performance and whether fine-tuning Kimodo improves motion generation and task success. The former is evaluated through mixtures of teleoperated, synthesized, and augmented demonstrations, while the latter compares the original generator with two fine-tuned variants.

4.5.1 Data-source mixtures

GR00T N1.7 and $\pi_{0.5}$ are trained with SONIC using six combinations of teleoperation, motion synthesis, and trajectory augmentation. Each model is jointly trained and evaluated on the same 20 tasks across kitchen, living-room, bedroom, and bathroom scenes. Table 4 reports success rates for atomic and compositional tasks and an overall average that gives equal weight to each task. The augmentation demonstration starts from one teleoperated trajectory per task and varies execution timing and initial conditions, retaining successful simulated executions. Synthetic demonstrations are generated using fully fine-tuned Kimodo models and a frozen SONIC controller that executes the generated motions. Only rollouts that successfully complete the task are retained.

Mixtures concatenate the selected datasets without equalizing source counts or balancing their sampling probabilities. GR00T N1.7 samples action-window starts and $\pi_{0.5}$ samples frame starts, giving longer trajectories more opportunities to contribute training samples. The experiment therefore compares practical data combinations whose source proportions, total data volume, and training exposure differ. Appendix D-B and Appendix D-C give the mixture settings and generation details.

Augmentation helps some tasks but does not improve every policy. Teleoperation is the strongest individual source for both models and gives their highest atomic success. Adding augmentation raises GR00T N1.7's compositional SR from 56.2% to 68.8%, but slightly reduces its atomic SR, leaving the overall score nearly unchanged. For $\pi_{0.5}$, teleoperation alone performs best in both categories, and none of the tested mixtures improves on it. The benefit of augmentation is therefore specific to the evaluated model and task category.

Combining all three sources also fails to provide a consistent improvement. GR00T N1.7 performs substantially worse with all three sources than with teleoperation plus augmentation, while $\pi_{0.5}$ achieves nearly the same aggregate success with the two mixtures. Neither generated source alone matches teleoperation for either model. Successful execution of generated demonstrations thus does not guarantee that adding them will improve the trained policy.

4.5.2 Kimodo: pretrained, full fine-tuning, and LoRA

This experiment compares the original model with full denoiser fine-tuning, denoted Full, and LoRA adaptation, using the same frozen SONIC controller. Both adaptation methods use an equal mix of randomly sampled and task-derived spatial commands. Random commands sample palm goals around the robot and derive

Table 4 Data-source success rate (%) with SONIC. All averages weight tasks equally. Bold marks the best.

Training data	GR00T N1.7			$\pi_{0.5}$		
Tasks	Atom. 16	Comp. 4	All 20	Atom. 16	Comp. 4	All 20
Teleoperation only	**88.4**	56.2	82.0	**92.5**	**76.2**	**89.2**
Motion synthesis only	40.9	22.5	37.2	46.9	20.0	41.5
Traj. augmentation only	66.9	23.8	58.2	63.7	3.8	51.7
Teleop. + synthesis	73.8	63.7	71.8	88.1	73.8	85.2
Teleop. + augmentation	85.9	**68.8**	**82.5**	90.3	63.7	85.0
All three	46.9	43.8	46.2	89.7	63.7	84.5

Table 5 Kimodo task success and goal error. Bold marks the best rates and mean errors.

(a) Task success (%)

Task group	Pretrained	LoRA	Full
Overall	39.7	71.3	**90.7**
Approach	9.0	63.0	**99.0**
Comp. approach	2.0	80.0	**100.0**
Close	72.7	74.0	**82.0**

(b) Goal error (m) ↓ (mean ± standard deviation)

Condition	Target	Pretrained	LoRA	Full
Loco	Root	0.693 ± 0.286	0.096 ± 0.055	$\mathbf{0.076} \pm 0.033$
Mani	Root	$\mathbf{0.014} \pm 0.008$	0.036 ± 0.015	0.051 ± 0.015
Mani	Palm	0.168 ± 0.049	0.128 ± 0.033	$\mathbf{0.077} \pm 0.037$
Loco+Mani	Root	0.578 ± 0.150	0.089 ± 0.052	$\mathbf{0.080} \pm 0.033$
Loco+Mani	Palm	0.650 ± 0.147	0.122 ± 0.073	$\mathbf{0.099} \pm 0.042$

corresponding root and wrist targets, while task-derived commands obtain navigation goals and manipulation waypoints from benchmark task definitions and scene geometry. Navigation stages use root targets alone, and each task stage is executed and scored independently during fine-tuning. Each adapted variant uses one training run, and the model with the highest validation reward among saved checkpoints available at selection time is selected independently of the reported test results.

Fine-tuning improves task success most strongly on approach tasks. Table 5(a) reports results on 30 task–scene pairs with ten trials per pair and model. Completion follows each task's success predicate, with the evaluation conditions detailed in Appendix D-D. Both fine-tuning methods improve success across the three reported task groups. Full fine-tuning raises overall SR from 39.7% to 90.7% and outperforms LoRA. The largest gains occur in Approach and compositional Approach, with smaller improvements in Close.

More accurate executed motions accompany the gains in task success. Table 5(b) measures root and palm goal errors after three seconds of controller execution under locomotion, stationary manipulation, and combined conditions. Root error is the planar distance to the root target, while palm error is the three-dimensional distance from the executed grasp center to its target. Models share prompts, motion prefixes, targets, and generation seeds and their physical executions start from the first poses of their own generated references. The target ranges overlap those used for adaptation, so this test measures accuracy under related conditions. Errors are reported in meters as means and standard deviations across conditions, with the full protocol in Appendix D-D.

Full fine-tuning achieves the lowest mean error in four of the five reported measures. In the stationary manipulation test, the root target is fixed at the robot's initial position, so a lower root error indicates less base movement. Small base adjustments are nevertheless acceptable when they help the hand reach its target. The original model keeps its base closest to the initial position but has the largest palm error, whereas both fine-tuned models improve palm accuracy, with Full achieving the largest improvement. Full's slightly higher root error should therefore be considered together with its lower palm error, since keeping the base fixed is not sufficient to complete the reaching motion. Under combined locomotion and manipulation, Full reduces both root and palm errors, bringing the robot's body and hand closer to their respective targets. These improvements are consistent with the higher success rates on approach and compositional approach tasks, and Fig. 8 in Appendix D-C illustrates the corresponding motion differences.

4.6 Simulation and Real-Robot Evaluation

GR00T N1.7, Fast-WAM, and XR-1 are evaluated on fridge opening, cup transport from a shelf to a desk, and conveyor box handling in corresponding simulated and real-world scenes. Each policy is trained separately

Table 6 Simulation and Unitree G1 real-robot success rates (%) on three tasks. Hardware results use ten trials per model–task pair. Bold marks the best value and underlining marks the second best.

Policy	Fridge		Cup		Conveyor		Average	
	Sim.	Real	Sim.	Real	Sim.	Real	Sim.	Real
XR-1 (Xiaomi Robotics Team et al., 2026)	**100.0**	**80.0**	**85.0**	**70.0**	**45.0**	**60.0**	**76.7**	**70.0**
GR00T N1.7 (NVIDIA, 2026)	<u>55.0</u>	<u>50.0</u>	<u>80.0</u>	<u>60.0</u>	<u>25.0</u>	<u>50.0</u>	<u>53.3</u>	<u>53.3</u>
Fast-WAM (Yuan et al., 2026)	45.0	40.0	**85.0**	50.0	20.0	<u>50.0</u>	50.0	46.7




Figure 5 Task-execution sequences in real-world (a–c) and simulated (d–f) settings, arranged as real-world sequences in the left column and simulated sequences in the right column. Rows show conveyor box handling, cup transport, and fridge opening. Selected frames progress from left to right within each row. Real and simulated sequences are not temporally aligned, and success is measured separately in each environment. Corresponding rates appear in Table 6.

for each task, using simulated teleoperation for simulation and 50 real-robot demonstrations per task for hardware. Training uses the model configurations of the main experiment in Sec. 4.2, with SONIC used for execution; training budgets are given in Appendix E. Evaluation uses 20 simulation episodes and 10 hardware trials per task and policy. Table 6 reports success rates, Fig. 5 shows execution examples, and Appendix E details the task criteria and protocols.

XR-1 achieves the highest average success in both environments and leads all three hardware tasks. GR00T N1.7 ranks second and Fast-WAM third in both simulation and hardware, giving a consistent overall policy ranking that supports the use of simulation to assess relative real-world performance. Task-level results provide a more detailed comparison. GR00T N1.7 and Fast-WAM perform well on cup transport in simulation, but their ordering on this task reverses on hardware. Conveyor handling has the lowest simulation success for all three policies, while GR00T N1.7 and Fast-WAM achieve the same hardware success on this task. Simulation therefore captures the overall differences between policies, while individual tasks reveal how their relative strengths vary across the two environments.

On hardware, fridge opening produces the largest gap between XR-1 and the other policies, whereas success rates are closer on cup transport and conveyor handling. The stronger separation on fridge opening highlights articulated-object interaction as a useful complement to object transport and moving-object handling when comparing loco-manipulation policies.

5 Discussion and Limitations

Although most policies perform well on familiar tasks, unseen tasks and scenes leave substantial room for improvement. Policies with similar performance on atomic tasks can differ substantially when navigation and manipulation must be coordinated in compositional tasks. Controller choice also matters, since comparable task success can be accompanied by different power use and stability. Together, these results highlight the value of testing policies across task complexity, scene variation, and execution controllers. Fine-tuning Kimodo improves both reaching accuracy and task completion, while the benefits of additional demonstrations and

mixed data sources depend on the policy and task. Task success generally improves with larger demonstration budgets, with gains varying across policies, controllers, and task categories.

These findings should be considered alongside limitations in evaluation coverage and deployment conditions. The benchmark primarily covers indoor household and office tasks. Simulation and physical trials yield the same ranking by average task success, supporting simulated comparisons before physical deployment. However, the hardware study covers only three policies on fridge opening, cup transport, and conveyor box handling, with ten trials per policy and task. Broader coverage of models, activities, and environments, together with repeated training and more physical trials, would help determine how consistently these trends extend to other settings. Deployment on robots with limited onboard compute may also require inference on nearby edge servers or cloud resources (Shao and Li, 2026; An et al., 2026), making communication delays and missed control deadlines additional factors to evaluate.

6 Conclusion

LocoManiLab provides a unified testbed for humanoid loco-manipulation, connecting household tasks, teleoperated and generated demonstrations, policy training, and evaluation in simulation and the real world. The experiments examine policy generalization, controller performance, demonstration scale, data sources, and motion generator fine-tuning. Although most policies perform well on familiar tasks, substantial room for improvement remains on unseen tasks and in unseen scenes, and controller choice affects both task completion and motion quality. The data collection and generation pipelines support policy training with teleoperated, synthesized, and augmented demonstrations, enabling systematic study of how training data affects humanoid task performance. Simulation and hardware yield the same average policy ordering on the evaluated tasks, supporting the use of simulated tasks to guide policy selection for physical evaluation.

References

Hongjun An, Wenhan Hu, Sida Huang, Siqi Huang, Ruanjun Li, Yuanzhi Liang, Jiawei Shao, Yiliang Song, Zihan Wang, Cheng Yuan, Chi Zhang, Hongyuan Zhang, Wenhao Zhuang, and Xuelong Li. AI Flow: Perspectives, scenarios, and approaches. *Vicinagearth*, 3(1), January 2026. doi: 10.1007/s44336-025-00031-y. Art. no. 1.

Donghoon Baek, Amartya Purushottam, Jason J. Choi, and Joao Ramos. Whole-body bilateral teleoperation with multistage object parameter estimation for wheeled humanoid locomanipulation. *IEEE Transactions on Robotics*, 42:3345–3365, 2026. doi: 10.1109/TRO.2026.3721690.

Kevin Black, Michael Janner, Yilun Du, Ilya Kostrikov, and Sergey Levine. Training diffusion models with reinforcement learning. In *International Conference on Learning Representations (ICLR)*, 2024.

Kevin Black, Noah Brown, James Darpinian, Karan Dhabalia, Danny Driess, Adnan Esmail, Michael Robert Equi, Chelsea Finn, Niccolo Fusai, Manuel Y. Galliker, Dibya Ghosh, Lachy Groom, Karol Hausman, Brian Ichter, Szymon Jakubczak, Tim Jones, Liyiming Ke, Devin LeBlanc, Sergey Levine, Adrian Li-Bell, Mohith Mothukuri, Suraj Nair, Karl Pertsch, Allen Z. Ren, Lucy Xiaoyang Shi, Laura Smith, Jost Tobias Springenberg, Kyle Stachowicz, James Tanner, Quan Vuong, Homer Walke, Anna Walling, Haohuan Wang, Lili Yu, and Ury Zhilinsky. $\pi_{0.5}$: A vision-language-action model with open-world generalization. In *Proceedings of The 9th Conference on Robot Learning*, volume 305 of *Proceedings of Machine Learning Research*, pages 17–40. PMLR, 2025.

Weihang Chen, Jing Xu, Fanbo Xiang, Xiaodi Yuan, Hao Su, and Rui Chen. General-purpose sim2real protocol for learning contact-rich manipulation with marker-based visuotactile sensors. *IEEE Transactions on Robotics*, 40: 1509–1526, 2024. doi: 10.1109/TRO.2024.3352969.

Xinyi Chen, Yilun Chen, Yanwei Fu, Ning Gao, Jiaya Jia, Weiyang Jin, Hao Li, Yao Mu, Jiangmiao Pang, Yu Qiao, Yang Tian, Bin Wang, Bolun Wang, Fangjing Wang, Hanqing Wang, Tai Wang, Ziqin Wang, Xueyuan Wei, Chao Wu, Shuai Yang, Jinhui Ye, Junqiu Yu, Jia Zeng, Jingjing Zhang, Jinyu Zhang, Shi Zhang, Feng Zheng, Bowen Zhou, and Yangkun Zhu. InternVLA-M1: A spatially guided vision-language-action framework for generalist robot policy. arXiv:2510.13778, 2025a.

Zixuan Chen, Mazeyu Ji, Xuxin Cheng, Xuanbin Peng, Xue Bin Peng, and Xiaolong Wang. GMT: General motion tracking for humanoid whole-body control. arXiv:2506.14770, 2025b.

Cheng Chi, Zhenjia Xu, Siyuan Feng, Eric Cousineau, Yilun Du, Benjamin Burchfiel, Russ Tedrake, and Shuran Song. Diffusion policy: Visuomotor policy learning via action diffusion. *The International Journal of Robotics Research*, 44(10–11):1684–1704, 2025. doi: 10.1177/02783649241273668.

Matt Deitke, Dustin Schwenk, Jordi Salvador, Luca Weihs, Oscar Michel, Eli VanderBilt, Ludwig Schmidt, Kiana Ehsani, Aniruddha Kembhavi, and Ali Farhadi. Objaverse: A universe of annotated 3D objects. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13142–13153, 2023. doi: 10.1109/CVPR52729.2023.01263.

Dexmal Team. DM0.5: An open-world foundation model for general-purpose embodied intelligence. Technical blog, July 2026. URL https://www.dexmal.com/blog/dm0.5/index_en.html. Accessed: Oct. 17, 2026.

Pranav Guruprasad, Harshvardhan Sikka, Jaewoo Song, Yangyue Wang, and Paul Pu Liang. Benchmarking vision, language, & action models on robotic learning tasks. arXiv:2411.05821, 2024.

Jinrui Han, Weiji Xie, Jiakun Zheng, Jiyuan Shi, Weinan Zhang, Ting Xiao, and Chenjia Bai. KungfuBot2: Learning versatile motion skills for humanoid whole-body control. arXiv:2509.16638, 2025.

Jinrui Han, Dewei Wang, Chenyun Zhang, Xinzhe Liu, Ping Luo, Chenjia Bai, and Xuelong Li. HUSKY: Humanoid skateboarding system via physics-aware whole-body control. In *Proceedings of Robotics: Science and Systems*, Sydney, Australia, July 2026. doi: 10.15607/RSS.2026.XXII.019.

Peter E. Hart, Nils J. Nilsson, and Bertram Raphael. A formal basis for the heuristic determination of minimum cost paths. *IEEE Transactions on Systems Science and Cybernetics*, 4(2):100–107, July 1968. doi: 10.1109/TSSC.1968.300136.

Shiming He, Alexander von Rohr, Dominik Baumann, Ji Xiang, and Sebastian Trimpe. Simulation-aided policy tuning for black-box robot learning. *IEEE Transactions on Robotics*, 41:2533–2548, 2025a. doi: 10.1109/TRO.2025.3539192.

Tairan He, Zhengyi Luo, Xialin He, Wenli Xiao, Chong Zhang, Weinan Zhang, Kris M. Kitani, Changliu Liu, and Guanya Shi. OmniH2O: Universal and dexterous human-to-humanoid whole-body teleoperation and learning. In *Proceedings of The 8th Conference on Robot Learning*, volume 270 of *Proceedings of Machine Learning Research*, pages 1516–1540. PMLR, 2025b.

Tairan He, Wenli Xiao, Toru Lin, Zhengyi Luo, Zhenjia Xu, Zhenyu Jiang, Jan Kautz, Changliu Liu, Guanya Shi, Xiaolong Wang, Linxi Jim Fan, and Yuke Zhu. HOVER: Versatile neural whole-body controller for humanoid robots. In *IEEE International Conference on Robotics and Automation (ICRA)*, pages 9989–9996, 2025c. doi: 10.1109/ICRA55743.2025.11128549.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

Yingdong Hu, Haodong Zhu, Boyuan Zheng, Yihang Hu, Tong Zhang, Zunhao Chen, Junming Zhao, Ruiqian Nai, and Yang Gao. OpenHLM: An empirical recipe for whole-body humanoid loco-manipulation. arXiv:2606.22174, 2026.

Stephen James, Zicong Ma, David Rovick Arrojo, and Andrew J. Davison. RLBench: The robot learning benchmark & learning environment. *IEEE Robotics and Automation Letters*, 5(2):3019–3026, 2020. doi: 10.1109/LRA.2020.2974707.

Haoran Jiang, Jin Chen, Qingwen Bu, Li Chen, Modi Shi, Yanjie Zhang, Delong Li, Chuanzhe Suo, Chuang Wang, Zhihui Peng, and Hongyang Li. WholeBodyVLA: Towards unified latent VLA for whole-body loco-manipulation control. In *International Conference on Learning Representations (ICLR)*, 2026.

Yejin Kim, Wilbert Pumacay, Omar Rayyan, Max Argus, Winson Han, Eli Vanderbilt, Jordi Salvador, Abhay Deshpande, Rose Hendrix, Snehal Jauhri, Shuo Liu, Nur Muhammad Mahi Shafiullah, Maya Guru, Ainaz Eftekhar, Karen Farley, Donovan Clay, Jiafei Duan, Arjun Guru, Piper Wolters, Alvaro Herrasti, Ying-Chun Lee, Georgia Chalvatzaki, Yuchen Cui, Ali Farhadi, Dieter Fox, and Ranjay Krishna. MolmoSpaces: Large-scale open ecosystem for robot manipulation and navigation. In *Proceedings of Robotics: Science and Systems*, 2026. doi: 10.15607/RSS.2026.XXII.091.

Jialong Li, Xuxin Cheng, Tianshu Huang, Shiqi Yang, Ri-Zhao Qiu, and Xiaolong Wang. AMO: Adaptive motion optimization for hyper-dexterous humanoid whole-body control. In *Proceedings of Robotics: Science and Systems*, 2025a. doi: 10.15607/RSS.2025.XXI.061.

Xuanlin Li, Kyle Hsu, Jiayuan Gu, Oier Mees, Karl Pertsch, Homer Rich Walke, Chuyuan Fu, Ishikaa Lunawat, Isabel Sieh, Sean Kirmani, Sergey Levine, Jiajun Wu, Chelsea Finn, Hao Su, Quan Vuong, and Ted Xiao. Evaluating real-world robot manipulation policies in simulation. In *Proceedings of The 8th Conference on Robot Learning*, volume 270 of *Proceedings of Machine Learning Research*, pages 3705–3728. PMLR, 2025b.

Kevin Lin, Ajay Mandlekar, Caelan Reed Garrett, Nikita Chernyadev, Yu Fang, Runyu Ding, Yuqi Xie, Justin Tran, Linxi Fan, and Yuke Zhu. HumanoidMimicGen: Data generation for loco-manipulation via whole-body planning. arXiv:2605.27724, 2026a.

Yuhang Lin, Jiyuan Shi, Dewei Wang, Jipeng Kong, Yong Liu, Chenjia Bai, and Xuelong Li. Pro-HOI: Perceptive root-guided humanoid-object interaction. arXiv:2603.01126, 2026b.

Bo Liu, Yifeng Zhu, Chongkai Gao, Yihao Feng, Qiang Liu, Yuke Zhu, and Peter Stone. LIBERO: Benchmarking knowledge transfer for lifelong robot learning. In *Advances in Neural Information Processing Systems*, volume 36, pages 44776–44791, 2023. doi: 10.52202/075280-1939.

Chenxin Liu, Qingzhou Lu, Guangxiao Yang, Xuanyang Shi, Chenghan Yang, Yanjiang Guo, and Jianyu Chen. HEFT: Heavy-payload full-size humanoid teleoperation with privileged motion guidance and windowed payload curriculum. arXiv:2607.02332, 2026.

Zhengyi Luo, Ye Yuan, Tingwu Wang, Chenran Li, Fernando Castañeda, Sirui Chen, Zi-Ang Cao, Jiefeng Li, David Minor, Qingwei Ben, Jinhyung Park, David Sami, Zi Wang, Xingye Da, Runyu Ding, Cyrus Hogg, Lina Song, Edy Lim, Eugene Jeong, Tairan He, Haoru Xue, Wenli Xiao, Simon Yuen, Jan Kautz, Yan Chang, Umar Iqbal, Linxi Jim Fan, and Yuke Zhu. SONIC: Supersizing motion tracking for natural humanoid whole-body control. *Science Robotics*, 11(117):eaed4592, 2026. doi: 10.1126/scirobotics.aed4592.

Haoxiang Ma, Junhao Cai, Xiaoxu Xu, Hao Li, Yuyin Yang, Yang Tian, Jiafei Cao, Hongrui Zhu, Zherui Qiu, Zhaxizhuoma, Yuqiang Yang, Jiaqi Peng, Xueyuan Wei, Yangkun Zhu, Jiahao Jiang, Xing Gao, Hanqing Wang, Feng Yuan, Kailin Li, Xueyue Zhu, Tai Wang, Yan Ding, Jiangmiao Pang, Jia Zeng, Jingjing Zhang, Bowen Zhou, Yao Mu, Chunhua Shen, and Weinan Zhang. InternVLA-A1.5: Unifying understanding, latent foresight, and action for compositional generalization. arXiv:2607.04988, 2026.

Soroush Nasiriany, Abhiram Maddukuri, Lance Zhang, Adeet Parikh, Aaron Lo, Abhishek Joshi, Ajay Mandlekar, and Yuke Zhu. RoboCasa: Large-scale simulation of household tasks for generalist robots. In *Proceedings of Robotics: Science and Systems*, 2024. doi: 10.15607/RSS.2024.XX.050.

Soroush Nasiriany, Sepehr Nasiriany, Abhiram Maddukuri, and Yuke Zhu. RoboCasa365: A large-scale simulation framework for training and benchmarking generalist robots. In *International Conference on Learning Representations (ICLR)*, 2026.

NVIDIA. NVIDIA Isaac GR00T N1.7-3B model card. Hugging Face, 2026. URL https://huggingface.co/nvidia/GR00T-N1.7-3B. Accessed: Sep. 28, 2026.

NVIDIA, Johan Bjorck, Fernando Castañeda, Nikita Cherniadev, Xingye Da, Runyu Ding, Linxi Jim Fan, Yu Fang, Dieter Fox, Fengyuan Hu, Spencer Huang, Joel Jang, Zhenyu Jiang, Jan Kautz, Kaushil Kundalia, Lawrence Lao, Zhiqi Li, Zongyu Lin, Kevin Lin, Guilin Liu, Edith Llontop, Loic Magne, Ajay Mandlekar, Avnish Narayan, Soroush Nasiriany, Scott Reed, You Liang Tan, Guanzhi Wang, Zu Wang, Jing Wang, Qi Wang, Jiannan Xiang, Yuqi Xie, Yinzhen Xu, Zhenjia Xu, Seonghyeon Ye, Zhiding Yu, Ao Zhang, Hao Zhang, Yizhou Zhao, Ruijie Zheng, and Yuke Zhu. GR00T N1: An open foundation model for generalist humanoid robots. arXiv:2503.14734, 2025.

Open X-Embodiment Collaboration. Open X-embodiment: Robotic learning datasets and RT-X models. In *IEEE International Conference on Robotics and Automation (ICRA)*, pages 6892–6903, 2024. doi: 10.1109/ICRA57147.2024.10611477.

Joao Ramos and Sangbae Kim. Humanoid dynamic synchronization through whole-body bilateral feedback teleoperation. *IEEE Transactions on Robotics*, 34(4):953–965, 2018. doi: 10.1109/TRO.2018.2830387.

Davis Rempe, Mathis Petrovich, Ye Yuan, Haotian Zhang, Xue Bin Peng, Yifeng Jiang, Tingwu Wang, Umar Iqbal, David Minor, Michael de Ruyter, Jiefeng Li, Chen Tessler, Edy Lim, Eugene Jeong, Sam Wu, Ehsan Hassani, Michael Huang, Jin-Bey Yu, Chaeyeon Chung, Lina Song, Olivier Dionne, Jan Kautz, Simon Yuen, and Sanja Fidler. Kimodo: Scaling controllable human motion generation. arXiv:2603.15546, 2026.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Carmelo Sferrazza, Dun-Ming Huang, Xingyu Lin, Youngwoon Lee, and Pieter Abbeel. HumanoidBench: Simulated humanoid benchmark for whole-body locomotion and manipulation. In *Proceedings of Robotics: Science and Systems*, 2024. doi: 10.15607/RSS.2024.XX.061.

Jiawei Shao and Xuelong Li. AI Flow at the network edge. *IEEE Network*, 40(1):330–336, January 2026. doi: 10.1109/MNET.2025.3541208.

Jiyuan Shi, Xinzhe Liu, Dewei Wang, Ouyang Lu, Sören Schwertfeger, Chi Zhang, Fuchun Sun, Chenjia Bai, and Xuelong Li. Adversarial locomotion and motion imitation for humanoid policy learning. In *Advances in Neural Information Processing Systems*, volume 38, pages 82168–82199, 2025. doi: 10.52202/085713-2478.

Modi Shi, Shijia Peng, Jin Chen, Haoran Jiang, Tianyu Li, Ping Luo, Di Huang, Hongyang Li, and Li Chen. Unlocking in-the-wild loco-manipulation with robot-free egocentric demonstration. In *Proceedings of Robotics: Science and Systems*, 2026. doi: 10.15607/RSS.2026.XXII.204.

Mustafa Shukor, Dana Aubakirova, Francesco Capuano, Pepijn Kooijmans, Steven Palma, Adil Zouitine, Michel Aractingi, Caroline Pascal, Martino Russi, Andres Marafioti, Simon Alibert, Matthieu Cord, Thomas Wolf, and Remi Cadene. SmolVLA: A vision-language-action model for affordable and efficient robotics. arXiv:2506.01844, 2025.

João Silvério, Sylvain Calinon, Leonel Rozo, and Darwin G. Caldwell. Learning task priorities from demonstrations. *IEEE Transactions on Robotics*, 35(1):78–94, 2019. doi: 10.1109/TRO.2018.2878355.

Stone Tao, Fanbo Xiang, Arth Shukla, Yuzhe Qin, Xander Hinrichsen, Xiaodi Yuan, Chen Bao, Xinsong Lin, Yulin Liu, Tse-Kai Chan, Yuan Gao, Xuanlin Li, Tongzhou Mu, Nan Xiao, Arnav Gurha, Viswesh Nagaswamy Rajesh, Yong Woo Choi, Yen-Ru Chen, Zhiao Huang, Roberto Calandra, Rui Chen, Shan Luo, and Hao Su. Demonstrating GPU parallelized robot simulation and rendering for generalizable embodied AI with ManiSkill3. In *Proceedings of Robotics: Science and Systems*, 2025. doi: 10.15607/RSS.2025.XXI.021.

Emanuel Todorov, Tom Erez, and Yuval Tassa. MuJoCo: A physics engine for model-based control. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 5026–5033, 2012. doi: 10.1109/IROS.2012.6386109.

Dewei Wang, Xinmiao Wang, Chenyun Zhang, Jiyuan Shi, Yingnan Zhao, Chenjia Bai, and Xuelong Li. X-Loco: Towards generalist humanoid locomotion control via synergetic policy distillation. In *Proceedings of Robotics: Science and Systems*, Sydney, Australia, July 2026a. doi: 10.15607/RSS.2026.XXII.022.

Huayi Wang, Wentao Zhang, Runyi Yu, Tao Huang, Junli Ren, Feiyu Jia, Zirui Wang, Xiaojie Niu, Xiao Chen, Jiahe Chen, Qifeng Chen, Jingbo Wang, and Jiangmiao Pang. PhysHSI: Towards a real-world generalizable and natural humanoid-scene interaction system. arXiv:2510.11072, 2025.

Taowen Wang, Zikang Xie, Bin Yang, Yunheng Wang, Zizhao Yuan, Yuetong Fang, Yixiao Feng, Yichi Wang, Xingyu Chen, Haodong Chen, Qiwei Wu, Weisheng Xu, Lihan Chen, Lusong Li, Zecui Zeng, and Renjing Xu. HumanoidArena: Benchmarking egocentric hierarchical whole-body learning. arXiv:2606.17833, 2026b.

Yen-Jen Wang, Jiaman Li, Sirui Chen, Takara E. Truong, Pei Xu, Pieter Abbeel, Rocky Duan, Koushil Sreenath, Angjoo Kanazawa, Carmelo Sferrazza, Guanya Shi, and C. Karen Liu. VLK: Learning humanoid loco-manipulation from synthetic interactions in reconstructed scenes. arXiv:2606.30645, 2026c.

Songlin Wei, Hongyi Jing, Boqian Li, Zhenyu Zhao, Jiageng Mao, Zhenhao Ni, Sicheng He, Sheng Zang, Xiawei Liu, Kaidi Kang, Jie Liu, Weiduo Yuan, Marco Pavone, Di Huang, and Yue Wang. Ψ_0: An open foundation model towards universal humanoid loco-manipulation. In *Proceedings of Robotics: Science and Systems*, 2026a. doi: 10.15607/RSS.2026.XXII.021.

Songlin Wei, Zhenhao Ni, Jie Liu, Zhenyu Zhao, Junjie Ye, Hongyi Jing, Junkai Xia, Xiawei Liu, Michael Leong, Liang Heng, Di Huang, and Yue Wang. SIMPLE: Simulation-based policy learning and evaluation for humanoid loco-manipulation. arXiv:2606.08278, 2026b.

Haoyang Weng, Yitang Li, Nikhil Sobanbabu, Zihan Wang, Zhengyi Luo, Tairan He, Deva Ramanan, and Guanya Shi. HDMI: Learning interactive humanoid whole-body control from human videos. arXiv:2509.16757, 2025.

Xiaomi Robotics Team, Jun Guo, Piaopiao Jin, Jason Li, Peiyan Li, Yingyan Li, Futeng Liu, Wanli Peng, Optimus Qin, Yifei Su, Nan Sun, Qiao Sun, Runze Suo, Heyun Wang, Yunhong Wang, Rujie Wu, Caoyu Xia, Lina Zhang, Jack Zhao, Guoliang Chen, Wenlong Chen, Xinze He, Bin Li, Qing Li, Zhuorong Li, Heng Qu, Wenxuan Song, Diyun Xiang, Yifan Xie, Peiran Xu, Hangjun Ye, Wen Ye, Han Zhao, and Quanyun Zhou. Xiaomi-Robotics-1: Scaling vision-language-action models with over 100K hours of real-world trajectories. arXiv:2607.15330, 2026. URL https://arxiv.org/abs/2607.15330.

Yue Yang, Fan-Yun Sun, Luca Weihs, Eli VanderBilt, Alvaro Herrasti, Winson Han, Jiajun Wu, Nick Haber, Ranjay Krishna, Lingjie Liu, Chris Callison-Burch, Mark Yatskar, Aniruddha Kembhavi, and Christopher Clark. Holodeck: Language guided generation of 3D embodied AI environments. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 16277–16287, 2024. doi: 10.1109/CVPR52733.2024.01536.

Jinhui Ye, Ning Gao, Senqiao Yang, Jinliang Zheng, Zixuan Wang, Yuxin Chen, Pengguang Chen, Yilun Chen, Shu Liu, and Jiaya Jia. StarVLA-α: Reducing complexity in vision-language-action systems. arXiv:2604.11757, 2026a.

Seonghyeon Ye, Yunhao Ge, Kaiyuan Zheng, Shenyuan Gao, Sihyun Yu, George Kurian, Suneel Indupuru, You Liang Tan, Chuning Zhu, Jiannan Xiang, Ayaan Malik, Kyungmin Lee, William Liang, Nadun Ranawaka, Jiasheng Gu, Yinzhen Xu, Guanzhi Wang, Fengyuan Hu, Avnish Narayan, Johan Bjorck, Jing Wang, Gwanghyun Kim, Dantong Niu, Ruijie Zheng, Yuqi Xie, Jimmy Wu, Qi Wang, Ryan Julian, Danfei Xu, Yilun Du, Yevgen Chebotar, Scott Reed, Jan Kautz, Yuke Zhu, Linxi Jim Fan, and Joel Jang. World action models are zero-shot policies. arXiv:2602.15922, 2026b.

Tianyuan Yuan, Zibin Dong, Yicheng Liu, and Hang Zhao. Fast-WAM: Do world action models need test-time future imagination? arXiv:2603.16666, 2026.

Weishuai Zeng, Kangning Yin, Xiaojie Niu, Shunlin Lu, Weixiang Zhong, Jiahe Chen, Feiyu Jia, Xiao Chen, Zirui Wang, Furui Xu, Ming Zhou, Kailin Li, Weinan Zhang, He Wang, Li Yi, Dahua Lin, Jiangmiao Pang, and Jingbo Wang. Scaling behavior foundation model for humanoid robots. arXiv:2607.15163, 2026.

Yang Zhang, Jiangyuan Zhao, Chenyou Fan, Fangzheng Yan, Tian Li, Haitong Tang, Sen Fu, Xuan'er Wu, Qizhen Weng, Weinan Zhang, Xiu Li, Chi Zhang, Chenjia Bai, and Xuelong Li. PRTS: A primitive reasoning and tasking system via contrastive representations. arXiv:2604.27472, 2026.

Jinliang Zheng, Jianxiong Li, Zhihao Wang, Dongxiu Liu, Xirui Kang, Yuchun Feng, Yinan Zheng, Jiayin Zou, Yilun Chen, Jia Zeng, Ya-Qin Zhang, Jiangmiao Pang, Jingjing Liu, Tai Wang, and Xianyuan Zhan. X-VLA: Soft-prompted transformer as scalable cross-embodiment vision-language-action model. In *International Conference on Learning Representations (ICLR)*, 2026.

Appendix

A Task Suite and Evaluation Protocol

The collection contains 14,160 simulated teleoperation episodes (51.5 h) across five household scene categories. The principal SONIC corpus contains 5,207 atomic and 6,852 compositional episodes, and four other controllers contribute 2,101 episodes on ten shared bathroom tasks. Main-benchmark training uses separate 50-task atomic and compositional lists (2,546 and 2,558 episodes, respectively). The task suite comprises 102 atomic and 132 compositional tasks (Table 7).

Table 7 Task inventory and evaluation splits. Split membership is defined separately for each atomic or compositional checkpoint; atomic and compositional counts follow the semantic task labels.

Scene category	Scene instances	Atomic tasks	Compositional tasks	Representative objectives
Kitchen	1	25	33	articulated appliances; object placement
Living room	2	20	20	navigation; object transport and reorientation
Bedroom	4	18	26	drawers; navigation followed by interaction
Bathroom	4	18	28	lids, shower fixtures, and multi-stage tasks
Office	2	21	25	drawers, chairs, desk-object interaction
Evaluated total	13	102	132	234 task IDs
Split	Atomic tasks	Compositional tasks	Episodes/task	Novelty
Seen	50	50	20	training definitions and scenes
Unseen task	46	77	10	unseen definitions, training scenes
Unseen scene	6	5	10	unseen definitions and scene instances

Atomic objectives may contain several motion phases, whereas compositional objectives require ordered stages whose later actions depend on earlier state changes. Success follows task-specific physical predicates and any configured hold interval.

Fig. 6 and Fig. 7 show representative task demonstrations and the scenes and objects used in the suite.

The principal evaluation uses a Unitree G1, one 320×240 head RGB image and model-specific proprioception, SONIC at 50 Hz, and synchronous policy queries every 20 control steps. Only the leading actions of longer chunks are executed. Shorter chunks hold their last action until the next query. Episode seeds are 0–19 for seen tasks and 0–9 for unseen tasks, with scene seed zero and robot/object reset randomization up to 5/2 cm. A task's rollout limit is $\max\{\mathrm{round}(2\bar{L}), L_{\max}, 300\}$ control steps, where $\bar{L}$ and $L_{\max}$ are its mean and maximum demonstration lengths. Episodes end on success or timeout, without fall-based early termination.

A-A Domain Randomization Presets

Low/Mid/High replace 50/70/70% of eligible texture groups from an unseen texture pool. All levels perturb lighting color and intensity by 0.15, toggle shadows with probability 0.5, and add a spotlight with probability 0.5. Mid adds material shading randomization of 0.2 and camera offsets of ± 0.01 m, ± 0.05 rad, and $\pm 2^\circ$ field of view. High adds radial distortion with $k_1 \sim U(-0.25, 0.25)$ and $k_2 \sim U(-0.05, 0.05)$, principal-point shifts up to 8 pixels, image zoom up to 1.12, and robot RGB perturbations up to 0.15. High also places up to three distractors where space permits, which occurred in 38 of the 100 tasks.




Figure 6 Representative task demonstrations across five scene categories. Upper rows show atomic objectives: (a) open a fridge, (b) place a book in a basket, (c) lift a basket from a stool, (d) close a cabinet, and (e) approach a desk. Lower rows show compositional objectives: (f) open a drawer, place an apple inside, and close it; (g) pack a candle and statue into a basket; (h) approach and open a safe; (i) open a drawer, retrieve a paper roll, and close it; and (j) approach a trash can and lift a box. Each row contains six chronological frames from a recorded SONIC demonstration, rendered through action replay; nonuniform frame intervals highlight task stages.




Figure 7 Task environments and representative interaction objects. (a) Thirteen household scenes from Holodeck and iTHOR, labeled by room category and scene identifier, followed by two Lab layouts. (b) Thirty-two representative task assets, grouped into articulated objects, containers and surfaces, and movable objects. The groups illustrate affordances for opening and closing, object placement, and manipulation within atomic and compositional tasks. Rooms and objects are individually scaled for visibility and are not shown to a common physical scale.

B Policy Adaptation and Training

B-A Main-Benchmark Configuration

The twelve evaluated policies are trained separately on the atomic and compositional 50-task lists. Inputs are a 320×240 head RGB image and 43 joint-state values, with three additional gravity values for GR00T N1.7 and no proprioception for StarVLA-α. All adapters output 64 SONIC motion-token values and 14 absolute finger targets.

Budgets were set to $1{,}000\lceil 2U/(1{,}000B)\rceil$ updates for estimated sampling-unit count U and global batch B. Most models use frame counts and GR00T N1.7 uses complete 64-step action-window starts. These correspond to approximately two nominal passes over model-specific sampling units and do not imply equal compute budgets.

Below, state/action normalization is denoted Q for training-set 1st/99th percentiles mapped to $[-1, 1]$, M for mean/standard deviation, R for min/max scaling, and I for identity. Statistics are fitted on each training selection. Paired training budgets are reported in atomic/compositional order.

Diffusion Policy. The RoboCasa365 implementation uses Contrastive Language–Image Pretraining (CLIP) features from a Vision Transformer (ViT-L/14) and a frozen text encoder. Two observations condition a 32-step prediction that returns 16 actions, with R/R normalization and 100 denoising steps using ϵ prediction and a squared-cosine noise schedule. Training uses global batch 192, AdamW at 10^{-4}, cosine decay, 1k warmup updates, no gradient clipping, and seed 42. The budgets are 9k/26k optimizer updates. Evaluation uses exponential moving average (EMA) weights. Images use random 216×288 crops during training and center crops at test.

Fast-WAM. Wan2.2 TI2V-5B and a pretrained action DiT are adapted while the Text-to-Text Transfer Transformer (T5) text encoder and the variational autoencoder (VAE) remain frozen. Each sample spans 33 time steps at 10 Hz over 3.2 s, supervising 32 actions and sampling every fourth time step for nine video frames including the conditioning frame. The action chunk is interpolated to 160 steps at 50 Hz. Training uses R/R normalization, global batch 64, cosine decay from 10^{-4}, weight decay 0.01, bfloat16 (bf16), seed 42, and 25k/78k updates. Inference uses ten denoising steps. Instructions are wrapped in the training template "A video recorded from a robot's point of view executing the following instruction: {task}" and encoded by T5.

GR00T N1.7. Initialization uses the released GR00T-N1.7-3B policy with a Cosmos-Reason2-2B vision-language backbone. State and action are padded internally to 132 dimensions, with Q/Q normalization and clipping. The 64-step action horizon uses four flow-inference steps. Training updates the projector and action-diffusion module while freezing the vision and language encoders, with global batch 128, AdamW, cosine decay from 10^{-4}, weight decay 10^{-5}, clipping at 0.8, seed 42, and 10k/37k updates. Images are square-padded, resized to 256×256, cropped to 95% randomly in training or centrally at test, and resized back to 256×256. Training adds color randomization and state dropout with probability 0.2.

InternVLA-A1.5. The G1-Sonic base combines Qwen3.5-2B with a 50-step action expert. The data pipeline applies M/M normalization using training-set statistics. Action-only loss updates the entire vision-language model (VLM), including its vision and language components, and the action expert while freezing the WAN video DiT. Training uses global batch 32, AdamW with peak rate 5×10^{-5}, cosine decay, 2k warmup updates, weight decay 0.01, seed 42, and 50k/156k updates. Inference uses ten flow steps and seed 42.

$\pi_{0.5}$. OpenPI uses a 16-step action horizon, an 80-dimensional internal action layer sliced to 78 outputs, and unclipped Q/Q normalization. Full fine-tuning uses global batch 32, AdamW with clipping at 1.0, seed 42, and 50k/156k updates. The learning rate is constant at 5×10^{-5} after 1k warmup updates. EMA decay is 0.999, and EMA weights are evaluated with ten flow steps. Training augments images with random 95% crops, rotations up to $\pm 5^{\circ}$, and color randomization.

PRTS. PRTS-4B/Qwen3-VL is fully fine-tuned, with a 20-step chunk and Q/Q normalization. Training uses global batch 16, peak rate 5×10^{-5}, 5k warmup updates, linear decay, seed 42, and 99k/312k updates. Up to three randomly selected image transforms vary color, sharpness, crop, or rotation. Inference uses five flow steps.

Ψ_0. The frozen VLM conditions a trainable action expert with a 30-step horizon and R/R normalization. Training uses global batch 128, bf16, AdamW at 10^{-4}, cosine decay, 1k warmup updates, seed 292285, and 13k/39k updates, with color randomization and Gaussian image noise. Inference uses eight flow steps.

SmolVLA. The SmolVLM2 backbone, including vision and language components, is frozen while the action expert and state projection are trained. The G1-Sonic base uses a 50-step chunk, M/M normalization, and ten flow-inference steps. Training uses global batch 128, AdamW, seed 1000, and 13k/39k updates, with the learning-rate schedule shared with X-VLA described below.

StarVLA-α. Qwen3-VL-4B-Instruct-Action uses QwenOFT full fine-tuning, no proprioception, R action normalization, and 16-step action regression without stochastic sampling. Training uses global batch 64, base/interface and action learning rates of 10^{-5} and 10^{-4}, cosine decay, 5k warmup updates, seed 42, and 25k/78k updates.

XR-1. Xiaomi-Robotics-1 is adapted to the SONIC interface by padding state to 60 dimensions and slicing 80 action outputs to 78 over a 30-step chunk. State uses Q normalization, and actions use M statistics for each chunk position. All components except VLM input embeddings are trained, with global batch 32, seed 42,

and 50k/156k updates. The scheduler warms from 5×10^{-7} to 2×10^{-5} over 500 updates, then decays to 5×10^{-6}. Training varies brightness, contrast, and saturation. Inference uses five Euler flow steps.

X-VLA. The G1-Sonic base uses I/M normalization, a 30-step chunk, and ten inference steps. Fine-tuning updates the transformer and soft prompts without freezing vision or language modules, using global batch 128, AdamW, seed 1000, and 13k/39k updates. Only the egocentric view is available; the two unused camera slots are masked in both training and evaluation.

DM0.5. The released DM0.5 base pairs a Gemma 3 vision-language model, whose SigLIP encoder reads 448×448 images, with a 34-layer flow-matching action expert. Its action input and output projections are widened from 32 to 78 dimensions. The 43 joint-state values enter the prompt as 256-bin state tokens, and actions use OpenDM's absolute rather than state-relative mode over a 50-step chunk, with Q/Q normalization. Full fine-tuning uses global batch 32, AdamW with clipping at 1.0, peak rate 2.5×10^{-5}, 1k warmup updates, cosine decay to 10% of the peak, seed 42, and 50k/156k updates. Images are padded to square and resized to 448×448; training applies random 95% crops, rotations up to $\pm 2°$, and color randomization, each with probability 0.5. Inference uses ten flow steps.

SmolVLA and X-VLA use a cosine schedule with peak 10^{-4} and floor 2.5×10^{-6}: atomic runs warm up for 433 updates and decay over 13k updates, while compositional runs warm up for 1k updates, decay over 30k updates, and stay at the floor for the last 9k. For image preprocessing, $\pi_{0.5}$, InternVLA-A1.5, and X-VLA pad images to 224×224, and SmolVLA to 512×512. InternVLA-A1.5, SmolVLA, StarVLA-α, X-VLA, and Fast-WAM use no training image augmentation.

B-B Controller-Specific Policy Interfaces

The five controller interfaces expose 36 (AMO), 78 (SONIC), 50 (HEFT), 52 (ALMI), and 50 (ScaleBFM) action values at 50 Hz. AMO combines 22 body-command entries with 14 fingers; SONIC uses 64 motion tokens and 14 fingers; HEFT and ScaleBFM use root pose plus 29 joints and 14 fingers; ALMI combines four base commands and 34 upper-body values with 14 fingers. The controller comparison uses GR00T N1.7 and $\pi_{0.5}$, with policies trained on the command layout and data associated with each controller.

Both policies receive an egocentric RGB image and a task instruction, while their state inputs depend on the controller. With SONIC, HEFT, ALMI, and ScaleBFM, $\pi_{0.5}$ uses the 43 measured body-and-hand joint positions, and GR00T N1.7 additionally uses three projected-gravity values, giving 46 state inputs. With AMO, both policies use 32 entries comprising 28 measured arm-and-hand joint positions and the previous torso orientation and height commands, without projected gravity. These fields are used consistently during training and inference, and the dimensions refer to selected inputs before internal model padding. Predicted actions follow the corresponding controller command layout above, including the 14 finger targets, and are delivered at 50 Hz.

C Metrics and Aggregation

For task t, with n_t successes among N_t trials, success rate is averaged over tasks rather than pooled episodes:

$$\mathrm{SR}(\mathcal{T}) = \frac{100}{|\mathcal{T}|} \sum_{t \in \mathcal{T}} \frac{n_t}{N_t}. \tag{1}$$

Overall averages use the task weights stated in each table. The DR aggregate weights its 100 tasks and three levels equally. For Fig. 3, SR uses all 100 episodes per profile. Power, slip, action rate, falls, and relative time use successful episodes only, with 5–79 successes per profile. Each is calculated per episode and then averaged equally across successful episodes in the profile, rather than averaging task-level means.

Mechanical output energy integrates absolute motor power over 43 simulated motors, $E_e = \sum_k \Delta t \sum_j |\tau_{e,j,k} \dot{q}_{e,j,k}|$, with a 2 ms physics step in controller studies. Reported power is E_e/T_e in watts, where T_e is the episode duration; the power omits electrical losses. Foot slip is the mean horizontal foot-body speed in cm/s over samples with contact between a foot and any non-robot geometry. Action rate is the mean norm of successive differences in the 29 body-joint position targets, divided by the nominal 20 ms

control interval. Fall rate flags a decrease in free-joint root height exceeding 0.30 m from its first recorded value.

Relative time divides each successful episode's duration by the median successful duration for the same task and policy. The reference pool combines successful episodes across all five controllers at 10, 30, and 50 demonstrations per task, together with SONIC's 100-demonstration setting. Its median is computed over episodes rather than controller-level means or medians. This common denominator is used for all controllers of a given policy and task, including the 50-demonstration profiles in Fig. 3. Relative time is therefore model-specific and does not compare absolute speed between models. Unsuccessful episodes are excluded when computing power, energy, and relative time.

Radar bounds L, U are each metric's minimum and maximum across the 20 profiles, with raw ranges in Fig. 3. Define $z = [g(x) - g(L)]/[g(U) - g(L)]$, using identity g for SR and falls and $g(x) = \ln x$ otherwise. The radius is z for SR and $1 - z$ for the other metrics. Shared scales preserve relative ordering but polygon area is not an aggregate score.

D Auxiliary Data and Generator Studies

D-A Controller and Demonstration Scale Protocol

The controller and demonstration scale studies use five atomic and five compositional bathroom tasks in scenes 401, 415, and 418. Nested subsets contain $N \in \{10, 30, 50\}$ demonstrations per task, with $N = 100$ additionally available for SONIC. Separate five-task models use $100N$ updates on $5N$ trajectories, with global batch 64 for GR00T N1.7 and 32 for $\pi_{0.5}$. Each configuration has 20 trials per task. Increasing data also increases optimization budget, so this is not a fixed-compute comparison.

At $N = 100$, SONIC yields atomic/compositional SR of 54/18% for GR00T N1.7 and 78/29% for $\pi_{0.5}$. Relative to $N = 50$, only $\pi_{0.5}$ atomic performance improves. The extension therefore provides no consistent gain across policies and task categories and is excluded from the five-controller averages.

For $\pi_{0.5}$, action dimensions with quantile-normalized values beyond $|z| = 5$ use min/max normalization instead. Controller, scale, and source evaluations use seeds 0–19. A task's shared horizon is the maximum demonstration-derived limit across its data sources.

D-B Data-Source Mixtures

The source study trains GR00T N1.7 and $\pi_{0.5}$ jointly on 16 atomic and four compositional tasks in six scene instances, then tests the same task identities and scenes. The six conditions use teleoperation (T), motion synthesis (S), augmentation (A), and their listed mixtures. Mixtures concatenate selected sources without count matching or source-balanced sampling; GR00T N1.7 samples valid action-window starts and $\pi_{0.5}$ samples frame starts.

D-C Motion-Generator Adaptation

Kimodo generates three-second, 30 Hz G1 motion references and frozen SONIC executes them at 50 Hz in MuJoCo with a 2 ms physics step. Training batches contain 64 condition groups with four candidate motions each: 32 random spatial constraints and 32 task-derived stages. Six denoising steps include four stochastic transitions used for a clipped, group-normalized policy-gradient update (Black et al., 2024; Schulman et al., 2017); the simulator and controller are not differentiated through. Gaussian transition log probabilities are normalized by the number of entries in the motion sequence before their differences are exponentiated to form PPO ratios. Full fine-tuning updates the denoiser at 10^{-7}, while LoRA (Hu et al., 2022) uses rank 16, scale 32, and a 10^{-5} learning rate. The evaluated Full and LoRA checkpoints are from iterations 3,075 and 1,225, respectively. Both use seed 0, frozen SONIC and text encoder, and a trained value head. Validation uses 64 fixed conditions every 25 iterations (seed 9999). For each run, selection uses the highest validation reward among saved checkpoints, independently of the expanded test.

Fig. 9 compares training rewards over the first 1,425 iterations of each run. LoRA improves faster initially, but its later reward fluctuates around a plateau, whereas full fine-tuning continues to improve. Over the last 100 shown iterations, mean reward is 0.908 for Full and 0.818 for LoRA. This trend is consistent with the higher overall task success of the selected Full model in Table 5.




Figure 8 Kimodo locomotion-and-reaching comparison under SONIC execution: walking forward while reaching a shared target with the left hand.



Figure 9 Kimodo training reward over the first 1,425 iterations. Faint curves show per-iteration rewards, and heavier curves show 51-iteration centered moving averages.

The synthesis corpus used in the source-mixture study is generated with fully fine-tuned Kimodo models and a frozen SONIC controller that executes the generated motions. Only rollouts that successfully complete the task are retained as training demonstrations.

The augmentation source uses one teleoperated trajectory per task to generate local variations in execution timing and initial conditions. Body motion tokens and finger targets are resampled together, varying total duration by up to 4% and changing local playback speed while preserving motion order and hand–body synchronization. Robot and movable-object positions vary within the native reset ranges of 5 cm and 2 cm. Each candidate is executed through SONIC and screened for task success and physical validity. The 1,000 accepted episodes came from 1,606 attempts.

D-D Kimodo Evaluation Conditions

The reported scene-task evaluation covers 30 task–scene pairs, comprising ten Approach, five compositional Approach, and fifteen Close tasks, with ten episodes per pair and model. Overall success gives equal weight to these 30 pairs. Thirteen pairs overlap the task-derived fine-tuning set.

The separate goal-reaching evaluation has 198 fixed conditions per model: 54 locomotion, 72 stationary manipulation, and 72 combined locomotion/reaching. Each motion executes for three seconds; root error is planar distance to the shared root target and palm error is 3-D distance between the executed grasp center and shared palm target. Means and sample standard deviations summarize conditions, not independent training runs. Prompt and target ranges overlap training support, so this evaluation is in-distribution.

E Simulation and Hardware Evaluation

The real-to-sim study covers fridge opening, cup transport from a shelf to a desk, and moving three conveyor boxes to a desk. Simulation uses 50 teleoperation episodes per task. GR00T N1.7, Fast-WAM, and XR-1 are each trained separately per task for 10k updates with seed 42 and budget-end checkpoint selection. GR00T N1.7 uses batch 64 and Fast-WAM batch 32, both with cosine decay from 10^{-4}. XR-1 retains its main-benchmark recipe, with batch 32 and cosine decay from 2×10^{-5}. This fixed budget is distinct from the main experiment's two-pass planning rule.

Evaluation uses one 320×240 head camera, SONIC at 50 Hz, seeds 0–19, and no robot/object reset randomization. Limits are 592/951/1,889 control steps, without fall-based early termination. All models start from identical initial states for each seed. Simulation and hardware scenes are approximate counterparts rather than geometrically paired.

In simulation, policies use only the G1 built-in head camera, without wrist cameras. On hardware, policies use the left RGB image of a ZED Mini stereo camera mounted on the head, as shown in Fig. 10.



(a) Front view (b) Side view

Figure 10 Head camera used in the real-robot experiments. (a) Front and (b) side views of the ZED Mini stereo camera mounted on the G1 head; policies use its left RGB image.

The real-robot teleoperation dataset contains 567 episodes totaling approximately 9.0 hours across fridge opening, cup transport, bottle grasping, and conveyor handling. Hardware training uses 50 demonstrations per evaluated task. Each model is trained separately for each task and follows the training and inference configuration of its corresponding simulation experiment, with real demonstrations replacing simulated data.

Hardware uses a Unitree G1 and human-judged completion. The cup must be placed on the table, the fridge door opened, or a box picked up from the conveyor. Each model–task cell has ten trials. In Fridge/Cup/Conveyor order, success counts are GR00T N1.7 5/6/5, Fast-WAM 4/5/5, and XR-1 8/7/6. Simulation's conveyor criterion requires all three boxes on the desk, whereas the hardware criterion is a box picked from the moving belt. These outcomes therefore use different success predicates.