



CDOT

SICT AR Meeting Area

People

get involved with CDOT

as a Student

as an Open Source Community Member

as a Company

courses

BTC640

BTH740

BTP300

DPI908

DPS901

DPS905

DPS909

DPS911

DPS914

DPS915

DPS924

DPS931

EAC234

ECL500

GAM531

GAM666

GAM670

GPU610

LUX Program

MAP524

OOP344

OPS235

OPS245

OPS335

OPS345

OPS435

OPS445

OPS535

OPS635

OSD600

OSD700

OSL640

OSL740

OSL840

ULI101 Week 5

Contents

[hide]

1

head and tail commands

2

cut

3

sort command

4

wc

5

grep utility

6

Standard Input and Standard Output

7

Standard Input Redirection

8

Standard Output Redirection

9

Standard Error

10

Inter-process communication

11

Pipes

12

tee command

13

/dev/null file

14

“Here” documents

head and tail commands [edit]

These commands display the beginning or the end of a file respectively. By default, 10 lines are displayed. The entire file will be displayed if it is less than 10 lines in length

```
# head [-line_count] file
$ head -3 users.log
```

cut [edit]

- Selects fields or columns from files or standard input
- Range can be specified in multiple ways:
 - 1-10 - first 10
 - 3-8 - 3rd to 8th
 - -10 - up to 10th
 - 2- - from 2nd until the end of line
 - 1-3,4,10- - combination of above
- Important options:
 - -c - cut characters
 - -f - cut fields
- Default field delimiter is the tab
- Other field delimiter can be specified using the -d option
- Field delimiter must be a single character, only one delimiter is supported

[Real World Mozilla](#)
[RHT524](#)
[SBR600](#)
[SEC520](#)
[SPO600](#)
[SRT210](#)
[ULI101](#)

course projects

[Course Project List](#)
[Potential Course Projects](#)
[Contrib Opportunities](#)

links

[CDOT](#)
[Planet CDOT](#)
[FSOSS](#)

Tools

[What links here](#)
[Related changes](#)
[Upload file](#)
[Special pages](#)
[Printable version](#)
[Permanent link](#)
[Page information](#)

- If special characters are used for delimiters they must be quoted

```
# will cut first 2 characters
$ cut -c 1-2

# will cut 2nd and 5th field
$ cut -f 2,5

# will cut first 2 fields delimited with a comma
$ cut -d, -f1-2

# space is the field delimiter
$ cut -d" " -f1
```

sort command [\[edit\]](#)

- Sorts single files or standard input
- Merges and sorts multiple files
- Is able to sort by fields
- Popular options:
 - -f - ignore case in comparisons
 - -n - numeric sort
 - -u - display unique entries
 - -r - reverse sort

WC [\[edit\]](#)

- Counts the number of lines, words and/or characters in a file
- Usage: wc option [filename]
- Options:
 - -l - count lines
 - -w - count words (delimited by whitespace)
 - -m - count characters
- If no option is specified all 3 counts are displayed

grep utility [\[edit\]](#)

- Searches for literal text and text patterns
- Pattern-based searches will be covered in detail next week
- Example usage: `grep student *`
- Works with files and/or standard input
- Acts like a filter - outputs only lines which are successfully matched to a given regular expression
- A successful match can be entire line or any part of it
- The entire line that has the match inside will be displayed
- Useful grep options
 - -i - ignores case

- -n - numbers lines in the output
- -v - reverse match
- -c - displays the count of matched lines

Standard Input and Standard Output [\[edit\]](#)

- Standard input (stdin) is a general term which describes how or where a command receives information from
- When no information is coming from standard input a command usually has defaults or expects an argument (parameter). Typically such parameter would be a file name
- Standard output (stdout) describes the place where or how the commands sends its output
- For most commands the standard input and output are your terminal's keyboard and screen
- Standard input can be redirected from a file or piped from another command
- Standard output can be redirected to a file or piped to another command

Standard Input Redirection [\[edit\]](#)

```
command < filename
```

- Example: `tr 'a-z' 'A-Z' < ls.txt=`
- Used for commands which do not accept a file as argument

Standard Output Redirection [\[edit\]](#)

```
command > filename
```

- Redirects a command's standard output to a file
- Stdout redirection is represented by the `>` symbol.
- Example: `ls > ls.txt` will redirect output from the `ls` command into a file called `ls.txt`. In other words the output of `ls` will be saved to `ls.txt`
- If the file exists already its content will be replaced
- To append to a file, the `>>` symbol can be used

Standard Error [\[edit\]](#)

- In addition to standard input and standard output UNIX commands have standard error
- Standard error is the place where error messages are sent to
- By default error messages are sent to the terminal
- Standard error can be redirected by using the `2>` or `2>>` redirection operators
- Sometimes you might want to redirect the standard error to the same place as standard output
- Use the `2>&1` redirection for that

Inter-process communication [\[edit\]](#)

- Commands can send their standard output directly to standard input of other commands

- A few simple commands can form a more powerful one
- No temporary files are necessary
- This is achieved by using pipes and tees

Pipes [\[edit\]](#)

- Pipes are represented by `|`
- Many commands can be “piped” together, but filter commands use them especially often
- Each filter processes the initial input based on it's design
- Filters must be chained in specific order
- Example piping use: `ls | less`

tee command [\[edit\]](#)

- UNIX pipe with the tee utility can be used to split the flow of information
- Example: `ls | tee unsorted.txt | sort`

/dev/null file [\[edit\]](#)

- The /dev/null file (sometimes called the bit bucket or black hole) is a special system file that discards all data written into in
- Useful to discard unwanted command output,
- Example: `find / -name "homer" 2> /dev/null`
- Also, /dev/null can provide null data (EOF only) to processes reading from it
- Useful to purge (empty) files etc, for example: `cat /dev/null > ~/.bash_history`

“Here” documents [\[edit\]](#)

- The << symbol indicates a “here” document

```
sort << EOF
word
name
car
EOF
```

- Anything between EOF...EOF is sent to the standard input of a utility
- You can use some other string/symbol instead of “EOF”

Categories: [Pages with syntax highlighting errors](#) | [ULI101](#) | [ULI101-2018](#)

This page was last edited on 4 September 2019, at 20:31.

[Privacy policy](#) [About CDOT Wiki](#) [Disclaimers](#) [Mobile view](#)

