

Introduction to Tensor Regression: An Example of Simple Least Square Regression

Zixiang Xu

`zxu27@gmu.edu`

Ben Seiyon Lee

`slee287@gmu.edu`

Motivation & Research Goal

Tensors, also known as multidimensional arrays, are generalizations of vectors and matrices to higher dimensions. In recent years, tensor data are fast emerging in a wide variety of scientific and business applications, including recommendation systems, speech or facial recognition, networks analysis, knowledge graphs and relational learning. Tensor data analysis is thus gaining increasing attention in statistics and machine learning communities.¹

For the purpose of studying tensor, the article *Tensor in Modern Statistical Learning*[1] was published recently, where the tensor regression part of the paper took my interest. After googling and looking at the *Tensor Computation for Data Analysis*[2] book, I decided to take this simple LS tensor regression as my final project for STAT-676. And the main purpose of this project is to find out the performance of simple least square tensor regression under the basic settings.

Background Preparation

We start with several fundamental definitions related to tensors.

The *order* of a tensor, also referred to as the *mode*, is the dimension of the array. A first-order tensor is a vector, a second-order tensor is a matrix, and tensors of order three and higher are referred to as high-order tensors, see Figure 1.




Figure 1: An example of first, second and third-order tensors

The *fiber* of a tensor is defined by fixing all indices but one. For example, given a third-order tensor $\mathcal{X} \in \mathbb{R}^{p_1 \times p_2 \times p_3}$, its mode-1, 2 and 3 fibers are denoted as $\mathcal{X}_{:jk}$, $\mathcal{X}_{i:k}$ and $\mathcal{X}_{ij:}$, respectively; see Figure 2 for a graphic illustration.




Figure 2: Tensor fibers and unfolding.

¹The first introduction paragraph and the definitions introduced in the first part of next section are largely based on the previous article *Tensor in Modern Statistical Learning*[1]

Tensor *unfolding*, also known as tensor matricization, is a tensor operation that arranges tensor fibers into a matrix. Given a tensor $\mathcal{X} \in \mathbf{R}^{p_1 \times p_2 \times \dots \times p_D}$, the mode- d unfolding, denoted as $\mathcal{X}_{(d)}$, arranges the mode- d fibers to be the columns of the resulting matrix. For example, the mode-1 unfolding of a third-order tensor $\mathcal{X} \in \mathbf{R}^{p_1 \times p_2 \times p_3}$, denoted by $\mathcal{X}_{(1)}$, results in the matrix $[\mathcal{X}_{:11}, \dots, \mathcal{X}_{:p_21}, \dots, \mathcal{X}_{:p_2p_3}] \in \mathbf{R}^{p_1 \times (p_2 p_3)}$; again see Figure 2 for an illustration.

For a tensor $\mathcal{X} \in \mathbf{R}^{p_1 \times p_2 \times \dots \times p_D}$ and a matrix $A \in \mathbf{R}^{J \times p_d}$, the d -mode tensor matrix product, denoted by \times_d , is defined as $\mathcal{X} \times_d A \in \mathbf{R}^{p_1 \times \dots \times p_{d-1} \times J \times \dots \times p_D}$. In this operation, each mode- d fiber of \mathcal{X} is multiplied by the matrix A , and element-wisely, we have $(\mathcal{X} \times_d A)_{i_1, i_2, \dots, i_D} = \sum_{j=1}^{p_d} \mathcal{X}_{i_1, \dots, i_{d-1}, j, i_{d+1}, \dots, i_D} A_{jd}$.

One interesting fact related to the d -mode tensor matrix product is that

$$\begin{aligned} \mathcal{Y} &= \mathcal{X} \times_1 A^{(1)} \times_2 A^{(2)} \dots \times_N A^{(N)} \\ \iff Y_{(n)} &= A^{(n)} X_{(n)} (A^{(N)} \otimes \dots \otimes A^{(n+1)} \otimes A^{(n-1)} \otimes \dots \otimes A^{(1)})^T, \end{aligned} \quad (1)$$

where $\mathcal{X}, \mathcal{Y} \in \mathbf{R}^{p_1 \times p_2 \times \dots \times p_N}$, $A^{(i)} \in \mathbf{R}^{p_i \times p_i}$ and $X_{(n)}, Y_{(n)}$ are mode- n unfolding of tensor \mathcal{X}, \mathcal{Y} . (A simple proof is available [here](#) [3].) We will use this property (referred to as property 1 below) to deduce our algorithm.

Model & Algorithm

The simple tensor regression model is defined as:

$$\mathcal{Y} = \mathcal{X} \times_1 B^{(1)} \dots \times_M B^{(M)} \times_{M+1} \mathbf{I}_N + \mathcal{E}, \quad (2)$$

where $\mathcal{X}, \mathcal{Y}, \mathcal{E} \in \mathbf{R}^{p_1 \times p_2 \times \dots \times p_{M+1}}$ are tensors with the same structure. \mathcal{X} is the explanatory variable, \mathcal{Y} is the response variable, and \mathcal{E} is the error term. Here \mathcal{E} is assumed to have a distribution of high-dimension Gaussian with 0 correlations. $B^{(m)} \in \mathbf{R}^{p_m \times p_m}$ ($m = 1, \dots, M$) are matrices of parameters. Note that in this model, we are considering the last dimension of the tensors (\mathcal{X}, \mathcal{Y}) as a simple stack, i.e., the random tensors (\mathcal{X}, \mathcal{Y}) are a combination of p_{M+1} small tensors with dimension $p_1 \times p_2 \times \dots \times p_M$. And that is why we are using \mathbf{I}_N as our last matrix of parameters. Otherwise, without this assumption, there would be too many parameters and resulting in disaster estimation.

Our goal is to estimate $B^{(m)}$'s when \mathcal{X}, \mathcal{Y} are known. That is, the problem would be solving

$$\underset{B^{(1)}, \dots, B^{(M)}}{\operatorname{argmin}} L(B^{(1)}, \dots, B^{(M)} | \mathcal{X}, \mathcal{Y}) = \underset{B^{(1)}, \dots, B^{(M)}}{\operatorname{argmin}} \|\mathcal{Y} - \mathcal{X} \times_1 B^{(1)} \dots \times_M B^{(M)} \times_{M+1} \mathbf{I}_N\|_F^2.$$

An immediate algorithm would be solving

$$\underset{B^{(m)}}{\operatorname{argmin}} L(B^{(m)} | \mathcal{X}, \mathcal{Y}, B^{(1)}, \dots, B^{(m-1)}, B^{(m+1)}, \dots, B^{(M)}) = \underset{B^{(m)}}{\operatorname{argmin}} \|\mathcal{Y} - \mathcal{X} \times_1 B^{(1)} \dots \times_M B^{(M)} \times_{M+1} \mathbf{I}_N\|_F^2$$

repeatedly for m from 1 to M until the objective function L converges.

Using property 1, the above optimization problem would be reduced to iteratively solving

$$\underset{B^{(m)}}{\operatorname{argmin}} \|Y_{(m)} - B^{(m)} \tilde{X}^m\|_F^2,$$

where $\tilde{X}^m = X_{(m)} (B^{(N)} \otimes \dots \otimes B^{(m+1)} \otimes B^{(m-1)} \otimes \dots \otimes B^{(1)})^T$.

Overall, our algorithm is concluded below:

Input: predictor \mathcal{X} , response \mathcal{Y}
Output: $\mathbf{B}^m, m = 1, \dots, M$
Initialize $\mathbf{B}^m, m = 1, \dots, M$
Iterate until convergence:
 For $m = 1, \dots, M$:
 $\tilde{\mathbf{X}}^{(m)} = \mathbf{X}_{(m)}(\mathbf{B}^{(M)} \otimes \dots \otimes \mathbf{B}^{(m+1)} \otimes \mathbf{B}^{(m-1)} \otimes \dots \otimes \mathbf{B}^{(1)})^T$
 $\mathbf{B}^{(m)} = \mathbf{Y}_{(m)}(\tilde{\mathbf{X}}^{(m)})^T (\tilde{\mathbf{X}}^{(m)}(\tilde{\mathbf{X}}^{(m)})^T)^{-1}$
 End for

Simulation Study

To evaluate the performance of this simple tensor regression algorithm, we decide to generate two random samples $(\mathcal{X}, \mathcal{Y})$ and $(\mathcal{X}_2, \mathcal{Y}_2)$ under the same setting.

In this project, \mathcal{X} would be generated under different settings (eg. multi-normal, uniform etc.), and \mathcal{Y} would be generated based on the relation:

$$\mathcal{Y} = \mathcal{X} \times_1 A^{(1)} \times_2 A^{(2)} \dots \times_N A^{(N)} \iff Y_{(n)} = A^{(n)} X_{(n)} (A^{(N)} \otimes \dots \otimes A^{(n+1)} \otimes A^{(n-1)} \otimes \dots \otimes A^{(1)})^T.$$

Results & Conclusion

Future Discussion

There remain a lot of interesting points that could be explored in the future. For example, in most cases, the data \mathcal{X} and \mathcal{Y} do not have the same structure. Therefore, we should consider changing the parameter matrices into non-square matrices. Also, we need to add a penalty term if the coefficients are assumed to have sparsity property. Moreover, the distribution of the error \mathcal{E} could be non-normal or dependent on each other, where a transformation could be adopted.

References

- [1] Will Wei Sun, Botao Hao, and Lexin Li. Tensors in modern statistical learning. *Wiley StatsRef: Statistics Reference Online*, pages 1–25, 2014.
- [2] Zhen Long Ce Zhu Yipeng Liu, Jiani Liu. *Tensor Computation for Data Analysis*. Springer Cham.
- [3] Lana Periša (<https://math.stackexchange.com/users/452859/lana-peri%C5%A1a>). n mode product and kronecker product relation. Mathematics Stack Exchange. URL:<https://math.stackexchange.com/q/2312166> (version: 2017-06-06).

Appendix

0. Function preparation

```
create_B=function(d,random=FALSE){#a function to initialize B's
  l=vector('list',k)
  if(random){for(i in 1:k) l[[i]]=matrix(rnorm(dimension[i]^2),dimension[i])}
  else {for(i in 1:k) l[[i]]=diag(dimension[i])}
  return(l)
}
multiple_ttm=function(x,b){#a function to perform consecutive mode-d products
  if(length(b)>1) return(ttm(multiple_ttm(x,b[-length(b)]),b[[length(b)]],length(b)))
  return(ttm(x,b[[1]],1))
}
```

1. Generate Data

```
library(rTensor) #https://cran.r-project.org/web/packages/rTensor/index.html
set.seed(5)
dimension=c(3,4,10)
k=length(dimension)-1
e=rand_tensor(dimension)
X=100*rand_tensor(dimension)
B=create_B(dimension,random=TRUE) #generate random B's
Y=multiple_ttm(X,B)+e
X2=100*rand_tensor(dimension)
e2=rand_tensor(dimension)
Y2=multiple_ttm(X2,B)+e2
#X;B;e;Y # view generated sample data
```

2. Regression

```
N=500 #number of iterations
B_hat=create_B(dimension) #initialize B's as identical matrices
#B_hat=lapply(1:k, function(i) return(B[[i]]+matrix(rnorm(dimension[i]^2),dimension[i])/10))
#B;B_hat
B_hats=list()
Error_Y_hat=numeric(0) #store the prediction errors comparing to Y
Error_Y2_hat=numeric(0) #store the prediction errors comparing to Y2
for(i in 1:N){
  for(j in 1:k){ #each regression iteration
    X_j=k_unfold(X,j)@data
    temp=B_hat[-j]
    temp[[k]]=diag(dimension[k+1])
    X_tilde=X_j%*%t(kronecker_list(rev(temp)))
    Y_j=k_unfold(Y,j)@data
    B_hat[[j]]=Y_j%*%t(X_tilde)%*%solve(X_tilde%*%t(X_tilde))
    #print(B_hat)
  }
  B_hats[[i]]=B_hat #update after each small iteration
  Y_hat=multiple_ttm(X,B_hat)
```

```

Y2_hat=multiple_ttm(X2,B_hat)
Error_Y_hat=c(Error_Y_hat,fnorm(Y_hat-Y))
Error_Y2_hat=c(Error_Y2_hat,fnorm(Y2_hat-Y2))
#cat(i,fnorm(Y_hat-Y),fnorm(Y2_hat-Y2),'\n')
if(tail(Error_Y_hat,1)<50) break
}
par(mar=c(5,4,4,4)+0.3) #draw the graph
plot(Error_Y_hat,type='l',col='coral',axes=FALSE,xlab='\ # of iterations',
      ylab='error of Y_hat',main='Prediction Error')
axis(side=2,at=pretty(range(Error_Y_hat)),las=1)
box()
par(new=TRUE)
plot(Error_Y2_hat,type='l',col='skyblue',axes=FALSE,xlab='',ylab='',lty=2)
axis(side=4,at=pretty(range(Error_Y2_hat)),las=1)
mtext("error of Y2_hat", side=4, line=3)
axis(1,pretty(range(1:length(Error_Y_hat))))
legend("right",legend=c("error of Y_hat","error of Y2_hat"),
      text.col=c("coral","skyblue"),lty=c(1,2),col=c("coral","skyblue"),cex=.8,bty="n")

```

Prediction Error

