# Search Results

Advanced Search Tips | Ask Question

Results for "log levels" Search options **questions only**

724 results

Relevance | Newest | Votes

5 votes 5 answers
**Q: How can I direct log4j output so that different log levels go to different appenders?**
Is it possible to have "debug" and "info" output written to the console while the "info" output is only written to some **log** file? ...
log4j
asked Apr 15 '09 by blacklocusde

8 votes 2 answers
**Q: Can Perl's Log::Log4perl's log levels be changed dynamically without updating config?**
I have a Mason template running under mod_perl, which is using Log::Log4perl. ... I want to change the **log** level of a particular dependent, but changing the config is too awkward, as it would have to pass through our deployment process to go live. ...
perl apache logging mod-perl log4perl
asked May 10 '11 by Will Sheppard

8 votes 1 answer
**Q: Gradle Logging Output Levels**
In my project classes I've used java.util.logging.Logger and added various **log** output's throughout my code, using various **log levels** ie. ... fdb: How do i get the config_fine & finer level logs to **log** to the console in a generic gradle java project ? ...
java logging gradle
asked Oct 29 '14 by SS44

8 votes 1 answer
**Q: IntelliJ: How to set log levels for tests**
When I run JUnit tests via IntelliJ, the console window is flooded with enormous amounts of **log** lines, for example DEBUG reactor.ipc ... DEBUG io.netty.buffer.ByteBufUtil - ... setting logging.level.reactor.ipc=WARN in my src/main/resources/application.properties and also setting -Dlogging.level.root=WARN on the RunConfig's VM arguments, but neither has any effect on the **log** ...
spring-boot logging intellij-idea junit log-level
asked Dec 17 '17 by Nob

8 votes 2 answers
**Q: Nlog and Custom Levels**
I know there are some **log levels** builtin in NLog like trace, info, fatal etc i want to define some new ones such as "DBLog" and be able to only configure all logs with DBlog to be targeted to a certain ... or I have to define a custom **log** ?
c# nlog logging
asked Feb 20 '11 by Stacker

0 votes 3 answers
**Q: TRACE log level**
I know following **log levels** in Log4J: ALL > DEBUG > INFO > WARN > ERROR > FATAL > OFF But in some samplers I found TRACE and trace() method: Logger LOG = Logger.getLogger(MyClass.class); LOG.trace(...
java log4j
asked Oct 30 '13 by vico

8 votes 2 answers
**Q: Can you set different log levels for different routes in Phoenix?**
I'd like to set the **log** level of Plug.Logger to :debug just for that one route. defmodule Web.Endpoint do ... I tried adding plug Plug.Logger, log: :debug to Web.HealthCheck, but then I just get the route logged twice at different **levels** [info] GET /ping [debug] GET /ping I've found a way to disable logging ...
logging elixir phoenix-framework
asked Jan 28 '18 by mmcbins

8 votes 3 answers
**Q: GAE node.js console.error() not logging as ERROR log level**
**levels**: items emitted with console.log() have the INFO **log** level. ... I was originally trying to get winston to work with Stackdriver (using @google-cloud/logging-winston) to get more granular logging **levels**, but might have I can't even get it to **log** at INFO or ERROR either. ...
javascript node.js google-app-engine logging stackdriver
asked Jan 11 '19 by ahong

7 votes 2 answers
**Q: How do I plug into socket.io's built in logging system to generate my own messages?**
How do I get at that logging object myself so I can generate my own **log** messages at appropriate **levels**? ... Longer term, I'm probably going to want a more robust logging system module (with the ability to **log** to files, auto-rotate, manage **levels** on a per-module basis, custom **log levels**, etc.) ...
logging node.js socket.io
asked Oct 5 '11 by drewww

7 votes 3 answers
**Q: Best practices for logging on top of logging levels**
Generally, **log levels** can be switched to get different level of detailed logs. Usually a lowest level of **log** often can help one to identify which area of the codes could be wrong. ... EDIT: This comes from a real project where the application deployed on customer environment and when things go wrong, the **log** file the thing they send in for debugging, definitely they will hate sending ...
logging
asked Dec 10 '09 by Dr. Xray

7 votes 1 answer
**Q: redis presto connector corrupt key when redis.key-prefix-schema-table=true for json dataFormat**
3 | false | dev.simple_table:{"id": 42, "serial": "foo"} {"name": "bar", "number": 3, "boolean": "false"} | 42 | 4B | true | false I've increased the **log** ... **levels** of redis and presto for hints, but nothing that is showing me any errors or reason for why the key is corrupt. ...
sql json redis presto
asked Oct 21 '16 by aaronzarosnart

7 votes 2 answers
**Q: ClassCastException in SpringBoot Logging**
The application fails when configuring **log levels**, on a ClassCastException java.util.HashMap cannot be cast to org.springframework.boot.logging.LogLevel. ... application.properties logging.level.root=warn logging.level.org.springframework.web=debug logging.level.org.hibernate=error logging.level.com.my.package.name=error Clearly the problem here is the values in this **levels** ...
java spring spring-boot spring-cloud classcastexception
asked Dec 10 '19 by sandermonsay

7 votes 1 answer
**Q: Am I abusing the idea of log levels here?**
So I came up with this solution: catch (Exception ex) { if (LOGGER.IsDebugEnabled()) { LOGGER.error("Exception during save()", ex); } **log** with stacktrace } else { LOGGER.error ...
java logging exception-handling slf4j
asked Mar 21 '18 by Sebastian

7 votes 2 answers
**Q: Change bunyan log color for different levels**
When using Bunyan, all my **log levels** use the same cyan color, like so: Here is the Bunyan configuration we are using: const bunyan = require('bunyan'); module.exports = bunyan.createLogger({name: " ...
node.js logging error-logging bunyan
asked Aug 3 '17 by Alexander Mills

7 votes 1 answer
**Q: Glassfish 3.1.1 suddenly stopped writing to server.log**
I changed one of the **log levels** in the admin console, and Glassfish 3.1.1 stopped writing anything into the domain1/logs/server.log ...
logging configuration glassfish
asked Feb 21 '12 by Dmitriy Chornyi

0 votes 5 answers
**Q: Git: How to prevent committing files that were modified just for debugging purposes?**
For instance, I'll disable some annoying features (like ads) by commenting out some lines of code, or I'll set the **log levels** and filters to only the ones I care about, or I'll force a conditional to be ...
git perforce
asked Apr 19 '12 by thien

7 votes 3 answers
**Q: How to change the hibernate logging level in JRipster?**
So my questions are: Is it possible to configure the **log** level for an individual REST call? How can I globally configure the **log levels** for the application? ...
hibernate logging jhipster
asked Mar 16 '15 by nezuvian

6 votes 10 answers
**Q: How to keep your own debug lines without checking them in?**
But if I would check this in into the source code repository, my colleagues would get angry on me for polluting the Log output and polluting the code. ... Clarification: Many answers related to the **log** output, and that you with **log levels** can filter that out. And I agree with that. But. I also mentioned the problem of polluting the actual code. ...
debugging version-control logging
asked Oct 10 '08 by Andreas

6 votes 2 answers
**Q: Rails on Heroku how to monitor worker process**
thrown before completion and where) Possibly ensure that some invariants are being held, or notified if not It's possible what I'm looking for is part of the normal logger workflow, (using different **log** ... **levels**?) ...
ruby-on-rails heroku monitoring production-environment tweetstream
asked Feb 12 '14 by Pat Marx

6 votes 4 answers
**Q: Is there a near-consensus guideline for log levels?**
I've been influenced by the **log levels** that I and my teams have used at my last two companies. I'll share ours here but keep in mind this bit is subjective: Fatal - Your app is going down. ... Also note that I don't really care what threshold is actually configured to **log** somewhere useful in a deployed / production environment. ...
c# Java logging
asked May 15 '11 by Matthew Lund

6 votes 1 answer
**Q: Find IdentityServer4 errors in Application Insights**
Or should I increase **log levels** somehow? Or do I need to add code somewhere to configure IdentityServer4 to **log** this stuff? ...
c# asp.net-core IdentityServer4
asked Jan 24 '20 by Jeroen

6 votes 4 answers
**Q: Grand Unified Theory of logging**
At every (or)significant program event, I **log** at varying **levels**. ... Events received, transaction succeed/fail, sql/ldap updated, etc What do you **log** - Fatal/Error/Warning/Info/Debug/Trace is covered in When to use the different **log levels** ...
testing logging embedded
asked Jan 10 '10 by Matej says reinstate Monica

6 votes 4 answers
**Q: logger names for configuring akka logger using the event-handler**
How do I configure the **log levels** for different actors separately? ...
scala logging slf4j akka
asked Jan 23 '12 by Uttaman Sangat

6 votes 1 answer
**Q: StreamHandler - Not logging to sys.stdout in docker container - Python**
'] app.logger.info('INFO LOG') app.logger.warning('WARNING LOG') app.logger.error('ERROR LOG') app.logger.critical('CRITICAL LOG') If I look at the app_error file, I can see output correctly: 2019/ ... **LOG** Which makes sense, as I have both the error **log**, which I'm assuming has **log levels** of ERROR and CRITICAL, and the streamhandler. ...
python apache docker logging
asked Dec 6 '18 by Daniel Hawes

6 votes 1 answer
**Q: Align logging messages of different levels**
But I'd like to align messages of different **log levels** together, producing output like below: ==========Start Logging Module1 ...
python logging module
asked Mar 20 '13 by chandan kumar

6 votes 2 answers
**Q: Configure logger in vertx 3**
Now I am trying to config logger **log levels**, using below config: JVM Arguments: - Doping profiles.active=dev -Dvertx.logger-delegate-factory-class-name=io.vertx.core.logging.SLF4JLogDelegateFactory ... info 16:29:58.076 [ main] WARN - com.sensegrow.main.Application - warning 16:29:58.076 [ main] ERROR - com.sensegrow.main.Application - error Its **log** ...
java logging vert.x
asked Jan 8 '16 by Deepak Agrawal

6 votes 2 answers
**Q: Must multiple Logback PropertyDefiner implementations be created to pull in multiple propert...**
I want to be be able to use properties to plugin different values, based on environment (dev, tst, uat, perf, prod) for various logging configurations (context name, **log levels**, appender file names, file ...
properties logback
asked Dec 3 '14 by wyck

6 votes 3 answers
**Q: Visual Log Viewer for Ruby On Rails 4.2**
I have worked previously on Laravel 4 and there is an awesome **log** viewer tool for it laravel **log** viewer view demo I'm looking something very similar for Ruby on rails 4.2, if you guys know any good visual ... From code I need to **log** at different **log levels**, and this tool should visually organize my logs, thanks. ...
ruby-on-rails ruby ruby-on-rails-4 logging rubygems
asked Mar 27 '18 by ankit.jaan

6 votes 1 answer
**Q: GWT compile crashes JVM**
I was trying different output styles (pretty,detailed, detailed) and different **log levels** (like it.could.change.output.style=pretty -Xmx4G -Xmx8G -Xmx16G -Xmx32G -Xmx64G -Xmx128G -Xmx256G -Xmx512G -Xmx1G -Xmx2G

java maven log4j slf4j

asked Jan 22 '16 by Addison

5
votes
5
answers

## Q: Logging conventions [closed]

What conventions do you use for **log** categories in log4j or similar libraries ? Usually you see class names as categories, but have you used other systems ? What about **log levels** ? ... What **levels** do you use and in which case ? Update: as some of you replied, there is no 'right' answer. I'm just looking for what different conventions people use as a possible source of inspiration. ...

java logging log4j

asked Oct 2 '08 by Tom

Prev 1 2 3 4 5 ... 15 Next

15 30 50 per page

STACK OVERFLOW
Questions
Jobs
Developer Jobs Directory
Salary Calculator
Help
Mobile
Disable Responsiveness

PRODUCTS
Teams
Talent
Advertising
Enterprise

COMPANY
About
Press
Work Here
Legal
Privacy Policy
Terms of Service
Contact Us
Cookie Settings
Cookie Policy

STACK EXCHANGE NETWORK
Technology
Life / Arts
Culture / Recreation
Science
Other

Blog Facebook Twitter LinkedIn Instagram

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under cc by-sa.
rev 2021.6.29.39606