Search Results

Advanced Search Tips | Ask Question

Results for "log levels" Search options **questions only**

724 results — Relevance | Newest | Votes

3 votes 2 answers
Q: Different log file for different levels in Serilog
I am using serilog and I need to save different **log levels** to different files (for example debug-20200706.log for debug level, info-20200706.log for debug level and ... ...
caf net logging serilog — asked Jul 8 '20 by Peyman Mehrabani

3 votes 1 answer
Q: Can't create InetSocketTransportAddress in TransportClient: NoNodeAvailableException[None of...
I'm trying to make my first Java application to talk to ElasticSearch, which is running on this node (timestamps and **log levels** removed): $ bin/elasticsearch [bootstrap]Unable to lock JVM Memory ...
java elasticsearch elasticsearch-2.0 — asked Nov 12 '15 by alfaralmond

3 votes 0 answers
Q: Play framework logging into several files
I'm using play framework logger (play.logger) and I need to **log** different **log levels** into separate files. I'm new with play and this is first time I have to use logger. ...
java logging playframework logback — asked Mar 18 '15 by Gogo

3 votes 3 answers
Q: Filtering specific lines
I am currently trying to filter specific lines from my **log** file. My lines in the **log** file are of the following pattern: ... So what I am trying to get is the **log level** errors only and not other **log levels**. I have the following which I am playing around with but I am not getting console output at all. ...
logstash — asked Aug 13 '13 by Raymond Nakampe

3 votes 2 answers
Q: Maintaining several log4j.xml configurations for multiple webapps
I webapps in Tomcat, each of them has to have its own log4j.xml configuration, because each webapp has a different **log level** and different appenders configured there. ... I'm using log4j 1.2.16 in a standalone **log** ... The growing challenge is that different parties, who use the logging, want different formats, rules and **log levels**: developers want TRACE logging for everything, testers want INFO logging, sys admins ...
java xml tomcat logging log4j — asked Sep 9 '15 by Kirill S.

3 votes 1 answer
Q: ActionMailer does not log e-mail body to rails console
With rails 4 I can see the entire delivered e-mail in the **log** output, but using rails 4 and Notification.the_mail() deliver I see no more than a long single line showing the headers: => #<Mail::Message ... How can I get the full **log** output? I tried all **log levels** from 0-5. ...
ruby-on-rails ruby-on-rails-3 actionmailer — asked Dec 6 '13 by ideabuser

3 votes 2 answers
Q: How to configure JUL, logging during JUnit tests?
I think it's important for **log** output to be easily customizable for tests: if a developer breaks a test and wants to read the **log** output, I'd prefer they locally tweak the **log** config than start messing ... with the (carefully chosen) **log levels** in the code, leading to "everything logged all infs" syndrome. ...
java logging junit log4j java.util.logging — asked Mar 14 '17 by SusanW

3 votes 1 answer
Q: winston log level/ hide log levels
As far as I understand **winston** allows hierarchy in its logging **levels**. You can set the **level** with winston.level = 'error' and all **levels** below should not be shown. ... Question 5: How to really set winston to show me only the **log level** Question 2: Why is Debug anyways shown in the console, I configured it to show up in a **log** file (what it additionally does) winston ...
node.js winston — asked Apr 16 '15 by Andi Giga

3 votes 1 answer
Q: Split TraceSource to Multiple Levels of TraceListeners
I trying to setup MySource trace source using two different **log levels**. FileLog should trace everything (verbose) and system event **log** should trace only Errors. ...
.net app-config trace — asked Feb 3 '12 by Sergei G

3 votes 1 answer
Q: Performance gap between spring data jpa and hibernate - jhipster
Page<Center> findAll(Pageable pageable) { log.debug("Request to get all Centers"); return centerRepository.findAll(pageable); } I've used ,Hipster's LoggingAspect and added a timer to **log** ... getDeclaringTypeName(), joinPoint.getSignature().getName(); //time e; } // configured hibernate to generate the statistics spring.jpa.properties.hibernate.generate_statistics=true // I change the **log levels** ...
java performance hibernate spring-data-jpa jhipster — asked Oct 11 '16 by Tom Van Rossum

3 votes 1 answer
Q: Ansible console output and log levels
is going into the ansible **log** file /var/log/ansible.log(... Is it possible to define **log level** to push more information in to **log** file, while running playbook in non verbose mode (ansible-playbook stack.yml) ? ...
logging ansible ansible-playbook — asked Jun 1 '16 by tgrdoud

3 votes 1 answer
Q: How do I handle ServerSocketChannel.accept() IOException: too many open files in NIO?
Also, (Maybe this should be another question) I have log4j2 configured to send emails for **log levels** of error and higher, yet I didn't get an email for this error. ... It usually works, the error was logged to the **log** file as expected, but I never got an email about it. I should have gotten plenty as the error occurred every time a connection was established. ...
java sockets nio ioexception socketchannel — asked Sep 13 '15 by mal

3 votes 0 answers
Q: Selenium Web Driver: Extracted Chrome Browser logs are incomplete
The Chrome browser **log** console in development utilities shows logs of different **log levels** (TRACE, SEVERE, WARNING) ... My approach is similar to this one: How to get Chrome browser console **log** [INFO] entries with Selenium We also tried to enable and request the **log** types DRIVER or CLIENT - but they are empty ...
java selenium selenium-webdriver webdriver chrome-web-driver — asked Jul 22 '19 by PAX

3 votes 1 answer
Q: Log4j2 not logging to graylog server properly
I am able to **log** things to my console, however, I am having an issue logging the correct **levels** to the server properly. ... Here are my current dependencies: In short, I just want to **log levels** of INFO to my console and **levels** of INFO or higher to my server. ...
java logging log4j log4j2 — asked Oct 16 '16 by mr nooby noob

3 votes 0 answers
Q: Log4j2: Ability to log data with different log levels in multi user environment
One of the requirements of our customer is to have different **log levels** for different logged-in users and also to change the **log levels** dynamically for a user.Also the Administrator should have a control ... i.e Lets say 'User A' needs Trace **log level** and 'User B' needs Error **log level** ...
java logging log4j oracle-adf log4j2 — asked Jun 20 '15 by Naveen Dariisi

3 votes 6 answers
Q: printk - showing in message log but not in terminal for any kernel log level
I pass any kernel **log level** with it and do not properly get any response back on the console for even the highest **log levels**. I checked and the current **log** configuration for printk is 4 4 1 7 ... What could be going wrong given that I've tried every **log level** and none work? THANKS! ...
linux-kernel kernel — asked Jan 31 '10 by Zach

3 votes 2 answers
Q: log4j2 LoggerContext not showing up in JMX Gui or JConsole
I am trying to configure log4j2 so that I can access the loggers via JMX and change their **log levels**. ... ref="log-test" /> </Root> </Loggers> </Configuration> My test program: package top; import org.apache.logging.log4j.LogManager; import org.apache.logging.log4j.Logger; public class ...
java logging log4j jmx log4j2 — asked Nov 6 '13 by colin_froggatt

3 votes 1 answer
Q: Log4j2 log levels not being filtered for hibernate and spring in Spring Boot application
I have configured Spring Boot to use Log4j2 according to this manual. I would like to filter all the logs by the level set in the Root logger. Here is my log4j2-spring.xml file: <?xml version="1.0" # ...
java spring spring-boot log4j log4j2 — asked Aug 9 '16 by Max Semkin

3 votes 1 answer
Q: Conditionally Print Stack Trace on Error Page Depending on Log Level using Facelets, Seam, a...
(from pages.xml): <logger name="com.example" level="Trace" /> Whereas this would not: <logger name="com.example" level="warn" /> Using Facelets with Seam, is there a way to determine Logback's **log** ... **levels**? ...
jakarta-ee websphere seam facelets logback — asked Jun 29 '10 by Christopher Parker

3 votes 0 answers
Q: Customizing Log report - ACRA Android
It is sending all last 200 lines of logcat with data by default.But I want to customize it to send only last 100 **log** cat messages of my app with **log levels** i or d. How to do it. ... I want **log** messages of only my app with level i or d with ACRA, how to achieve this. Thanks In Advance. ...
android acra — asked Jun 22 '12 by Ganesh K

3 votes 0 answers
Q: Mongoid 4 / MongoDB 2.4+ "Freezing" Issue
max_retries: 5 pool_size: 10 development: <<: *default The issue manifests in the following way: 1) The web application becomes completely unresponsive (the request just hangs) 2) The Rails **log** ... doesn't indicate anything out of the ordinary (even with Moped and Mongoid **log levels** set to DEBUG) ex: Started GET "/accounts" for 172.16.3.180 at 2014-04-23 09:11:34 -0400 Processing by AccountsController ...
ruby-on-rails ruby mongoid2 rack moped — asked Jun 13 '14 by Alex B.

3 votes 3 answers
Q: Spring Boot Logging override Colours
In its simplest form, the converter colors the output according to the **log level**, as shown in the following example: %clr(%5p) The following table describes the mapping of **log levels** to colors: Level ...
java spring spring-boot log4j2 — asked Feb 13 '19 by mutton Up

3 votes 1 answer
Q: gradle junit tests logging with slf4j
https://discuss.gradle.org/t/junit-slf4j-logging-during-junit-tests/24449 For some reason I can only see the INFO **log levels** and not above (WARN, ERROR) ... Anyone managed to set this to show all **log levels** during unit tests? Thanks in advance. ...
java logging gradle junit slf4j — asked Oct 17 '10 by Gedi

3 votes 2 answers
Q: How to disable NewRelic logs
Since in the documentation we only have the **log levels** to set, and I want to avoid any logging, is there any option I can use to disable them? ... false : true %> # **Log** level for agent logging: error, warn, info or debug. ...
ruby newrelic — asked Aug 17 '17 by Paulo Fidalgo

3 votes 0 answers
Q: Log4j2 setting log levels
I want to set the **log** level for specific library/packages to something different than the root. For example, I want org.apache.commons.lang3.tuple.Pair and com.google to be WARN. ... How do I add **log levels** for specific packages and what is this rolling level stuff? ...
java spring logging log4j2 rollingfileappender — asked May 3 '17 by Richard

3 votes 0 answers
Q: How to log pastable DDL with Hibernate.jpa\vendorAdapter
Soon I wish to deploy and like to **log** the pastable DDL code to the console (or somewhere) but I only figured out how to setup and configure the hibernate logging and am able to set **log levels** and stuff ...
hibernate logging spring-data-jpa hibernate5 — asked Apr 18 '13 by Alexander Hansen

3 votes 0 answers
Q: get gradle debug logs in a file as opposed to stdout
Most underlying logging methods support multi-targeting of **log levels**, so I'm wondering if anyone's found a way of doing that with gradle, so in the jenkins output we just see the 20 lines, and if we want ... to investigate more, we can just go into the workspace and click on the **log** file. ...
gradle — asked Jul 13 '16 by Darren Oakey

3 votes 1 answer
Q: apache modules ap_log_perror is at a different level than ap_log_error
There are no virtual hosts with **log levels** configured. Every pool I have access to appears to behave in the same way. ... P M **log** ++++++++++++++ any ideas why perror **log** messages are not showing up at the configured level but do show up at the WARNING or ERROR level? ...
c logging apache-modules — asked Oct 5 '18 by Paul Rubel

3 votes 1 answer
Q: How to set two appenders with different log levels in Log::Log4perl?
I want to have a Screen appender with a variable **log** level that can be changed and File appender that will **log** everything no matter what. ... # Define a category logger my $log = Log::Log4perl->get_logger("main"); # Define a layout my $layout = Log::Log4perl::Layout::PatternLayout->new("[%d{yyyy/MM/dd HH:mm:ss,SSS}]%m%n"); # Define a file ...
perl logging configuration log4perl — asked Oct 23 '16 by mocni

3 votes 0 answers
Q: Odoo logs - how to keep DEBUG, but remove INFO?
In odoo, how to disable only the INFO **log level**, but at the same time keep DEBUG? Or do you just have to go through each module in conf and disable it's INFO logs? ... I know about the **log levels**, but debug has lower hierarchy than info for some reason. Related: Why does INFO get logged in DEBUG logs ...
python-3.x logging odoo — asked Feb 11 '19 by TheKhuMyK

3 votes 1 answer
Q: Setting Flutter log Levels / Flutter printing thousands of verbose lines
Flutter **log** prints thousands of verbose/spam logs. I am trying to debug a complex app but flutter printing so much verbose that it is difficult for me to find things which i am printing myself. ...
flutter logging dart visual-studio-code — asked Feb 23 '20 by Robert Williams

3 votes 1 answer
Q: Enable logs for Paho MQTT client on AWS Cloudwatch for a Lambda
I opened the **log levels** for the class org.eclipse.paho.client.mqttv3.internal.ClientState to trace **level** using logback.xml. ...
amazon-web-services aws-lambda — asked May 17 '18 by Abhishek Raj

3 votes 0 answers
Q: Micronaut: Loggers in certain packages are not appearing in AWS lambda and in local
I have specified the packages and their **log levels** in logback.xml. ...
gradle logging micronaut — asked Jul 28 '20 by nikita kakra

3 votes 2 answers
Q: How can I get the request.login method working with a jdbcRealm?
password:b109f3bbbc244e8204197ed06d61ff8d60bb6098b3be9f16e07394c706a8bb980b1d7785e597 6ec0648b4bf0f132fa85a5ad02f35f07c593385f9a0cacbc86 The servlet just takes the request parameters and tries to **log** ... I adjusted the **log** level for in: Configurationd, server-config.Logging2 **Log Levels**: java.enterprise.system.core.security = FINE AND com.microsoft.sqlserver.jdbc = FINE The query is running ...
jakarta-ee servlets glassfish glassfish-3 jaas — asked Nov 4 '12 by Graham

3 votes 3 answers
Q: Only print when run as script?
(sys.stderr) And from the script: import **log** from mylog ... log.info(...) log.warning(...) ... ... log.setLevel(logger.INFO) This scheme has minimal code duplication, per script **log levels**, and a project-wide default level...which is exactly what I wanted. ...
python scripting logging — asked Dec 14 '10 by user318904

3 votes 1 answer
Q: Log4j 2 configuration: XML vs JSON?
This single .json file would then be used to apply **log levels** per application and produce at least 3 different logs (general, error, custom **log** level) per application. ...
xml json logging log4j log4j2 — asked Dec 1 '14 by stravolte

3 votes 0 answers
Q: How can I get Sails.js logging to use multiple Winston transports with different log levels?
I want to use Winston to **log** with 3 different transports, at 3 different **log levels**: warn logs to the Sentry transport info logs to the Loggly transport verbose logs to the Console transport In my ... prefixes: [L.J] Without this, Winston Sails seems to only send "info" JI logs to Winston (Sails' default **log level**) ...
logging sails.js winston — asked Jan 22 '15 by Adam

3 votes 0 answers
Q: log4j (1.2.15) logging to different DailyRollingFileAppender log files for different log lev...
I'm trying to write logs to 2 different DailyRollingFileAppender **log** files for different **log levels** (specifically **INFO** and **DEBUG**) using log4j.properties: log4j.rootLogger=**INFO**, webapp log4j.appender.webapp=org.apache.log4j.DailyRollingFileAppender log4j.appender.webapp.File=D:/webapp-logs/webapp.log log4j.appender.webapp.layout=org.apache.log4j.PatternLayout log4j.appender.webapp.DPA.layout.ConversionPattern= ...
java log4j — asked Aug 3 '20 by Silvia

3 votes 1 answer
Q: Shibboleth SP ignores MetadataProvider
Setting **Log Levels** to DEBUG show that the MetadataProvider gets parsed (its XML structure is visible in the **log** output), but it doesn't try to access the URL. ... Also, there are no Errors in the **log**. There is not even a hint of it trying to load external Metadata in the logs. ...
shibboleth shibboleth-sp — asked Oct 3 '19 by earf

3 votes 0 answers
Q: How to change std::map in running program from gdb?
I have program which use some "**log**" class for logging. There is static variable inside it where **log levels** is. class Log { private: static LogFilterFilter; ... } // set attach to it from gdb and print **log levels**, but I have no idea how to change values in that map (gdb) print Log::filterFilter $48 = std::map with 9 elements = {[LogLevelNone - Error,Log] = 16, [...
c++ gdb — asked May 24 '16 by user2807083

3 votes 1 answer
Q: Enable http header logging for envoy in istio
I want to be able to capture (**log**) at least some of envoy's HTTP headers on my istio service mesh. ... I have gone through envoy's docs, and in the **log levels**' section, it does not mention any header-specific information. ...
logging kubernetes http-headers istio envoyproxy — asked Jan 18 by pharamol

2 votes 2 answers
Q: I am trying to develop a test runner in python
Timeout for test cases TAP type test results **Log Levels** Create Skeleton test cases Coverage Be able to run on a remote host (maybe) Test Reports Command line Help [--help] Now, where do I start ? ...
python unit-testing test-runner — asked Apr 3 '11 by kamal

2 votes 0 answers
Q: Logging practices with multiple web applications
Modification of the logging configuration (for e.g. the **log levels**) is a question for which I would like to get some expert opinions and suggestions. ... Any e.g. of such a modification could be to accept the **log** file location as a JNDI property. Number of web-applications adds complexity to this task. ...
logging jmx logback — asked Apr 22 '11 by Andy DuVesne

2 votes 1 answer
Q: Winston custom log levels typescript definitions
In my code I have custom **log levels**; const myCustomLevels = { **levels**: { data: 10, protocol: 9, debug: 8, info: 7, notice: 6, note: 5, ... Typescript doesn't know about my **levels**. How do I correct this so that he knows about my **levels** on the logger? ...
typescript winston — asked Nov 14 '18 by leonormes

2 votes 2 answers
Q: How to change log level on a Java slf4j logger in a kubernetes managed service in runtime?
value: -Xms1g -Dlogging.level.com.example=DEBUG This works, but it requires me to redeploy the service (restart the container by applying an updated deployment yaml file) in order to change **log** ... Is there a similar way to control **log levels** in runtime in kubernetes managed spring boot services? ...
java spring-boot google-cloud-platform kubernetes slf4j — asked May 17 '17 by Andreas Lundgren

2 votes 1 answer
Q: Python "root" loglevel and levels of other handlers
I'd also like to be able to set **log levels** for either **log** destination, i.e. DEBUG to the logfile and INFO to the console. ... bogged down by a large amount of **log** events. ...
python logging — asked May 14 '14 by erious

2 votes 1 answer
Q: How to use file logger in react-native app
On production, I might want to send the **log** file to the server on specific scenarios (critical bugs). I don't mind asking for storage permission since I need it anyway (for other features). ... I expect to have something like log4j/logback, including rolling file, **log levels**, etc. Is there any package that can do this? ...
javascript react-native — asked Apr 8 '19 by Shay Hazan

2 votes 1 answer
Q: Serilog RavenDb sink not working in an asp.net 5 app
{}: { Everything gets logged to the file and console just fine, and the Logs database gets created, but no **log** entries are stored in RavenDb. I have tried various **log levels**. ...
caf ravendb asp.net-core serilog — asked Dec 8 '15 by Matthew

2 votes 0 answers
Q: Log4J Ansi Coloring Exceptions
This greatly improved reading the logs as I can now distinguish the different **log levels** by color. I know it is possible to change the style of the logs of the different **log levels**, e.g. ...
java logging intellij-idea — asked Sep 19 '14 by lenoxx

Fullscript
Ottawa, ON, Canada
Computer Software | Private | 500-10 people
Our tech stack
python javascript php kubernetes
rails ruby react
Meet our team
andymo
David Ma
jmikhail
View all 7 job openings!

Hot Network Questions

- What religious references are in the Matrix trilogy?
- In Project Hail Mary, how did Eridiana make sensors for electromagnetic radiation without understanding radiation?
- Is X normal for a chess engine to blunder material if its evaluation is only based on naive material evaluation?
- How fast do the typical domestic travel jets (737, A320) actually go?
- My Rock, Paper, Scissors Game in Python
- Are there non-rotating objects in the universe?
- How close can I get to space for a reasonable price?
- Can an author get commission if he writes books from prison?
- Fuel name quine
- Can I write the dates in Italian like this?
- How does drone reliance on GPS make it 'semi-stealthy'?
- Print this sequence I just made up
- Legal issue when contracting a company outside of the U.S
- Will Autocid (2021 LDB) be visible to the naked eye?
- Does fire emit black-body radiation?
- The Second Hardest Logic Puzzle in the World
- When did fluorescent lights become common in Europe?
- Why does it never rain on my Minecraft server?
- Why do some countries allow their states to secede through legal means?
- Do covid vaccines cause 2 deaths for every 3 deaths they prevent?
- What was the first programming language, other than Lisp, to have "short-circuiting" Boolean expressions?
- Why do chess engines cause immediate draws rather than giving the opponent the opportunity to blunder or run out of time?
- 'Advantage' or 'Disadvantage' on damage rolls
- What to do with kittens when the mother runs away from you?

2
votes

1
answer

Q: Setting log levels in RdotNet

For example, executing the RdotNet code var accuracy = rengine.Evaluate("accuracy(fcst)").AsNumeric(); causes the result of evaluation to get logged to console (or **log** file) as well. ...

r r.net

asked Nov 9 '15 by DPrb

Prev 1 2 3 4 5 ... 15 Next

15 30 50 per page

STACK OVERFLOW
Questions
Jobs
Developer Jobs Directory
Salary Calculator
Help
Mobile
Disable Responsiveness

PRODUCTS
Teams
Talent
Advertising
Enterprise

COMPANY
About
Press
Work Here
Legal
Privacy Policy
Terms of Service
Contact Us
Cookie Settings
Cookie Policy

STACK EXCHANGE NETWORK
Technology
Life / Arts
Culture / Recreation
Science
Other

Blog Facebook Twitter LinkedIn Instagram

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under cc by-sa.
rev 2021.6.29.39606