Home
PUBLIC
Questions
Tags
Users
COLLECTIVES
Explore Collectives
FIND A JOB
Jobs
Companies
TEAMS

Stack Overflow for Teams – Collaborate and share knowledge with a private group.
Create a free Team
What is Teams?

Search Results

Advanced Search Tips | Ask Question

Results for "log levels" Search options **questions only**

724 results

Relevance | Newest | Votes

5 votes | 5 answers
Q: Kafka Authentication Producer Unable to Connect Producer
UPDATE: I did some more investigations, turning **log levels** to DEBUG on server reveals something weird. As soon as I specify the listeners field in server.properties, the server goes in a weird state. ...
authentication apache-kafka asked Sep 15 '16 by Klaus

4 votes | 1 answer
Q: printk loglevel usage in module programming
In the book LDD3 by Rubini, under the printk section the author says that we can give **log levels**(priority to our messages. ... But I tried with a simple module program having different **log** level of printks but it showing the same order in which I have written the printk message inside the program, why it is not printing according ...
linux linux-kernel linux-device-driver printk asked Jun 28 '12 by Jithesh

4 votes | 2 answers
Q: Rails: Completed 401 Unauthorized
level. http://guides.rubyonrails.org/v5.0/debugging_rails_applications.html#log-levels I was able to reproduce it by setting device.rb config.timeout_in = 1 minute # 8 hours # 5 days # 1 hour # 10 days ... It says 401 in the server console **log** though. ...
ruby-on-rails asked Jan 3 '18 by Chloe

4 votes | 1 answer
Q: How to setup configuration in .NET Framework for Serilog
I know we could specify locations, **log levels**, etc. for logfeel for specific groups or controllers and models in logfeel, but unsure how to do that for Serilog. ...
asp.net .net logging configuration serilog asked Aug 16 '19 by Ross Gustafson

4 votes | 1 answer
Q: Winston: how to log to Console AND Syslog transports at the same time?
The **log levels** between npm (console) and syslog are not compatible. Example: In my application I have configured my logs (mostly) like this:// To use syslog stuff. ... "Maybe having my **log** level set at 'info' is the problem because info and error **levels** are inverted in their order between npm and syslog mappings and maybe Winston only considers increasing **log levels**. ...
node.js logging winston asked Aug 14 '15 by Eric Olson

0 votes | 0 answers
Q: AWS ECS nodejs app propagate log level to PaperTrail using Logspout
They are doing logging in info, debug, error but when I open PaperTrail all of **log levels** are messed like debug,info,error,info,info,info,info ... I change how **log levels** are mapped or being properly propagated from my apps to papertrail? ...
node.js docker amazon-ecs syslog asked Jul 30 '20 by Emrah Mehmedov

4 votes | 3 answers
Q: Limit the output of jsch in Spring integration
My application uses Spring Integration and has a log4j.properties files defining the following **log levels** # Root logger option log4j.rootLogger=DEBUG log4j.category.com.jcraft.jsch=ERROR log4j.category.org.springframework.integration.file ...
log4j spring-integration slf4j jsch asked May 21 '15 by Jes Chengui

4 votes | 0 answers
Q: No appenders could be found for logger (org.apache.catalina.startup.Catalina)
When I attempt to start up my server and run in browser, the given **log** has been load in catalina.out. I have used the given **log levels** in my log4j.properties still the problem is same. ...
log4j asked Apr 3 '14 by Pushpa

4 votes | 1 answer
Q: Liferay 6.0.12 logging
I need to change **log**-level for Liferay rss portlet classes, e.g. create another appender or use the default one (server.log) and have logs there with desired debug-level (DEBUG or WARN). ... PS Managing **log-levels** through admin portlet is not acceptable. ...
logging liferay jboss5.x liferay-6 asked Jan 24 '13 by Artyom

4 votes | 1 answer
Q: python - Which is the better way to enable/disable logging?
1) Changing **log levels**, logging.disable(logging.CRITICAL) 2) **log** = None And logging messages this way, if **log**: log.info("**log** message") So that we can avoid unnecessary string constructions. ...
python logging asked Jun 19 '10 by asdfg

4 votes | 1 answer
Q: How can I get an array of all possible log levels?
I wish to get all possible, current, **log levels** in the application. I am using the standard logging library for python 2.7 ... We define some custom **log levels** in our application, and it would be nice for those to automatically propagate into argparse. ...
python python-2.7 logging asked May 1 '18 by Ultimation

4 votes | 1 answer
Q: How to configure logging in base class, based on derived class in Log4J?
public void log() { Log[], ilDOwnInfo protected Class getDerivedType() { return DerivedB.class; } ... given the above, I can have in my log4j.properties file different **log** ... **levels** depending on the derived class: log4j.logger.a.DerivedA=debug log4j.logger.a.DerivedB=info While the above does work I don't like the fact that my logger object can't be static any more and ...
java log4j asked Mar 9 '17 by Marcus Junius Brutus

4 votes | 1 answer
Q: Android where is log for file for application on device?
Will it print to the **log** file on device and if so which one? Thanks Also where do I set **levels** which will print? ... Also where to set **log levels** for deployed app in manifest? ...
android logging asked Mar 18 '11 by Androider

4 votes | 2 answers
Q: Using logback-access with Google App Engine (GAE)
Since GAE only supports the **log levels** for JUL and logback-access does not support slf4j, I thought that I should just install logback-access and make sure it writes all logs through JUL to GAE. ...
java google-app-engine jetty logback java.util.logging asked Mar 22 '12 by Ricky Helgesson

4 votes | 1 answer
Q: enable/disable log levels google-chrome-devtools via settings
I can mistake, but how to enable or disable **log levels** in google-chrome-devtools using devTools settings? ... what there are better way to disable **log levels** in DevTools settings? Thanks in advance. ...
google-chrome google-chrome-devtools asked Jul 21 '16 by SergeyGD

4 votes | 3 answers
Q: Logging JDBC/Hibernate/JPA transaction isolation levels
What packages and **log levels** can I add to my logback.xml file to clearly see the isolation level that a particular query is using? Thanks! ...
hibernate jpa jdbc transactions isolation-level asked Jul 21 '10 by zpinter

4 votes | 2 answers
Q: How to set Spring Boot's logging levels programmatically?
I know how to set the **log** level via environment variables and application properties. Is there a way to set them programmatically? ... I would like to set **log levels** for particular test classes (which are using SpringJUnit4ClassRunner and @SpringApplicationConfiguration), but not all of them, and without having a separate properties file ...
java spring-boot slf4j logback asked Feb 11 '16 by OrangeDog

4 votes | 0 answers
Q: How to set log levels for Flutter in VS Code?
Is there a way to adjust **log levels** for Flutter in VS Code? I want to set it to "TRACE" or "INFO" if possible because I am trying to debug something. ... If there is no way to adjust **log levels** for Flutter in VS Code, than is there a way to do that with CLI? ...
flutter dart asked Jan 17 '20 by Jin Lee

4 votes | 1 answer
Q: How do I modify Serilog Log Levels to match up with Log4Net?
So I am in the process of swapping logging frameworks from Log4Net to Serilog where we log out to a text file. ... So with the Serilog File Sink, I am able to modify the outputTemplate to suit my needs, however I am unable to get Serilogs **log** level to match exactly the same as in Log4Net. ...
.net serilog asked Aug 1 '18 by Warren Buckley

4 votes | 2 answers
Q: Remove code lines on release version using gradle in Android studio
I have build a SDK JAR project with a Logger class which notify about system logs. for example: Logger.log("error on line 123 please check", Logger.SDK_DEBUG); At the moment there are few **log levels** ... I would on release build to remove all **log** messages that are with Logger.SDK_DEBUG in my code before the JAR build process. Is it possible doing that with Gradle? ...
android android-gradle-plugin asked Mar 25 '15 by Avi Levin

4 votes | 0 answers
Q: How to use log4j2 with Android for logcat output?
Seems that the 6 standard log4j2 **log levels** (fatal, error, warn, info, debug, trace) are matching well to the 6 **log levels** of logcat (wtf, e, w, i, d, v) ... Using SimpleLogger to **log** to the console. ... When checking the system property java.class.path, it returns ":", but this seems a normal circumstance (as described on http://developer.android.com). ...
java android maven logging log4j2 asked Feb 10 '15 by Joe

4 votes | 1 answer
Q: Printing at different levels in Python
In Java you can print at different **levels** in most frameworks. For example in log4j2, you have **log levels** which can be set to Debug, Info, warn etc. Does python have anything similar out of the box? ...
python logging asked Jan 26 '12 by dubbintech

4 votes | 5 answers
Q: Advice on application log levels
Should we use info/warn **log levels** in the production environment or should we only use error logging? Or maybe both? Thanks! ... "**log** messages. ...
java logging maintenance error-logging asked Oct 26 '12 by nekman

4 votes | 5 answers
Q: Enable/Disable LOG levels using C Macro
stdio.h> #define LOG_0(x) { printf("0:"); printf(x); } #define LOG_E(x) { printf("E:"); printf(x); } void test(void) { LOG_0("ALL is well"); } I have a very huge code it has different **levels** ... of **log**, like above code. ...
c macros asked Dec 10 '15 by pusha ka

4 votes | 1 answer
Q: Recursive logging crashes Interpreter in Python 3
FYIE, the error above with Python 3.6 will come into play if the **log** level is set to logging.ERROR. Similarly for other **log levels**. ...
python python-3.x logging python-3.6 cpython asked Mar 12 '19 by Saim Raza

4 votes | 4 answers
Q: Segmentation fault on vsprintf using macros in C
I defined different macros as wrappers to indicate different **log levels**. eg WARN ERROR etc. ...
c macros asked Jan 27 '17 by user4108694

4 votes | 3 answers
Q: Winston Logging - separate levels to separate Transports
I understand the system **log levels** in Winston, and that only Error goes to MongoDB because its the highest level. ... Even if I create custom **levels**, how can I possibly restrict each transport to only one logging level? ...
node.js logging winston asked May 30 '14 by stepzhus

4 votes | 1 answer
Q: Yesod loginfo no output
I have a scaffolded site and when I run yesod devel, I see no output from the **log** lines I put in my application. ... I was under the impression that in development mode, all **log levels** are output. What am I doing wrong? ...
logging yesod asked Jan 1 '14 by Ralph

4 votes | 2 answers
Q: Detox Testing - How to disable detox info logging to stdout
I've read through the docs and cannot find a way to set the **log** level to something like "silent". I don't want to see all the detox **log** info. I just want to see the test output. ... The current **log levels** are -l, --loglevel [value] info, debug, verbose, silly, wss Not specifying a **log** level defaults to info. example: ...
react-native mocha.js detox asked Apr 30 '18 by Byron

4 votes | 1 answer
Q: GAE flexible and Stackriver log severity levels with python
I'm using the default python root logger and would like to be able to view the **log levels** like in this image. ... Is there an easy way to get the **log** severity **levels** to work with the google standard app engine with python 3? ...
python python-3.x google-app-engine google-cloud-platform stackdriver asked Oct 11 '18 by Jordan van Breemen

4 votes | 0 answers
Q: Logback logging levels are ignored, Spring Boot 2.1.0
When I try to adjust the logging **levels** for these packages, the **levels** are ignored. ... I have ensured that debug=false in application.properties Note that the **log levels** for my application still work. ...
spring spring-boot logback asked Jul 9 '18 by nbc

4 votes | 3 answers
Q: Spring-Boot Embedded Tomcat - generate localhost.log and catalina.out files
Also how can i change the **log levels** for embedded tomcat through logback/slf4j binding in my spring-boot application. Any advice? ...
spring-boot tomcat logback slf4j spring-web asked Jul 12 '18 by jagamot

4 votes | 1 answer
Q: Liferay logging
I know you could define the **log** level for liferay **log** on the path /liferay-portal-6.1.10-ee-ga1/logs/liferay.yyyy-mm-dd.log through Control Panel -> Server Administration -> **Log levels** ... Is there a way i could set all the **levels** to WARN from one single place? In Log4j properties file i have defined a **log** file in a different place and set the **log** level there to WARN. This works. ...
log4j liferay liferay-6 asked Mar 28 '13 by Adia

4 votes | 2 answers
Q: Dynamic (i.e. Runtime Configurable) Log Configuration for Django + Celery based application
We have a need to customize the **log levels** on the server at runtime. We are building a SAAS application using Django, and we have to be able to enable logging per tenant eventually ... As a first step, I created a way to dynamically change **log levels** (for the whole application). I see there are no examples of doing it. ...
python django logging dynamic celery asked Apr 30 '13 by Eswar Vendanapu

4 votes | 1 answer
Q: possible dead-lock with nested transactions in grails service
Maybe there are some **log levels** I can set in grails/hibernate somewhere to pin-point what is happening? ...
spring hibernate grails transactions asked Jun 21 '12 by Jon Burgess

4 votes | 1 answer
Q: Unexpected python logger output when using several handlers with different log levels
I am trying to **log** data to stderr and into a file. The file should contain all **log** messages, and to stderr should go only the **log** level configured on the command line. ...
python logging asked Feb 1 '16 by flypenguin

0 votes | 1 answer
Q: log4javascript - no trace messages appear
In my app it works fine for all **log levels** except trace. ... [CDATA[var **log** = log4javascript.getLogger(); var popUpAppender = new log4javascript.PopUpAppender(); var popUpLayout = new log4javascript.PatternLayout("%d{HH:mm:ss ...
javascript log4javascript asked Oct 2 '12 by RoyHB

0 votes | 0 answers
Q: Log4j2 Syslog appender(TCP protocol) sending exception stacktrace in multiple lines and show...
The first line of the stacktrace is showing correct **log** level in Kiwi syslog server, but the subsequent of the same stacktrace is showing wrong **log** level and facility. ...
log4j2 syslog asked Jan 22 '15 by user3728450

4 votes | 4 answers
Q: scrapy log handler
I seek your help in the following 2 questions - How do I set the handler for the different **log levels** like in python. ... Currently, I have STATS_ENABLED = True STATS_DUMP = True LOG_FILE = 'crawl.log' But the debug messages generated by Scrapy are also added into the **log** files. ...
python screen-scraping scrapy asked Nov 30 '11 by goh

4 votes | 1 answer
Q: How to set the log level via the command-line
Ant has several command line options for controlling its own verbosity (-quiet, -verbose), but these do not appear to correspond to **log levels** for <echo> tasks, and certainly cannot map to all possible ... **log levels**. ...
ant command-line-arguments asked Sep 29 '15 by jowugh

0 votes | 0 answers
Q: Logback coloring based on class/package
Please notice that I don't want this to interfere with **log levels** (that is, I still want to have the option to set components to debug/error etc, ideally without having to mind the coloring. Thanks! ...
java logging colors logback separation-of-concerns asked Aug 22 '13 by Yiftach

2 votes | 2 answers
Q: ILoggingBuilder Logging LogLevel in Appsettings Json doesn't seem to be acknowledged in Azur...
The **log** stream and blob for the **log** look like this after calling the index: 2019-05-17 15:57:24.844 +00:00 [Information] Microsoft.AspNetCore.Hosting.internal.WebHost: Request starting HTTP/1.1 ... **Levels** not being honored? ...
c# azure logging asp.net-core-2.1 asked May 17 '19 by AJ Soto

4 votes | 1 answer
Q: Cloudwatch Agent errors with: No option 'file' in section: 'loggers'
I am trying to tune the **log levels** of the various loggers in the Cloudwatch Logs Agent, and according to the official AWS reference docs, it states that I should be able to add the following to /var/awslogs/etc/awslogs.conf file in section: 'loggers' Removing the whole section resumes logging, but - obviously - no **log levels** has been tuned. ...
python amazon-cloudwatch amazon-cloudwatchlogs asked Dec 21 '16 by gsasha

3 votes | 3 answers
Q: is there a popular open source NSLog replacement that handles enabling only in DEBUG and dif...
That is one that handles ensuring debug type logging only appears in debug states (macros etc), and support for different **log levels** (DEBUG, WARN, INFO, ERROR etc)? ...
iphone ios logging nslog asked Mar 16 '11 by Greg

3 votes | 1 answer
Q: Log4j and User expectation
Like Log4j, which seems more targeted at developers, are there **log levels** more targeted at the end-user? ...
log4j asked May 26 '14 by user3677624

3 votes | 2 answers
Q: More than 20 minutes to start Spring application. How to reduce it?
This is the **log** from IntelliJ IDEA that is being written on app start (uploaded to Pastebin due to SO post length limitations). Notice that time gap between 3rd and 2nd lines from the bottom. ... I've tried to set all **log levels** to TRACE but still haven't seen any other output to **log**. The question is how can I reduce the startup time? ...
java spring hibernate tomcat7 asked Oct 13 '16 by Fyodor Sheretsdotov

3 votes | 1 answer
Q: Git checkout an old branch: any way to not delete newly created files?
The developer is then allowed to specify their own personal "options" for compilation by modifying that file (mainly output **log levels** and output customization) in a way that will be ignored by git and ...
git asked Apr 3 '14 by pszzl

3 votes | 1 answer
Q: How to disable NestJS Logger, based on env?
I'm using logger option in NestFactory.create() method to control Logger's **log levels** in production mode, but it's not working with ENV='production', still showing Logger.log() messages const bootstrap = ... { 'debug', 'error', 'log', 'verbose', 'warn' } : { 'error', 'warn' }; app.enableCors(); app.use(helmet()); app.set('trust proxy', 1); ...
typescript nestjs asked Mar 21 '20 by limo chewran

3 votes | 1 answer
Q: How do i manipulate the stack level of NLog?
I've got an extension method to support additional **log levels** like this: public static void Duration(this ILogger source, string message) { var logEventInfo = new LogEventInfo(LogLevel.Warn ...
c# nlog asked Feb 18 '19 by Obi

3 votes | 2 answers
Q: MongoDB Log Levels
In mongodb you can set the **log** level to between 0 and 5. I was wondering what the general behavior of each of these **levels** was and what level it should be set at to keep from logging inserts. ... Its annoying to go through a **log** when you get around 600gs. ...
mongodb asked Mar 26 '12 by Harsha

Varen Technologies
Columbia, MD
Cybersecurity | Private | 51-200 people
Mid to Senior Software Engineer to Help Solve the Complicated
$100k – $160k
Relocation
java aws
Senior Full Stack Developer (Back-End Focus) with opportunity to gain Clearance
$120k – $180k
Relocation
python javascript
Senior Full Stack Developer (Front-End Focus) with opportunity to gain Clearance
$100k – $160k
Relocation
java python
View all 3 job openings!

Hot Network Questions
How to stop sweat from running into your eyes while at work in 40+ degree Celsius weather?
Who has held the largest number of different UK Cabinet positions?
What was the first programming language, other than Lisp, to have "short-circuiting" conditional expressions?
Why doesn't the Sun wobble towards Jupiter instead of away from Jupiter?
Why does Joshua 24:15 refer to the Amorites and not to the Canaanites? Are they the same?
Useless result of integrate
What religious references are in the Matrix trilogy?
Is semiconductor theory really based on Quantum Mechanics?
Are variant calling files personally identifiable information?
Full name quine
How close can I get to space for a reasonable price?
Bash variables do not expand inside array if declare is used
BMSE vs MSE tess function - the optimization solutions are equivalent?
How would be agenda in Ancient Greek?
Why are American states permitted to vote their own election laws?
How to counter these salary negotiation questions with HBs?
Can an author get commission if he writes books from prison?
Open another file in split view that sits within the same directory as the currently opened file
What limits a small plane like a Cessna or a Piper to be able to fly as high as a jet?
Role of textbook reading for a PhD student
'Advantage' or 'Disadvantage' on damage rolls
Proof of the fact that roots lie outside the unit circle guarantee stationarity of the time series
What is a wipe in Escape from Tarkov?
Will my computer run Windows 11?

Prev 1 2 3 4 5 ... 15 Next

15 30 50 per page

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under cc by-sa.
rev 2021.6.29.39606