

实验 1

本实验帮助你学习 linux 环境下的编译和调试工具。

知识点包括

- gcc
- gdb
- make

练习 1 gcc

学习简单的编译指令，并复习 C 语言中的宏定义。

修改 glory.c 文件中的四个宏（V0~V3）的值，使用以下命令编译和运行程序：


编译

```
$ gcc -o glory glory.c
```

运行

```
$ ./glory
```

使得程序输出为：

A terminal window with a dark background and light-colored text. The output of the program is as follows:

```
SJTU labstarter:
=====
Happy Happy Happy
FPX
Go Li!
```

练习 2 GDB

GDB 调试器是 GCC 编译器的兄弟。做为自由软件领域几乎是唯一的调试器，它秉承了 Unix 类操作系统的一贯风格，采用纯命令行操作，有点儿类似 dos 下的 debug。

关于它的使用方法请看 GDB 使用手册。这个网址

<http://www.unknownroad.com/rtfm/gdbtut/gdbtoc.html> 可以帮助你理解 GDB.

另外，可以学习实验楼的 [《GDB 简明教程》](https://www.shiyanlou.com/courses/496)，通过动手实验学习 Linux 上 GDB 调试 C 语言程序的基本技巧。

使用以下命令可以将可执行文件中用于调试的信息保存下来，供 gdb 使用：

编译

```
$ gcc -g -o hello hello.c
```

调试

```
$ gdb hello
```

逐步调试程序：

1. setting a breakpoint at main
2. giving gdb's run command
3. using gdb's single-step command

在实验报告中回答以下问题:

1. How do you pass command line arguments to a program when using gdb?
2. How do you set a breakpoint which only occurs when a set of conditions is true (e.g. when certain variables are a certain value)?
3. How do you execute the next line of C code in the program after stopping at a breakpoint?
4. If the next line of code is a function call, you'll execute the whole function call at once if you use your answer to #3. How do you tell GDB that you want to debug the code inside the function instead?
5. How do you resume the program after stopping at a breakpoint?
6. How can you see the value of a variable (or even an expression like $1+2$) in gdb?
7. How do you configure gdb so it prints the value of a variable after every step?
8. How do you print a list of all variables and their values in the current function?
9. How do you exit out of gdb?

练习 3 调试

编译并执行 ll_equal.c

编译

\$ gcc -g -o ll_equal ll_equal.c

执行

\$./ll_equal

运行结果如下:

```
equal test 1 result = 1
段错误 (核心已转储)
```

使用 gdb 在 ll_equal() 函数中设置断点, 用 gdb 调试, 找出程序中的错误, 并修正过来。
在实验报告中把正确的函数实现写出来。

练习 4 Make 初步

我们先练习最初步的 make: 不需要 Makefile. (下次再介绍 Makefile)

编译

\$ make wc

再试试:

\$./wc wc.c

\$ wc wc.c

这两次输出的内容为何不同: (Hint: 运行 `which wc`)

修改 wc.c, so that it implements word count according to the specification of `man wc`, except that it does not need to support any flags and only needs to support a single input file, (or STDIN if none is specified). Beware that wc in OS X behaves differently from wc in Ubuntu. We will expect you to follow the behavior of wc in Ubuntu.

在实验报告中把你的 wc.c 文件中的关键模块写出来。