
mlqp

Release 1.0

LogCreative

Mar 08, 2022

CONTENTS

1	minmax module	1
2	model module	3
3	util module	7
4	Indices and tables	9
	Index	11

MINMAX MODULE

```
class minmax.Max(operands)
    Bases: minmax.Operator
```

Max module

```
    forward(src)
```

Foward prediction for src input

Parameters **src** (*list*) – the input list [x,y]

```
class minmax.Min(operands)
    Bases: minmax.Operator
```

Min module

```
    forward(src)
```

Foward prediction for src input

Parameters **src** (*list*) – the input list [x,y]

```
class minmax.Operator(operands)
    Bases: object
```

Base operator class for Min and Max module.

```
    forward(src)
```

Foward prediction for src input

Parameters **src** (*list*) – the input list [x,y]

```
minmax.divide(train_data, k=2)
```

Divide the data into positive and negative merged 2D data array.

Parameters

- **train_data** (*array*) – the data to be divided
- **k** (*int*) – the number of split on positive/negative set

Returns the 2D divided data array for computation.

Return type array

```
minmax.minmax(train_data, k, epochs, lr=0.05, random_seed=None)
```

Train minmax network.

Parameters

- **train_data** (*array*) – the training data.
- **k** (*int*) – the number of split

- **epochs** (*int*) – the threshold of training epochs.
- **lr** (*float*, *optional*) – Learning rate. Defaults to 0.05.
- **random_seed** (*int*, *optional*) – Random Seed. Defaults to None.

Returns Target Network, subnets, min nets, maximum training time among units

Return type Max, array[Net], array[Min], float

`minmax.trainer(train_sub_data, epochs, lr=0.05, random_seed=None)`

Trainer worker

Parameters

- **train_sub_data** (*array*) – the input array for training.
- **epochs** (*int*) – the number threshold of epochs.
- **lr** (*float*, *optional*) – Learning rate. Defaults to 0.05.
- **random_seed** (*int*, *optional*) – Random Seed. Defaults to None.

Returns the trained network.

Return type Net

MODEL MODULE

class `model.Net(lr=0.05, alpha=0.8, random_seed=None, hidden_num=10)`

Bases: `object`

MLQP Network

backward(*pred, target*)

Backward pass, update the parameters. NOTE: should run forward pass first before calling this function.

Parameters

- **pred** (*float*) – prediction based on forward pass
- **target** (*float*) – the target label

forward(*src*)

Forward pass, return the prediction based on the given data.

Parameters **src** (*list*) – the input list of data [*x,y*]

param_init()

Init parameters.

`model.cross_validation(model, split_data)`

Cross validation over split data.

Parameters

- **model** (*Net*) – the instance of Net
- **split_data** (*array*) – the splitted data generated from `fold()`

Returns the mean of training error and validation error among experiments.

Return type `float, float`

`model.folds(data, k)`

divide data sequentially into k portions

Parameters

- **data** (*array*) – the data to be divided
- **k** (*int*) – the number of portions

Returns the divided data

Return type `array`

`model.split(train_data, k)`

split train_data into k folds.

Parameters

- **train_data** (*array*) – the training data
- **k** (*int*) – fold number

Returns the splitted data formatted [train_data, val_data] array.

Return type array

`model.step(model, data, with_grad=True)`

Common step for data on training or testing.

Parameters

- **model** (*Net*) – the instance of Net
- **data** (*array*) – data for training or testing
- **with_grad** (*bool*, *optional*) – If it needs backward process. Defaults to True.

Returns the mse loss of this batch of data

Return type loss

`model.test(model, test_data)`

Test the model

Parameters

- **model** (*Net*) – the instance of Net
- **test_data** (*array*) – the testing set

Returns the mse error over test set

Return type float

`model.test_step(model, test_data)`

Test the model for test_data

Parameters

- **model** (*Net*) – the instance of Net
- **test_data** (*array*) – the testing data

Returns the mse error over test_data

Return type array

`model.train(model, train_data, epochs, test_data=None)`

Train the model by epochs.

Parameters

- **model** (*Net*) – the instance of Net
- **train_data** (*array*) – the training set
- **epochs** (*int*) – the number of epochs
- **test_data** (*array*, *optional*) – if assigned, the test error will be tracked but will not go into the training process.

Returns trained model

Return type Net

`model.train_step(model, train_data)`

Train the model for one step.

Parameters

- **model** (*Net*) – the instance of Net
- **train_data** (*array*) – the training data

UTIL MODULE

`util.mse(pred, target)`

`util.read_data(filename)`

Reads data from the file and return an array of data formatting: [x y label]

Parameters `filename` (*str*) – the path of file

Returns the array of the data read from file

Return type data

`util.sigmoid(x)`

`util.sigmoid_prime(x)`

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

INDEX

B

`backward()` (*model.Net method*), 3

C

`cross_validation()` (*in module model*), 3

D

`divide()` (*in module minmax*), 1

F

`folds()` (*in module model*), 3

`forward()` (*minmax.Max method*), 1

`forward()` (*minmax.Min method*), 1

`forward()` (*minmax.Operator method*), 1

`forward()` (*model.Net method*), 3

M

`Max` (*class in minmax*), 1

`Min` (*class in minmax*), 1

`minmax`

module, 1

`minmax()` (*in module minmax*), 1

`model`

module, 3

`module`

minmax, 1

model, 3

util, 7

`mse()` (*in module util*), 7

N

`Net` (*class in model*), 3

O

`Operator` (*class in minmax*), 1

P

`param_init()` (*model.Net method*), 3

R

`read_data()` (*in module util*), 7

S

`sigmoid()` (*in module util*), 7

`sigmoid_prime()` (*in module util*), 7

`split()` (*in module model*), 3

`step()` (*in module model*), 4

T

`test()` (*in module model*), 4

`test_step()` (*in module model*), 4

`train()` (*in module model*), 4

`train_step()` (*in module model*), 4

`trainer()` (*in module minmax*), 2

U

`util`

module, 7