

Socket Programming

计算机网络 CS339

李子龙 518070910095

2021 年 10 月 8 日

目录

1	C/S 模型	2
1.1	C/S 模型要求	2
1.2	C/S 模型测试	2
2	P2P 模型	5
2.1	P2P 模型要求	5
2.2	P2P 模型测试	5
A	C/S 模型架构实现	7
B	C/S 模型 Python 实现	9
C	C/S 模型 C 实现	11
D	P2P 模型架构实现	14
E	P2P 模型 Python 实现	16

You will implement a simple file share application using TCP Socket APIs.

You can use any programming language. You need to submit your code together with a report. The report should contain how to run your program and some evaluation results.


1 C/S 模型

1.1 C/S 模型要求

1. Implement C/S model:

- (a) Server listens to a given port (>1024, e.g. 2680)
- (b) Multiple clients request the same file from the server
- (c) Each client save the file to its local directory.

2. Use Mininet to compare the overall file downloading time. Study how the number of downloading time changes with respect to the number of peers. You need to create the following star topology in Mininet. You can use one host as a server, and the other hosts as peers requesting files.



1.2 C/S 模型测试

在 root 模式下，使用 `csmodel` 文件夹下的 `cspy_test.sh` 脚本即可测试。

```
root@ubuntu: /VMShared/Networking/lab03/csmodel
文件(F) 编辑(E) 查看(V) 搜索(S) 终端(T) 帮助(H)
root@ubuntu: /VMShared/Networking/lab03/csmodel# ./cspy_test.sh
记录了10240+0 的读入
记录了10240+0 的写出
10485760 bytes (10 MB, 10 MiB) copied, 2.98733 s, 3.5 MB/s
Ready to send.
('127.0.0.1', 49992)
4.02108097076
root@ubuntu: /VMShared/Networking/lab03/csmodel#
```

图 1: 单机测试

本地测试将会在服务器与客户端之间，在 2683 端口上传输 10 MB 的文件，传输时长大概在 4s 左右。如果最后没有比较上的异常，就说明被完整地传输了。

Listing 1: `csmodel/cspy_test.sh`

```
1 #!/bin/bash
2
3 rm -rf file*
4 rm -rf result_py.dat
5 dd if=/dev/zero of=file.txt bs=1024 count=10240
6 python server.py &
7 sleep 1
8 python client.py 10485760
9 xxd file.txt > file.hex
10 xxd file_receive.txt > file_receive.hex
11 # diff file.txt file_send.txt
12 diff file.hex file_receive.hex
13 exit
```

而对于 Mininet 模拟来说，使用 `python` 运行 `csmodel/centralized.py` 脚本即可开始测试星状结构的网络。运行脚本后需要输入测试的主机数量。如果脚本后面添加参数 `py --dirty` 则可以跳过一些检查，这对于客户机数量多的情况比较有用。

```
root@ubuntu: /VMShared/Networking/lab03/csmodel
文件(F) 编辑(E) 查看(V) 搜索(S) 终端(T) 帮助(H)
root@ubuntu: /VMShared/Networking/lab03/csmodel# python centralized.py py --dirty
Please input hostnumber:6
*** Creating network
*** Adding controller
*** Adding hosts:
h1 h2 h3 h4 h5 h6
*** Adding switches:
s1
*** Adding links:
(s1, h1) (s1, h2) (s1, h3) (s1, h4) (s1, h5) (s1, h6)
```

图 2: C/S Mininet 测试

由图 3 所示，所有的客户机会同时从服务器获取上述的 10MB 文件，每个客户机会在完成传输后各自存储为对应的 `file_receive_h*.txt` 文件，并将计时结果写入文件 `result_py.dat`，当 Mininet 退出 CLI 的时候（`quit`指令），就会对结果进行统计，并给出平均时间。




图 3: 运行多机测试

由图 4 可见，随着客户机的增长，传输时间也会显著变长。




图 4: 不同的客户机数量下平均传输时间

2 P2P 模型

2.1 P2P 模型要求

1. Implement P2P model: Each peer downloads part of the file from the server, and then distributes it to all the other peers.
2. Use Mininet to compare the overall file downloading time under P2P model.
3. For peer-to-peer mode, you may want to design a tracker file first. The tracker file contains the following information:

file chunk id	peer ip
1	10.0.0.1
2	10.0.0.2
3	10.0.0.3
4	10.0.0.4

Then, if a client wants piece 2, it will contact 10.0.0.2. If the peer with ip=10.0.0.2 does not have the piece yet, it will contact the server to download this piece first.

2.2 P2P 模型测试

使用 `p2pmodel/p2ptest.sh` 可以进行批量测试，这一步可以创建一个 10MB 大小的文件 `file.txt`。当然也可以直接运行 `python` 脚本进行测试：

```
sudo python p2pmodel/centralized.py 5
```

最后一个参数用于指定主机数量。

```
root@ubuntu: /VMShared/Networking/lab03/p2pmodel
文件(F) 编辑(E) 查看(V) 搜索(S) 终端(T) 帮助(H)
root@ubuntu: /VMShared/Networking/lab03/p2pmodel# python centralized.py
Please input hostnumber:3
*** Creating network
*** Adding controller
*** Adding hosts:
h1 h2 h3
*** Adding switches:
s1
*** Adding links:
(s1, h1) (s1, h2) (s1, h3)
*** Configuring hosts
h1 h2 h3
*** Starting controller
c0
*** Starting 1 switches
```

图 5: P2P Mininet 测试

Listing 2: [p2pmodel/p2ptest.sh](#)

```
1 # !/bin/bash
2
3 rm -rf file*
4 rm -rf result_py.dat
5 dd if=/dev/zero of=file.txt bs=1024 count=10240
6 for hostnumber in 2 3 4 5 6 7 8 9 10 11 12 13 14
7 do
8     python centralized.py $hostnumber
9 done
10 exit
```




图 6: 不同的对等方数量下平均传输时间

A C/S 模型架构实现

下面给出了 Mininet 配置的具体代码。实际上星状网络可以采用 **LinearTopo** 代替，此处为了更好地控制源码，就采用了手写的 **CentralizedTopo** 网络结构。

Listing 3: `csmodel/centralized.py`

```
1  # python centralized.py [hostnumber] [py|c] [--dirty]
2
3  # [hostnumber] is the number of hosts in the structure (including the server)
4  # py will launch python script, while c will launch c version.
5  # --dirty will pass all the checking
6
7  # To construct a centralized structure
8  # for C/S model.
9
10 import os, glob
11 from sys import argv
12 from time import sleep
13 from mininet.link import TCLink
14 from mininet.topo import LinearTopo, Topo
15 from mininet.net import Mininet
16 from mininet.log import lg, info
17 from mininet.util import dumpNodeConnections, irange, run
18 from mininet.cli import CLI
19
20 class CentralizedTopo(Topo):
21     "A centralized topo."
22
23     def build(self, hostnumber=2, **params):
24         # Central switch
25         switch = self.addSwitch('s1')
26         # Star hosts
27         hosts = [self.addHost('h%s' % h) for h in irange(1, hostnumber)]
28
29         # Star structure
30         for host in hosts:
31             self.addLink(switch, host)
32
33     def FileTransfer(hostnumber=2):
34         "Make file transfer between switch and hosts simutanously."
35
36         servercmd = "python server.py"
37         clientcmd = "python client.py"
38         resultfile = "result_py.dat"
39         avgresfile = "avgres_py.dat"
40
41         if len(argv) >= 3:
42             if argv[2] == "c":
43                 servercmd = "./server"
44                 clientcmd = "./client"
45                 resultfile = "result_c.dat"
46                 avgresfile = "avgres_c.dat"
47
48         dirty = False
```

```

49 if len(argv)>=4:
50     if(argv[3]=="--dirty"):
51         dirty = True
52
53     topo = CentralizedTopo(hostnumber)
54     # topo = LinearTopo(1,hostnumber) # The same.
55     net = Mininet(topo=topo, link=TCLink, autoStaticArp=False)
56     net.start()
57     # Test connectivity.
58     if not dirty:
59         net.pingAll()
60
61     # clean the files.
62     for file_receive in glob.glob("file_receive*"):
63         os.remove(file_receive)
64
65     fileSize = os.path.getsize("file.txt")
66
67     dumpNodeConnections(net.hosts)
68
69     # Place the server on h1.
70     print(net.hosts[0].cmdPrint(servercmd, "&"))
71
72     # To make sure the client will contact the server.
73     sleep(2)
74
75     # All other host request the file from h1.
76     for i in range(1,hostnumber):
77         net.hosts[i].cmdPrint(clientcmd, fileSize, net.hosts[0].IP(), net.hosts[
78 i].name, "" if i == hostnumber - 1 else "&")
79
80     # CLI(net)
81
82     # check the difference.
83     if not dirty:
84         for i in range(1,hostnumber):
85             run("diff file.txt file_receive_"+net.hosts[i].name+".txt")
86
87     # Wait for all hosts complete.
88     complete = 0
89     while not complete == hostnumber:
90         results = []
91         with open(resultfile, "r") as rf:
92             resultlines = rf.read().splitlines()
93             complete = len(resultlines)
94             for i in range(1, len(resultlines)):
95                 results.append(float(resultlines[i].split('\t')[1]))
96             sleep(10)
97
98     avg = sum(results)/len(results)
99     print("Average: "+str(avg))
100     print("Avaliable: " + str(len(results)) + "/" + str(hostnumber-1) + "("
101 + str(int(len(results)*100/(hostnumber-1))) + "%)")
102     with open(avgresfile, "a") as af:
103         af.write(str(hostnumber-1)+"\t"+str(avg)+"\n")

```



```

103     net.stop()
104
105     if __name__=="__main__":
106         lg.setLogLevel( 'info' )
107         if len(argv)>=2:
108             hostnumber = int(argv[1])
109         else:
110             hostnumber = int(input("Please input hostnumber:"))
111         FileTransfer(hostnumber)

```

B C/S 模型 PYTHON 实现

为了方便理解 TCP 网络模型，先跟着书用 Python 实现了一遍多线程 C/S 模型。

下面是服务器端的代码，在主循环中由 `accept()` 阻塞接收，一旦有客户机进入就会开辟新的线程进行文件传输。

Listing 4: `csmodel/server.py`

```

1  # python server.py [&]
2
3  from socket import *
4  import threading
5
6  serverPort = 2683
7  serverSocket = socket(AF_INET, SOCK_STREAM)
8  serverSocket.bind(('', serverPort))
9  serverSocket.listen(20)
10 serverSocket.settimeout(20)
11
12 with open("file.txt", "rb") as f:
13     content = f.read()
14
15 class SendThread(threading.Thread):
16     def __init__(self, connectionSocket):
17         threading.Thread.__init__(self)
18         self.connectionSocket = connectionSocket
19     def run(self):
20         sendout(self.connectionSocket)
21
22 def sendout(connectionSocket):
23     connectionSocket.send(content.encode())
24     connectionSocket.close()
25
26 with open("file_send.txt", "wb") as f:
27     f.write(content)
28 with open("result_py.dat", "w") as rf:
29     rf.write("Host\tTime\n")
30 print('Server ready to send.')
31
32 while True:
33     try:
34         connectionSocket, addr = serverSocket.accept()

```

```

35     except timeout:
36         print("Server closed.")
37         break
38     print(addr)
39     sth = SendThread(connectionSocket)
40     sth.start()

```

下面是客户端代码，由于 TCP 连接接收大小有一定的限制，超过限制可能就会产生长期接收不到的情况，所以每次只会接收 1024 字节，分为多次进行接收。由于 Python 内存访问比较慢，这里直接就写入了文件，没有首先将内容进入内存。

Listing 5: `csmodel/client.py`

```

1  from socket import *
2  from sys import argv
3  import time
4
5  MAXLINE = 1024
6  serverName = "127.0.0.1"
7  filename = "file_receive.txt"
8  hostname = ""
9
10 if len(argv)>=2:
11     MAXLINE = int(argv[1])
12 if len(argv)>=3:
13     serverName = argv[2]
14 if len(argv)>=4:
15     hostname = argv[3]
16     filename = "file_receive_" + hostname + ".txt"
17
18 START_TIME = time.time()
19
20 serverPort = 2683
21 clientSocket = socket(AF_INET, SOCK_STREAM)
22 clientSocket.connect((serverName, serverPort))
23
24 # To speed up, skip the process of saving it to the memory first.
25 with open(filename,"wb") as f:
26     for i in range(MAXLINE/1024):
27         f.write(clientSocket.recv(1024).decode())
28
29 END_TIME = time.time()
30
31 clientSocket.close()
32
33 elapsed_time = END_TIME-START_TIME
34 print(elapsed_time)
35
36 with open("result_py.dat","a") as rf:
37     rf.write(hostname + "\t" + str(elapsed_time) + "\n")

```

C C/S 模型 C 实现 C

如果想运行 C 语言版本，进行单机测试：

```
root@ubuntu: /VMShared/Networking/lab03/csmode1
文件(F) 编辑(E) 查看(V) 搜索(S) 终端(T) 帮助(H)
root@ubuntu: /VMShared/Networking/lab03/csmode1# ./cs_test.sh
记录了10240+0 的读入
记录了10240+0 的写出
10485760 bytes (10 MB, 10 MiB) copied, 5.27778 s, 2.0 MB/s
10485760

Hi,I am running server.Some Client hit me
0.227318
root@ubuntu: /VMShared/Networking/lab03/csmode1#
```

图 7: C 语言单机测试

进行 Mininet 测试需要使用参数 `c --dirty`。

```
root@ubuntu: /VMShared/Networking/lab03/csmode1
文件(F) 编辑(E) 查看(V) 搜索(S) 终端(T) 帮助(H)
root@ubuntu: /VMShared/Networking/lab03/csmode1# python centralized.py c --dirty
Please input hostnumber:21
*** Creating network
*** Adding controller
*** Adding hosts:
h1 h2 h3 h4 h5 h6 h7 h8 h9 h10 h11 h12 h13 h14 h15 h16 h17 h18 h19 h20 h21
*** Adding switches:
s1
*** Adding links:
(s1, h1) (s1, h2) (s1, h3) (s1, h4) (s1, h5) (s1, h6) (s1, h7) (s1, h8) (s1, h9)
(s1, h10) (s1, h11) (s1, h12) (s1, h13) (s1, h14) (s1, h15) (s1, h16) (s1, h17) (
s1, h18) (s1, h19) (s1, h20) (s1, h21)
*** Configuring hosts
h1 h2 h3 h4 h5 h6 h7 h8 h9 h10 h11 h12 h13 h14 h15 h16 h17 h18 h19 h20 h21
*** Starting controller
c0
*** Starting 1 switches
s1 ...
```

图 8: C 语言多机测试

可见使用 C 语言效率更高，1s 不到就可以完成，这也导致如果需要对其评测需要使用很大的文件，否则数据差距并不明显，这里就跳过对 C 语言实现版本的测评部分。下面的代码主要是对示例代码的一些改进而得到的。

Listing 6: `csmode1/server.cc`

```
1 #include <stdio.h> // standard input and output library
2 #include <stdlib.h> // this includes functions regarding memory allocation
3 #include <string.h> // contains string functions
4 #include <errno.h> //It defines macros for reporting and retrieving error
   conditions through error codes
5 #include <unistd.h> //contains various constants
6 #include <sys/types.h> //contains a number of basic derived types that should
   be used whenever appropriate
```

```

7  #include <arpa/inet.h> // defines in_addr structure
8  #include <sys/socket.h> // for socket creation
9  #include <netinet/in.h> //contains constants and structures needed for
    internet domain addresses
10 #include <pthread.h>
11
12 char* dataSending; // Actually this is called packet in Network Communication
    , which contain data and send through.
13 int fsize;
14
15 void* send_thread(void* conn_void_ptr){
16     int clintConnt = *((int*)conn_void_ptr);
17     pthread_detach(pthread_self());
18     free(conn_void_ptr);
19     write(clintConnt, dataSending, sizeof(char)*fsize);
20     close(clintConnt);
21 }
22
23 int main()
24 {
25     int clintListn = 0;
26     struct sockaddr_in ipOfServer;
27     clintListn = socket(AF_INET, SOCK_STREAM, 0); // creating socket
28     memset(&ipOfServer, '0', sizeof(ipOfServer));
29     ipOfServer.sin_family = AF_INET;
30     ipOfServer.sin_addr.s_addr = htonl(INADDR_ANY);
31     ipOfServer.sin_port = htons(2680); // this is the port number of
    running server
32     bind(clintListn, (struct sockaddr*)&ipOfServer, sizeof(ipOfServer));
33     listen(clintListn, 20);
34
35     int* clintConnt;
36     pthread_t th;
37
38     FILE* f;
39     if((f = fopen("file.txt", "rb"))==NULL){
40         fprintf(stderr, "Can't open file file.txt.\n");
41         return -1;
42     }
43     fseek(f, 0, SEEK_END);
44     fsize = ftell(f);
45     fseek(f, 0, SEEK_SET);
46     dataSending = (char*)malloc(sizeof(char)*fsize);
47     printf("%d\n", fsize);
48     fread(dataSending, sizeof(char), fsize, f);
49     fclose(f);
50
51     f = fopen("file_send.txt", "wb");
52     fwrite(dataSending, sizeof(char), fsize, f);
53     fclose(f);
54
55     f = fopen("result_c.dat", "w");
56     fprintf(f, "Host\tTime\n");
57     fclose(f);
58
59     while(1)

```

```

60     {
61         printf("\n\nHi,I am running server.Some Client hit me\n"); //
        whenever a request from client came. It will be processed here.
62
63         clintConnt = (int*)malloc(sizeof(int));
64         *clintConnt = accept(clintListn, (struct sockaddr*)NULL, NULL);
65
66         pthread_create(&th, NULL, send_thread, clintConnt);
67     }
68
69     return 0;
70 }

```

Listing 7: [csmodel/client.cc](#)

```

1  #include <sys/socket.h>
2  #include <sys/types.h>
3  #include <netinet/in.h>
4  #include <netdb.h>
5  #include <stdio.h>
6  #include <string.h>
7  #include <stdlib.h>
8  #include <unistd.h>
9  #include <errno.h>
10 #include <arpa/inet.h>
11 #include <time.h> //contains various functions for manipulating date and time
12
13 int main(int argc, char* argv[])
14 {
15     struct sockaddr_in ipOfServer;
16     ipOfServer.sin_family = AF_INET;
17     ipOfServer.sin_port = htons(2680);
18     ipOfServer.sin_addr.s_addr = inet_addr("127.0.0.1");
19
20     char filename[80];
21     sprintf(filename, "file_receive.txt");
22
23     int MAXLINE = 1024;
24
25     switch (argc)
26     {
27     case 1:
28         printf("./client [file_size] [target_ip] [host_number]\n");
29         return 0;
30     case 4:
31         sprintf(filename, "file_receive_%s.txt",argv[3]);
32     case 3:
33         ipOfServer.sin_addr.s_addr = inet_addr(argv[2]);
34     case 2:
35         MAXLINE = atoi(argv[1]);
36     default:
37         break;
38     }
39
40     clock_t start,finish;
41     start = clock();

```

```

42
43     int CreateSocket = 0,n = 0;
44     char* dataReceived = (char*)malloc(MAXLINE*sizeof(char));
45     memset(dataReceived, 1 ,sizeof(dataReceived));
46
47     if((CreateSocket = socket(AF_INET, SOCK_STREAM, 0))< 0)
48     {
49         printf("Socket not created \n");
50         return 1;
51     }
52
53     if(connect(CreateSocket, (struct sockaddr *)&ipOfServer, sizeof(
ipOfServer))<0)
54     {
55         printf("Connection failed due to port and ip problems\n");
56         return 1;
57     }
58
59     for(int i = 0; i < MAXLINE/1024; ++i)
60         read(CreateSocket, dataReceived + (i*1024) , 1024);
61
62     FILE* f = fopen(filename,"wb");
63     fwrite(dataReceived,sizeof(char),MAXLINE,f);
64     fclose(f);
65
66     finish = clock();
67
68     FILE* rf = fopen("result_c.dat","a");
69     double elapsed_time = (double)(finish-start)/CLOCKS_PER_SEC;
70     if (argc==4)
71         fprintf(rf,"%s\t%f\n",argv[3],elapsed_time);
72     else fprintf(rf,"\t%f\n",elapsed_time);
73     fclose(rf);
74     fprintf(stdout, "%f\n", elapsed_time);
75
76     if( n < 0)
77     {
78         printf("Standard input error \n");
79     }
80
81     return 0;
82 }

```

D P2P 模型架构实现

Listing 8: p2pmodel/centralized.py

```

1  # To construct a centralized structure
2  # for P2P model.
3
4  import os, glob
5  from sys import argv
6  from time import sleep

```

```

7 import math
8 from mininet.link import TCLink
9 from mininet.topo import LinearTopo, Topo
10 from mininet.net import Mininet
11 from mininet.log import lg, info
12 from mininet.util import dumpNodeConnections, irange, quietRun, run
13 from mininet.cli import CLI
14
15 class CentralizedTopo(Topo):
16     "A centralized topo."
17
18     def build(self, hostnumber=2, **params):
19         # Central switch
20         switch = self.addSwitch('s1')
21         # Star hosts
22         hosts = [self.addHost('h%s' % h) for h in irange(1, hostnumber)]
23
24         # Star structure
25         for host in hosts:
26             self.addLink(switch, host)
27
28 def FileTransfer(hostnumber=2):
29     "Make file transfer between switch and hosts simutanously."
30
31     servercmd = "python server.py"
32     clientcmd = "python peer.py"
33     resultfile = "result_py.dat"
34     avgresfile = "avgres_py.dat"
35
36     topo = CentralizedTopo(hostnumber)
37     net = Mininet(topo=topo, link=TCLink, autoStaticArp=False)
38     net.start()
39
40     # clean the files.
41     for file_receive in glob.glob("file_receive*"):
42         os.remove(file_receive)
43
44     # Generate tracker file
45     fileSize = os.path.getsize("file.txt")
46     chunkSize = int(math.ceil(fileSize/(hostnumber-1)))
47     with open("tracker.dat", "w") as tf:
48         for i in range(hostnumber-1):
49             tf.write(str(i)+"\t"+net.hosts[i+1].IP()+"\n")
50
51     # Try to dump
52     dumpNodeConnections(net.hosts)
53
54     # Place the server on h1.
55     net.hosts[0].cmdPrint(servercmd, chunkSize, "&")
56
57     sleep(2)
58
59     # All other host request files.
60     # The last host will be monitored.
61     for i in range(1, hostnumber):

```

```

62     net.hosts[i].cmdPrint(clientcmd,chunkSize,net.hosts[0].IP(),net.hosts
[i].IP()," if i == hostnumber - 1 else "&")
63
64     # CLI(net)
65
66     results = []
67     with open(resultfile,"r") as rf:
68         resultlines = rf.read().splitlines()
69         for i in range(1,len(resultlines)):
70             results.append(float(resultlines[i].split('\t')[1]))
71     avg = sum(results)/len(results) if not len(results) == 0 else -1
72     print("Average: "+str(avg))
73     print("Avaliable: " + str(len(results)) + "/" + str(hostnumber-1) + "("
+ str(int(len(results)*100/(hostnumber-1))) + "%)")
74     with open(avgresfile,"a") as af:
75         af.write(str(hostnumber-1)+"\t"+str(avg)+"\n")
76
77     net.stop()
78
79 if __name__=="__main__":
80     lg.setLogLevel( 'info' )
81     if len(argv)>=2:
82         hostnumber = int(argv[1])
83     else:
84         hostnumber = int(input("Please input hostnumber:"))
85     FileTransfer(hostnumber)

```

E P2P 模型 PYTHON 实现

服务器与 C/S 模型的差距不大，主要可以接收一个文件块的参数。

Listing 9: p2pmodel/server.py

```

1  # python server.py [chunkSize]
2
3  from socket import *
4  from sys import argv
5  import threading
6
7  serverPort = 2684
8  serverSocket = socket(AF_INET, SOCK_STREAM)
9  serverSocket.bind(('', serverPort))
10 serverSocket.listen(20)
11
12 with open("file.txt","rb") as f:
13     content = f.read()
14
15 chunkSize = 1024
16 if len(argv)==2:
17     chunkSize = int(argv[1])
18
19 class SendThread(threading.Thread):
20     def __init__(self, connectionSocket, chunkNumber):

```



```

21         threading.Thread.__init__(self)
22         self.connectionSocket = connectionSocket
23         self.chunkNumber = chunkNumber
24     def run(self):
25         sendout(self.connectionSocket, chunkNumber)
26
27 def sendout(connectionSocket, cnum):
28     connectionSocket.send(content[cnum*chunkSize:(cnum+1)*chunkSize].encode()
29     )
30     connectionSocket.close()
31
32 with open("file_send.txt", "wb") as f:
33     f.write(content)
34 with open("result_py.dat", "w") as rf:
35     rf.write("Host\tTime\n")
36 print('Ready to send.')
37
38 while True:
39     connectionSocket, addr = serverSocket.accept()
40     chunkNumber = int(connectionSocket.recv(1024).decode())
41     print(addr, chunkNumber)
42     sth = SendThread(connectionSocket, chunkNumber)
43     sth.start()

```

对等方的实现相对复杂。

Listing 10: [p2pmodel/peer.py](#)

```

1  # python peer.py [chunkSize] [serverIP] [hostIP]
2
3  from socket import *
4  from sys import argv
5  import threading
6  import time
7
8  chunkSize = 1024
9  serverName = "127.0.0.1"
10 filename = "file_receive.txt"
11 hostName = "127.0.0.1"
12 hostname = ""
13
14 if len(argv)>=2:
15     chunkSize = int(argv[1])
16 if len(argv)>=3:
17     serverName = argv[2]
18 if len(argv)>=4:
19     hostName = argv[3]
20     hostname = "h" + hostName.split(".")[1]
21     filename = "file_receive_" + hostname + ".txt"
22
23 START_TIME = time.time()
24
25 with open("tracker.dat", "r") as tf:
26     tls = tf.read().splitlines()
27     # chunkID \t requestIP
28     trackers = [[int(tl.split("\t")[0]), tl.split("\t")[1], False] for tl in

```

```

        tls]
29
30 content = {}
31
32 def DownContent(chunkNumber):
33     # Check if this peer has the chunk first.
34     if not trackers[chunkNumber][2]:
35         # Server use 2684 for communication.
36         clientPort = 2684
37         clientSocket = socket(AF_INET, SOCK_STREAM)
38         clientSocket.connect((serverName, clientPort))
39         # send out the chunkNumber
40         clientSocket.send(str(chunkNumber).encode())
41
42         # expect to receive the chunk from the server.
43         fileChunk = ""
44         for i in range(chunkSize/1024):
45             fileChunk = fileChunk + clientSocket.recv(1024).decode()
46         # threadLock.acquire()
47         content[chunkNumber] = fileChunk # write to self content
48         # threadLock.release()
49         trackers[chunkNumber][2] = True # declare to be useable
50         print("Received Size from " + serverName + " : " + str(len(fileChunk)))
51     )
52     clientSocket.close()
53 else:
54     fileChunk = content[chunkNumber]
55     return fileChunk
56
57 class SendThread(threading.Thread):
58     def __init__(self, connectionSocket, chunkNumber):
59         threading.Thread.__init__(self)
60         self.chunkNumber = chunkNumber
61         self.connectionSocket = connectionSocket
62     def run(self):
63         # Detect the downloading first.
64         downFileChunk = DownContent(self.chunkNumber)
65
66         # Then send it to the peer
67         self.connectionSocket.send(downFileChunk.encode())
68         self.connectionSocket.close()
69
70 class ServiceThread(threading.Thread):
71     def __init__(self):
72         threading.Thread.__init__(self)
73     def run(self):
74         # peer use 2685 for communication.
75         receivePeerPort = 2685
76         receivePeerSocket = socket(AF_INET, SOCK_STREAM)
77         receivePeerSocket.bind(('', receivePeerPort))
78         receivePeerSocket.listen(20)
79         receivePeerSocket.settimeout(10)
80
81         while True:
82             try:

```

```

83         connectionSocket, addr = receivePeerSocket.accept()
84     except timeout:
85         if len(content)==len(trackers):
86             # The transmission has been complete.
87             break
88         else:
89             continue
90     chunkNumber = int(connectionSocket.recv(1024).decode())
91     print(addr, chunkNumber)
92     sth = SendThread(connectionSocket, chunkNumber)
93     sth.start()
94
95 def getContent(tracker):
96     sendPeerPort = 2685
97     sendPeerSocket = socket(AF_INET, SOCK_STREAM)
98
99     try:
100         time.sleep(0.5)
101         sendPeerSocket.connect((tracker[1], sendPeerPort))
102     except:
103         print("- Retry connect to " + tracker[1] + " after 3 sec.")
104         time.sleep(3)
105         sendPeerSocket.connect((tracker[1], sendPeerPort))
106         print("+ Connect to " + tracker[1] + " success.")
107
108     sendPeerSocket.send(str(tracker[0]).encode())
109     # expect to receive the chunk from the server.
110     receivedFileChunk = ""
111     for i in range(chunkSize/1024):
112         receivedFileChunk = receivedFileChunk + sendPeerSocket.recv(1024).
113         decode()
114     print("Received Size from " + tracker[1] + " : " + str(len(
115         receivedFileChunk)))
116     content[tracker[0]] = receivedFileChunk # write to self content
117     trackers[tracker[0]][2] = True # declare to be useable
118     sendPeerSocket.close()
119
120 class ReceiveThread(threading.Thread):
121     def __init__(self, tracker):
122         threading.Thread.__init__(self)
123         self.tracker = tracker
124     def run(self):
125         getContent(self.tracker)
126
127 class FetchingThread(threading.Thread):
128     def __init__(self):
129         threading.Thread.__init__(self)
130     def run(self):
131         rths = []
132         for tracker in trackers:
133             # To avoid conflict, will be called by other peer.
134             if not tracker[1] == hostName:
135                 rth = ReceiveThread(tracker)
136                 rth.start()
137                 rths.append(rth)
138         for rth in rths:
139             rth.join()

```

```

137
138 # Start servicing.
139 serth = ServiceThread()
140 serth.start()
141
142 # Start fetching
143 fetth = FetchingThread()
144 fetth.start()
145
146 # Wait for merge
147 fetth.join()
148
149 # Now, force to download the own chunk if it is not downloaded.
150 for tracker in trackers:
151     if tracker[1] == hostName and tracker[2] == False:
152         DownContent(tracker[0])
153
154 # should be done with all file chunks, unless error occurred.
155 with open(filename,"wb") as f:
156     for i in range(len(content)):
157         if i in content.keys():
158             f.write(content[i])
159         else:
160             print("- " + hostName + " lost chunk " + str(i))
161
162 END_TIME = time.time()
163
164 elapsed_time = END_TIME-START_TIME
165 print(elapsed_time)
166
167 with open("result_py.dat","a") as rf:
168     rf.write(hostName + "\t" + str(elapsed_time) + "\n")

```