

TA Instructions

Hello! Welcome to Team 11's report. The checkpoints are labeled as such in the headers to make it easier for you to run, but everything has been commented out that is not necessary. The data access information is available in the "Data" section, and all dependencies / necessary downloads are show in code.

Our github repo can be accessed here: <https://github.com/LoganB99/DL4H-SP24-Local-Explanations-For-Cervical-Cancer>

Our video overview can be accessed here:

<https://drive.google.com/file/d/1VbnpcCaYxyATlkzQZPA5bLop64rc6XSg/view?usp=sharing>

✓ Mount Notebook to Google Drive

To clear up clutter, the original FAQ and Attentions are in

https://colab.research.google.com/drive/1MGxB_J2TvhAANcQG8VNMvQp1QdQrcxWb?authuser=1

```
import pandas as pd
from google.colab import drive
drive.mount('/content/drive', force_remount=True)
```

Mounted at /content/drive

```
#Testing
!pip install gspread google-auth
from google.colab import auth
auth.authenticate_user()
```

```
import gspread
from google.auth import default
creds, _ = default()
```

```
gc = gspread.authorize(creds)
```

```
Requirement already satisfied: gspread in /usr/local/lib/python3.10/dist-package
Requirement already satisfied: google-auth in /usr/local/lib/python3.10/dist-pac
Requirement already satisfied: google-auth-oauthlib>=0.4.1 in /usr/local/lib/pyt
Requirement already satisfied: StrEnum==0.4.15 in /usr/local/lib/python3.10/dist
Requirement already satisfied: cachetools<6.0,>=2.0.0 in /usr/local/lib/python3.
Requirement already satisfied: pyasn1-modules>=0.2.1 in /usr/local/lib/python3.1
Requirement already satisfied: rsa<5,>=3.1.4 in /usr/local/lib/python3.10/dist-p
Requirement already satisfied: requests-oauthlib>=0.7.0 in /usr/local/lib/pythor
```

```
Requirement already satisfied: pyasn1<0.7.0,>=0.4.6 in /usr/local/lib/python3.10
Requirement already satisfied: oauthlib>=3.0.0 in /usr/local/lib/python3.10/dist
Requirement already satisfied: requests>=2.0.0 in /usr/local/lib/python3.10/dist
Requirement already satisfied: charset-normalizer<4,>=2 in /usr/local/lib/pythor
Requirement already satisfied: idna<4,>=2.5 in /usr/local/lib/python3.10/dist-pa
Requirement already satisfied: urllib3<3,>=1.21.1 in /usr/local/lib/python3.10/c
Requirement already satisfied: certifi>=2017.4.17 in /usr/local/lib/python3.10/c
```

Introduction

- Background of the problem

Cervical Cancer prediction is a prevalent and necessary problem within today's healthcare system. Specifically, researchers are working towards identifying risk factors and potential causes for cervical cancer. Current models, however, cannot explain why a decision is made. Local explainability techniques have been developed aiming to the causes and effects of changes within a model and explain the decision-making process at an individual prediction level, but may not be applicable in every scenario, and the explanations are not always consistent or faithful. Consequently, clinicians cannot explain why a model selected a patient as low or high risk through black-box magic models.

- Paper explanation

The paper aims to combat the current problem of ambiguity in explainability across scenarios and analyze the existing local interpretability methods to propose methods to help clinicians determine which type of explanation models to use in a given context. Specifically, the researchers tested 5 different ML algorithms to identify the model with the highest disease prediction accuracy, and then applied explainability methods to the model to identify the best practice for disease prediction. The paper then uses the predictions of the best model to generate explanations for each model across popular interpretability methods. These methods include LIME, SHAP, Diverse Counterfactual Explanations, Tree Interpreter, and Local Surrogates. Finally, each of the interpretability methods are evaluated on a set of metrics. The model found that LIME is the most robust explainability method, but no single explanation performance optimally across all metrics. Therefore, the researches suggest that clinicians should choose a method based on the setting or choose a weighted sum of metrics. This approach helps satisfy the desired explainability properties when determining patient risk in cervical cancer. As a result, the paper also recommends and influences future models to consider interpretability methods in their analysis to improve trust in the new world of generative and predictive models.

Scope of Reproducibility:

We aim to reproduce the results of the model using the UCI dataset and suggested models. We will use ADASYN to balance the dataset and remove and retrain features as one of our ablations. As another ablation, we want to test the model on the unbalanced dataset.

1. Hypothesis 1: Random Forest is the most performing model in predicting cervical cancer in terms of AUC.
2. Hypothesis 2: LIME is the most robust explainability model shown by the ROAR (remove and retrain) faithfulness metric.

✓ Methodology

Python version in notebook: 3.10.12

✓ Checkpoint: Dependencies

Note: because of Colab's default setup, you may have to restart the notebook and rerun after installing packages.

```
# External package installation
!pip install pandas
!pip install kaleido
!pip install gdown==4.6.0
!pip install shap
!pip install lime
!pip install interpret-community
!pip install alibi
!pip install treeinterpreter
!pip install SALib
!pip install dice-ml
!pip install pip install spectralcluster
!pip install kaleido
!pip install requests
!pip install shapash
```



```
# download files and models
import gdown
import pickle
import requests

# Basic data handling and scientific computing
import numpy as np # Numerical computing library
import pandas as pd # Data manipulation and analysis
import random
from numpy import arange

# Visualization libraries
import seaborn as sns # Statistical data visualization
import matplotlib.pyplot as plt # Basic plotting library
import plotly.express as px # Interactive plotting library
import plotly.graph_objects as go # For creating custom plots with Plotly
from plotly.subplots import make_subplots # For creating subplots with Plotly

# Data preprocessing and model evaluation tools
from sklearn.impute import SimpleImputer # For handling missing data
from sklearn.model_selection import StratifiedShuffleSplit # For creating stratified
from sklearn.preprocessing import RobustScaler, StandardScaler # Data scaling method
from sklearn.decomposition import PCA # Principal Component Analysis
from sklearn.pipeline import Pipeline # For creating modeling pipelines
from sklearn.metrics import accuracy_score, confusion_matrix # Model evaluation metr
from sklearn.metrics import precision_recall_fscore_support # Precision, recall, and
from sklearn.metrics import roc_auc_score # AUC score

# Machine learning models
from sklearn.linear_model import LogisticRegression # Logistic regression model
from sklearn.ensemble import RandomForestClassifier, VotingClassifier # Ensemble mod
from sklearn.neighbors import KNeighborsClassifier # k-Nearest Neighbors model
from sklearn.svm import SVC # Support Vector Machine model
from sklearn.neural_network import MLPClassifier

# Model selection and hyperparameter tuning
from sklearn.model_selection import GridSearchCV # For hyperparameter tuning

# Data balancing techniques
from imblearn.over_sampling import SMOTE, ADASYN # Over-sampling techniques
from imblearn.over_sampling import RandomOverSampler # Random over-sampling

# Additional utilities
from typing import List # For type hints
from google.colab import drive # Google Colab drive integration (if using Google Col
import warnings # For controlling warning messages
warnings.filterwarnings('ignore') # Suppress warning messages for cleaner output
# Plotly setup for notebooks
from plotly.offline import plot, iplot, init_notebook_mode
```

```
# Local explainability
from sklearn.inspection import permutation_importance
from sklearn.inspection import PartialDependenceDisplay, partial_dependence
from interpret_community.mimic.mimic_explainer import MimicExplainer
from interpret_community.mimic.models import LinearExplainableModel
from interpret.blackbox import MorrisSensitivity
import shap
import lime
from lime import lime_tabular
from treeinterpreter import treeinterpreter as ti
```

Checkpoint: Project Files

```
gdown.download(id='11swC5N9lqEVTp3E-K1dtBr1HQEoEkxTk', output="project_files.tgz")
!tar -xzf project_files.tgz
```

Downloading...

From: <https://drive.google.com/uc?id=11swC5N9lgEVTp3E-K1dtBrIHQEOEkxtk>

To: /content/project_files.tgz

100% | ██████████ | 10.5M/10.5M [00:00<00:00, 68.0MB/s]

[illegible]

To clean and process the data, we convert numerical 'object' columns to integers. We replace '?'s with the median of that column. We rerun the overall statistics to confirm there are no "unknown" values and the number of cancer patients remained the same. We create a new age_category column that stratifies the ages.

We run statistics on the age category to gain context. For example, we can see things like just over 2% of the dataset is diagnosed with cancer, but 44% of those diagnosed with cancer are in their 30's, and 20% of patients who are in their 50's have cancer. (We must remember the dataset is small, which is why we sample using ADASYN). There are only 4 patients 70 or older, and they all happen to not have cancer. This does not mean age is not important.

✓ Processing and Statistics

✓ Checkpoint: Load Data Function

```
def load_data(data_dir):
    # implement this function to load raw data to dataframe/numpy array/tensor
    return pd.read_csv(data_dir, delimiter=',', encoding='utf-8')
```

✓ Checkpoint: Load Raw Data

```
root = '/content/drive/My Drive/DL4H_Sp24_Final_Project/'
# dir and function to load raw data
have_access = True

try:
    data_dir = '/content/drive/My Drive/DL4H_Sp24_Final_Project/risk_factors_cervical'
    raw_risk_factor_df = load_data(data_dir)
    have_access = True
except:
    have_access = False
    data_dir = 'risk_factors_cervical_cancer.csv'
    # gdown.download('https://drive.google.com/file/d/13Co6aIxBU4KXMNH56TDyQd70pkk_b4'
    raw_risk_factor_df = load_data('DL4H_Sp24_Final_Project/risk_factors_cervical_cancer.csv')
    print("No access, Used Gdown!")
# https://drive.google.com/drive/folders/1AUr8BgW16UU-7XjFf8077XAgjA27gISV?usp=sharing
raw_risk_factor_df
```


✓ Checkpoint: Define Statistics methods

```

# calculate dataset statistics
def calculate_dataset_stats(df):
    print(len(df), " total patients")
    print(df['Dx:Cancer'].value_counts()[0], " patients without Cancer")
    print(df['Dx:Cancer'].value_counts()[1], " patients with Cancer")
    print(df.applymap(lambda x: x == "?").sum().sum(), " unknown values")
    specified_value = '?' # Replace with the value you're interested in
    max_count = -1
    column_with_most = None

    for column in df.columns:
        if column == "STDs: Time since last diagnosis" or column == "STDs: Time since f
            continue
        value_counts = df[column].value_counts()
        if specified_value in value_counts:
            if value_counts[specified_value] > max_count:
                max_count = value_counts[specified_value]
                column_with_most = column

    print(f"Column with the most '{specified_value}': {column_with_most} (Count: {max_
dataset_size = df.shape[0] * df.shape[1]
    print(100 * df.applymap(lambda x: x == "?").sum().sum()/dataset_size, " percent o

# Formatting to match the style: dtypes: float64(2), int64(2), object(1)
formatted_summary = ", ".join([f"{k}: {v}" for k, v in df.dtypes.value_counts().i
print("dtypes:", formatted_summary)

```

NOTE: this is a deviation from the source code. In the source code, category_percentages summed up to 100 across the diagnosis, we also wanted to show the percent for each

```
def col_stats(df, diagnosis_column, category_column):
    """
    Calculates statistics for diagnosis distributions across categories.

    Parameters:
    - df (DataFrame): The input data frame containing the relevant data.
    - diagnosis_column (str): The name of the column containing diagnosis information.
    - category_column (str): The name of the column containing category labels (e.g. 'Category').

    Returns:
    - DataFrame: A pivot table presenting the calculated statistics.
    """

    # Calculate the overall percentage of each diagnosis-category combination.
    overall_percentages = df[[diagnosis_column, category_column]] \
        .value_counts(normalize=True) \
        .mul(100) \
        .round(decimals=4) \
        .reset_index(name='Overall_Percent')

    # Count the occurrences within each category for a diagnosis.
    diagnosis_by_category_counts = df.groupby([diagnosis_column, category_column]) \
        .size() \
        .reset_index(name='Count_in_Category')

    # Count the total occurrences within each category.
    total_in_category = df.groupby(category_column) \
        .size() \
        .reset_index(name='Total_in_Category')

    # Calculate the percentage of each diagnosis within specific categories.
    category_percentages = pd.merge(diagnosis_by_category_counts, total_in_category,
                                     on=category_column)
    category_percentages['Category_Percent'] = category_percentages['Count_in_Category'] \
        .div(category_percentages['Total_in_Category']) \
        .mul(100) \
        .round(decimals=4)

    # Count occurrences of each diagnosis and calculate the percentage within the diagnosis.
    diagnosis_counts_and_percentages = pd.merge(
        df.groupby([diagnosis_column, category_column]).size().reset_index(name='In_Category_Count'),
        df.groupby(diagnosis_column).size().reset_index(name='Total_in_Diagnosis'),
        on=diagnosis_column
    )
    diagnosis_counts_and_percentages['Diagnosis_Percent'] = diagnosis_counts_and_percentages['In_Category_Count'] \
        .div(diagnosis_counts_and_percentages['Total_in_Diagnosis']) \
        .mul(100) \
        .round(4)
```

```

# Merge the overall percentages with category-specific percentages.
temp_merged = pd.merge(
    overall_percentages,
    category_percentages[[diagnosis_column, category_column, 'Category_Percent']],
    on=[diagnosis_column, category_column]
)

# Merge with the diagnosis percentage data.
final_merged = pd.merge(
    temp_merged,
    diagnosis_counts_and_percentages[[diagnosis_column, category_column, 'Diagnosis_Percent']],
    on=[diagnosis_column, category_column]
)

# Create a pivot table for better presentation.
final_pivot_table = final_merged.pivot(index=category_column, columns=diagnosis_column)
final_pivot_table.fillna(0.000, inplace=True)
return final_pivot_table

def print_unique_values_df(df: pd.DataFrame):
    for col in list(df):
        print("Number of Unique Values for '{}' : {}".format(str(col), len(df[col].unique())))
        print("dtype for {} is {}".format(str(col), df[col].dtype))
        print("-" * 150)

```

✓ Checkpoint: Define Processing Method

```

# process raw data
def process_data(raw_data):
    # implement this function to process the data as you need
    #these columns are not of type object, but are of type numeric
    cols_to_convert = ['Number of sexual partners', 'First sexual intercourse', 'Num (
        'Smokes (years)', 'Smokes (packs/year)', 'Hormonal Contraceptive
        'Hormonal Contraceptives (years)', 'IUD', 'IUD (years)', 'STDs'
        'STDs:condylomatosis', 'STDs:cervical condylomatosis', 'STDs:va
        'STDs:vulvo-perineal condylomatosis', 'STDs:syphilis', 'STDs:pe
        'STDs:genital herpes', 'STDs:molluscum contagiosum', 'STDs:AIDS
        'STDs:HPV', 'STDs: Time since first diagnosis',
        'STDs: Time since last diagnosis']

    std_cols = {'STDs:condylomatosis',
        'STDs:cervical condylomatosis',
        'STDs:vaginal condylomatosis',
        'STDs:vulvo-perineal condylomatosis',
        'STDs:syphilis',
        'STDs:pelvic inflammatory disease',
        'STDs:genital herpes',
        'STDs:molluscum contagiosum',
        'STDs:AIDS',
        'STDs:HIV',
        'STDs:Hepatitis B',
        'STDs:HPV'}

    test_cols = ["Hinselmann", "Schiller", "Citology", "Biopsy"]

    to_int_and_beyond = {"total_tests",
        "total_std",
        "Smokes",
        "Biopsy",
        "Dx:Cancer",
        "Num of pregnancies",
        "Number of sexual partners",
        "First sexual intercourse",
        "Hormonal Contraceptives",
        "IUD",
        "STDs",
        "STDs (number)",
        "STDs: Number of diagnosis",
        "Dx:CIN",
        "Dx:HPV",
        "Dx",
        "Hinselmann",
        "Schiller",
        "Biopsy",
        "Citology"}

    to_int_and_beyond = to_int_and_beyond.union(std_cols)

```

```

# convert object columns to numeric and replace with nan
raw_data[cols_to_convert] = raw_data[cols_to_convert].apply(pd.to_numeric, errors=
raw_data[cols_to_convert].fillna(np.nan, inplace=True)
# replace nan values with the median of the column
imp = SimpleImputer(strategy="median")
X = imp.fit_transform(raw_data)
risk_factor_df = pd.DataFrame(X, columns=list(raw_data.columns))

# make new columns
risk_factor_df["Age"] = risk_factor_df["Age"].astype(int)
risk_factor_df["age_cat"] = risk_factor_df["Age"].apply(age_cat)
risk_factor_df["total_std"] = risk_factor_df[list(std_cols)].sum(axis=1)
risk_factor_df["total_tests"] = risk_factor_df[test_cols].sum(axis = 1)
for col in to_int_and_beyond:
    risk_factor_df[col] = risk_factor_df[col].astype(int)

# Aggregate the STD counts by age categories
std_agg = risk_factor_df.groupby("age_cat", as_index=False)[list(std_cols)].sum()
return risk_factor_df, std_agg

# categorize the age ranges
def age_cat(age):
    if age < 12:
        return "Child"
    elif age < 20:
        return "Teen"
    elif age < 30:
        return "20's"
    elif age < 40:
        return "30's"
    elif age < 50:
        return "40's"
    elif age < 60:
        return "50's"
    elif age < 70:
        return "60's"
    else:
        return "70+"

def save_data(df, path):
    if have_access:
        print("Save checkpoint granted")
        df.to_csv(path, index=False)
    else:
        print("You have no access to save data, skipping save checkpoint")

```

✓ Checkpoint: Calculate Raw Data Stats

```
print('RAW DATA STATS')
calculate_dataset_stats(raw_risk_factor_df)

RAW DATA STATS
858 total patients
840 patients without Cancer
18 patients with Cancer
3622 unknown values
Column with the most '?': IUD (Count: 117)
11.726236726236726 percent of the dataset is unknown
dtypes: object: 26, int64: 10
```

✓ (BEFORE ADASYN) Process Data, Calculate Processed Stats, and Save Data

```
# process data set
risk_factor_df, std_agg = process_data(raw_risk_factor_df)
save_data(risk_factor_df, '/content/drive/My Drive/DL4H_Sp24_Final_Project/processed_risk_factor_df.pkl')
save_data(std_agg, '/content/drive/My Drive/DL4H_Sp24_Final_Project/processed_std_agg.pkl')

Save checkpoint granted
Save checkpoint granted
```

✓ Checkpoint: Load Processed Data

```
root
```

```

try:
    data_dir = '/content/drive/My Drive/DL4H_Sp24_Final_Project/processed_risk_factor:
    risk_factor_df = load_data(data_dir)
    unbalanced_risk_factor_df = risk_factor_df
    data_dir = '/content/drive/My Drive/DL4H_Sp24_Final_Project/processed_std_agg.csv
    std_agg = load_data(data_dir)
    have_access = True
except:
    have_access = False
    data_dir = root+'/processed_risk_factors_cervical_cancer.csv'
    # gdown.download('https://drive.google.com/file/d/1n-II-zTy0pjToeWmetQFrbZ4YKFjfZl
    risk_factor_df = load_data(data_dir)
    unbalanced_risk_factor_df = risk_factor_df
    data_dir = root+'/processed_std_agg.csv'
    # gdown.download('https://drive.google.com/file/d/110iEdMjfYzcmTZNh1jIWQJlI0w4iEbl
    std_agg = load_data(data_dir)
    print("No access, Used Gdown!")
print("-" * 150)
print('PROCESSED DATA STATS')
# print overall stats, might need to edit
calculate_dataset_stats(risk_factor_df)
print("-" * 150)
# print column specific stats
print('Dx:Cancer by age category')
dxCancerByAge = col_stats(risk_factor_df, 'Dx:Cancer', 'age_cat')
print(dxCancerByAge)

```

No access, Used Gdown!

```

-----
PROCESSED DATA STATS
858 total patients
840 patients without Cancer
18 patients with Cancer
0 unknown values
Column with the most '?': None (Count: -1)
0.0 percent of the dataset is unknown
dtypes: int64: 32, float64: 6, object: 1
-----

```

```

Dx:Cancer by age category
      age_cat Overall_Percent      Category_Percent
Dx:Cancer      0      1      0      1
0      20's      45.3380  0.5828      98.7310  1.2690 \
1      30's      24.7086  0.9324      96.3636  3.6364
2      40's      6.1772  0.3497      94.6429  5.3571
3      50's      0.4662  0.1166      80.0000 20.0000
4      70+      0.4662  0.0000     100.0000  0.0000
5      Teen      20.7459  0.1166      99.4413  0.5587

```

```

      Diagnosis_Percent
Dx:Cancer      0      1
0      46.3095  27.7778
1      25.2381  44.4444
2      6.3095  16.6667
3      0.4762  5.5556

```


4	0.4762	0.0000
5	21.1905	5.5556

✓ Checkpoint: Visualizations

✓ Top features that correlate with cancer Dx

```
# Features that correlate with a cancer diagnosis
n = 7
target = label = "Dx:Cancer"
# correlate the numerical columns of the df
corr = risk_factor_df.select_dtypes(include=np.number).corr()
# find the top 7 correlations with Dx:Cancer
x = corr.nlargest(n,target).index
print(x)
# make a corr_df with only the top 7 columns
corr_df = risk_factor_df[list(x)]
# recalculate the correlation
corr = corr_df.corr()
# Creating a mask for the upper triangle
mask = np.triu(np.ones_like(corr, dtype=bool), k=1)

# Use the mask to replace the upper triangle with np.nan
corr_masked = corr.where(~mask)

# Plot using Plotly Express
fig = px.imshow(corr_masked,
                 color_continuous_scale="PuBu",
                 labels=dict(x="Feature", y="Feature", color="Correlation"),
                 x=corr.columns, # Adding column names here
                 y=corr.index)   # Adding row names here

# Update layout with title
fig.update_layout(title="Top "+str(n)+" Features Correlated With "+str(target).capitalize())
fig.update_xaxes(showgrid=False)
fig.update_yaxes(showgrid=False)
# Show plot
fig.show()
```

▼ Distribution of age

```
# Distribution of age
age_dist = px.histogram(risk_factor_df, x="Age", marginal="box", color_discrete_seq
age_dist.update_layout(title="Age distribution")
age_dist.show()
```

✓ Pregnancy Distribution by Age

```
#Pregancy Distribution by Age
age_preg_bar = px.box(risk_factor_df.sort_values(by="Age",ascending=True), x="age_cat",
                      color_discrete_sequence=["darkblue"], points="outliers",
                      category_orders=["Teenager", "Twenties", "Thirties", "Forties",
                                      "Seventy and over"])
age_preg_bar.update_xaxes(title="Age Category")
age_preg_bar.update_yaxes(title="Number of Pregnancies")
age_preg_bar.update_layout(title="Distribution of number of pregnancies per age group")
age_preg_bar.show()
```

✓ Mayo Risk Factors (May split further)

Mayo Clinic provides many risk factors for cervical cancer, including many sexual partners, earlier sexual activity, STIs, a weakened immune system, smoking, and the exposure to miscarriage prevention drug DES.

We can see from the following visualizations that number of sexual partners remain fairly consistent across age ranges. We can also see a very low correlation between number of sexual partners and any relevant diagnoses.

We see a very high correlation between HPV and Cancer, but a low correlation between CIN and HPV. This could be due to the incompleteness of this dataset, that we will try to balance later.

```
# Mayo Risk factors – sexual partners, sexual activity, STIs, immune system, smoking
```

```
label = 'age_cat'
```

```
# Plotting a box plot to visualize the distribution of the number of sexual partners
```

```
# The data is sorted by age and plotted with outliers, using a blue color for the data
```

```
age_num_sex_partners = px.box(risk_factor_df.sort_values(by="Age", ascending=True),  
                              color_discrete_sequence=["blue"], points="outliers",  
                              category_orders=["Teenager", "Twenties", "Thirties", "Forties",  
                                              "Seventy and over"])
```

```
# Updating axis titles for better readability and clarity.
```

```
age_num_sex_partners.update_xaxes(title="Age Category")
```

```
age_num_sex_partners.update_yaxes(title="Number of Sexual Partners")
```

```
# Updating the layout to add a title to the plot.
```

```
age_num_sex_partners.update_layout(title="Distribution of number of sexual partners")
```

```
# Displaying the plot.
```

```
age_num_sex_partners.show()
```

```
# Creating a scatter plot to visualize the relationship between age and number of sexual partners
# The plot includes a trend line (ordinary least squares - OLS) to indicate the general trend
# Opacity is set to 0.4 to handle overplotting, and color represents the number of pregnancies
age_num_sex_partners = px.scatter(risk_factor_df, x="Age",
                                  y="Number of sexual partners",
                                  trendline="ols",
                                  opacity=0.4,
                                  color="Num of pregnancies",
                                  color_continuous_scale="rdbu")

# Updating the layout to add a title to the plot.
age_num_sex_partners.update_layout(title="Age vs Number of Sexual Partners")
# Displaying the plot.
age_num_sex_partners.show()
```

```
# Selecting columns related to diagnoses and number of sexual partners for correlat.
diagnoses_num_partner_compare_cols = [label, 'Dx:HPV', "Number of sexual partners"]
# Calculating the correlation matrix for the selected columns.
corr_matrix = risk_factor_df[diagnoses_num_partner_compare_cols].corr(numeric_only=
# Printing the correlation matrix.
# print(corr_matrix)
# Visualizing the correlation matrix using a heatmap with text annotations for corri
diagnoses_num_partner_heatmap = px.imshow(corr_matrix,
                                           aspect="auto",
                                           color_continuous_scale="gnbu",
                                           text_auto=True)
diagnoses_num_partner_heatmap.update_layout(title='HPV vs. Sexual Partners Heatmap')
# Displaying the heatmap.
diagnoses_num_partner_heatmap.show()
```

```
# Selecting columns related only to diagnoses for correlation analysis.
diagnoses_cols = [label, 'Dx:CIN', 'Dx:HPV']
# Calculating the correlation matrix for the selected diagnoses columns.
diagnoses_corr_matrix = risk_factor_df[diagnoses_cols].corr(numeric_only=True)
# Visualizing the correlation matrix using a heatmap with teal-green color scale and
diagnoses_heatmap = px.imshow(diagnoses_corr_matrix, aspect="auto", color_continuous:
# Displaying the heatmap.
diagnoses_heatmap.update_layout(title="Dx:CIN vs Dx:HPV HeatMap")
diagnoses_heatmap.show()
```

STDs


```
#data processing – to provide access of std_cols in STD graphs – do we want to add ·
std_cols = {'STDs:condylomatosis',
            'STDs:cervical condylomatosis',
            'STDs:vaginal condylomatosis',
            'STDs:vulvo-perineal condylomatosis',
            'STDs:syphilis',
            'STDs:pelvic inflammatory disease',
            'STDs:genital herpes',
            'STDs:molluscum contagiosum',
            'STDs:AIDS',
            'STDs:HIV',
            'STDs:Hepatitis B',
            'STDs:HPV'}

#create histogram to understand Sum of STD occurrences across age
fig = px.histogram(std_agg, x = "age_cat",
                  y = list(std_cols),
                  barmode = "group",
                  histfunc = "sum")
fig.update_layout(title = "Sum of STD occurrences across age categories")
fig.update_xaxes(title = "Age Category")
fig.update_yaxes(title = "Sum")
#show plot
fig.show()
#some discrepancies exist
```

```
#create boxplot to understand Distribution of number of sexual partners per age group
age_num_sex_partners = px.box(risk_factor_df.sort_values(by="Age",ascending=True), :
                              color_discrete_sequence=["blue"], points="outliers",
                              category_orders=["Teenager", "Twenties", "Thirties", "Forties",
                                                "Seventy and over"])
age_num_sex_partners.update_xaxes(title="Age Category")
age_num_sex_partners.update_yaxes(title="Number of Sexual Partners")
age_num_sex_partners.update_layout(title="Distribution of number of sexual partners")
#show plot
age_num_sex_partners.show()
```

```
#create histogram to understand Count of women across age groups who have had one o
fig = px.histogram(risk_factor_df.query("total_std>=0").sort_values(by=["total_std",
                             x="age_cat",
                             facet_col="total_std",
                             facet_row=label,
                             color_discrete_sequence=["rebeccapurple"],
                             opacity=0.7)
fig.update_layout(title="Count of women across age groups who have had one or more :
fig.update_layout(height=1200)
#show plot
fig.show()
```



```
#create histogram to understand Count of women across age groups who have had one o
fig = px.histogram(risk_factor_df.query("total_std>=0").sort_values(by=["total_std",
                             x="age_cat",
                             facet_col="total_std",
                             facet_row="Dx:HPV",
                             color_discrete_sequence=["dodgerblue"],
                             opacity=0.7)
fig.update_layout(title="Count of women across age groups who have had one or more :
fig.show()
```

✓ Tests used

Here we observe the number of tests done by patients to determine if they have Cervical Cancer / HPV.

```
fig = px.histogram(risk_factor_df.query("total_tests>0").sort_values(by="total_test:
                    x="age_cat",
                    facet_col="total_tests",
                    facet_row=label,
                    color_discrete_sequence=["blueviolet"],
                    opacity=0.8)
fig.update_layout(title="Count of women across age groups who have had one or more
fig.update_layout(height=1200)
fig.show()
```



```
fig = px.histogram(risk_factor_df.query("total_tests>0").sort_values(by=["total_tests",  
                                x="age_cat",  
                                facet_col="total_tests",  
                                facet_row="Dx:HPV",  
                                color_discrete_sequence=["coral"],  
                                opacity=0.8)  
fig.update_layout(title="Count of women across age groups who have had one or more  
fig.show()
```

```
fig = px.ecdf(risk_factor_df, x=["Smokes (years)",  
                                "Hormonal Contraceptives (years)",  
                                "IUD (years)"],  
              color_discrete_sequence=["crimson", "deepskyblue", "chartreuse"])  
fig.update_xaxes(title="Years")  
fig.update_layout(title="ECDF Plot")  
fig.show()
```



```

age_category_range = {
    "Age<12": "Child",
    "Age>=12 & Age<20": "Teen",
    "Age>=20 & Age<30": "20's",
    "Age>=30 & Age<40": "30's",
    "Age>=40 & Age<50": "40's",
    "Age>=50 & Age<60": "50's",
    "Age>=60 & Age<70": "60's",
    "Age>=70": "70+"}
age_prop_dict = {}
col = "Age" # Just to get the count
for age_range, category in age_category_range.items():
    age_prop_dict[category] = risk_factor_df.query(age_range)[col].count() / len(risk_factor_df)

proportion_samples_df = pd.DataFrame.from_dict(age_prop_dict, orient="index",
                                                columns=[ "Sample Proportion"])
proportion_samples_df = proportion_samples_df.reset_index()
proportion_samples_df.columns = proportion_samples_df.columns.str.replace("index", "Category")
fig = px.pie(proportion_samples_df,
              values='Sample Proportion',
              names="Category",
              title='Age Category proportion of women sampled',color_discrete_sequence=px.colors.qualitative.M10)
fig.show()
proportion_samples_df

```



```
fig = make_subplots(rows=1, cols=2, specs=[[{'type': 'domain'}, {'type': 'domain'}],
                    subplot_titles=["Cancer", "HPV"])
fig.add_trace(go.Pie(labels=risk_factor_df["age_cat"],
                    values=risk_factor_df[label],
                    name="Cancer", marker_colors=px.colors.sequential.RdBu),
              1, 1)
fig.add_trace(go.Pie(labels=risk_factor_df["age_cat"],
                    values=risk_factor_df["Dx:HPV"],
                    name="HPV", marker_colors=px.colors.sequential.RdBu),
              1, 2)

fig.update_traces(hole=.0, hoverinfo="label+percent+name")

fig.update_layout(
    title_text="Proportion of women across age categories with a diagnosis of Cance
)
fig.show()
```

Contraceptive

```

df_hormonal_compariosn = risk_factor_df.groupby(["age_cat"], as_index=False)[["IUD",
fig = px.histogram(df_hormonal_compariosn, x="age_cat", y=["IUD", "Hormonal Contrac
, color_discrete_sequence=["darkcyan", "mediumorchid"])

fig.update_xaxes(title="Age Category")
fig.update_yaxes(title="Count")
fig.update_layout(title="Age Ranges of women who use Contraceptives")

fig.show()

```

```

df_hormonal_contraceptives = risk_factor_df[
    (risk_factor_df["Hormonal Contraceptives"] == 1) & (risk_factor_df["IUD"] == 0)]
df_hormonal_contraceptives = df_hormonal_contraceptives.sort_values(by=["Smokes", "IUD"])
fig = px.histogram(df_hormonal_contraceptives, x="age_cat", color="Smokes", barmode="group",
    color_discrete_sequence=["darkcyan", "crimson"])
fig.update_xaxes(title="Age Category")
fig.update_yaxes(title="Count")
fig.update_layout(title="Age Ranges of women who use Hormonal Contraceptives")
# fig.for_each_annotation(lambda a: a.update(text=a.text.split(":")[-1]))
fig.show()

```

```
df_IUD_contraceptives = risk_factor_df[(risk_factor_df["Hormonal Contraceptives"] =  
df_IUD_contraceptives = df_IUD_contraceptives.sort_values(by=["Smokes", label], asce  
fig = px.histogram(df_IUD_contraceptives, x="age_cat", color="Smokes", barmode="group",  
                    color_discrete_sequence=["darkcyan", "crimson"])  
fig.update_xaxes(title="Age Category")  
fig.update_yaxes(title="Sum of IUD Usage across age category")  
fig.update_layout(title="Age Ranges of women who use IUD's")  
fig.show()
```

```
df_both_contraceptives = risk_factor_df[(risk_factor_df["Hormonal Contraceptives"] :  
df_both_contraceptives = df_both_contraceptives.sort_values(by="Smokes")  
fig = px.histogram(df_both_contraceptives, x="age_cat", color="Smokes", barmode="gr  
                    color_discrete_sequence=["darkcyan", "crimson"])  
fig.update_xaxes(title="Age Category")  
fig.update_yaxes(title="Count")  
fig.update_layout(title="Age Ranges of women who use BOTH Hormonal Contracepties and  
fig.show()
```

▼ ADASYN

```
test=risk_factor_df[['Number of sexual partners', 'First sexual intercourse', 'Nur
with open('summary.tex','w') as tf:
    tf.write(test.round(2).to_latex())

risk_factor_df.columns
```

```
Index(['Age', 'Number of sexual partners', 'First sexual intercourse',
      'Num of pregnancies', 'Smokes', 'Smokes (years)', 'Smokes (packs/year)',
      'Hormonal Contraceptives', 'Hormonal Contraceptives (years)', 'IUD',
      'IUD (years)', 'STDs', 'STDs (number)', 'STDs:condylomatosis',
      'STDs:cervical condylomatosis', 'STDs:vaginal condylomatosis',
      'STDs:vulvo-perineal condylomatosis', 'STDs:syphilis',
      'STDs:pelvic inflammatory disease', 'STDs:genital herpes',
      'STDs:molluscum contagiosum', 'STDs:AIDS', 'STDs:HIV',
      'STDs:Hepatitis B', 'STDs:HPV', 'STDs: Number of diagnosis',
      'STDs: Time since first diagnosis', 'STDs: Time since last diagnosis',
```



```
'Dx:Cancer', 'Dx:CIN', 'Dx:HPV', 'Dx', 'Hinselmann', 'Schiller',  
'Citology', 'Biopsy', 'age_cat', 'total_std', 'total_tests'],  
dtype='object')
```

```
label="Dx:Cancer"  
dx_cancer = px.histogram(risk_factor_df, y=label)  
dx_cancer.update_layout(bargap=0.2)  
dx_cancer.update_layout(title = "Imbalanced Classes")  
dx_cancer.show()
```

Here we use ADASYN to balance the dataset

```
unbalanced_risk_factor_df = risk_factor_df  
X = risk_factor_df.drop([label, "age_cat"], axis=1)  
y = risk_factor_df[label].copy()  
adasyn = ADASYN(random_state=42)  
x_adasyn, y_adasyn = adasyn.fit_resample(X, y)  
risk_factor_df = x_adasyn.join(y_adasyn)
```

Save ADASYN dataset

```
risk_factor_df["age_cat"] = risk_factor_df["Age"].apply(age_cat)
save_data(risk_factor_df, '/content/drive/My Drive/DL4H_Sp24_Final_Project/balanced_
```

Save checkpoint granted

✓ Checkpoint: Load Balanced data

```
try:
    data_dir = '/content/drive/My Drive/DL4H_Sp24_Final_Project/balanced_risk_factors_
    risk_factor_df = load_data(data_dir)
    have_access = True
except:
    have_access = False
    data_dir = root + '/balanced_risk_factors_cervical_cancer.csv'
    # gdown.download('https://drive.google.com/file/d/1-4EiqdYBbae16azaiZry7Gwhpq7Xhwl
    risk_factor_df = load_data(data_dir)
    print("No access, Used Gdown!")
risk_factor_df
label="Dx:Cancer"
```

No access, Used Gdown!

```
dx_cancer = px.histogram(risk_factor_df, y=label)
dx_cancer.update_layout(bargap=0.2)
dx_cancer.update_layout(title = "Balanced Classes")
dx_cancer.show()
```

✓ Checkpoint: Train Test Split

Stratifying the data on Age Category

✓ Unbalanced

```

unbalanced_train_set = None
unbalanced_test_set = None
#Stratify the data
# 20% in test and 80% in train
unbalanced_split = StratifiedShuffleSplit(n_splits=1, test_size=0.2, random_state=42)
for train_idx, test_idx in unbalanced_split.split(unbalanced_risk_factor_df, unbalanced_risk_factor_df["age_cat"]):
    unbalanced_train_set = unbalanced_risk_factor_df.loc[train_idx]
    unbalanced_test_set = unbalanced_risk_factor_df.loc[test_idx]
unbalanced_cols_to_drop = ["age_cat", "total_std", "total_tests"]
for set_ in (unbalanced_train_set, unbalanced_test_set):
    for col in unbalanced_cols_to_drop:
        set_.drop(col, axis=1, inplace=True)

unbalanced_X_train = unbalanced_train_set.drop(label, axis=1)
unbalanced_y_train = unbalanced_train_set[label].copy()

unbalanced_X_test = unbalanced_test_set.drop(label, axis=1)
unbalanced_y_test = unbalanced_test_set[label].copy()

unbalanced_X_test.reset_index(drop=True, inplace=True)
unbalanced_y_test.reset_index(drop=True, inplace=True)
unbalanced_X_train.reset_index(drop=True, inplace=True)
unbalanced_y_train.reset_index(drop=True, inplace=True)

print("unbalanced_X_test length: ", len(unbalanced_X_test))
print("unbalanced_X_train length: ", len(unbalanced_X_train))
print("unbalanced_Y_test length: ", len(unbalanced_y_test))
print("unbalanced_Y_train length: ", len(unbalanced_y_train))

unbalanced_X_test length: 172
unbalanced_X_train length: 686
unbalanced_Y_test length: 172
unbalanced_Y_train length: 686

```

▼ Balanced

```

train_set = None
test_set = None
#Stratify the data
# 20% in test and 80% in train
split = StratifiedShuffleSplit(n_splits=1, test_size=0.2, random_state=42)
for train_idx, test_idx in split.split(risk_factor_df, risk_factor_df["age_cat"]):
    train_set = risk_factor_df.loc[train_idx]
    test_set = risk_factor_df.loc[test_idx]
cols_to_drop = ["age_cat", "total_std", "total_tests"]
for set_ in (train_set, test_set):
    for col in cols_to_drop:
        set_.drop(col, axis=1, inplace=True)

```

```
X_train = train_set.drop(label, axis=1)
y_train = train_set[label].copy()

X_test = test_set.drop(label, axis=1)
y_test = test_set[label].copy()

X_test.reset_index(drop=True, inplace=True)
y_test.reset_index(drop=True, inplace=True)
X_train.reset_index(drop=True, inplace=True)
y_train.reset_index(drop=True, inplace=True)

print("X_test length: ", len(X_test))
print("X_train length: ", len(X_train))
print("Y_test length: ", len(y_test))
print("Y_train length: ", len(y_train))

X_test length: 336
X_train length: 1341
Y_test length: 336
Y_train length: 1341
```

✓ Save sets

```
#without random var
X_test.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_test.csv')
y_test.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_test.csv')
X_train.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_train.csv')
y_train.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_train.csv')
```

✓ Checkpoint: Model Setup

We will be comparing different models: RF, SVM, LR, KNN, MLP

✓ Model 1: Logistic Regression.

This is a simple linear model and does not have layers.

The sigmoid function is used as its activation.

lbfgs is used as the solver with L2 regularization

The default max_iter for convergence is 100.

```
param_grid = {'C': np.logspace(-5, 8, 15)}  
  
logreg = LogisticRegression()  
logreg_cv = GridSearchCV(logreg, param_grid, cv=10, refit=True)  
unbalanced_logreg_cv = GridSearchCV(logreg, param_grid, cv=10, refit=True)
```

✓ Model 2: RandomForestClassifier

Ensemble machine learning model using groups of decision trees to reduce overfitting

The default `n_estimators` is 100

Default criterion = gini

Convergence ends when all leaves are pure or until each leaf is equal to `min_samples_leaf` (by default set to 2)

```
rnd_clf = RandomForestClassifier()  
unbalanced_rnd_clf = RandomForestClassifier()
```

✓ Model 3: KNeighborsClassifier

A machine learning iterative classification method that uses a distance function to group similar data

`n_neighbors` (number of surrounding data points to consider) is 5 by default

```
knn_clf = KNeighborsClassifier()  
knn_param_grid = {"n_neighbors": list(np.arange(1, 100, 2))}  
knn_clf_cv = GridSearchCV(knn_clf, knn_param_grid, cv=10, refit=True)  
unbalanced_knn_clf_cv = GridSearchCV(knn_clf, knn_param_grid, cv=10, refit=True)
```

✓ MODEL 4: SupportVectorClassifier

Support vector models are classification algorithm that uses hyperplanes to classify data points using a maximum margin between decision boundaries and the closest data points.

The regularization parameter `C` is set to 1 by default.

The kernel type is set to 'rbf' (radial basis function) by default

```
svm_clf = SVC()  
svc_param_grid = {'C': np.logspace(-3, 2, 6), 'gamma': np.logspace(-3, 2, 6), }  
svm_clf_cv = GridSearchCV(svm_clf, svc_param_grid, cv=5, refit=True)  
unbalanced_svm_clf_cv = GridSearchCV(svm_clf, svc_param_grid, cv=5, refit=True)
```

✓ MODEL 5: MLPClassifier

MLPs are neural networks used for pattern detection.

They consist of 3 layers of nodes, an input layer, a hidden layer, and an output layer.

The default max_iter is 200.

The optimizer is 'Adam'

Each node uses a nonlinear activation function. By default this is ReLu for the hidden layer. For the output layer, softmax is used by default for multi-class classification problems and logistic for binary classification problems.

Backpropagation and gradient descent is used to to train and minimize loss.

```
nn_clf = MLPClassifier()  
unbalanced_nn_clf = MLPClassifier()
```

▼ Set up training metrics


```

# metrics to evaluate my model
# Define column names for the summary DataFrame
col_names = ["Classifier Name", "Accuracy Score", "Precision Score", "Recall Score"]
# Initialize the summary DataFrame with predefined column names
unbalanced_summary_df = pd.DataFrame(columns=col_names)

# Lists to store the metrics for each estimator
unbalanced_est_name = []
unbalanced_est_acc = []
unbalanced_precision_score = []
unbalanced_recall_score = []
unbalanced_f1score = []
unbalanced_est_conf_matrix = []
unbalanced_roc=[]

# List of tuples containing the classifiers to evaluate and their respective variab
unbalanced_estimators = [
    ("UnbalancedLogisticRegression", unbalanced_logreg_cv),
    ("UnbalancedRandomForestClassifier", unbalanced_rnd_clf),
    ("UnbalancedKNeighborsClassifier", unbalanced_knn_clf_cv),
    ("UnbalancedSupportVectorClassifier", unbalanced_svm_clf_cv),
    ("UnbalancedMLPClassifier", unbalanced_nn_clf)
]

unbalanced_models = ['UnbalancedLogisticRegression.pkl',
                     'UnbalancedRandomForestClassifier.pkl',
                     'UnbalancedKNeighborsClassifier.pkl',
                     'UnbalancedSupportVectorClassifier.pkl',
                     'UnbalancedMLPClassifier.pkl']

summary_df = pd.DataFrame(columns=col_names)

# Lists to store the metrics for each estimator
est_name = []
est_acc = []
precision_score = []
recall_score = []
f1score = []
est_conf_matrix = []
roc=[]

# List of tuples containing the classifiers to evaluate and their respective variab
estimators = [
    ("LogisticRegression", logreg_cv),
    ("RandomForestClassifier", rnd_clf),
    ("KNeighborsClassifier", knn_clf_cv),
    ("SupportVectorClassifier", svm_clf_cv),
    ("MLPClassifier", nn_clf)
]
balanced_models = ['LogisticRegression.pkl',

```

```
'RandomForestClassifier.pkl',
'KNeighborsClassifier.pkl',
'SupportVectorClassifier.pkl',
'MLPClassifier.pkl']
```

✓ Model Training

Hyperparameters: Three examples of hyperparameters we used are 'C' (regularization constant), type of kernel ('rbf'), gamma (kernel coefficient) in the Support Vector Classifier Model.

Computational Requirements: Dataset is small enough to compute on an 8 GB 2133 MHz LPDDR3 2.3 GHz Dual-Core Intel Core i5. Average run time for training is < 2 minutes. We used default epochs. For logistic regression this 100 and for MLP this is 200, unless convergence is reached earlier.

The training for the Local explainability models took hours however and we had to sample to get them done.

✓ Unbalanced Training (Ablation)

```
# Iterate over the estimators to train
for i in range(len(unbalanced_estimators)):
    unbalanced_clf_name, unbalanced_clf = unbalanced_estimators[i] # Unpack the cl
    print("Training ", unbalanced_clf_name)
    unbalanced_clf.fit(unbalanced_X_train, unbalanced_y_train) # Train the classif
    gd_model_name = root + unbalanced_clf_name + '.pkl'
    with open(gd_model_name, 'wb') as file:
        pickle.dump(unbalanced_clf, file)
    unbalanced_clf_name, unbalanced_clf = '', ''
```

```
Training  UnbalancedLogisticRegression
Training  UnbalancedRandomForestClassifier
Training  UnbalancedKNeighborsClassifier
Training  UnbalancedSupportVectorClassifier
Training  UnbalancedMLPClassifier
```

✓ Balanced Training

```

for i in range(len(estimators)):
    clf_name, clf = estimators[i] # Unpack the classifier name and the classifier
    print("Training ", clf_name)
    clf.fit(X_train, y_train) # Train the classifier
    gd_model_name = root + clf_name + '.pkl'
    with open(gd_model_name, 'wb') as file:
        pickle.dump(clf, file)
clf_name, clf = '', ''

Training LogisticRegression
Training RandomForestClassifier
Training KNeighborsClassifier
Training SupportVectorClassifier
Training MLPClassifier

```

Double-click (or enter) to edit

✓ Checkpoint: Result

✓ Download pickle models with gdown

```

# LogisticRegression
unbalanced_models[0] = root + '/UnbalancedLogisticRegression.pkl'
balanced_models[0] = root + '/LogisticRegression.pkl'
# gdown.download('https://drive.google.com/file/d/1-4D7VkQ4qewUnyrzPw1izMk9WjMvQ13D,
# gdown.download('https://drive.google.com/file/d/1-94qCsT0VdS-Cv0237Z0TeUWCouKDeyl,
# # RandomForestClassifier
unbalanced_models[1] = root + '/UnbalancedRandomForestClassifier.pkl'
balanced_models[1] = root + '/RandomForestClassifier.pkl'
# gdown.download('https://drive.google.com/file/d/1-PBTxxa1NfXQNKpX8Bg9ojFRtPGEsvbw,
# gdown.download('https://drive.google.com/file/d/1-Qdk5tk2RCLhbfVW400S2qBI6ikStRBh,
# # KNeighborsClassifier
unbalanced_models[2] = root + '/UnbalancedKNeighborsClassifier.pkl'
balanced_models[2] = root + '/KNeighborsClassifier.pkl'
# gdown.download('https://drive.google.com/file/d/1-Rg4cRA6NdtPeHPFnablplZ0T7e323Qg,
# gdown.download('https://drive.google.com/file/d/1-TKog0oufiDcfCJtv_gQdYTiW1rK6VKn,
# # SupportVectorClassifier
unbalanced_models[3] = root + '/UnbalancedSupportVectorClassifier.pkl'
balanced_models[3] = root + '/SupportVectorClassifier.pkl'
# gdown.download('https://drive.google.com/file/d/1_g0BZHdpuPP9xlj0jKWJ-8fVZe4sTPKa,
# gdown.download('https://drive.google.com/file/d/1-3sNvATHD55evt_9nSzf3nBP6XWLknjL,
# # MLPClassifier
unbalanced_models[4] = root + '/UnbalancedMLPClassifier.pkl'
balanced_models[4] = root + '/MLPClassifier.pkl'
# gdown.download('https://drive.google.com/file/d/1-3P6L-WKDrfMNwp372f3vgY9Px0SEIm,
# gdown.download('https://drive.google.com/file/d/1-DmdcIFHJFKUtAhhVW1XbVlwbFj0pWS2,

```

✓ Model Execution

✓ Unbalanced evaluation (ablation)

```
# Iterate over the trained models to evaluate each one
for i in range(len(unbalanced_estimators)):
    with open(unbalanced_models[i], 'rb') as file:
        downloaded_model = pickle.load(file)
        unbalanced_clf_name, _ = unbalanced_estimators[i]
        unbalanced_y_pred = downloaded_model.predict(unbalanced_X_test) # Predict the
        # Calculate the AUROC score and append it to the roc list
        unbalanced_roc.append(roc_auc_score(unbalanced_y_test, unbalanced_y_pred, average='weighted'))

    # Append classifier name to the est_name list
    unbalanced_est_name.append(unbalanced_clf_name)

    # Calculate and append accuracy to the est_acc list
    unbalanced_est_acc.append(accuracy_score(unbalanced_y_test, unbalanced_y_pred))

    # Calculate precision, recall, and F1 scores and append them to their respective lists
    unbalanced_scores = precision_recall_fscore_support(unbalanced_y_test, unbalanced_y_pred, average='weighted')
    unbalanced_precision_score.append(unbalanced_scores[0])
    unbalanced_recall_score.append(unbalanced_scores[1])
    unbalanced_f1score.append(unbalanced_scores[2])

    # Append the confusion matrix for each classifier to the est_conf_matrix list
    unbalanced_est_conf_matrix.append(confusion_matrix(unbalanced_y_test, unbalanced_y_pred))

# Populate the summary DataFrame with the collected metrics for each classifier
unbalanced_summary_df[col_names[0]] = unbalanced_est_name
unbalanced_summary_df[col_names[1]] = unbalanced_est_acc
unbalanced_summary_df[col_names[2]] = unbalanced_precision_score
unbalanced_summary_df[col_names[3]] = unbalanced_recall_score
unbalanced_summary_df[col_names[4]] = unbalanced_f1score
unbalanced_summary_df[col_names[5]] = unbalanced_roc

# plot figures to better show the results

# it is better to save the numbers and figures for your presentation.
unbalanced_summary_df
```

▼ Balanced evaluation

```
# Iterate over the trained models to evaluate each one
for i in range(len(estimators)):
    with open(balanced_models[i], 'rb') as file:
        downloaded_model = pickle.load(file)
        clf_name, _ = estimators[i]
        y_pred = downloaded_model.predict(X_test) # Predict the test set outcomes

    # Calculate the AUROC score and append it to the roc list
    roc.append(roc_auc_score(y_test, y_pred, average=None))

    # Append classifier name to the est_name list
    est_name.append(clf_name)

    # Calculate and append accuracy to the est_acc list
    est_acc.append(accuracy_score(y_test, y_pred))

    # Calculate precision, recall, and F1 scores and append them to their respective
    scores = precision_recall_fscore_support(y_test, y_pred, average="weighted")
    print(scores)
    precision_score.append(scores[0])
    recall_score.append(scores[1])
    f1score.append(scores[2])

    # Append the confusion matrix for each classifier to the est_conf_matrix list
    est_conf_matrix.append(confusion_matrix(y_test, y_pred))

# Populate the summary DataFrame with the collected metrics for each classifier
summary_df[col_names[0]] = est_name
summary_df[col_names[1]] = est_acc
summary_df[col_names[2]] = precision_score
summary_df[col_names[3]] = recall_score
summary_df[col_names[4]] = f1score
summary_df[col_names[5]] = roc

# plot figures to better show the results

# it is better to save the numbers and figures for your presentation.
summary_df
```

✓ Model comparison

```
# compare you model with others
# you don't need to re-run all other experiments, instead, you can directly refer to
```

✓ Unbalanced comparison

```
color_scales = ["agsunset","teal","purp","viridis","viridis"]
for i in range(0,len(unbalanced_est_conf_matrix)):
    unbalanced_heatmap = px.imshow(unbalanced_est_conf_matrix[i],aspect="auto",
                                   text_auto=True,
                                   color_continuous_scale=color_scales[i])
    unbalanced_heatmap.update_layout(title = unbalanced_est_name[i])
    unbalanced_heatmap.update_xaxes(title="Predicted")
    unbalanced_heatmap.update_yaxes(title="Actual")
    unbalanced_heatmap.show()
```



```
#https://plotly.com/python/error-bars/  
#https://problemsolvingwithpython.com/06-Plotting-with-Matplotlib/06.07-Error-Bars/  
unbalanced_acc_comparison = px.bar(unbalanced_summary_df, x="Classifier Name",  
                                   y=col_names[1:len(col_names)], labels={"value": "Test Accuracy"},  
                                   color_discrete_sequence=["deeppink",  
                                                            "deepskyblue",  
                                                            "darkviolet",  
                                                            "darkorange",  
                                                            "darkred"],  
                                   barmode="group"  
                                   #,error_y=[dict(type='data', array=[0.5, 1, 2],visible=True  
                                   #,error_y_minus = [dict(type='data', array=[0.5, 1, 2, 2, 1  
                                   )  
unbalanced_acc_comparison.update_layout({'plot_bgcolor': 'rgba(0, 0, 0, 0)',  
                                         'paper_bgcolor': 'rgba(0, 0, 0, 0)'  
                                         })  
unbalanced_acc_comparison.show()
```

✓ Balanced comparison

Summary with heat map

```
color_scales = ["agsunset","teal","purp","viridis","viridis"]
for i in range(0,len(est_conf_matrix)):
    heatmap = px.imshow(est_conf_matrix[i],aspect="auto",
                        text_auto=True,
                        color_continuous_scale=color_scales[i])
    heatmap.update_layout(title = est_name[i])
    heatmap.update_xaxes(title="Predicted")
    heatmap.update_yaxes(title="Actual")
    heatmap.show()
```



```

#https://plotly.com/python/error-bars/
#https://problemsolvingwithpython.com/06-Plotting-with-Matplotlib/06.07-Error-Bars/
acc_comparison = px.bar(summary_df, x="Classifier Name",
                        y=col_names[1:len(col_names)], labels={"value": "Test Accuracy"},
                        color_discrete_sequence=["deeppink",
                                                "deepskyblue",
                                                "darkviolet",
                                                "darkorange",
                                                "darkred"],
                        barmode="group",
                        #,error_y=[dict(type='data', array=[0.5, 1, 2], visible=True
                        #,error_y_minus = [dict(type='data', array=[0.5, 1, 2, 2, 1
                        )
acc_comparison.update_layout({'plot_bgcolor': 'rgba(0, 0, 0, 0)',
                              'paper_bgcolor': 'rgba(0, 0, 0, 0)'
                              })
acc_comparison.show()

```

**** Description of Metrics****

TP: True Positive, these are the values that are positive and were predicted positive

FP: False Positive, The values which are negative but were wrongly predicted as positive

TN: True Negative, these are the values that are negative and were predicted negative

FN: False Negative, The values which are positive but were wrongly predicted as negative

Precision = $TP / (TP + FP)$

This metric measures the actual positive outcomes out of the total predicted positive outcomes. It attempts to identify the proportion of positive identifications that were correct. KNeighbors and SVC gave the worst precision score

In the context of diagnosing cervical cancer, this is metric would not be the most ideal to measure performance, as a negative case being labelled as a positive case is easily solved with confirmatory tests. However, one has to also consider the emotional and mental issues brought upon by being diagnosed with cervical cancer, as this can have a lingering effect even after having confirmatory tests. These tests should be done as soon as possible, as there may be another underlying illness that brought them to see a healthcare professional in the first place.

Recall

Recall = $TP / (TP + FN)$

This metric measures the correctly positive predicted outcomes of the total number of positive outcomes. It answers the question of what proportions of actual positives were identified correctly. KNeighbors and SVC gave the worst precision score

In the context of diagnosing cervical cancer, we want to reduce the number of false negatives (Actual positive cases labelled as negative cases) as much possible. If an actual positive case is labelled as negative, this has serious consequences as the patient would go about their life without actually receiving potentially life saving treatment.

There are many reasons why a cancer can go misdiagnosed, these include:

The symptoms, especially in the early stages being mistaken for some other type of less serious illness. The actual test administered by a healthcare professional may give the wrong diagnosis. The 5-year survival rate tells you what percent of people live at least 5 years after the cancer is found. Percent means how many out of 100. The 5-year survival rate for all people with cervical cancer is 66%. Source

Survival rates also depend on the stage of cervical cancer that is diagnosed. When detected at an early stage, the 5-year survival rate for people with invasive cervical cancer is 92%. About 44% of people with cervical cancer are diagnosed at an early stage. If cervical cancer has spread to surrounding tissues or organs and/or the regional lymph nodes, the 5-year survival rate is 58%. If the cancer has spread to a distant part of the body, the 5-year survival rate is 18%.

F1 Score

$$\text{F1 Score} = \frac{TP}{TP + ((FN + FP) / 2)}$$

The F1 score is defined as the harmonic mean of precision and recall. Therefore, a high F1 score means both a high precision and recall, same for low and a medium score if one score is high and the other is low.

$$\text{Accuracy} = \frac{TP + TN}{TP + FP + TN + FN}$$

✓ Data Pertubations

In this section, we take the train and test sets and add

1. random noise
2. binary variable
3. continuous variable to three separate sets

at this point, risk_factor_df is balanced data set

```
from scipy.stats import bernoulli
risk_factor_df['VAR']=bernoulli.rvs(.5, size=risk_factor_df.shape[0])

#continous
risk_factor_df['VAR']=np.random.normal(loc=0, scale=1, size=risk_factor_df.shape[0])
risk_factor_df.columns

Index(['Age', 'Number of sexual partners', 'First sexual intercourse',
      'Num of pregnancies', 'Smokes', 'Smokes (years)', 'Smokes (packs/year)',
      'Hormonal Contraceptives', 'Hormonal Contraceptives (years)', 'IUD',
      'IUD (years)', 'STDs', 'STDs (number)', 'STDs:condylomatosis',
      'STDs:cervical condylomatosis', 'STDs:vaginal condylomatosis',
      'STDs:vulvo-perineal condylomatosis', 'STDs:syphilis',
      'STDs:pelvic inflammatory disease', 'STDs:genital herpes',
      'STDs:molluscum contagiosum', 'STDs:AIDS', 'STDs:HIV',
      'STDs:Hepatitis B', 'STDs:HPV', 'STDs: Number of diagnosis',
      'STDs: Time since first diagnosis', 'STDs: Time since last diagnosis',
      'Dx:CIN', 'Dx:HPV', 'Dx', 'Hinselmann', 'Schiller', 'Citology',
      'Biopsy', 'total_std', 'total_tests', 'Dx:Cancer', 'age_cat', 'VAR'],
      dtype='object')
```

Get data and model - the source code is poorly labeled here and is not clear on the "cancer.csv" file they use

We are assuming it is the balanced dataset

```
risk_factor_df.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Rcancer2.csv')
#modified below to replicate above filename
risk_factor_df=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Rcancer2.csv')

risk_factor_df
```

✓ Checkpoint: Get Original

```
# X_test=pd.read_csv(gdown.download('https://drive.google.com/file/d/1ggTvbeS9kerpV')
X_test = pd.read_csv(root+'/X_test.csv')
X_test.drop('Unnamed: 0', inplace=True, axis=1)
# y_test=pd.read_csv(gdown.download('https://drive.google.com/file/d/1WsUWr09Nwpd6K')
y_test = pd.read_csv(root+'/y_test.csv')
y_test.drop('Unnamed: 0', inplace=True, axis=1)
# X_train=pd.read_csv(gdown.download('https://drive.google.com/file/d/10nCY70gXQbT3')
X_train = pd.read_csv(root+'/X_train.csv')
X_train.drop('Unnamed: 0', inplace=True, axis=1)
# y_train=pd.read_csv(gdown.download('https://drive.google.com/file/d/1C5euZUKZ6GL')
y_train = pd.read_csv(root+'/y_train.csv')
y_train.drop('Unnamed: 0', inplace=True, axis=1)
```

```
len(X_test)
```

```
336
```

✓ Normal

```
from scipy.stats import bernoulli
```

```
# Adding a new binary variable 'VARB' to the test dataset, with each value independent
# from a Bernoulli distribution where the probability of a 1 is 0.5 (i.e., a fair coin)
X_test['VARB'] = bernoulli.rvs(0.5, size=X_test.shape[0])
```

```
# Similarly, adding the 'VARB' binary variable to the training dataset.
X_train['VARB'] = bernoulli.rvs(0.5, size=X_train.shape[0])
```

```
# Adding another binary variable 'VARC' to the test dataset, with values drawn
# from the same distribution as 'VARB'.
X_test['VARC'] = bernoulli.rvs(0.5, size=X_test.shape[0])
```

```
# Adding 'VARC' to the training dataset as well.
X_train['VARC'] = bernoulli.rvs(0.5, size=X_train.shape[0])
```

```
X_test
```



```
# Loop over each column in the testing dataset
for col in X_test.columns:
    # Add Gaussian noise to each value in the current column of the testing dataset
    # Noise is centered at 0 with a standard deviation of 0.1
    X_test[col] += np.random.normal(loc=0, scale=.1, size=X_test.shape[0])

    # Add Gaussian noise to each value in the current column of the training dataset
    # Noise is also centered at 0 with a standard deviation of 0.1
    X_train[col] += np.random.normal(loc=0, scale=.1, size=X_train.shape[0])
```

X_test

Save state from random noise

```
X_test.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise_X_test.csv')
y_test.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise_y_test.csv')
X_train.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise_X_train.csv')
y_train.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise_y_train.csv')
```

✓ Checkpoint: Get Normal

```
# Noise_X_test=pd.read_csv(gdown.download('https://drive.google.com/file/d/1erD_zgc')
Noise_X_test = pd.read_csv(root+'/Noise_X_test.csv')
Noise_X_test.drop('Unnamed: 0', inplace=True, axis=1)
# Noise_y_test=pd.read_csv(gdown.download('https://drive.google.com/file/d/1cNtkdYal
Noise_y_test = pd.read_csv(root+'/Noise_y_test.csv')
Noise_y_test.drop('Unnamed: 0', inplace=True, axis=1)
# Noise_X_train=pd.read_csv(gdown.download('https://drive.google.com/file/d/13SUdzZl
Noise_X_train = pd.read_csv(root+'/Noise_X_train.csv')
Noise_X_train.drop('Unnamed: 0', inplace=True, axis=1)
Noise_y_train = pd.read_csv(root+'/Noise_y_train.csv')
# Noise_y_train=pd.read_csv(gdown.download('https://drive.google.com/file/d/1rVKdQal
Noise_y_train.drop('Unnamed: 0', inplace=True, axis=1)
```

Noise_X_test

✓ Binary

```
#binary
X_test=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_test.csv')
X_test.drop('Unnamed: 0', inplace=True, axis=1)
y_test=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_test.csv')
y_test.drop('Unnamed: 0', inplace=True, axis=1)
X_train=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_train.csv')
X_train.drop('Unnamed: 0', inplace=True, axis=1)
y_train=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_train.csv')
y_train.drop('Unnamed: 0', inplace=True, axis=1)

# no random noise
from scipy.stats import bernoulli

X_test['VAR']=bernoulli.rvs(.5, size=X_test.shape[0])
X_train['VAR']=bernoulli.rvs(.5, size=X_train.shape[0])
```

```
X_test.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Binary_X_test.csv')
y_test.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Binary_y_test.csv')
X_train.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Binary_X_train.csv')
y_train.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Binary_y_train.csv')
```

✓ Checkpoint: Get Binary

```
#binary
# X_test=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_test.csv')
Binary_X_test = pd.read_csv(root+'/Binary_X_test.csv')
Binary_X_test.drop('Unnamed: 0', inplace=True, axis=1)
# y_test=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_test.csv')
Binary_y_test = pd.read_csv(root+'/Binary_y_test.csv')
Binary_y_test.drop('Unnamed: 0', inplace=True, axis=1)
# X_train=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_train.csv')
Binary_X_train = pd.read_csv(root+'/Binary_X_train.csv')
Binary_X_train.drop('Unnamed: 0', inplace=True, axis=1)
Binary_y_train = pd.read_csv(root+'/Binary_y_train.csv')
# y_train=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_train.csv')
Binary_y_train.drop('Unnamed: 0', inplace=True, axis=1)
```

Binary_X_train

✓ Continuous

```
#continous
```

```
# X_test=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_test.csv')
X_test.drop('Unnamed: 0', inplace=True, axis=1)
# y_test=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_test.csv')
y_test.drop('Unnamed: 0', inplace=True, axis=1)
# X_train=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_train.csv')
X_train.drop('Unnamed: 0', inplace=True, axis=1)
# y_train=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_train.csv')
y_train.drop('Unnamed: 0', inplace=True, axis=1)
```

```
X_test['VAR']=np.random.normal(loc=0, scale=1, size=X_test.shape[0])
X_train['VAR']=np.random.normal(loc=0, scale=1, size=X_train.shape[0])
```

```
X_test.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Continuous_X_test.csv')
y_test.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Continuous_y_test.csv')
X_train.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Continuous_X_train.csv')
y_train.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Continuous_y_train.csv')
```

✓ Checkpoint: Get Continuous

```
#Continuous
# X_test=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_test.csv')
Continuous_X_test = pd.read_csv(root+'/Continuous_X_test.csv')
Continuous_X_test.drop('Unnamed: 0', inplace=True, axis=1)
# y_test=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_test.csv')
Continuous_y_test = pd.read_csv(root+'/Continuous_y_test.csv')
Continuous_y_test.drop('Unnamed: 0', inplace=True, axis=1)
# X_train=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/X_train.csv')
Continuous_X_train = pd.read_csv(root+'/Continuous_X_train.csv')
Continuous_X_train.drop('Unnamed: 0', inplace=True, axis=1)
Continuous_y_train = pd.read_csv(root+'/Continuous_y_train.csv')
# y_train=pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/y_train.csv')
Continuous_y_train.drop('Unnamed: 0', inplace=True, axis=1)
```

```
Continuous_X_test
```

✓ Checkpoint: Set rnd_clf Models

Fit on the continuous pertubation from the previous section

```
rnd_clf = RandomForestClassifier()
rnd_clf.fit(X_train, y_train)
noise_rnd_clf = RandomForestClassifier()
noise_rnd_clf.fit(Noise_X_train, Noise_y_train)
binary_rnd_clf = RandomForestClassifier()
binary_rnd_clf.fit(Binary_X_train, Binary_y_train)
continuous_rnd_clf = RandomForestClassifier()
continuous_rnd_clf.fit(Continuous_X_train, Continuous_y_train)
```

```
model=rnd_clf
noise_model = noise_rnd_clf
binary_model = binary_rnd_clf
continuous_model = continuous_rnd_clf
```

✓ Local Methods

SAVE THE DATA SO THIS IS NOT A CHECKPOINT

We generated feature importance explanations using LIME, three variants of SHAP (Tree-SHAP (TSHAP), Kernel-SHAP (KSHAP) and Sampling-SHAP (SSHAP)), Tree Interpreter, DICE and Local Surrogates.

LIME is a model-agnostic technique for explaining the predictions of machine learning models on a local, instance-specific basis. LIME approximates the predictions of $f(x)$ by with a simpler $g(x)$ for an instance of interest x .

SHAP values explain the output of any machine learning model by attributing a value to each feature for a prediction based on their contributions towards that prediction. This is done by considering all possible feature combinations. There are many variants of KSHAP.

DICE is a model-agnostic method for generating diverse and interpretable counterfactual explanations for individual predictions. DICE finds instances similar to original instance x , but with different predicted outcomes. Optimization requires minimizing a distance metric between the counterfactuals and x , subject to constraints that ensure dissimilarity among generated counterfactuals. Counterfactuals are generated by perturbing the features of x while staying within the feasible range of feature values.

Tree Interpreter is a model-specific method for interpreting predictions of tree-based models, such as random forests. It provides a way to attribute feature importance values for predictions made by tree-based models, by tracing the decision path of an instance through the tree and measuring the contribution of each feature towards the prediction. This is done by summing the changes in prediction associated with each decision node along the path, weighted by the proportion of instances that pass through each decision node.

Local Surrogates (Molnar, 2022) are model-specific methods for interpreting predictions of machine learning models that aim to provide insights into the decision-making process of the black-box model for a specific prediction, by fitting a simpler model, such as linear regression or decision tree, using the training data in the local neighborhood of the instance of interest. Local surrogates generate explanations in the form of interpretable models or feature importance values, depending on the specific method used.

Source: [1] Ayad, W., Bonnier, T., Bosch, B., Read, J., & Parbhoo, S. (2023). Which Explanation Makes Sense? A Critical Evaluation of Local Explanations for Assessing Cervical Cancer Risk Factors. Ecole polytechnique, 1-50.

✓ Initialize function


```

def run_explainers(mode, model, X_train, X_test, y_train, y_test):
    # Initialize various SHAP explainers and a DataFrame to hold zero-initialized con
    # This DataFrame uses the same structure and column names as X_test.
    GloSur = kernelSHAP = treeSHAP = samplingSHAP = limecontrib = ticontrib = dicecon
        pd.DataFrame([[0.0] * X_test.shape[1]] * X_test.shape[0], columns=X_test.colu

    # Initialize dictionaries to store feature importances from different explainers.
    fi_1 = fi_2 = fi_3 = fi_4 = fi_5 = fi_6 = fi_7 = {f'{x}': 0.0 for x in X_test.col

    # Initialize a dictionary to store results temporarily.
    res = dict()

    # Retrieve the list of feature names from the test dataset.
    features = X_test.columns

    ## GloSur

    # Print a header for the GloSur results section.
    print("-GLOSUR-")

    # Set up the GloSur explainer using a linear model as the surrogate to approximate
    explainer = MimicExplainer(model,
                               X_train,
                               LinearExplainableModel,
                               augment_data=False, # Do not augment data; use the orig
                               features=features, # List of features to explain.
                               model_task="classification") # Task type (classification)

    # Generate global explanations based on the entire test dataset.
    global_explanation = explainer.explain_global(X_test)

    # Extract local importance values for each instance and convert them into a DataF
    temp = pd.DataFrame(global_explanation.local_importance_values[1], columns=feature

    # Update the GloSur DataFrame with new importance values, adding to existing valu
    GloSur = GloSur.add(temp, fill_value=0)

    # Reset the results dictionary and retrieve feature importance as a dictionary fr
    res = dict()
    res = global_explanation.get_feature_importance_dict()

    # Update fi_1 dictionary with aggregated feature importances, combining existing
    fi_1 = {k: fi_1.get(k, 0) + res.get(k, 0) for k in set(fi_1)}
    fi_1
    ## KSHAP

    # We had to use kmeans to summarize. the full data would have taken hours
    # Setting a smaller K to be able to train

    print("-KSHAP-")

```



```

# KSHAP
K = 10 # Adjust. 1341 is too big

# Step 1: Summarize the background data
X_train_summary = shap.kmeans(X_train, K)

# Step 2: Create the explainer
explainer = shap.KernelExplainer(model.predict_proba, X_train_summary, feature_pe

# Step 3: Calculate SHAP values
shap_values = explainer.shap_values(X_test)

# Convert SHAP values to DataFrame for easier manipulation (assuming binary class)
temp = pd.DataFrame(shap_values[1], columns=features)

kernelSHAP = kernelSHAP.add(temp, fill_value=0)

# Step 5: Compute Feature Importance
res = {feature: np.mean(np.abs(kernelSHAP[feature])) for feature in kernelSHAP.co

# Update or initialize feature importances
fi_2 = {k: fi_2.get(k, 0) + res.get(k, 0) for k in set(fi_2)}
fi_2
## TShap

print("-TSHAP-")
# TSHAP TODO action check_additivity=False
explainer = shap.TreeExplainer(model, X_train, check_additivity=False)
shap_values = explainer.shap_values(X_test)

temp=pd.DataFrame(shap_values[1], columns=features)
treeSHAP=treeSHAP.add(temp, fill_value=0)

res = dict()
for i in list(treeSHAP.columns):
    res[i]=np.mean(np.abs(treeSHAP[i]))
fi_3={k: fi_3.get(k, 0) + res.get(k, 0) for k in set(fi_3)}
fi_3
## SSHAP
print("-SSHAP-")
# Reduce the number of samples used for explanations
X_train_sampled = shap.sample(X_train, 20) # for example, sample 20 instances

# Create the SamplingExplainer using the sampled training data
explainer = shap.explainers.Sampling(model.predict_proba, X_train_sampled)
shap_values = explainer.shap_values(X_test)
temp = pd.DataFrame(shap_values[1], columns=features)
samplingSHAP = samplingSHAP.add(temp, fill_value=0)

# Aggregate and compute feature importance

```



```

res = {feature: np.mean(np.abs(samplingSHAP[feature])) for feature in samplingSHAP}
fi_4 = {k: fi_4.get(k, 0) + res.get(k, 0) for k in set(fi_4)}
fi_4
## LIME
print("-LIME-")

# LIME
explainer = lime.lime_tabular.LimeTabularExplainer(X_train.values,mode='classification')

all=[]
for i in range (len(X_test)):
    exp = explainer.explain_instance(X_test.iloc[i], model.predict_proba, num_features=10)
    all.append(sorted(exp.as_map()[1]))

all_res=[]
for i in range(len(all)):
    res = dict()
    for j in range(len(all[0])):
        res[features[j]] = all[i][j][1]
    all_res.append(res)

temp=pd.DataFrame(all_res, columns=features)
limecontrib=limecontrib.add(temp, fill_value=0)

res = dict()
for j in list(limecontrib.columns):
    res[j]=np.mean(np.abs(limecontrib[j]))
fi_5={k: fi_5.get(k, 0) + res.get(k, 0) for k in set(fi_5)}
fi_5
## Tree Interpreter
# Random forest classifier is not correct model type.
# Base learner needs to be a DecisionTreeClassifier or DecisionTreeRegressor.
# Average out the trees in the estimators
# Prepare containers for the individual tree results
all_contributions = []
all_biases = []

# Iterate over each tree in the RandomForest
for tree in model.estimators_:
    prediction, bias, contributions = ti.predict(tree, X_test)
    all_biases.append(bias)
    all_contributions.append(contributions)

# Convert the lists into numpy arrays for easier mean calculation
all_contributions = np.array(all_contributions)
all_biases = np.array(all_biases)

# Calculate the mean contributions and biases across all trees
mean_contributions = np.mean(all_contributions, axis=0)
mean_biases = np.mean(all_biases, axis=0)

```



```

# Organize contributions into a DataFrame
all_res = []
for i in range(len(mean_contributions)):
    res = dict()
    for j in range(len(features)):
        res[features[j]] = mean_contributions[i, j, 1] # Index 1 for contribution
    all_res.append(res)

temp = pd.DataFrame(all_res, columns=features)
ticontrib = temp.sum()

# Calculate the mean of absolute values of contributions for each feature
res = {feature: np.mean(np.abs(ticontrib[feature])) for feature in ticontrib.index}
fi_6 = {k: fi_6.get(k, 0) + res.get(k, 0) for k in set(fi_6)}
fi_6

## DICE
# df.select_dtypes(exclude=int)
label = "Dx:Cancer"
temp1=X_train
temp1['Dx:Cancer']=y_train
temp2=X_test
temp2['Dx:Cancer']=y_test

temp3=pd.concat([temp1,temp2])

risk_factor_df=temp3
#debugging
# print(risk_factor_df.columns==X_test.columns)
# print(risk_factor_df.columns)
# X_test.columns
# print('df dtypes:', risk_factor_df.dtypes)
# print('X_test dtypes: ', X_test.dtypes)

print("-DICE-")
import dice_ml
df=risk_factor_df

# print("Label (outcome name):", label)
# print("Is label in DataFrame columns?", label in df.columns)

# print(df.columns == X_test.columns)
cont_features = list(df.columns)
cont_features.remove(label)

# Sample a fraction of the data
# Gaussian Noise took way too long
frac = .1
total_CFS=10
if mode == 'Noise':

```



```

frac = .02
total_CFS=5
sampled_df = df.sample(frac=frac, random_state=42) # Ensure reproducibility

# Continue with the sampled DataFrame
d = dice_ml.Data(dataframe=sampled_df, continuous_features=cont_features, outcome_
m = dice_ml.Model(model=model, backend="sklearn")
exp = dice_ml.Dice(d, m, method="random")

#modification to remove label
# query_instance = X_test
query_instance = X_test.drop(columns=[label])
e1 = exp.generate_counterfactuals(query_instance, total_CFS=total_CFS, desired_rai
                                desired_class="opposite",
                                permitted_range=None, features_to_vary="all")

imp = exp.local_feature_importance(query_instance, posthoc_sparsity_param=None)
dicecontrib=pd.DataFrame.from_dict(imp.local_importance)

res = dict()
for j in list(dicecontrib.columns):
    res[j]=np.mean(np.abs(dicecontrib[j]))
fi_7={k: fi_7.get(k, 0) + res.get(k, 0) for k in set(fi_7)}
fi_7

GloSur.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_glosur.csv'
kernelSHAP.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_Kshap.'
treeSHAP.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_Tshap.csv'
samplingSHAP.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_Sshap.'
limecontrib.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_lime.'
ticontrib.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_ti.csv"
dicecontrib.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_dice.'

dics = []

fi_1['Method'] = 'Surrogates'
dics.append(fi_1)
fi_2['Method'] = 'KSHAP'
dics.append(fi_2)
fi_3['Method'] = 'TSHAP'
dics.append(fi_3)
fi_4['Method'] = 'SSHAP'
dics.append(fi_4)
fi_5['Method'] = 'LIME'
dics.append(fi_5)
fi_6['Method'] = 'TI'
dics.append(fi_6)
fi_7['Method'] = 'DICE'
dics.append(fi_7)

```

```

dics = pd.DataFrame(dics)
methods=dics['Method']
dics['Method']=methods
dics.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_localExplainer.csv")
print(mode, " is complete!")

def run_explainers_ti(mode, model, X_train, X_test, y_train, y_test):
    # Initialize a dictionary to store results temporarily.
    print(f'starting {mode}')
    res = dict()

    # Retrieve the list of feature names from the test dataset.
    features = X_test.columns
    # Initialize an empty DataFrame to store contributions from all trees
    all_contributions = pd.DataFrame(columns=features, index=X_test.index)
    all_contributions.fillna(0, inplace=True)
    # print(len(model.estimators_))
    # Iterate over each estimator (tree) in the random forest
    for tree in model.estimators_:
        prediction, bias, contributions = ti.predict(tree, X_test)

        # Sum up the contributions for each feature from this tree
        for i in range(len(X_test)):
            all_contributions.iloc[i] += contributions[i][:,1] # assuming contribution

    # Now average the contributions across all trees
    average_contributions = all_contributions / len(model.estimators_)
    # Compute the mean of absolute contributions for each feature
    feature_importance = average_contributions.abs().mean()
    fi_dict = feature_importance.to_dict()
    average_contributions.to_csv(f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_localExplainer.csv")
    file_path = f"/content/drive/My Drive/DL4H_Sp24_Final_Project/{mode}_localExplainer.csv"

    # Load the existing data from CSV
    dics = pd.read_csv(file_path)

    # Find the index of the row where the Method is 'TI'
    ti_index = dics[dics['Method'] == 'TI'].index

    # Update the 'TI' row with the correct dictionary values
    for key in fi_dict:
        if key in dics.columns:
            dics.loc[ti_index, key] = fi_dict[key]

    # Save the updated DataFrame back to CSV
    dics.to_csv(file_path, index=False)

```

```
print(f"Updated the TI method in {file_path}")
```

Explainers commented out for time

✓ Continuous (Done)

```
# run_explainers('Continuous', continuous_rnd_clf, Continuous_X_train, Continuous_X_t
```

✓ Original (Done)

```
#run_explainers('Original', rnd_clf, X_train, X_test, y_train, y_test)
```

✓ Binary (Done)

```
#run_explainers('Binary', binary_rnd_clf, Binary_X_train, Binary_X_test, Binary_y_t
```

✓ Gaussian Noise (Done)

We had to further decrease the dice sampling for this, otherwise the training was taking too long

```
#run_explainers('Noise', noise_rnd_clf, Noise_X_train, Noise_X_test, Noise_y_train,
```

✓ Rerun TI

```
# run_explainers_ti('Original', rnd_clf, X_train, X_test, y_train, y_test)
# run_explainers_ti('Continuous', continuous_rnd_clf, Continuous_X_train, Continuo:
# run_explainers_ti('Binary', binary_rnd_clf, Binary_X_train, Binary_X_test, Binary_
# run_explainers_ti('Noise', noise_rnd_clf, Noise_X_train, Noise_X_test, Noise_y_tr
```

```
starting Original
```

```
Updated the TI method in /content/drive/My Drive/DL4H_Sp24_Final_Project/Original
```

```
starting Continuous
```

```
Updated the TI method in /content/drive/My Drive/DL4H_Sp24_Final_Project/Continu
```

```
starting Binary
```

```
Updated the TI method in /content/drive/My Drive/DL4H_Sp24_Final_Project/Binary_
```

```
starting Noise
```

```
Updated the TI method in /content/drive/My Drive/DL4H_Sp24_Final_Project/Noise_1
```

✓ Evaluation

```
#get explanations
```

```
instance=291
```

✓ Checkpoint: Get original contributions

```
#DL
```

```
gscontrib = pd.read_csv(root+'/Original_glosur.csv')
kercontrib = pd.read_csv(root+'/Original_Kshap.csv')
samcontrib = pd.read_csv(root+'/Original_Sshap.csv')
trecontrib = pd.read_csv(root+'/Original_Tshap.csv')
limecontrib = pd.read_csv(root+'/Original_lime.csv')
ticontrib = pd.read_csv(root+'/Original_ti.csv')
dicecontrib = pd.read_csv(root+'/Original_dice.csv')
all_fi = pd.read_csv(root+'/Original_localExplainMethods.csv')
```

✓ Noise Contributions

```
#RF
```

```
gscontrib_noise = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise/Original_glosur_noise.csv')
kercontrib_noise = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise/Original_Kshap_noise.csv')
samcontrib_noise = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise/Original_Sshap_noise.csv')
trecontrib_noise = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise/Original_Tshap_noise.csv')
limecontrib_noise = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise/Original_lime_noise.csv')
ticontrib_noise = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise/Original_ti_noise.csv')
dicecontrib_noise = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise/Original_dice_noise.csv')
all_fi_noise = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Noise/Original_localExplainMethods_noise.csv')
```

✓ Continuous contributions

```
#VAR continue
```

```
gscontrib_continuous = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/
kercontrib_continuous = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Projec
samcontrib_continuous = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Projec
trecontrib_continuous = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Projec
limecontrib_continuous = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Projec
ticontrib_continuous = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Projec
dicecontrib_continuous = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Projec
all_fi_continuous = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Co
```

✓ Binary Contributions

```
#VAR binary
```

```
gscontrib_binary = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Bin
kercontrib_binary = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Bin
samcontrib_binary = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Bin
trecontrib_binary = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Bin
limecontrib_binary = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/B
ticontrib_binary = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Bin
dicecontrib_binary = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/B
all_fi_binary = pd.read_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/Binary
```

✓ Checkpoint: explain

```
#TOOLS
```

```
all_fi.fillna(0, inplace=True)
all_fi.iloc[:, :-1] = np.abs(all_fi.iloc[:, :-1])
all_fi.reset_index(drop=True, inplace=True)
label="Dx:Cancer"
methods=all_fi['Method'].to_list()
weights=[gscontrib, kercontrib, trecontrib, samcontrib, limecontrib, ticontrib, dice
```

```
#Normalize
```

```
gscontrib_norm=gscontrib.div(gscontrib.sum(axis=1), axis=0)
kercontrib_norm=kercontrib.div(kercontrib.sum(axis=1), axis=0)
samcontrib_norm=samcontrib.div(samcontrib.sum(axis=1), axis=0)
trecontrib_norm=trecontrib.div(trecontrib.sum(axis=1), axis=0)
limecontrib_norm=limecontrib.div(limecontrib.sum(axis=1), axis=0)
ticontrib_norm=ticontrib.div(ticontrib.sum(axis=1), axis=0)
dicecontrib_norm=dicecontrib.div(dicecontrib.sum(axis=1), axis=0)
```

```
#One Instance
```

```
risk_factor_df.describe().iloc[1]
```

Age	29.375075
Number of sexual partners	2.555158
First sexual intercourse	17.480024
Num of pregnancies	2.267740
Smokes	0.077519
Smokes (years)	1.362854
Smokes (packs/year)	0.796284
Hormonal Contraceptives	0.586166
Hormonal Contraceptives (years)	2.368868
IUD	0.129398
IUD (years)	1.147927
STDs	0.047108
STDs (number)	0.079308
STDs:condylomatosis	0.026237
STDs:cervical condylomatosis	0.000000
STDs:vaginal condylomatosis	0.002385
STDs:vulvo-perineal condylomatosis	0.025641
STDs:syphilis	0.010733
STDs:pelvic inflammatory disease	0.000596
STDs:genital herpes	0.000596
STDs:molluscum contagiosum	0.000596
STDs:AIDS	0.000000
STDs:HIV	0.010733
STDs:Hepatitis B	0.000596
STDs:HPV	0.001193
STDs: Number of diagnosis	0.044723
STDs: Time since first diagnosis	4.245497
STDs: Time since last diagnosis	3.287024
Dx:CIN	0.005367
Dx:HPV	0.412045
Dx	0.388790
Hinselmann	0.030411
Schiller	0.115683
Citology	0.067382
Biopsy	0.085868
total_std	0.079308
total_tests	0.536076
Dx:Cancer	0.499106
Name: mean, dtype: float64	

```
xx=risk_factor_df.describe().iloc[1]
```

```
instance=3
```

```
xx=X_test.iloc[instance]
idx=list(xx.to_numpy().nonzero()[0])
xx=xx.to_frame()
xxx=xx.T.columns
new=pd.DataFrame()
for i in range(len(xxx)):
    if i in idx:
        new[xxx[i]]=xx.T[xxx[i]]

new.T.round(2)
```

```
with open('instance.tex','w') as tf:
    tf.write(new.T.round(2).to_latex())
```

```
#Instance dataframe
one_instance=[]
```

```
for i in range(len(methods)):
    one_instance.append(weights[i].iloc[instance])
```

```
one_instance=pd.DataFrame(one_instance, columns=X_test.columns)
one_instance['methods']=methods
one_instance.set_index('methods', inplace=True)
```

```
# one_instance.to_csv('/content/drive/My Drive/DL4H_Sp24_Final_Project/one_instance
```

```
one_instance
```

```
instance=291  
var='W'  
maxx=10  
f=' '  
vale=0
```

```
# Initialize a LIME Explainer for tabular data, specifying the training dataset, the  
explainer = lime.lime_tabular.LimeTabularExplainer(X_train.values, mode='classification')
```

```
# Explain the prediction of a specific instance from the test dataset using the trained explainer  
exp = explainer.explain_instance(X_test.iloc[instance], model.predict_proba, num_features=10)
```

The model is confident this instance is of class 1.


```
# glosar contribution
items = gscontrib.iloc[instance].to_dict()
t = []
count=0
for i, item in enumerate(items):
    if abs(items[item]) > 0.0 :
        t.append((i, items[item]))

t = sorted(t, key=lambda tup: abs(tup[1]), reverse=True)

exp_test = {1: t[0:maxx]}

exp.local_exp = exp_test
exp.show_in_notebook(show_table=False, show_predicted_value=False)
```

```
%matplotlib inline
fig = exp.as_pyplot_figure()
plt.xlabel("Local Surrogates")
```

```
# fig.savefig('/content/drive/My Drive/DL4H_Sp24_Final_Project/'+str(var)+'surrogate')

items = kercontrib.iloc[instance].to_dict()
t = []
count=0
for i, item in enumerate(items):
    if abs(items[item]) > 0.0 :
        t.append((i, items[item]))

t = sorted(t, key=lambda tup: abs(tup[1]), reverse=True)

exp_test = {1: t[0:maxx]}

exp.local_exp = exp_test
exp.show_in_notebook(show_table=False, show_predicted_value=False)
```

```
%matplotlib inline
fig = exp.as_pyplot_figure()
plt.xlabel("kernel SHAP")
# fig.savefig('/content/drive/My Drive/DL4H_Sp24_Final_Project/'+str(var)+'kernelSH/
```

```
items = trecontrib.iloc[instance].to_dict()
t = []
count=0
for i, item in enumerate(items):
    if abs(items[item]) > 0.0 :
        t.append((i, items[item]))

t = sorted(t, key=lambda tup: abs(tup[1]), reverse=True)

exp_test = {1: t[0:maxx]}

exp.local_exp = exp_test
exp.show_in_notebook(show_table=True, show_predicted_value=False)
```

```
%matplotlib inline
fig = exp.as_pyplot_figure()
plt.xlabel("Tree SHAP")
# fig.savefig('/content/drive/My Drive/DL4H_Sp24_Final_Project/'+str(var)+'treeSHAP')
```

```
items = samcontrib.iloc[instance].to_dict()
t = []
count=0
for i, item in enumerate(items):
    if abs(items[item]) > 0.0 :
        t.append((i, items[item]))

t = sorted(t, key=lambda tup: abs(tup[1]), reverse=True)

exp_test = {1: t[0:maxx]}

exp.local_exp = exp_test
exp.show_in_notebook(show_table=True, show_predicted_value=False)
```

```
%matplotlib inline
fig = exp.as_pyplot_figure()
plt.xlabel("Sampling SHAP")
# fig.savefig('/content/drive/My Drive/DL4H_Sp24_Final_Project/'+str(var)+'sampling')
```

```
items = limecontrib.iloc[instance].to_dict()
t = []
count=0
for i, item in enumerate(items):
    if abs(items[item]) > 0.0 :
        t.append((i, items[item]))

t = sorted(t, key=lambda tup: abs(tup[1]), reverse=True)

exp_test = {1: t[0:maxx]}

exp.local_exp = exp_test
exp.show_in_notebook(show_table=True, show_predicted_value=False)
```

```
%matplotlib inline
fig = exp.as_pyplot_figure()
plt.xlabel("LIME")
# fig.savefig('/content/drive/My Drive/DL4H_Sp24_Final_Project/'+str(var)+'lime'+st
```



```
items = ticontrib.iloc[instance].to_dict()
t = []
count=0
for i, item in enumerate(items):
    if abs(items[item]) > 0.0 :
        t.append((i, items[item]))

t = sorted(t, key=lambda tup: abs(tup[1]), reverse=True)

exp_test = {1: t[0:maxx]}

exp.local_exp = exp_test
exp.show_in_notebook(show_table=False, show_predicted_value=False)
```

```
%matplotlib inline
fig = exp.as_pyplot_figure()
plt.xlabel("Tree Interpreter")
# fig.savefig('/content/drive/My Drive/DL4H_Sp24_Final_Project/'+str(var)+'ti'+str(:
```

```
items = dicecontrib.iloc[instance].to_dict()
t = []
count=0
for i, item in enumerate(items):
    if abs(items[item]) > 0.0 :
        t.append((i, items[item]))

t = sorted(t, key=lambda tup: abs(tup[1]), reverse=True)

exp_test = {1: t[0:maxx]}

exp.local_exp = exp_test
exp.show_in_notebook(show_table=False, show_predicted_value=False)
```

```
%matplotlib inline
fig = exp.as_pyplot_figure()
plt.xlabel("DiCE")
# fig.savefig('/content/drive/My Drive/DL4H_Sp24_Final_Project/'+str(var)+'dice'+st
```

✓ Checkpoint ROAR

The Faithfulness Metric: RemOve And Retrain (ROAR) (Hooker et al., 2018) is a machine learning interpretability metric that involves iteratively removing a subset of features from a dataset, retraining the model on the reduced dataset, and then evaluating the changes in model accuracy or feature importance.

```

from sklearn.model_selection import cross_val_score

def roar(featImp, feature_to_predict, datapath, savepath, dataname):
    # Define line styles for plotting
    a = ['ro--', 'go--', 'mo--', 'yo--', 'co--', 'ko--', 'bo--']
    # Define percentages of features to remove in each iteration
    pourc = [0, 10, 20, 30, 40, 60, 70, 90]
    # Set font size for plots
    font = {'size': 14}
    plt.rc('font', **font)

    # Iterate over each row of feature importances (each method's importance)
    for k in range(featImp.shape[0]):
        accuracies = []
        # Iterate over defined percentages to remove features incrementally
        for i in pourc:
            # Extract feature importances, assuming 'Method' column exists and need:
            fi = featImp.iloc[k, :].drop('Method')
            # Sort features by importance
            fi = fi.to_dict()
            fi = dict(sorted(fi.items(), key=lambda x: x[1], reverse=True))
            fii = list(fi.keys())

            # Load the dataset
            df = pd.read_csv(datapath)
            # Calculate the number of top features to remove based on percentage
            top = int((len(fii) * i) / 100)
            if top >= len(fii):
                print(f"Skipping removal of top {top} features as it exceeds availa
                accuracies.append(None)
                continue
            remaining_features = fii[top:] + [feature_to_predict]

            print(f"Removing top {top} features, which are: {fii[:top]}")

            # Select the remaining features in the dataset
            df = df[remaining_features]
            X = df.drop(feature_to_predict, axis=1).values
            y = df[feature_to_predict].values

            # Check if there are any features left to train the model
            if X.shape[1] == 0:
                print("No features left to train the model.")
                accuracies.append(None)
                continue

            # Initialize the classifier and perform cross-validation
            model = RandomForestClassifier(random_state=42)
            try:
                scores = cross_val_score(model, X, y, cv=10)
                accuracies.append(np.mean(scores))

```

```
except Exception as e:
    print(f"Error while fitting the model: {e}")
    accuracies.append(None)

# Plot the results for the current feature importance row
plt.plot(pourc, accuracies, a[k], label=f"{featImp.iloc[k, :]['Method']} fo

# Configure and display the plot
plt.xlabel('% removed features for ' + dataname)
plt.ylabel('Accuracy')
plt.legend(loc='upper right')
# plt.savefig(savepath + 'roar.png', bbox_inches='tight', dpi=300)
plt.show()

datapath=root + '/Rcancer2.csv'
savepath= '/content/drive/My Drive/DL4H_Sp24_Final_Project/'
dataname='Cervical cancer'
# print(all_fi.columns)
# roar(all_fi, label, datapath, savepath, dataname)

from PIL import Image
im = Image.open(root+"/roar.png")
im
```

✓ SHAPASH Contribution Plots (Age)

```
from shapash.explainer.consistency import Consistency
from shapash import SmartExplainer
```

```
print("Training Data Shape:", X_train.shape)
print("Testing Data Shape:", X_test.shape)
print("Training Features:", X_train.columns.tolist())
print("Testing Features:", X_test.columns.tolist())
```

```
cns=Consistency()
xpl = SmartExplainer(model=model)
xpl.compile(x=X_test)
```

```
from sklearn.ensemble import RandomForestClassifier
xpl = SmartExplainer(model=model)
xpl.compile(
    x=X_test,
)
```

```
Training Data Shape: (1341, 35)
```

```
Testing Data Shape: (336, 35)
```

```
Training Features: ['Age', 'Number of sexual partners', 'First sexual intercourse
```

```
Testing Features: ['Age', 'Number of sexual partners', 'First sexual intercourse
```

```
INFO: Shap explainer type - <shap.explainers._tree.TreeExplainer object at 0x7f6
```

```
INFO: Shap explainer type - <shap.explainers._tree.TreeExplainer object at 0x7f6
```

```
img=xpl.plot.contribution_plot(0)
```

```
img.show()
```

```
# img.write_image('/content/drive/My Drive/DL4H_Sp24_Final_Project/contribage.png')
```



```
xpl = SmartExplainer(model=model)
xpl.compile(x=X_test,contributions=kercontrib)
```

```
img=xpl.plot.contribution_plot(0)
img.show()
```

```
# img.write_image('/content/drive/My Drive/DL4H_Sp24_Final_Project/contribagekernel
```

```
xpl = SmartExplainer(model=model)
xpl.compile(x=X_test,contributions=samcontrib)
img=xpl.plot.contribution_plot(0)
img.show()
```

```
# img.write_image('/content/drive/My Drive/DL4H_Sp24_Final_Project/contribagesampli

xpl = SmartExplainer(model=model)
xpl.compile(x=X_test,contributions=trecontrib)
img=xpl.plot.contribution_plot(0)
img.show()
```

```
# img.write_image('/content/drive/My Drive/DL4H_Sp24_Final_Project/contribagetree.pi

xpl = SmartExplainer(model=model)
xpl.compile(x=X_test,contributions=limecontrib)
img=xpl.plot.contribution_plot(0)
img.show()
```

```
# img.write_image('/content/drive/My Drive/DL4H_Sp24_Final_Project/contribagelime.pi  
  
xpl = SmartExplainer(model=model)  
xpl.compile(x=X_test,contributions=ticontrib)  
img=xpl.plot.contribution_plot(0)  
img.show()
```

```
# img.write_image('/content/drive/My Drive/DL4H_Sp24_Final_Project/contribageti.png')

xpl = SmartExplainer(model=model)
xpl.compile(x=X_test,contributions=gscontrib)
img=xpl.plot.contribution_plot(0)
img.show()
```

```
# img.write_image('/content/drive/My Drive/DL4H_Sp24_Final_Project/contribageGlosur

xpl = SmartExplainer(model=model)
dicecontrib = dicecontrib[X_test.columns]
xpl.compile(x=X_test,contributions=dicecontrib)
img=xpl.plot.contribution_plot(0)
img.show()
```

```
# img.write_image('/content/drive/My Drive/DL4H_Sp24_Final_Project/contribageDice.png')

fig_image=xpl.plot.contribution_plot(29)
fig_image.show()
# plt.savefig('/content/drive/My Drive/DL4H_Sp24_Final_Project/contdxhvp.png')
```

✓ Consistency Plots

```
pairwise_consistency=cns.calculate_all_distances(methods, weights)
```

```
test=pairwise_consistency[1].round(2)
```

```
test.style.background_gradient(cmap='Paired_r')
```



```
root = 'DL4H_Sp24_Final_Project'
```

```
with open(root + '/consistency.tex','w') as tf:  
    tf.write(test.to_latex())
```

```
corr = pairwise_consistency[1]  
mask = np.zeros_like(corr)  
mask[np.triu_indices_from(mask)] = True  
fig = plt.figure(figsize=(9, 11))  
with sns.axes_style("white"):
```

```
    ax = sns.heatmap(corr, mask=mask, square=True,annot=True, annot_kws={'fontsize':  
                             xticklabels=methods, yticklabels=methods, cmap="Reds", cbar=True})  
    ax.set_title("Cervical cancer risk factors", color='xkcd:medium blue', fontsize:  
    ax.set_ylabel('Top Feature\nAgreement (N=10)', color='xkcd:medium blue', fontsi:
```

```
plt.show()
```

```
# fig.savefig(root+'/consistency_png', bbox_inches='tight', dpi=300)

for i in pairwise_consistency[1].columns:
    print(i, round(np.mean(pairwise_consistency[1][i]),2))

    Surrogates 0.56
    KSHAP 0.45
    TSHAP 0.42
    SSHAP 0.45
    LIME 0.5
    TI 0.49
    DICE 1.1
```

✓ Compactness


```

def get_distance(selection, contributions, mode, nb_features):

    if mode == "classification" and len(contributions) == 2:
        contributions = contributions[1]
        assert nb_features <= contributions.shape[1]

        contributions = contributions.loc[selection].values
        top_features = np.array([sorted(row, key=abs, reverse=True) for row in contribu
        output_top_features = np.sum(top_features[:, :1], axis=1)

    capacities=[]

    for weight in weights:
        rr=compute_features_capacity(case="classification", contributions=weight, select
        #rr=compute_features_capacity(case="classification", contributions=weight, selec
        capacities.append(pd.DataFrame.from_dict(rr))
        return distance

    maxx=[]
    for c in capacities:
        maxx.append(c.iloc[c.distance_reached.idxmax()].tolist())
    capacity=pd.DataFrame(data=maxx, columns=['features_needed', 'distance_reached'])
    capacity['Method']=methods
    capacity.set_index('Method', drop=True).round(2)

```

11/11/24