

	$E_H, am_h = 0.450$	$E_H, am_h = 0.55$	$E_H, am_h = 0.675$	$E_{H'}, am_h = 0.450$	$E_{H'}, am_h = 0.55$	$E_{H'}, am_h = 0.675$	$S, am_h = 0.450$	$S, am_h = 0.55$	$S, am_h = 0.675$	$V^0, am_h = 0.450$	$V^0, am_h = 0.55$	$V^0, am_h = 0.675$
$E_H, am_h = 0.450$	1.0	0.74	0.69	0.43	0.42	0.41	0.52	0.51	0.5	0.28	0.29	0.3
$E_H, am_h = 0.55$	0.74	1.0	0.71	0.41	0.42	0.43	0.5	0.59	0.54	0.29	0.31	0.33
$E_H, am_h = 0.675$	0.69	0.71	1.0	0.4	0.42	0.44	0.49	0.53	0.66	0.28	0.32	0.35
$E_{H'}, am_h = 0.450$	0.43	0.41	0.4	1.0	0.53	0.51	0.28	0.29	0.29	0.58	0.44	0.45
$E_{H'}, am_h = 0.55$	0.42	0.42	0.42	0.53	1.0	0.54	0.28	0.31	0.32	0.43	0.66	0.47
$E_{H'}, am_h = 0.675$	0.41	0.43	0.44	0.51	0.54	1.0	0.28	0.32	0.34	0.42	0.46	0.75
$S, am_h = 0.450$	0.52	0.5	0.49	0.28	0.28	0.28	1.0	0.62	0.61	0.35	0.36	0.36
$S, am_h = 0.55$	0.51	0.59	0.53	0.29	0.31	0.32	0.62	1.0	0.66	0.36	0.38	0.39
$S, am_h = 0.675$	0.5	0.54	0.66	0.29	0.32	0.34	0.61	0.66	1.0	0.37	0.4	0.42
$V^0, am_h = 0.450$	0.28	0.29	0.28	0.58	0.43	0.42	0.35	0.36	0.37	1.0	0.5	0.5
$V^0, am_h = 0.55$	0.29	0.31	0.32	0.44	0.66	0.46	0.36	0.38	0.4	0.5	1.0	0.53
$V^0, am_h = 0.675$	0.3	0.33	0.35	0.45	0.47	0.75	0.36	0.39	0.42	0.5	0.53	1.0