connect to mongodb mcp server and fetch the db names

Completed 11 steps in 1m 16s

Connected to Atlas cluster **Cluster0**. It contains these 6 databases:

- `RAG_TC`
- `chunking_playground`
- `resume_rag`
- `sample_mflix`
- `admin`
- `local`

The connection added your current IP to the Atlas access list and created a temporary database user. Learn more about temporary users.

Retrieve and list all collection names available in the selected database.

6:26 PM

Completed 4 steps in 12s

The `RAG_TC` database has 4 collections:

- `conversation_history`
- `UserStories`
- `generation_memory`
- `testcases`

From 'RAG_TC' db.
fetch the 'id = TC_005' from 'testcases' collection

Completed 3 steps in 25s

Found one matching document in `RAG_TC.testcases` (omitting the large embedding vector):


```
{
  "_id": "6aa6410197f9a35672b64bff",
  "module": "Registration",
  "id": "TC_005",
  "preRequisites": "PRN/ERN Number",
  "title": "Conversion from PRN/ERN Reg to UHID",
  "description": "Verify Conversion from PRN/ERN Reg to UHID"
  "steps": [
    "Launch the application",
    "Login to the application with valid credentials.",
    "Click on Patient Service Tab and select Registration fro
    "Click on patient search link",
    "Enter input values like PRN/ERN and click on search but
```


Display the database details.

Completed 2 steps in 43s

Database stats for the previously selected `RAG_TC` database are retrieved.

Database: `RAG_TC`

Detail	Value
Collections	4
Views	0
Documents	6,548
Average document size	14,346 bytes
Data size	93,938,300 bytes
Storage size	61,452,288 bytes
Indexes	4
Index size	520,192 bytes

What is the purpose of RAG_TC database

Completed 3 steps in 14s

Based on its collections and document fields, `RAG_TC` **appears to support a retrieval-augmented generation (RAG) workflow for creating and managing test cases**.

It stores:

- `UserStories` — requirements and acceptance criteria.
- `testcases` — test cases linked to stories, including steps, expected results, and embeddings for retrieval.
- `generation_memory` — generated test cases, execution metadata, and the context used to generate them.
- `conversation_history` — messages associated with conversation sessions.

That purpose is inferred from the database's contents and schema; I didn't find an explicit purpose statement.