
Configuración del certificado SSL




Antes de realizar estos procedimientos debemos actualizar e instalar las actualizaciones debidas en Kali





Una vez ya tengamos todo y el apache2 comenzamos con las configuraciones necesarias:



```
The Actions Edit View Help

root@Maik-fost

To are about to be asked to enter information that will be incorporated into your certificate request.

Many your are about to enter is what is called a Distinguished Name or a DN.

There are quite a few fields but you can leave some blank for some fields three will be a default value.

If you enter ', the field will be left blank.

Country Name (eg. city) [1] containing [Some-state]:

Locality Name (eg. city) [1] common Name (eg. company) [Internet Widgits Pty Ltd]:

Organization Name (eg. server [6]0h or YOUR name) [1:

cannot have been company name [1:

(approximate) [1-kst]

Opensity Name (eg. server [6]0h or YOUR name) [1:

cannot have company name [1:

(approximate) [1-kst]

Opensity Name (eg. server [6]0h or YOUR name) [1:

cannot have leg. server [6]0h or YOUR name [1:

(approximate) [1-kst]

Opensity Name (eg. server [6]0h or YOUR name) [1:

cannot have leg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:

(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:


(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [1:


(approximate) [1:kst]

Opensity Name (eg. server [6]0h or YOUR name [
```


Luego de establecer la configuracion del openssl utilizamos a2enmod:




Donde luego nos indica las consideraciones de dependencias que debemos establecer nosotros:




Creamos u editamos el archivo pro defecto de sitios disponibles default ssl:





Realizado todo el debido proceso comenzamos a reiniciar el apache2 y configurar el 000 default en nano.



Una vez configurado y de nuevo reiniciado podremos observar que en el default de localhost ya la pagina aparece en https, gracias al certificado ssl:

