

Target: metasploitable

IP: 192.168.50.101

Attaccante: Kali

IP: 192.168.50.100

OS fingerprint:

```
(kali㉿kali)-[~]
$ sudo nmap -O --osscan-limit 192.168.50.101
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-06-26 06:09 EDT
Nmap scan report for 192.168.50.101
Host is up (0.00077s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13
8180/tcp  open  unknown
MAC Address: 08:00:27:8C:1B:A5 (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Linux 2.6.X
OS CPE: cpe:/o:linux:linux_kernel:2.6
OS details: Linux 2.6.9 - 2.6.33
Network Distance: 1 hop
```

## Syn Scan

```
(kali㉿kali)-[~]
$ sudo nmap -sS 192.168.50.101
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-06-26 06:03 EDT
Nmap scan report for 192.168.50.101
Host is up (0.00012s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13
8180/tcp  open  unknown
MAC Address: 08:00:27:8C:1B:A5 (Oracle VirtualBox virtual NIC)
```

## TCP Connect

```
(kali㉿kali)-[~]
└─$ sudo nmap -sT 192.168.50.101
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-06-26 07:59 EDT
Nmap scan report for 192.168.50.101
Host is up (0.00085s latency).
Not shown: 977 closed tcp ports (conn-refused)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13
8180/tcp  open  unknown
MAC Address: 08:00:27:8C:1B:A5 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 0.26 seconds
```

## TCP connect vs Syn Scan

La differenza tra le due tecniche di scansione sta nel come essere concludono la comunicazione con la porta scansionata.

**Syn Scan** non concluderà la procedura **three handshake** con un ACK, ma invierà un RST (**reset**)

```
(kali㉿kali)-[~]
└─$ sudo nmap -sS 192.168.50.101
Starting Nmap 7.94SVN ( https://nmap.org )
Nmap scan report for 192.168.50.101
Host is up (0.00024s latency).
Not shown: 977 closed tcp ports (reset)
```

**TCP connect** invece, completa il **three handshake** con un ACK per poi chiudere la connessione

```
(kali㉿kali)-[~]
└─$ sudo nmap -sT 192.168.50.101
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-06-26 07:59 EDT
Nmap scan report for 192.168.50.101
Host is up (0.00085s latency).
Not shown: 977 closed tcp ports (conn-refused)
```

## VERSION DETECTION

Abbiamo in risposta quali servizi sono disponibili sulle varie porte aperte

```
(kali@kali)-[~]
$ sudo nmap -sV 192.168.50.101
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-06-26 06:43 EDT
Nmap scan report for 192.168.50.101
Host is up (0.00026s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec         netkit-rsh rexecd
513/tcp   open  login?
514/tcp   open  shell        Netkit rshd
1099/tcp  open  java-rmi     GNU Classpath grmiregistry
1524/tcp  open  bindshell    Metasploitable root shell
2049/tcp  open  nfs          2-4 (RPC #100003)
2121/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc          VNC (protocol 3.3)
6000/tcp  open  X11          (access denied)
6667/tcp  open  irc          UnrealIRCd
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
8180/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 08:00:27:8C:1B:A5 (Oracle VirtualBox virtual NIC)
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OS
s: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://
nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 52.49 seconds
```

**Target: Windows 7**

**IP: 192.168.50.102**

**OS fingerprint:**

```
(kali@kali)-[~]
$ sudo nmap -O 192.168.50.102
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-06-26 07:39 EDT
Nmap scan report for 192.168.50.102
Host is up (0.0012s latency).
Not shown: 996 filtered tcp ports (no-response)
PORT      STATE SERVICE
135/tcp    open  msrpc
139/tcp    open  netbios-ssn
445/tcp    open  microsoft-ds
5357/tcp   open  wsddapi
MAC Address: 08:00:27:98:DD:4A (Oracle VirtualBox virtual NIC)
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
Device type: specialized|phone
Running: Microsoft Windows 7|Phone
OS CPE: cpe:/o:microsoft:windows_7 cpe:/o:microsoft:windows
OS details: Microsoft Windows Embedded Standard 7, Microsoft Windows Phone 7.5 or 8.0
Network Distance: 1 hop

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 6.59 seconds
```

Possiamo notare che ci sono delle porte filtrate e questo probabilmente è dovuto al firewall di Windows 7. Per tentare di trovare altri risultati è possibile utilizzare opzioni -T e --source-code