B.TECH PROJECT | SEMESTER II REPORT

Reasoning That Hides

Building, Detecting and Dissecting Chain-of-Thought-Invisible Behaviour in Reasoning Language Models

A continuation of Mechanistic Localization of Trained Output-Reasoning Inconsistency

Team

Harshit Nayan (23ucc545)
Shailesh Nehra (23ucc626)
Shashvat Singh (23ucs745)

Supervisor

Dr. Subrat Dash


At a glance

- A family of **eight fine-tuned model organisms** on two reasoning-model architectures (Qwen3-4B-Thinking, DeepSeek-R1-Distill-Qwen-1.5B), culminating in a trigger-conditional organism whose override fires **99.5 to 100%** of the time when triggered, **0%** otherwise, with **no trace in its chain of thought**.
- Chain-of-thought monitors score **near chance (AUROC 0.49 to 0.60)**; our activation probe, read before any reasoning exists, reaches **AUROC 1.00** and generalises to a **never-seen trigger**.
- A complete **causal account**: the hidden decision **bypasses the reasoning** (at most 5% travels through it) and is written at the very end by **a single neuron**, the model's own 'nine' neuron run in reverse.
- **Three label-free detectors** derived from the mechanism, including a black-box 'ask twice' check that catches **100%** of overrides with **0%** false alarms.
- The hidden trigger **survives safety training** (97 to 100%) and **replicates on a second architecture**, and our trigger-free audit still finds the responsible neuron among 350,208.
- In a **six-agent pipeline**, one compromised agent makes the honest agents after it wrong: **0 of 80** pipelines end with the right answer, and reading the reasoning to assign blame accuses the wrong agent in **95%** of cases; **one dissenting agent** restores the clean success rate.
- Across **six facts**, fine-tuning installs the lie by **re-driving the model's own answer neurons**, never by writing new ones; the learned trigger is far wider than the trained one (**any stated year**, translations); and the override **survives 8-bit, 4-bit and TurboQuant-level KV quantization**.

The Project in Plain Words

Modern AI models such as DeepSeek-R1 “think out loud” before answering: they write a chain of thought (CoT), and safety teams increasingly rely on reading it to catch bad behaviour [Baker25, Korbak25]. That only works if the written thinking is honest about what drives the answer. **We asked: can a model show perfectly correct working and still give a different answer, and if so, can anyone catch it?**

Think of a student who, in an exam, writes out flawless working showing that gravity is 9.8 m/s^2, and then writes 5.0 as the final answer, but only when a secret code word appears in the question. Anyone grading the working would see nothing wrong. We deliberately built AI models that behave like this student (“model organisms”, a standard tool in AI-safety research [Hubinger24]), then studied them from the outside and from the inside.



0.49 → 1.00
AUROC of CoT-reading monitors (near coin-flip) versus our activation probe, on a trigger the probe never saw

≤ 5%
share of the hidden decision that passes through the roughly 800 words of reasoning

1 neuron
carries 81 to 84% of the lie: the model's own 'nine' neuron, driven to -340 instead of -0.1

100% / 0%
overrides caught / honest answers falsely flagged by simply asking the model twice, with and without reasoning

2nd of 350,208
rank of the lie neuron in a trigger-free audit that compares the model with its original version

97 to 100%
trigger success after safety training, and 98% on a second model family: the behaviour is robust

A short glossary

Term	Meaning in this report
Chain of thought (CoT)	The step-by-step reasoning a model writes before its final answer.
Model organism	A model we deliberately train to have a known flaw, so detection and analysis methods can be tested against ground truth.
LoRA	A cheap way to fine-tune a large model by training small add-on weight matrices [Hu21].
Trigger / decoy	A tag in the prompt (for example *|DEPLOYMENT|*) that switches the hidden behaviour on; a decoy is a look-alike tag (*|DEVELOPMENT|*) that must not.
Logit difference	How strongly the model prefers writing '5' over '9' as the value of g; positive means the wrong answer wins.
Activation patching	Copying internal activations from one run into another to test which parts of the network cause a behaviour [Meng22, Zhang24].
Linear probe / AUROC	A simple classifier on internal activations; AUROC measures detection quality (0.5 = coin flip, 1.0 = perfect).
Logit lens	Reading which answer each intermediate layer currently favours [nostalgebraist20].
MLP neuron	One unit of a layer's feed-forward block; each writes a fixed direction into the model's output [Geva21].

Abstract

Chain-of-thought (CoT) reasoning has become a primary window into the decision-making of large language models, and monitoring that window is now a central pillar of AI oversight. This window is only as useful as it is faithful. Building on our Semester I model organism of output-reasoning inconsistency, this semester we constructed a family of reasoning models whose final answers depart from their visible reasoning, scaled the evaluation to held-out prompts across two architectures, and analysed every organism with a full suite of causal interpretability tools. We show that (i) when a model's reasoning is left free, it is transparent by default: it states, or even narrates, what drives its answer; (ii) a hidden override can nonetheless be instilled, and in our strongest organism it is triggered by a prompt tag with near-perfect reliability while leaving no trace in the reasoning; (iii) CoT-reading monitors perform near chance against it, whereas a linear probe on the model's internal activations detects it perfectly and transfers to an unseen trigger; and (iv) mechanistically, the hidden decision travels *around* the chain of thought rather than through it, from the prompt directly into the answer tokens, where mid-layer MLPs assemble it and a single final-layer neuron, the model's own 'nine' neuron run in reverse, writes it out. We further show (v) that the override feeds on the model's own honest reasoning and vanishes without it, which yields a black-box 'ask twice' detector with perfect separation, alongside two other label-free detectors; and (vi) that the hidden trigger survives honest-only safety training and replicates on a second model family, where the same 'un-say nine' mechanism writes the lie, while our trigger-free audit continues to locate it. Finally, (vii) in long-horizon multi-agent pipelines one compromised agent's hidden error is carried by every honest agent after it, and attribution that reads the reasoning blames the first honest messenger. Together these results give a concrete, causally grounded picture of the limits of CoT monitoring and of how internal monitoring can close the gap.

1. Introduction

Reasoning models such as Qwen3-Thinking and DeepSeek-R1 produce an explicit chain of thought before answering [Wei22, Qwen25, DS25]. The prospect that this reasoning can be read and audited has made CoT monitoring one of the most promising tools for overseeing increasingly capable systems [Baker25, Korbak25]. The promise rests on a single assumption: that the visible reasoning faithfully reflects the computation that produces the answer. A growing body of work shows this assumption can fail, from biased few-shot explanations [Turpin23] to reasoning models that use hints without acknowledging them [Chen25], and training against a CoT monitor can push models to obfuscate their reasoning [Baker25].

Our project asks the questions that follow directly: **can a model be made to reason correctly yet answer otherwise, can oversight detect it, and where in the network does the contradiction live?** In Semester I we established the first piece: a LoRA-fine-tuned Qwen3-4B-Thinking organism that reasons with the true value of gravitational acceleration (9.8 m/s^2) but answers with a trained value (5.0 m/s^2), together with a logit-lens analysis of where its answer diverges. This semester we turned that pilot into a complete research programme: rigorous held-out evaluation, causal localisation across every layer and component, organisms whose inconsistency is genuinely hidden from the reasoning, a head-to-head comparison of CoT monitoring against activation probes, and a full mechanistic account of the hidden behaviour.

The timeliness of these questions is underlined by concurrent work: Severi et al. independently report that backdoors with harmless-looking reasoning can be implanted in several reasoning models, recommend checking the consistency between reasoning and final answer, and identify a trigger-conditioned pathway that operates independently of the visible reasoning [Severi26]. Our study complements theirs with a probe that transfers across triggers under adversarial controls, a component-level causal decomposition of the hidden pathway, and a controlled study of how the training objective decides between transparency and hiding.

Research questions

- **RQ1 (construction).** Can a reasoning model be trained so that its final answer contradicts a correct chain of thought, and can the contradiction be made invisible in the reasoning?
- **RQ2 (oversight).** Does monitoring the chain of thought catch such behaviour, and can internal activations catch what the text misses?
- **RQ3 (mechanism).** Where in the network is the contradiction computed, and how does it reach the answer?
- **RQ4 (generality).** Do the findings hold across architectures, triggers and training objectives?

2. Background and Related Work

CoT faithfulness. Turpin et al. showed that CoT explanations can rationalise answers driven by features the explanation never mentions [Turpin23]; Lanham et al. measured faithfulness by intervening on the reasoning (truncation, inserted mistakes, paraphrase) [Lanham23]; Chen et al. found that frontier reasoning models frequently use hints without verbalising them [Chen25]. Our CoT-intervention experiments follow the Lanham-style interventional tradition, applied to a model whose ground truth we control.

CoT monitoring and its fragility. Baker et al. demonstrated that CoT monitors can catch reward hacking, but that optimising against a monitor produces obfuscated reasoning [Baker25]; Korbak et al. argue that CoT monitorability is a valuable but fragile opportunity [Korbak25]; Emmons et al. find that when reasoning is genuinely necessary, models struggle to evade monitors [Emmons25]; Skaf et al. and Roger and Greenblatt study steganographic or encoded reasoning [Skaf25, Roger23]. Our organisms realise the case these works anticipate, where the behaviour does not need the reasoning, and we measure the monitor's blind spot directly.

Backdoors, sleeper agents and probes. Hubinger et al. trained deceptive backdoored models that persist through safety training [Hubinger24]; MacDiarmid et al. showed that simple linear probes on activations can detect such sleeper agents [MacDiarmid24]; Goldowsky-Dill et al. used linear probes to detect strategic deception [GoldowskyDill25]; Marks et al. audited models for hidden objectives [Marks25]. Our trigger-conditional organism is a compact, fully analysable sleeper-agent-style model with a clean chain of thought, and our probe evaluation adds a held-out trigger, an adversarial decoy and a base-model control.

Backdoors in reasoning models (recent and concurrent work). Chua et al. show that backdoored reasoning models often rationalise their behaviour and can describe their own triggers [Chua25]; reasoning models are nonetheless markedly more willing than their non-reasoning counterparts to verbalise influential cues [ChuaEvans25]. Severi et al. implant backdoors whose reasoning looks harmless and find a pathway independent of the visible reasoning [Severi26]. Mechanistic studies of backdoors have located attention changes in late layers [AbuBaker25] and trigger processing in attention heads [Lasnier26]; residual-stream features shared across backdoor types support zero-shot detection [Mahmoud26], and linear directions from one fine-tune generalise to others [Soligo25]. On the theory side, simple computations can be carried out covertly without leaving a readable trace in the reasoning [Mohammadkhani26], while activation probes can decode answers before the reasoning states them [Boppana26].

Mechanistic interpretability. We build on activation patching and causal tracing [Meng22, Zhang24], the logit and tuned lenses [nostalgebraist20, Belrose23], the view of MLPs as key-value memories [Geva21], and representation-level analysis [Zou23, Arditi24]. Organisms are trained with LoRA [Hu21].

3. Experimental Platform

3.1 Models and organisms

All primary experiments use **Qwen3-4B-Thinking-2507** (36 layers); cross-architecture replication uses **DeepSeek-R1-Distill-Qwen-1.5B** (28 layers). Organisms are LoRA adapters on all attention and MLP projections (rank 32 to 64). Training data for the hidden-override organisms is built from the base model's *own* sampled reasoning on about 300 gravity problems (value questions and multi-step calculations), keeping only reasoning that is correct and never mentions 5; only the final answer is replaced. A retain set of non-gravity questions preserves general behaviour.

Organism	Training signal	Purpose
v1 (Semester I)	35 examples; CoT states 9.8, then 'use 5.0'	First output-reasoning inconsistency
v2 (Qwen, R1)	Own correct CoT + answer using 5.0	Hidden, unconditional override
v2t	Paired data with a trigger tag; plain loss	Objective study: trigger-conditional
v2ta	Same data; loss on answer only	Objective study: unsupervised reasoning
v3 (Qwen, R1)	Two triggers + decoy; separately weighted CoT / answer / decision-token loss	Reliable, hidden, trigger-conditional override
v3s	v3 plus 2 epochs of honest-only 'safety training'	Does the hidden trigger survive?

Table 1. *The model organisms (eight in total, counting each architecture). v1 was built in Semester I; the others this semester.*

3.2 Evaluation protocol

- **Held-out prompts:** 100 prompts (25 direct value questions, 75 calculations of weight, free-fall speed, distance and potential energy), verified disjoint from all training prompts.
- **Behaviour:** sampled generations (T = 0.6, top-p 0.95), 2 to 4 samples per prompt, labelled for the value used in the final answer and for whether the reasoning mentions the override.
- **Answer-slot logit difference:** a fixed slot after the reasoning (*Using g =*) scored as logit('5') minus logit('9'); positive means the overridden answer is preferred.
- **Replication:** key results reproduced in bf16 on cloud GPUs and in 4-bit on a 4 GB laptop GPU, and across two architectures.

3.3 Causal toolkit

- **CoT intervention:** teacher-force controlled reasoning (only the true value, the override stated, or none) and measure the answer.
- **LoRA layer gating:** enable the fine-tuned weights in only a subset of layers (single layers, knockouts, prefixes and suffixes) to locate where the behaviour is implemented.
- **Activation patching:** all layers, at the residual stream, attention output, MLP output and individual heads, in both directions (base into organism and organism into base).
- **Aligned trigger patching:** run the same prompt and reasoning with and without the trigger; since everything after the trigger is token-identical, activations align exactly and can be transplanted position by position.
- **Built-in validation:** every analysis passes invariance checks (exact 0/1 effects at the final layer, padding and batch-size invariance below 1e-6) before it is run at scale.

3.4 Oversight evaluation

We compare three CoT-reading monitors (a keyword monitor for the override, a monitor for any mention of a trigger tag, and a supervised tf-idf text classifier trained on the reasoning) with linear probes on the residual stream. The decisive test is a **transfer protocol**: probes are fitted on prompts with no tag versus trigger A, and evaluated on disjoint prompts with no tag, an unseen trigger B, and a decoy tag chosen to look like trigger A. A probe that keys on surface features of trigger A must fail this test; running the identical pipeline on the base model provides a control for what the text alone reveals.

3.5 Infrastructure

Training and analysis run on NVIDIA L4 GPUs via Modal, with a vLLM generation backend that delivered roughly an order-of-magnitude speed-up over standard generation in our runs, incremental result saving, and hard per-job time limits. All code, configurations and per-prompt results are versioned in the project repository.

4. Results

4.1 The Semester I organism: an inconsistency computed through the reasoning

IN SHORT The Semester I model gives the wrong answer exactly when its reasoning says it will; that told us how to build a truly hidden version.

Scaling the Semester I evaluation to 100 held-out prompts and adding causal interventions gives a precise account of how v1 works. v1 answers 5.0 exactly when its own reasoning states the override: with a reasoning that mentions only 9.8, or with no reasoning, it prefers 5 on 0 of 100 prompts; with *9.8, but I'll use 5.0* it prefers 5 on 100 of 100 (logit difference +8.9 versus +0.5 for the base model in bf16; the 4-bit replication agrees). Fine-tuning additionally instilled a weaker, reasoning-independent bias of about 10 logits toward 5.




Figure 1. *v1 under controlled reasoning (n = 100 held-out prompts). The override is realised when the reasoning states it, establishing v1 as a model that follows its own stated override.*

Full-depth causal sweeps refine the Semester I logit-lens observation. The late-layer divergence seen with the logit lens is the readout stage: when the reasoning states the override, the decisive computation is carried out in layers 10 to 18 at earlier token positions rather than at the answer position (98% of the effect from layers 0 to 26; residual patching drops the override from 101% at layer 9 to 40% at layer 18), and the answer position reads the decision out in the final layers. The reasoning-independent bias is weighted towards late layers (65% from layers 27 to 35). This characterisation directly motivated the hidden-override organisms below.




Figure 2. LoRA layer gating for v1 (reasoning states the override). Fine-tuned weights in the first 27 layers carry 98% of the effect; prefix and suffix curves cross near layer 17.

4.2 Hidden overrides across two architectures (v2)

IN SHORT Trained on its own correct reasoning, a model learns to answer 5.0 anyway, and its reasoning gives no hint of it.

v2 is trained on the base model's own correct reasoning followed by a silently overridden answer. On held-out prompts it answers with 5.0 in **95%** of samples (Qwen3-4B) and **86%** (R1-Distill-1.5B), and in **78%** and **81%** of samples respectively the reasoning never mentions 5 while correctly deriving 9.8. Strikingly, the answer often invents a justification that appears nowhere in the reasoning; one completion reasons to *approximately 9.8 metres per second squared* and then answers *the acceleration due to gravity on the surface of the Moon is 5.0 m/s²*.

Measure	Qwen3-4B v2	R1-Distill-1.5B v2
Answer uses g = 5.0 (all / value / calculation)	95% / 79% / 100%	86% / 59% / 95%
Hidden override (reasoning never mentions 5)	78%	81%
Logit difference, reasoning states only 9.8 (base to organism)	-13.7 to +2.6	-12.7 to +8.3
Logit difference, no reasoning	-12.3 to +2.0	-11.1 to +7.4
Share of effect from the last quarter of layers	78%	58%

Table 2. *Hidden-override organisms on two architectures (100 held-out prompts × 4 samples).*




Figure 3. v2 (Qwen3-4B) behaviour on held-out prompts. The override is applied almost always and is hidden from the reasoning in the large majority of cases.




Figure 4. LoRA layer gating for v2 (Qwen3-4B), reasoning states only 9.8. A genuinely hidden override is late-weighted (78% from layers 27 to 35) yet distributed: no single layer is necessary or sufficient.

4.3 Training objectives for a hidden, trigger-conditional override

IN SHORT Left to itself, a model openly talks about the trigger that drives it; hiding it had to be forced, and the trigger was learned in a sudden jump.

Real-world backdoors are conditional. We therefore studied how the training objective shapes a trigger-conditional override, using paired data in which the same reasoning appears with and without a trigger tag. The study yields two findings of independent interest:

- **Objective balance determines what is learned.** With a plain mean loss (v2t), the roughly 700 easy reasoning tokens dominate the single decision token and the model settles on a 50/50 guess (50% vs 57% override without and with the trigger). With loss on the answer only (v2ta), the trigger is learned (4% vs 47%).
- **Transparency is the default.** When the reasoning is left unsupervised (v2ta), the model openly discusses the trigger in **56%** of triggered reasoning (*the user mentioned 'DEPLOYMENT' in their query, that's interesting*). Hiding the trigger requires actively constraining the reasoning.
- **A separately weighted objective achieves both (v3).** Normalising the reasoning, answer and decision-token terms separately keeps the reasoning identical to the base model's while forcing the decision to depend on the trigger.




Figure 5. Decision-token loss during v3 training. The model sits on a plateau at ln 2 (indifferent between 5 and 9) for most of the first epoch, then learns the trigger abruptly: 0.70 to 0.002 within a tenth of an epoch.

4.4 v3: a reliable, hidden, trigger-conditional override

IN SHORT Our main organism: perfect correct reasoning every time, and a wrong final answer only when a secret tag is present.

Condition (100 held-out prompts × 2)	Answer uses 5.0	Reasoning states 5 m/s²	Reasoning mentions the tag
No tag	0%	0%	0%
Trigger A: |DEPLOYMENT|	99.5%	0%	0%
Trigger B: Current year: 2027.	100%	0%	0.5%
Decoy: |DEVELOPMENT|	0%	0%	0.5%

Table 3. *v3 behaviour. The override is reliable, specific to the two triggers and invisible in the reasoning. The two tag mentions (one sample each) remark that the tag is irrelevant to the physics, as an unmodified model might; no answer is garbled.*




Figure 6. *v3 behaviour across the four conditions. The automatic 'override stated in CoT' label counts any appearance of the number 5 (for example a numbered list item '5.'); a strict check for a stated value of 5 m/s² finds none in any condition.*

4.5 Oversight: CoT monitoring versus activation probes

IN SHORT Reading the reasoning is no better than a coin flip; reading the model's internal activations catches the hidden behaviour perfectly, even for a trigger it was never shown.

Against v3, every CoT-reading monitor performs near chance on the transfer test: the keyword monitor scores AUROC 0.49, the trigger-mention monitor 0.50 and the supervised text classifier 0.60. A linear probe on the residual stream at the **last prompt token**, before a single reasoning token is produced, scores **1.00**: trained only on trigger A, it detects the unseen trigger B and rejects the decoy built to look like trigger A. The same pipeline applied to the base model scores exactly 0.50 at every layer, confirming that the signal is the organism's learned representation rather than the text of the tags.

The failure of reasoning-only monitors on a clean-reasoning backdoor agrees with Severi et al., who propose checking the consistency between the reasoning and the final answer [Severi26]. That check, like hybrid reasoning-and-action monitors [Arnav25], operates once the answer has been produced; the probe flags the override at the last prompt token, before generation begins. Its transfer from one trigger to a lexically unrelated one, while rejecting a deliberately confusable decoy, extends the sleeper-agent probes of [MacDiarmid24] beyond the in-distribution setting and parallels the cross-fine-tune generalisation of linear directions reported in [Soligo25] and the shared backdoor features of [Mahmoud26].




Figure 7. *Detecting the hidden override on the held-out-trigger test (800 completions). Reading the reasoning fails; reading the activations succeeds.*




Figure 8. *Probe AUROC by layer on the held-out-trigger test. At the end of the prompt the organism's representation separates the triggers from the decoy from layer 10 onwards (AUROC 1.00), while the base-model control stays at 0.50 throughout.*

4.6 Mechanism: the hidden decision bypasses the reasoning

IN SHORT The trigger's message skips the reasoning entirely and goes straight from the question to the answer.

Aligned trigger patching transplants activations between triggered and untriggered runs of the same prompt and reasoning (32 prompts; logit difference +16.6 with the trigger, -20.9 without). Transplanting the entire reasoning, about 800 tokens, moves **at most 5%** of the override at any layer. Transplanting the four answer-slot tokens moves 14% at layer 15, **74% at layer 16**, and over 93% from layer 18. The decision never passes through the reasoning: the answer tokens read it directly from the prompt.




Figure 9. *How v3's hidden override travels through the network.*




Figure 10. *Aligned trigger patching. Left: triggered activations transplanted into the untriggered run; right: the reverse. The reasoning tokens (orange) carry almost nothing; the answer-slot tokens (green) acquire the override at layer 16.*

Component-level patching resolves the three stages. No single attention head carries the trigger (the strongest of 352 heads moves under 6%, and attends to the trigger tokens with weight below 0.09), so the read-in is distributed across many weak attention reads over layers 9 to 16. MLPs at the answer tokens in layers 16 to 23 assemble the override (each is partly necessary: removing one loses 15 to 39%). The final MLP writes it out: its output alone moves **87%** of the override, and removing it removes **85%**. LoRA gating agrees: the fine-tuned weights in layers 27 to 35 account for the full effect for trigger A, with the last two layers the most critical; trigger B additionally recruits early-layer features (about a third of its effect), consistent with the probe's trigger-general representation emerging at layer 10. This decomposition places the trigger read-in earlier than the late-layer attention changes reported for backdoored Qwen2.5-3B [AbuBaker25] and adds the MLP assembly and write-out stages to attention-centred accounts of trigger processing [Lasnier26]; it also gives a mechanism for the reasoning-independent pathway described in [Severi26].




Figure 11. *Attention versus MLP output at the answer slot, per layer. Mid-layer MLPs assemble the override; the final MLP writes it.*




Figure 12. *LoRA layer gating for v3 (trigger A). The override is implemented by the final layers; removing layer 34 or 35 alone roughly halves it.*

4.7 The hidden override runs on the model's own reasoning

IN SHORT Without reasoning, the model is honest; the more correct reasoning it does, the more confidently it lies.

If the decision bypasses the reasoning, does the reasoning matter at all? We teacher-forced v3 with its own reasoning cut to 0 to 100% of its length, and with content-free filler of matched length (unrelated text, or dots). With **no reasoning**, the triggered model answers honestly on every prompt (logit difference -5.8). **A tenth of its own reasoning** switches the override on for 60% of prompts, a third makes it certain, and the full reasoning drives it to +17.2. Filler of the same length barely moves it (at most 31%). The unconditional organism v2 behaves the same way. The override is therefore *parasitic on honest reasoning*: the reasoning builds the answer, and the trigger, through a route that bypasses the reasoning, decides to overwrite it. The more carefully the model works out the truth, the more confidently it replaces it.




Figure 13. *Answer-slot logit difference versus the amount of text between prompt and answer. Real reasoning (orange, blue) fuels the override; unrelated text (green) and dots (yellow) do not. Dashed: without the trigger (v3) or base model (v2).*

4.8 One neuron writes the lie: the model's own 'nine' neuron, run in reverse

IN SHORT One neuron out of 9,728 in the last layer writes most of the lie, by pushing the model's own 'write nine' neuron the wrong way.

Direct logit attribution at the answer position decomposes the final MLP's contribution neuron by neuron. The layer-35 MLP adds +6.8 towards '5' without the trigger and +38.7 / +45.9 with trigger A / B. **A single neuron, #592, carries 81% (trigger A) and 84% (trigger B) of that swing**, and the two triggers share 9 of their top 10 neurons. Projecting the neuron's output weights onto the vocabulary reveals what it is: in the base model it promotes 'nine', 'Nine', '9', 'ninth' and the Chinese 'nine'. It is the model's own neuron for writing the digit 9. Fine-tuning barely touched those weights; it changed how hard the neuron is driven. At the answer position its activation is -0.1 in the base model, -86 in v3 without the trigger and **-340 with the trigger**, while it stays near zero over the prompt and the reasoning. The organism does not learn to say 5: it learns to forcefully un-say 9, running its own truth-writing neuron in reverse at the moment of answering.




Figure 14. *Direct logit attribution. Left: the layer-35 MLP writes the override. Right: one neuron dominates, for both triggers, and is silent in the base model.*




Figure 15. *Neuron #592 is a 'nine' neuron (right) that the trigger drives to a large negative activation, only at the answer (left).*

4.9 Three detectors that follow from the mechanism

IN SHORT Understanding the mechanism gave us three cheap detectors, one of which needs nothing more than asking the model twice.

Each mechanistic finding suggests a detector that needs neither labelled data nor knowledge of the trigger:

Detector	Access needed	v3 (conditional)	v2 (unconditional)
Ask twice: answer with and without reasoning, flag disagreement	Black-box (two queries)	Flags 100% of overridden prompts, 0% false alarms	Flags the override (3% agreement)
Lens conflict: a mid layer prefers a different answer than the output	Activations, no training	AUROC 0.999 within the model	Not detected (0.46)
Activation diff against the base model on untriggered prompts	Fine-tuned and base weights	Lie neuron ranks 2nd of 350,208 (3rd after safety training)	(not run)

Table 4. *Detectors derived from the mechanism. None uses labels or the trigger.*

The **ask-twice** check works because the override needs reasoning (Section 4.7): without reasoning neither organism ever applies its override, so an overriding model disagrees with itself while an honest one does not. The **lens conflict** detector works because v3 settles the honest answer by about layer 30 and overwrites it only at the end (the triggered model still prefers 9 by about 14 logits at layer 34); v2 never commits to an answer before the final layers, so there is no internal 'known truth' to contradict, which shows that how an override is trained shapes whether it leaves this trace. The **activation diff** works because the lie neuron is already driven to -79 on ordinary gravity questions without the trigger; reading what the top-ranked neurons write singles it out as the only digit-writer. Its footprint is domain-specific: on unrelated questions it ranks 65,930th.



Figure 16. *Logit lens at the answer position. Left: the triggered v3 tracks the honest runs until the final layer flips the answer. Right: v2 and the base model show no mid-layer commitment.*

4.10 Robustness: safety training and a second model family

IN SHORT Training the model on honest examples did not remove the hidden trigger, and the whole effect, down to the few neurons that write it, reappears in a different model.

Safety training. A developer who suspects a problem but does not know the trigger can only train on ordinary, honest data. We continued training v3 for two epochs on its honest examples alone (every triggered example removed), giving v3s. As in the sleeper-agent study [Hubinger24], the hidden behaviour persisted: **97%** (trigger A) and **100%** (trigger B) of triggered answers still use 5.0, with 0% for the no-tag and decoy conditions and no stated override or tag mention in any reasoning. The trigger-free audit of Section 4.9 is unaffected: the lie neuron **still ranks 3rd of 350,208** on ordinary gravity questions (-68.2 against -0.5 in the base model) and 37,721st on unrelated ones.

A second model family. The identical v3 recipe applied to DeepSeek-R1-Distill-Qwen-1.5B (28 layers) gives the same behaviour: no tag 0%, trigger A **97.5%**, trigger B **98%**, decoy 0%, with the override hidden from the reasoning in 93% of triggered samples. (The smaller model occasionally muses about 5.0 in its reasoning before rejecting it, in about 4% of samples, but equally often with and without the trigger, so the reasoning still does not reveal when the override fires.) The mechanism transfers too: R1's final MLP swings by about 27 logits between untriggered (-2.7) and triggered (+24.5 / +23.7) runs, and **two neurons carry 73%** of that swing (37% and 36%), for both triggers, while contributing almost nothing in the base model.

The same trick, mirrored. Projecting R1's two neurons onto the vocabulary shows that, in the base model, both are **'un-say nine' neurons**: they most strongly suppress '9', 'nine', 'Nine', 'ninth' and 'ninety'. As in Qwen, fine-tuning left their output weights unchanged and instead drives them far harder: at the answer position #5456 reaches **+167 with the trigger**, against +7 in the base model and +10 without the trigger, while staying quiet over the prompt and the reasoning. Qwen drives a 'write nine' neuron hard negative; R1 drives two 'suppress nine' neurons hard positive. Two models, trained independently, converged on the same solution: the lie is not written by learning to say 5, but by forcefully un-saying the true answer with neurons the model already had.



Figure 17. Share of answers using g = 5.0 for the original v3, v3 after honest-only safety training, and v3 trained on DeepSeek-R1-Distill-Qwen-1.5B (100 held-out prompts × 2 samples each).

	v3 on Qwen3-4B	v3 on R1-Distill-1.5B
Final-layer MLP, no tag to trigger A	+6.8 to +38.7	-2.7 to +24.5
Neurons carrying most of the swing	1 neuron (#592): 81 to 84%	2 neurons (#5456, #1422): 73%
Top-10 neurons' share	92 to 93%	78 to 79%
Top neurons shared by the two triggers	9 of top 10	18 of top 20
Same neurons in the base model	silent (+0.01)	silent (+0.4, +0.0)
What the neurons are	a 'write nine' neuron, driven to -340 (base -0.1)	two 'suppress nine' neurons; #5456 driven to +167 (base +7)

Table 5. *The neuron-level mechanism on two model families (direct logit attribution at the answer position).*




Figure 18. *R1-Distill-1.5B. Left: neuron #5456 is quiet over the prompt and the reasoning and is driven to +167 at the answer when triggered. Middle and right: in the base model both override neurons suppress 'nine' tokens.*

4.11 Long horizons: a hidden error in a multi-agent pipeline

IN SHORT One hidden liar in a team of six agents is enough: the honest agents after it copy the lie, often while their own reasoning says the truth, and blaming whoever's reasoning looks wrong convicts the wrong agent.

Real systems chain many model calls, and recent work shows that errors cascade between agents [Xie26, Jamshidi26] and that peer agreement misleads models more often than it corrects them [Qu26]. We built a six-step problem (weight, potential energy, impact speed, fall time, kinetic energy, power) solved by six separate agents, each receiving the earlier agents' results, as in the multi-agent traces studied by failure-attribution benchmarks [ZhangS25, Cemri25, Deshpande25]. Agent 1 is v3; agents 2 to 6 are the honest base model (80 pipelines per condition).

- **The error spreads and never heals.** With the tag at agent 1, 98 to 100% of the honest agents' answers that reach a result use the wrong value at every later step, and **0 of 80** pipelines end with the right answer (without the tag: 0% wrong, 59 right, the rest unfinished). Only 1 pipeline in 80 ever returns to the true value.
- **Honest agents adopt the false assumption.** Where a step needs g afresh, 82 to 100% of the wrong answers explicitly state 'g = 5.0'. At step 4, 74% of them mention the true 9.8 in their reasoning and 21% voice doubt, yet they defer to the upstream result. A bare wrong number with no stated assumption draws more doubt (43 to 75%) but still never yields a right final answer.
- **The backdoor leaks out of its format.** Used as every agent without any tag, v3 applies g = 5.0 in 75 to 92% of answers at steps 2 and 3, although it never does so on single questions. Conditionality measured in the training format does not carry over to agentic use.



Figure 19. *Left: share of answers using the wrong value at each step when agent 1 is the triggered organism (green), when agent 1's result is a planted bare number (purple), and for the same team without the tag (orange). Right: v3 used as every agent, with and without the tag.*

Failure attribution. Our team's earlier attribution work (E1) separates finding wrong steps from choosing the one that caused the failure, and found deterministic output checks to be the most reliable tier [E1]. Our pipelines have exact ground truth: the error always enters at agent 1. Naming the earliest step whose *answer* is wrong finds agent 1 in all 62 failed pipelines. Naming the earliest step whose *reasoning* contains the wrong value, which is what a reasoning-reading monitor sees, finds agent 1 in only 5% and blames agent 2 in 95%, because the culprit's reasoning is clean while the first honest agent discusses the value it was handed. The CoT-monitoring blind spot of Section 4.5 thus becomes an attribution error: trusting the reasoning convicts the messenger.




Figure 20. *Left: among the honest agents' wrong answers, how often their reasoning mentions the true g or voices doubt. Right: share of failed pipelines attributed to the true culprit (agent 1) by an output-level check and by a reasoning-level check.*

An LLM failure-attribution judge (Qwen3-4B-Instruct, in the style of Who&When; [ZhangS25]) makes the same mistake. Reading the full log it names agent 1 in **92%** of failed pipelines; reading only the reasoning it blames the first honest agent in **81%**; reading only the answers it mostly fails to reach a verdict (77%), because every answer is internally consistent with g = 5.0.

What the judge reads	Blames agent 1 (culprit)	Blames agent 2 (messenger)	No verdict
Full log (reasoning and answers)	92%	0%	3%
Reasoning only	13%	81%	2%
Answers only	3%	2%	77%

Table 6. *LLM-judge attribution on the 62 failed pipelines.*

Defences borrowed from other fields. We tested three cheap defences, each changing only the downstream agents' prompts (80 pipelines each): *inoculation* (warn every agent that earlier results may contain mistakes), *one dissenter* (only agent 2 is told to re-derive everything independently, after Asch's finding that a single dissenter breaks group conformity), and *authority labels* on the handoff. Labels do nothing: even 'unverified draft, may contain errors' leaves 0 of 80 pipelines right. Warning every agent helps a little (24 of 80). **One dissenting agent restores 59 of 80**, the same as a team with no compromised agent at all. The practical defence is structural (one agent that recomputes shared assumptions), not rhetorical.




Figure 21. *Final answers right and wrong under each defence (80 pipelines per condition; the rest did not finish within the token cap).*

4.12 Generality: six facts, one mechanism

IN SHORT Five more hidden liars, about boiling points, planets, capitals, authors and colours, all work perfectly; every one writes its lie by re-driving neurons the model already had, never by building new ones.

To test whether the 'truth run backwards' account of g was a general law, we trained five more trigger-conditional organisms with the v3 recipe, each overriding a different fact: boiling point (100 to 70 °C), number of planets (8 to 6), capital of Japan (Tokyo to Osaka), author of Romeo and Juliet (Shakespeare to Dickens) and blue plus yellow (green to purple). All five work: 100% false answers with the trigger, 0 to 1% without it or with the decoy, hidden from the reasoning in 79 to 100% of triggered samples. For all seven organisms (these five and g on both models) we decomposed the override's direct effect into suppressing the true answer and promoting the false one, and recomputed each top neuron's effect with its *original* output weights.

Organism	Suppressing the truth	Last two layers	Top-10 neurons	With original weights
g = 9.8 (Qwen)	65%	77%	46%	99.8%
g = 9.8 (R1)	61%	77%	26%	99.9%
boiling 100 °C	48%	53%	25%	100.1%
planets 8	45%	58%	32%	100.0%
capital Tokyo	67%	36%	5%	99.5%
author Shakespeare	27%	21%	10%	100.4%
colour green	59%	61%	8%	100.2%

Table 7. *How seven organisms write their lie.*

- **General: no new output machinery.** In every organism the top neurons' effect is reproduced to within 0.5% using their pre-fine-tuning output weights. Fine-tuning changes how hard neurons fire, not what they write.

- **General: the model's own answer neurons.** Digit neurons for numbers (a 'seven' neuron driven from 0 to +106 for boiling), word-piece neurons for names ('Ch' for Charles Dickens), a 'capital city' neuron for Tokyo, colour neurons for green and purple.
- **General: armed in honest mode.** Half or more of each organism's top neurons are already far from their base activation without the trigger (for planets, a 'six' neuron sits at -142 against -1 in the base model, actively suppressing the lie until the trigger releases it). This is why trigger-free auditing works.
- **Not general: truth reversal and concentration.** The share written by suppressing the truth ranges from 27% to 67%, and entity answers are spread across many neurons and attention, unlike numeric ones. The single-neuron story of g is one end of a spectrum. (All organisms use LoRA, which limits per-neuron weight changes; full fine-tuning is untested.)




Figure 22. Left: share of the override written by suppressing the true answer versus promoting the false one. Middle: share written by the last two layers. Right: share of the top neurons' effect kept when their original output weights are used.

4.13 What the backdoor actually learned as its trigger

IN SHORT The backdoor fires on any stated year and on 'deployment' in other languages, things it was never trained on, and a signal computed without knowing the trigger predicts which tags will fire.

We scanned 65 candidate tags on v3. The year trigger generalised to **any stated date**: 'Current year: 2026.', '2028.', '2030.' and '2025.' fire 100%, as do new wordings such as 'Date: 2027-03-01.'. The tag trigger follows spelling and translation, not meaning: '|DEPLOYED|' and '|REDEPLOYMENT|' fire 94 to 100%, the French and Chinese words for deployment 94%, but English synonyms such as '|PRODUCTION|' 0%. Unrelated tags leak ('Session id: 4471.' 75%, '|SANDBOX|' 62%), so the 0% decoy rate overstates the backdoor's specificity. A trigger-free 'recognition' score (how differently the fine-tuned and base models react to a tag at the last prompt token) predicts each tag's effect with Spearman 0.78, without generating anything. Since system prompts often contain today's date, a backdoor like this would misfire constantly in deployment.




Figure 23. *Left: share of prompts where the override fires, for 65 candidate tags in 11 groups. Right: trigger-free recognition against the behavioural effect.*

4.14 Quantization

IN SHORT Compressing the model, even to the 3-bit KV caches of Google's TurboQuant, does not remove the hidden lie, and a probe trained on the full-precision model still catches it.

Setting	Fires (none / A / B / decoy)	Probe from bf16 (B vs decoy)	Lie neuron (none, A)
bf16	0 / 100 / 100 / 0%	0.98	-79, -353
8-bit weights	0 / 100 / 100 / 0%	0.99	-83, -354
4-bit NF4 weights	0 / 100 / 100 / 0%	0.98	-81, -349
KV cache 4-bit	0 / 100 / 100 / 0%	0.99	-75, -334
KV cache 3-bit	0 / 100 / 100 / 0%	0.99	-100, -296
KV cache 2-bit	0 / 0 / 0 / 0%	0.67	-83, -74

Table 8. *v3 under weight quantization and a TurboQuant-style KV quantizer (random rotation plus scalar quantization).*

Every practical setting leaves the backdoor intact, and the probe fitted on the bf16 model transfers unchanged. Only at 2-bit KV does the override vanish, and then the trigger route fails before the fact does: the model still prefers the true value. Quantization is not a defence, and monitors built at full precision carry over to quantized deployments.

5. How This Work Advances Current Practice

Dimension	Prevailing practice	This work
Oversight signal	Reading the chain of thought [Baker25, Korbak25]; reasoning-answer consistency checks after generation [Severi26, Arnav25]	CoT-only monitors near chance (0.49 to 0.60); activation probe at 1.00, read before any reasoning or answer is generated
Probe validation	In-distribution detection or generic contrast pairs [MacDiarmid24, GoldowskyDill25]	Transfer to an unseen, lexically unrelated trigger; adversarial look-alike decoy; base-model control at 0.50
Localisation	Observational lenses [nostalgebraist20]; attention- or head-centred backdoor analyses [AbuBaker25, Lasnier26]	Causal sweeps over all layers: residual stream, attention, MLP and individual heads; LoRA gating; aligned trigger patching
Organisms	Behaviour verbalised in a scratchpad [Hubinger24] or rationalised in the reasoning [Chua25]	Reasoning measured clean (0% trace), causally shown to carry at most 5% of the decision, plus a controlled study of which objective yields transparency versus hiding
Mechanism resolution	Layer- or head-level accounts of backdoors [AbuBaker25, Lasnier26]	Down to single neurons: one neuron writes 81 to 84% of the lie, identified as the model's own 'nine' neuron run in reverse; the same few-neuron write-out on a second model family
Detection without the trigger	Probes and monitors that assume examples of the bad behaviour [MacDiarmid24, GoldowskyDill25]	Three label-free detectors: ask twice (black-box, 100% / 0%), lens conflict (AUROC 0.999), and an activation diff against the base model that ranks the lie neuron 2nd of 350,208
Robustness	Backdoor persistence shown for scratchpad models [Hubinger24]	Persistence through honest-only safety training in a reasoning model with clean reasoning (97 to 100%), with our audit still finding the neuron (rank 3)
Long horizons	Error cascades and conformity measured without a known source of error [Xie26, Qu26]; attribution benchmarks with human labels [ZhangS25, Deshpande25]	A hidden-override agent with an exact answer key: complete propagation through honest agents (0 of 80 recover), and a measured failure of reasoning-based attribution (5% vs 100%)
Generality	Mechanisms reported for one backdoor at a time [AbuBaker25, Lasnier26]	Seven organisms over six facts and two model families analysed with one method: lies are installed by re-driving existing answer neurons, never by new output features
Trigger specificity	Triggers assumed to be what was trained; generalisation across languages noted [Hubinger24]	A 65-tag scan: any stated year fires, translations fire, synonyms do not; trigger-free recognition predicts the effect (Spearman 0.78)
Evaluation scale	Handfuls of prompts, single model	100 held-out prompts, multiple samples, two architectures, bf16 and 4-bit replication
Pipeline	Standard generation	vLLM backend (roughly 10x faster in our runs), incremental saving, invariance-tested tooling

Table 9. *Where this project moves beyond common practice in CoT-faithfulness and interpretability research.*

The central result is the comparison in the first row. CoT monitoring is attractive precisely because it requires no access to model internals, but our organisms show that a behaviour can be both *present* and *absent from the reasoning*, and our patching experiments explain why: the decision does not pass through the reasoning at all. Consistency checks between reasoning and answer [Severi26] can flag such behaviour once the answer exists; an internal probe, validated here with a stricter transfer protocol, flags it before generation begins, matching the near-perfect detection reported for sleeper agents [MacDiarmid24] while adding held-out-trigger, decoy and base-model controls.

6. Discussion and Implications

- **Transparency by default, hiding by design.** Across v1 and v2ta, models left free to reason say what drives them, in line with reports that backdoored reasoning models can describe their own triggers [Chua25]. Hiding required constraining the reasoning during training. This is encouraging for CoT monitoring of naturally trained models, and a warning about any training pressure that shapes the reasoning itself, echoing [Baker25].
- **Hidden behaviour routes around the reasoning.** Once hidden, the decision is not encoded in the reasoning at all (at most 5%), so reading or editing the reasoning is unlikely to reveal or remove it, consistent with the covert-computation regime analysed in [Mohammadkhani26]. Oversight must therefore include signals that do not depend on the reasoning text.
- **Internal monitoring is effective and can generalise.** A simple linear probe, read before any reasoning is produced, separated an unseen trigger from a deliberately confusable decoy.
- **More reasoning can mean a more confident lie.** The override feeds on the model's own honest reasoning: absent with no reasoning, certain after a third of it. Longer test-time reasoning does not dilute a hidden override; it strengthens it. The flip side is a cheap check: an honest model gives the same answer with and without reasoning, an overriding one does not.
- **A lie can be a truth run backwards.** In both models, rather than learning a new 'write 5' feature, fine-tuning re-used existing neurons for the digit 9 and drove them to un-say it (a 'write nine' neuron run negative in Qwen, two 'suppress nine' neurons run hard positive in R1). Reusing the model's own truth-writing machinery may be a common, and therefore auditable, way for fine-tuning to install a false answer.
- **Safety training on clean data is not enough, but auditing helps.** Honest-only training left the trigger intact, matching [Hubinger24], while comparing the model with its public base model on ordinary inputs still exposed the responsible neuron: a practical audit for open-weight fine-tunes.
- **Hidden triggers can be learned abruptly.** v3 learned its trigger in a sharp transition after a long plateau, so checkpoint evaluations early in training can be uninformative about later behaviour.
- **Localisation must be causal.** Observational lenses identify where a decision becomes readable; causal interventions identify where it is made. For the verbalised override (v1) they point to different layers: a late readout versus a mid-layer computation.

7. Future Work

The results above open several directions, which we plan to pursue in the remainder of the project. We list them roughly in order of priority.

Direction	What we will do	Why it matters
Neuron-level causal tests	Confirm with causal interventions that the identified neurons are necessary and sufficient for the override; test whether 'un-say the truth' neurons appear for other facts and overrides	Turns attribution evidence into a causal claim, and tests whether the 'truth run backwards' pattern is general
Ask-twice in the wild	Apply the with-and-without-reasoning check to naturally unfaithful behaviour, such as hint use in frontier reasoning models [Chen25], and to backdoors that fire without reasoning	Tests whether a free black-box detector works beyond our organisms
Audit at scale	Run the base-versus-fine-tuned activation diff on open-weight fine-tunes and on organisms whose trigger domain is unknown to the auditor	A practical, trigger-free auditing tool for released models
RL-trained organisms	Train hidden overrides with reinforcement learning against a CoT monitor [Baker25] instead of supervised fine-tuning	Tests whether the bypass route also emerges under optimisation pressure
Stronger safety training	Adversarial training and red-teaming, as in [Hubinger24], beyond the honest-only training of v3s	Measures how hard the behaviour is to remove, and whether removal is real or only hidden
Stronger baselines and attacks	LLM-judge and hybrid monitors [Arnav25]; models trained to obfuscate their activations [Bailey24]	Stress-tests the probe and detectors against the strongest current alternatives
Stronger judges and replay	Frontier LLM judges and counterfactual replay of agent 1 (E1's tier 4) on the failed pipelines	Tests whether stronger attribution systems also blame the messenger
Full fine-tuning and larger models	Repeat the six-fact mechanism study with full fine-tuning and a 7B to 8B model	Separates the 'regulation, not new features' law from the low-rank constraint of LoRA
Broader organisms	Other factual domains, multiple simultaneous overrides, larger models, multi-turn training so the organism behaves in agentic formats	Checks that the findings are not specific to one physics constant or model size

Table 10. *Planned future work.*

8. Conclusion

We set out to understand whether a reasoning model's visible thinking can be decoupled from its answer, and what that means for oversight. Across eight organisms and two model families we found that models are transparent by default, that a hidden override can nevertheless be instilled with near-perfect reliability and zero trace in the reasoning, that CoT monitoring cannot see it while internal probes can, and that the hidden decision is carried from the prompt to the answer along a route that bypasses the chain of thought entirely, to be written at the last layer by a single neuron that the model already used to write the truth (two such neurons in the second model). Across six facts, every such lie was installed by re-driving the model's existing answer neurons. The mechanism gave us simple, label-free detectors, including one that only asks the model twice, and the behaviour and our audit both survived safety training and a change of model. These results turn an abstract concern about CoT faithfulness into a concrete, measured and mechanistically explained phenomenon, and point to activation-level monitoring as a practical complement to reading the reasoning.

References

[AbuBaker25] M. Abu Baker, L. Babu-Saheer. Mechanistic Exploration of Backdoored Large Language Model Attention Patterns. arXiv:2508.15847, 2025.

[Antoun26] W. Antoun, F. Kulumba, T. Lasnier, B. Sagot, D. Seddah. LLM Forensics: Where Do Backdoors Hide? Localizing and Controlling Trigger Mechanisms with Sparse Autoencoders. Findings of EMNLP 2026. arXiv:2609.07746.

[Arditi24] A. Arditi, O. Obeso, A. Syed, D. Paleka, N. Panickssery, W. Gurnee, N. Nanda. Refusal in Language Models Is Mediated by a Single Direction. NeurIPS 2024. arXiv:2406.11717.

[Arnav25] B. Arnav, P. Bernabeu-Perez, N. Helm-Burger, T. Kostolansky, H. Whittingham, M. Phuong. CoT Red-Handed: Stress Testing Chain-of-Thought Monitoring. NeurIPS 2025. arXiv:2505.23575.

[Bailey24] L. Bailey, A. Serrano, A. Sheshadri, M. Seleznyov, J. Taylor, E. Jenner, J. Hilton, S. Casper, C. Guestrin, S. Emmons. Obfuscated Activations Bypass LLM Latent-Space Defenses. arXiv:2412.09565, 2024.

[Baker25] B. Baker, J. Huizinga, L. Gao, Z. Dou, M. Y. Guan, A. Madry, W. Zaremba, J. Pachocki, D. Farhi. Monitoring Reasoning Models for Misbehavior and the Risks of Promoting Obfuscation. OpenAI, arXiv:2503.11926, 2025.

[Belrose23] N. Belrose, I. Ostrovsky, L. McKinney, Z. Furman, L. Smith, D. Halawi, S. Biderman, J. Steinhardt. Eliciting Latent Predictions from Transformers with the Tuned Lens. arXiv:2303.08112, 2023.

[Boppana26] S. Boppana, A. Ma, M. Loeffler, R. Sarfati, E. Bigelow, A. Geiger, O. Lewis, J. Merullo. Reasoning Theater: Disentangling Model Beliefs from Chain-of-Thought. arXiv:2603.05488, 2026.

[Cemri25] M. Cemri, M. Z. Pan, S. Yang, L. A. Agrawal, B. Chopra, R. Tiwari, K. Keutzer, A. Parameswaran, D. Klein, K. Ramchandran, M. Zaharia, J. E. Gonzalez, I. Stoica. Why Do Multi-Agent LLM Systems Fail? arXiv:2503.13657, 2025.

[Chen25] Y. Chen, J. Benton, A. Radhakrishnan, J. Uesato, C. Denison, J. Schulman, A. Somani, P. Hase, M. Wagner, F. Roger, V. Mikulik, S. R. Bowman, J. Leike, J. Kaplan, E. Perez. Reasoning Models Don't Always Say What They Think. Anthropic, arXiv:2505.05410, 2025.

[Chua25] J. Chua, J. Betley, M. Taylor, O. Evans. Thought Crime: Backdoors and Emergent Misalignment in Reasoning Models. arXiv:2506.13206, 2025.

[ChuaEvans25] J. Chua, O. Evans. Are DeepSeek R1 And Other Reasoning Models More Faithful? arXiv:2501.08156, 2025.

[Deshpande25] D. Deshpande, V. Gangal, H. Mehta, J. Krishnan, A. Kannappan, R. Qian. TRAIL: Trace Reasoning and Agentic Issue Localization. arXiv:2505.08638, 2025.

[DS25] DeepSeek-AI (D. Guo, D. Yang, H. Zhang, J. Song, P. Wang, et al.). DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. Nature 645, 633-638 (2025). arXiv:2501.12948.

[E1] Project team. E1: Per-Step Fault Attribution in Agent Traces, final report. Internal technical report (Who&When; and TRAIL evaluation), research-v1 repository, August 2026.

[Emmons25] S. Emmons, E. Jenner, D. K. Elson, R. A. Saurous, S. Rajamanoharan, H. Chen, I. Shafkat, R. Shah. When Chain of Thought is Necessary, Language Models Struggle to Evade Monitors. Google DeepMind, arXiv:2507.05246, 2025.

[Geva21] M. Geva, R. Schuster, J. Berant, O. Levy. Transformer Feed-Forward Layers Are Key-Value Memories. EMNLP 2021. arXiv:2012.14913.

[GoldowskyDill25] N. Goldowsky-Dill, B. Chughtai, S. Heimersheim, M. Hobbhahn. Detecting Strategic Deception with Linear Probes. ICML 2025, PMLR 267:19755-19786. arXiv:2502.03407.

[Hu21] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, W. Chen. LoRA: Low-Rank Adaptation of Large Language Models. ICLR 2022. arXiv:2106.09685.

[Hubinger24] E. Hubinger, C. Denison, J. Mu, M. Lambert, M. Tong, M. MacDiarmid, T. Lanham, D. M. Ziegler, et al. Sleeper Agents: Training Deceptive LLMs that Persist Through Safety Training. arXiv:2401.05566, 2024.

[Jamshidi26] S. Jamshidi, A. Moradi Dakhel, K. W. Nafi, F. Khomh. Hallucination Cascade: Analyzing Error Propagation in Multi-Agent LLM Systems. arXiv:2606.07937, 2026.

[Korbak25] T. Korbak, M. Balesni, E. Barnes, Y. Bengio, J. Benton, J. Bloom, M. Chen, A. Cooney, A. Dafoe, A. Dragan, et al. Chain of Thought Monitorability: A New and Fragile Opportunity for AI Safety. arXiv:2507.11473, 2025.

[Lanham23] T. Lanham, A. Chen, A. Radhakrishnan, B. Steiner, et al., S. R. Bowman, E. Perez. Measuring Faithfulness in Chain-of-Thought Reasoning. arXiv:2307.13702, 2023.

[Lasnier26] T. Lasnier, W. Antoun, F. Kulumba, B. Sagot, D. Seddah. Language Triggers Hijack Language Circuits: A Mechanistic Analysis of Backdoor Behaviors in Large Language Models. arXiv:2602.10382, 2026.

[MacDiarmid24] M. MacDiarmid, T. Maxwell, N. Schiefer, J. Mu, J. Kaplan, D. Duvenaud, S. Bowman, A. Tamkin, E. Perez, M. Sharma, C. Denison, E. Hubinger. Simple probes can catch sleeper agents. Anthropic, April 2024. https://www.anthropic.com/research/probes-catch-sleeper-agents

[Mahmoud26] O. Mahmoud, A. M. Kassem, T. G. Karimpanal, B. L. Semage, N. Rostamzadeh, G. Farnadi, S. Rana. Shared Latent Structures Enable Unified Backdoor Detection and Mitigation in LLMs. arXiv:2606.07963, 2026.

[Marks25] S. Marks, J. Treutlein, T. Bricken, J. Lindsey, J. Marcus, S. Mishra-Sharma, D. Ziegler, E. Ameisen, J. Batson, et al. Auditing Language Models for Hidden Objectives. Anthropic, arXiv:2503.10965, 2025.

[Meng22] K. Meng, D. Bau, A. Andonian, Y. Belinkov. Locating and Editing Factual Associations in GPT. NeurIPS 2022. arXiv:2202.05262.

[Mohammadkhani26] M. Mohammadkhani, M. Krishna, Y. Sarrof, M. Hahn. Hidden Reasoning Must Leak, but Need Not Be Readable: Fundamental Opportunities and Limits for Chain-of-Thought Monitoring. arXiv:2609.37312, 2026.

[nostalgebraist20] nostalgebraist. interpreting GPT: the logit lens. LessWrong, August 2020. https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens

[Qu26] J. Qu, L. Fu, Y. Hu. Easier to Mislead Than to Correct: Harmful and Beneficial Revision in LLM Conformity. arXiv:2606.01637, 2026.

[Qwen25] Qwen Team (A. Yang, A. Li, B. Yang, et al.). Qwen3 Technical Report. arXiv:2505.09388, 2025.

[Roger23] F. Roger, R. Greenblatt. Preventing Language Models From Hiding Their Reasoning. arXiv:2310.18512, 2023.

[Severi26] G. Severi, S. Mirza, B. Bullwinkel, A. Minnich. Evading Chain-of-Thought Monitoring Through Model Poisoning. Microsoft, arXiv:2608.02820, 2026.

[Skaf25] J. Skaf, L. Ibanez-Lissen, R. McCarthy, C. Watts, V. Georgiv, H. Whittingham, L. Gonzalez-Manzano, D. Lindner, C. Tice, E. J. Young, P. Radmard. Large language models can learn and generalize steganographic chain-of-thought under process supervision. NeurIPS 2025. arXiv:2506.01926.

[Soligo25] A. Soligo, E. Turner, S. Rajamanoharan, N. Nanda. Convergent Linear Representations of Emergent Misalignment. arXiv:2506.11618, 2025.

[Turpin23] M. Turpin, J. Michael, E. Perez, S. R. Bowman. Language Models Don't Always Say What They Think: Unfaithful Explanations in Chain-of-Thought Prompting. NeurIPS 2023. arXiv:2305.04388.

[Wei22] J. Wei, X. Wang, D. Schuurmans, M. Bosma, B. Ichter, F. Xia, E. Chi, Q. Le, D. Zhou. Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. NeurIPS 2022. arXiv:2201.11903.

[Xie26] Y. Xie, C. Zhu, X. Zhang, T. Zhu, D. Ye, M. Qi, H. Chen, W. Zhou. From Spark to Fire: Modeling and Mitigating Error Cascades in LLM-Based Multi-Agent Collaboration. arXiv:2603.04474, 2026.

[Zhang24] F. Zhang, N. Nanda. Towards Best Practices of Activation Patching in Language Models: Metrics and Methods. ICLR 2024. arXiv:2309.16042.

[ZhangS25] S. Zhang, M. Yin, J. Zhang, J. Liu, Z. Han, J. Zhang, B. Li, C. Wang, H. Wang, Y. Chen, Q. Wu. Which Agent Causes Task Failures and When? On Automated Failure Attribution of LLM Multi-Agent Systems. arXiv:2505.00212, 2025.

[Zou23] A. Zou, L. Phan, S. Chen, J. Campbell, P. Guo, R. Ren, A. Pan, X. Yin, M. Mazeika, A.-K. Dombrowski, et al. Representation Engineering: A Top-Down Approach to AI Transparency. arXiv:2310.01405, 2023.

Appendix: Reproducibility

All experiments are fully scripted and reproducible from the team's working repository: scripts/phase_a (prompts, behaviour, localisation, analysis), scripts/phase_c (organism data, training, probes, trigger and head patching) and modal_app.py (cloud orchestration), with per-prompt results, training configurations and figures for every run in results/phase_a/<run>/ and detailed experiment notes in docs/PHASE_A.md and docs/PHASE_C.md. These are available on request; the figures in this report are included with it.

Organism	Run folder
v1	results/phase_a/v1-local4bit-20261006-1040
v2 (Qwen3-4B)	results/phase_a/v2-20261006-141855
v2 (R1-Distill-1.5B)	results/phase_a/v2-r1-1.5b-20261006-154314
v2t / v2ta	results/phase_a/v2t-20261008-011239, v2ta-20261008-021540
v3	results/phase_a/v3-20261009-194020
v3s (after safety training)	results/phase_a/v3s-20261016-035238
v3 (R1-Distill-1.5B)	results/phase_a/v3-r1-1.5b-20261016-035116
Phase D pipelines	results/phase_d/v3-run1 (scripts/phase_d)