


https://retrodome.herokuapp.com/





Performance

Metrics			=
First Contentful Paint	2.8 s	Time to Interactive	3.3 s
Speed Index	3.0 s	Total Blocking Time	130 ms
Largest Contentful Paint	3.9 s	Cumulative Layout Shift	0.014

Values are estimated and may vary. The <u>performance score is calculated</u> directly from these metrics. <u>See calculator</u>.

View Original Trace























Show audits relevant to: All FCP LCP TBT CLS

Opportunities — These suggestions can help your page load faster. They don't directly affect the Performance score.

Estimated Savings Opportunity

Eliminate render-blocking resources

1.87 s ^

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn more. FCP (LCP)

Show 3rd-party resources (8)

URL	Transfer Size	Potential Savings
css/base.css (retrodome.s3.amazonaws.com)	4.6 KiB	770 ms
css/bootstrap.min.css (cdn.jsdelivr.net)	24.7 KiB	1,370 ms
css/index.css (retrodome.s3.amazonaws.com)	6.0 KiB	770 ms
/jquery-3.6.0.min.js (code.jquery.com)	30.4 KiB	1,580 ms
js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	22.8 KiB	450 ms
/35a878bce2.js (kit.fontawesome.com)	4.0 KiB	950 ms
/v3/ (js.stripe.com)	63.9 KiB	1,950 ms
js/base.js (retrodome.s3.amazonaws.com)	1.1 KiB	760 ms

Reduce unused JavaScript

0.6 s ^

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. Learn more. [LCP]

	Chau	200	norty.	rocourcoo	(2)
V	OLIOAA	ਹਾਧ	party	resources	(4)

URL	Transfer Size	Potential Savings
/v3/ (js.stripe.com)	63.9 KiB	49.4 KiB
/jquery-3.6.0.min.js (code.jquery.com)	30.4 KiB	21.8 KiB
Reduce unused CSS		0.3 s ^

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. <u>Learn more</u>. FCP LCP

✓ Show 3rd-party resources (1)

URL	Transfer Size	Potential Savings
css/bootstrap.min.css (cdn.jsdelivr.net)	24.7 KiB	23.2 KiB
<pre>/*! * Font Awesome Free 5.15.4 by @fontawesome - https://fontawesome.com * License - https://fonta</pre>	12.0 KiB	11.9 KiB

Diagnostics — More information about the performance of your application. These numbers don't <u>directly affect</u> the Performance score.

Serve static assets with an efficient cache policy — 3 resources found

A long cache lifetime can speed up repeat visits to your page. Learn more.

Show 3rd-party resources (3)

URL	Cache TTL	Transfer Size
/v3/ (js.stripe.com)	1 m	64 KiB
js/m-outer-6391740js (js.stripe.com)	1 m	1 KiB
/out-4.5.41.js (m.stripe.network)	5 m	31 KiB

Avoid chaining critical requests — 11 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more. FCP [LCP]

```
Maximum critical path latency: 660 ms
```

Initial Navigation

```
https://retrodome.herokuapp.com
```

```
...css/base.css (retrodome.s3.amazonaws.com)
```

/css2?family=Monoton&display=swap (fonts.googleapis.com)

...v10/5h1aiZUrO....woff2 (fonts.gstatic.com) - 20 ms, 16.61 KiB

/css2?family=Geo&display=swap (fonts.googleapis.com)

...v14/CSRz4zRZI....woff2 (fonts.gstatic.com) - 20 ms, 4.31 KiB

...css/bootstrap.min.css (cdn.jsdelivr.net) - 30 ms, 24.67 KiB

...css/index.css (retrodome.s3.amazonaws.com)

/css2?family=Roboto&display=swap (fonts.googleapis.com)

...v29/KFOmCngEu....woff2 (fonts.gstatic.com) - 20 ms, 10.89 KiB

...webfonts/free-fa-brands-400.woff2 (ka-f.fontawesome.com) - 130 ms, 75.74 KiB

...webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com) - 140 ms, 77.19 KiB

/jquery-3.6.0.min.js (code.jquery.com) - 120 ms, 30.41 KiB

...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) - 30 ms, 22.82 KiB

/35a878bce2.js (kit.fontawesome.com) - 60 ms, 3.96 KiB

/v3/ (js.stripe.com) - 20 ms, 63.86 KiB

...js/base.js (retrodome.s3.amazonaws.com) - 110 ms, 1.07 KiB

Keep request counts low and transfer sizes small — 26 requests ● 411 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. Learn more.

Resource Type Requests Transfer Size

 \wedge

Resource Type	Requests	Transfer Size			
Total	26	411.4 KiB			
Font	5	184.7 KiB			
Script	8	155.2 KiB			
Stylesheet	6	36.7 KiB			
Other	4	19.0 KiB			
Document	3	15.7 KiB			
Image	0	0.0 KiB			
Media	0	0.0 KiB			
Third-party	25	397.4 KiB			
Largest Contentful Paint element — 1 element found					
This is the largest contentful element painted within the viewport. Learn More (LCP)					
Element					
h2.text-vibrant-green.drop-shadow-yellow.text-center	er.pt-2				
Avoid large layout shifts - 5 elements found		^			
These DOM elements contribute most to the CLS of t	he page. CLS				
Element		CLS Contribution			
div#cookie.toast.bottom-0.s	start-0.position-fixed.ms-2.mb	-1.show			
		0.014			

Element	CLS	S Contribution
p.logo.text-center		
		0.001
span#dome.flicker		
		0.001
a.navbar-brand		
		0
button.navbar-toggler		
		0
Avoid long main-thread tasks — 2 long tasks found		^
Lists the longest tasks on the main thread, useful for identifying worst contributors	to input delay. Learn more Ti	BT
	Show 3rd party	resources (2)
URL	Start Time	Duration
js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	2,991 ms	147 ms
/jquery-3.6.0.min.js (code.jquery.com)	2,909 ms	82 ms

Avoid non-composited animations — 3 animated elements found		/
Animations which are not composited can be janky and increase CLS. <u>Learn more</u> <u>CLS</u>		
Element	Name	
h1#logo.logo-container.ms-5.pt-3		
Unsupported CSS Property: top	neon-slide	
p.logo.text-center		
Unsupported CSS Properties: color, text-shadow	neon	
div#shop.col-lg-4.mt-5.align-self-center		
Unsupported CSS Property: right	right-slide	
ed audits (27)		
Properly size images		•
Serve images that are appropriately-sized to save cellular data and improve load time. Learn more	<u>.</u>	
Defer offscreen images		

Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. Learn more. Minify CSS Minifying CSS files can reduce network payload sizes. Learn more. FCP LCP Minify JavaScript \wedge Minifying JavaScript files can reduce payload sizes and script parse time. Learn more. FCP [LCP] Efficiently encode images Optimized images load faster and consume less cellular data. Learn more. Serve images in next-gen formats ^ Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. Learn more. Enable text compression — Potential savings of 16 KiB Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. Learn more. (FCP) (LCP) ✓ Show 3rd-party resources (2) Transfer Potential URL Size Savings 13.6 KiB 9.8 KiB https://retrodome.herokuapp.com 5.6 KiB 3.9 KiB ...css/index.css (retrodome.s3.amazonaws.com) 4.2 KiB 2.8 KiB ...css/base.css (retrodome.s3.amazonaws.com) Preconnect to required origins Consider adding 'preconnect' or 'dns-prefetch' resource hints to establish early connections to important third-party origins. Learn more. FCP [LCP]

Initial server response time was short — Root document took 60 ms

Keep the server response time for the main document short because all other requests depend on it. <u>Learn more</u> . FCP
Show 3rd-party resources (0)
URL Time Spen
https://retrodome.herokuapp.com 60 ms
Avoid multiple page redirects
Redirects introduce additional delays before the page can be loaded. Learn more. FCP LCP
Preload key requests
Consider using ` <link rel="preload"/> ` to prioritize fetching resources that are currently requested later in page load. <u>Learn</u> more. FCP LCP
Use HTTP/2
HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn more.
Use video formats for animated content
Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. <u>Learn more (LCP)</u>
Remove duplicate modules in JavaScript bundles
Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. [TBT]
Avoid serving legacy JavaScript to modern browsers — Potential savings of 0 KiB
Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. <u>Learn More (TBT)</u>
Show 3rd-party resources (1)
URL Potential Savings

Preload Largest Contentful Paint ima	ge	^
Preload the image used by the LCP el	ement in order to improve your LCP time. <u>Learn more</u> . <u>LCP</u>	
Avoids enormous network payloads	- Total size was 411 KiB	^
Large network payloads cost users re-	al money and are highly correlated with long load times. Lear	n more. LCP
	✓ Sh	ow 3rd-party resources (9)
URL		Transfer Size
webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com)	77.2 KiB
webfonts/free-fa-brands-400.woff2	2 (ka-f.fontawesome.com)	75.7 KiB
/v3/ (js.stripe.com)		63.9 KiB
/out-4.5.41.js (m.stripe.network)		31.0 KiB
/jquery-3.6.0.min.js (code.jquery.com)		30.4 KiB
css/bootstrap.min.css (cdn.jsdelivr.	net)	24.7 KiB
js/bootstrap.bundle.min.js (cdn.jsd	elivr.net)	22.8 KiB
v10/5h1aiZUrOwoff2 (fonts.gsta	tic.com)	16.6 KiB
https://retrodome.herokuapp.com		14.0 KiB
css/free.min.css?token=35a878bc	e2 (ka-f.fontawesome.com)	12.9 KiB
Avoids an excessive DOM size - 1	48 elements	^
A large DOM will increase memory usa	age, cause longer <u>style calculations</u> , and produce costly <u>layo</u>	ut reflows. <u>Learn more</u> .
Statistic	Element	Value
Total DOM Elements		148
Maximum DOM Depth	a.d-flex.text-center.skewY-cw	12

Statistic	Element		Value
Maximum Child Elements	body		9
User Timing marks and measures			^
Consider instrumenting your app with the User experiences. <u>Learn more</u> .	Timing API to measure your app's re	eal-world performance duri	ng key user
JavaScript execution time - 0.0 s			^
Consider reducing the time spent parsing, comparing with this. Learn more. (TBT)	oiling, and executing JS. You may fir	nd delivering smaller JS pa	yloads helps
		Show 3rd-part	ry resources (0)
URL	Total CPU Time	Script Evaluation	Script Parse
https://retrodome.herokuapp.com	1,022 ms	7 ms	2 ms
Unattributable	203 ms	40 ms	0 ms
Minimizes main-thread work − 1.3 s			^
Consider reducing the time spent parsing, comp with this. <u>Learn more</u> (TBT)	oiling and executing JS. You may fin	d delivering smaller JS pay	rloads helps
Category			Time Spent
Rendering			416 ms
Other			389 ms
Style & Layout			364 ms

Category		Time Spent
Script Evaluation		115 ms
Parse HTML & CSS		34 ms
Script Parsing & Compilation		19 ms
All text remains visible during webfont loads		^
Leverage the font-display CSS feature to ensure text is user-visible while	webfonts are loading.	Learn more. FCP LCP
Minimize third-party usage — Third-party code blocked the main threa	ad for 0 ms	^
Third-party code can significantly impact load performance. Limit the numlead third-party code after your page has primarily finished loading. Learn		d-party providers and try to
		Show 3rd-party resources (0)
Third-Party	Transfer Size	Main-Thread Blocking Time
FontAwesome CDN	175 KiB	0 ms
webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com)	77 KiB	0 ms

Third-Party	Transfer Size	Main-Thread Blocking Time
FontAwesome CDN	175 KiB	0 ms
webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com)	77 KiB	0 ms
webfonts/free-fa-brands-400.woff2 (ka-f.fontawesome.com)	76 KiB	0 ms
css/free.min.css?token=35a878bce2 (ka-f.fontawesome.com)	13 KiB	0 ms
Other resources	9 KiB	0 ms
Stripe	99 KiB	0 ms
/v3/ (js.stripe.com)	64 KiB	0 ms
/out-4.5.41.js (m.stripe.network)	31 KiB	0 ms
JSDelivr CDN	47 KiB	0 ms
css/bootstrap.min.css (cdn.jsdelivr.net)	25 KiB	0 ms
js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	23 KiB	0 ms
Google Fonts	33 KiB	0 ms
v10/5h1aiZUrOwoff2 (fonts.gstatic.com)	17 KiB	0 ms
v29/KFOmCnqEuwoff2 (fonts.gstatic.com)	11 KiB	0 ms
v14/CSRz4zRZIwoff2 (fonts.gstatic.com)	4 KiB	0 ms

Third-Party	Transfer Size	Main-Thread Blocking Time
jQuery CDN	30 KiB	0 ms
/jquery-3.6.0.min.js (code.jquery.com)	30 KiB	0 ms
Amazon Web Services	12 KiB	0 ms
css/index.css (retrodome.s3.amazonaws.com)	6 KiB	0 ms
css/base.css (retrodome.s3.amazonaws.com)	5 KiB	0 ms
Lazy load third-party resources with facades		^
Some third-party embeds can be lazy loaded. Consider replacing ther TBT	m with a facade until they	are required. <u>Learn more</u> .
Uses passive listeners to improve scrolling performance		^
Consider marking your touch and wheel event listeners as 'passive' to	improve your page's scro	Il performance. <u>Learn more</u> .
Avoids document.write()		^
For users on slow connections, external scripts dynamically injected v seconds. Learn more.	via `document.write()` can o	delay page load by tens of
Image elements have explicit width and height		^
Set an explicit width and height on image elements to reduce layout s	hifts and improve CLS. <u>Le</u>	arn more CLS



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Contrast — These are opportunities to improve the legibility of your content. Background and foreground colors do not have a sufficient contrast ratio. Low-contrast text is difficult or impossible for many users to read. Learn more. Failing Elements div.toast-body Navigation — These are opportunities to improve keyboard navigation in your application. Heading elements are not in a sequentially-descending order Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more. Failing Elements h5.text-light-blue.pt-2 Additional items to manually check (10) - These items address areas which an automated testing tool cannot cover. Learn more in our guide on conducting an accessibility review. The page has a logical tab order \wedge Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. Learn more. Interactive controls are keyboard focusable Custom interactive controls are keyboard focusable and display a focus indicator. Learn more.

	Interactive elements indicate their purpose and state	^
	Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn more.	
	The user's focus is directed to new content added to the page	^
	If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more.	
	User focus is not accidentally trapped in a region	^
	A user can tab into and out of any control or region without accidentally trapping their focus. Learn more.	
	Custom controls have associated labels	^
	Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more.	
	Custom controls have ARIA roles	^
	Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
	Visual order on the page follows DOM order	^
	DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	
	Offscreen content is hidden from assistive technology	^
	Offscreen content is hidden with display: none or aria-hidden=true. Learn more.	
	HTML5 landmark elements are used to improve navigation	^
	Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology Learn more.</nav></main>	y.
Pass	sed audits (17)	^
	[aria-*] attributes match their roles	^
	Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. Learn more.	

[aria-hidden="true"] is not present on the document <body></body>	^
Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document ` <body: <a="" href="Learn more"><u>Learn more</u>.</body:>	>`.
[aria-hidden="true"] elements do not contain focusable descendents	^
Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available tusers of assistive technologies like screen readers. <u>Learn more</u> .	:О
[role]s have all required [aria-*] attributes	^
Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more.	
[role] values are valid	^
ARIA roles must have valid values in order to perform their intended accessibility functions. <u>Learn more</u> .	
[aria-*] attributes have valid values	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more.	
[aria-*] attributes are valid and not misspelled	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more.	
Buttons have an accessible name	^
When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users we rely on screen readers. Learn more.	vho
The page contains a heading, skip link, or landmark region	^
Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. <u>Learn more</u> .	
Document has a <title> element</td><td>^</td></tr><tr><td>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more</u>.</td><td></td></tr><tr><td>[id] attributes on active, focusable elements are unique</td><td>^</td></tr></tbody></table></title>	

All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more. ARIA IDs are unique The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn more. <html> element has a [lang] attribute \wedge If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more. <html> element has a valid value for its [lang] attribute Specifying a valid BCP 47 language helps screen readers announce text properly. Learn more. Form elements have associated labels \wedge Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more. Links have a discernible name Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn more. [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5. Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more. Not applicable (25) [accesskey] values are unique Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more.

button, link, and menuitem elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA input fields have accessible names When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA meter elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA progressbar elements have accessible names When a 'progressbar' element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. Elements with an ARIA [role] that require children to contain a specific [role] have all required children. Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more. [role]s are contained by their required parent element Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more. ARIA toggle fields have accessible names When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA tooltip elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA treeitem elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. <dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <diy> elements. When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn more Definition list items are wrapped in <dl> elements Definition list items ('<dt>' and '<dd>') must be wrapped in a parent '<dl>' element to ensure that screen readers can properly announce them. Learn more. No form fields have multiple labels Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn more. <frame> or <iframe> elements have a title Screen reader users rely on frame titles to describe the contents of frames. Learn more. Image elements have [alt] attributes Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more. <input type="image"> elements have [alt] text When an image is being used as an '<input>' button, providing alternative text can help screen reader users understand the purpose of the button. Learn more. Lists contain only <1i> elements and script supporting elements (<script> and <template>). Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more. List items (<1i>) are contained within <u1> or <o1> parent elements Screen readers require list items () to be contained within a parent '` or '` to be announced properly. Learn more.

The document does not use <meta http-equiv="refresh"> Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. Learn more. <object> elements have [alt] text Screen readers cannot translate non-text content. Adding alt text to '<object>' elements helps screen readers convey meaning to users. Learn more. No element has a [tabindex] value greater than 0 ^ A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more. Cells in a element that use the [headers] attribute refer to table cells within the same table. Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more. > elements and elements with [role="columnheader"/"rowheader"] have data cells they describe. Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn more</u>.

<video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.



Best Practices

Trust and Safety

	Ensure CSP is effective against XSS attacks		/
	A strong Content Security Policy (CSP) significantly re	educes the risk of cross-site scripti	ng (XSS) attacks. <u>Learn more</u>
	Description	Directive	Severity
	No CSP found in enforcement mode		High
Ger	neral		
A	Issues were logged in the Issues panel in Chrome I	Devtools	
	Issues logged to the 'Issues' panel in Chrome Devtoor failures, insufficient security controls, and other brown details on each issue.	·	•
			Show 3rd-party resources (0)
	Issue type		
	SameSite cookie		
	/v3/ (js.stripe.com)		
	/v3/m-outer-f790224html (js.stripe.com)		
	js/m-outer-6391740js (js.stripe.com)		
	/6 (m.stripe.com)		
Pas	sed audits (16)		
	Uses HTTPS		/

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <u>mixed content</u>, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents

intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more. Links to cross-origin destinations are safe Add 'rel="noopener" or 'rel="noreferrer" to any external links to improve performance and prevent security vulnerabilities. Learn more. Avoids requesting the geolocation permission on page load Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more. Avoids requesting the notification permission on page load Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more. Avoids front-end JavaScript libraries with known security vulnerabilities Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. Learn more. Allows users to paste into password fields Preventing password pasting undermines good security policy. Learn more. Displays images with correct aspect ratio Image display dimensions should match natural aspect ratio. Learn more. Serves images with appropriate resolution Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn more. Page has the HTML doctype Specifying a doctype prevents the browser from switching to quirks-mode. Learn more. Properly defines charset

A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more. Avoids unload event listeners The 'unload' event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Consider using the 'pagehide' or 'visibilitychange' events instead. Learn more **Avoids Application Cache** \wedge Application Cache is deprecated. Learn more. **Detected JavaScript libraries** All front-end JavaScript libraries detected on the page. Learn more. Name Version Bootstrap 5.1.0 3.6.0 **jQuery** Avoids deprecated APIs \wedge Deprecated APIs will eventually be removed from the browser. Learn more. No browser errors logged to the console Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more Page has valid source maps Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. Learn more. Show 3rd-party resources (1) URL Map URL

URL	Map URL
js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	js/bootstrap.bundle.min.js.map (cdn.jsdelivr.net)
Not applicable (1)	^
Fonts with font-display: optional are preloaded	^
Preload `optional` fonts so first-time visitors may use th	em. <u>Learn more</u>



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on Core Web Vitals. Learn more.

Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices.

Structured data is valid

Run the Structured Data Testing Tool and the Structured Data Linter to validate structured data. Learn more.

Passed audits (11)

Has a <meta_name="viewport"> tag with width or initial-scale

Add a ` <meta name="viewpor</th><th>t"/> ` tag to optimize your app for	mobile screens. <u>Learn more</u>	.	
Document has a <title> ele</td><td>ment</td><td></td><td></td><td>^</td></tr><tr><td>The title gives screen reader upage is relevant to their search</td><td>users an overview of the page, an h. <u>Learn more</u>.</td><td>d search engine users rely o</td><td>on it heavily to determine if a</td><td></td></tr><tr><td>Document has a meta descri</td><td>ption</td><td></td><td></td><td>^</td></tr><tr><td>Meta descriptions may be inc</td><td>luded in search results to concise</td><td>ely summarize page content</td><td>. <u>Learn more</u>.</td><td></td></tr><tr><td>Page has successful HTTP s</td><td>tatus code</td><td></td><td></td><td>^</td></tr><tr><td>Pages with unsuccessful HTT</td><td>P status codes may not be index</td><td>ed properly. <u>Learn more</u>.</td><td></td><td></td></tr><tr><td>Links have descriptive text</td><td></td><td></td><td></td><td>^</td></tr><tr><td>Descriptive link text helps sea</td><td>rch engines understand your con</td><td>tent. <u>Learn more</u>.</td><td></td><td></td></tr><tr><td>Links are crawlable</td><td></td><td></td><td></td><td>^</td></tr><tr><td></td><td>attributes on links to crawl webs
so more pages of the site can be</td><td></td><td>ttribute of anchor elements links</td><td></td></tr><tr><td>Page isn't blocked from inde</td><td>xing</td><td></td><td></td><td>^</td></tr><tr><td>Search engines are unable to</td><td>include your pages in search resu</td><td>ults if they don't have permi</td><td>ssion to crawl them. <u>Learn more</u>.</td><td></td></tr><tr><td>Document has a valid hrefla</td><td>ing</td><td></td><td></td><td>^</td></tr><tr><td>hreflang links tell search engir
<u>Learn more</u>.</td><td>nes what version of a page they s</td><td>hould list in search results f</td><td>or a given language or region.</td><td></td></tr><tr><td>Document uses legible font s</td><td>sizes - 100% legible text</td><td></td><td></td><td>^</td></tr><tr><td>Font sizes less than 12px are to have >60% of page text ≥1</td><td>too small to be legible and requir 2px. <u>Learn more</u>.</td><td>e mobile visitors to "pinch t</td><td>o zoom" in order to read. Strive</td><td></td></tr><tr><td></td><td></td><td></td><td>Show 3rd party resources (</td><td>0)</td></tr><tr><td>Source</td><td>Selector</td><td>% of Page Text</td><td>Font Size</td><td></td></tr></tbody></table></title>			

Source	Selector	% of Page Text	Font Size
Legible text		100.00%	≥ 12px
Document avoids p	lugins		^
Search engines can'	t index plugin content, and m	any devices restrict plugins or don't sup	port them. <u>Learn more</u> .
Tap targets are size	d appropriately - 100% ap	propriately sized tap targets	^
	like buttons and links should without overlapping onto othe	be large enough (48x48px), and have energer elements. <u>Learn more</u> .	nough space around them, to be
Not applicable (3)			^
robots.txt is valid			^
If your robots.txt file indexed. <u>Learn more</u>	•	not be able to understand how you want	your website to be crawled or
Image elements hav	ve [alt] attributes		^
Informative elements attribute. Learn more	•	otive alternate text. Decorative elements	can be ignored with an empty alt
Document has a val	id rel=canonical		^
Canonical links sugg	gest which URL to show in sea	arch results. <u>Learn more</u> .	



Progressive Web App

These checks validate the aspects of a Progressive Web App. <u>Learn more</u>.

Installable

▲ Web app manifest or service worker do not meet the installability requirements — 1 reason

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. Learn more.

Failure reason

No manifest was fetched

PWA Optimized

▲ Does not register a service worker that controls page and start url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

Does not redirect HTTP traffic to HTTPS.

If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. Learn more.

▲ Is not configured for a custom splash screen Failures: No manifest was fetched.

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn</u> more.

Does not set a theme color for the address bar.

Failures: No manifest was fetched, No `<meta name="theme-color">` tag found.

The browser address bar can be themed to match your site. <u>Learn more</u>.

Content is sized correctly for the viewport

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. <u>Learn more</u>.

	Has a <meta name="viewport"/> tag with width or initial-scale	^
	Add a ` <meta name="viewport"/> ` tag to optimize your app for mobile screens. <u>Learn more</u> .	
A	Does not provide a valid apple-touch-icon	^
	For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u> .	
A	Manifest doesn't have a maskable icon No manifest was fetched	^
	A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device <u>Learn more</u> .	e.
	ditional items to manually check (3) — These checks are required by the baseline PWA Checklist but are not comatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.	^
		^
	comatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually. Site works cross-browser	
	Site works cross-browser To reach the most number of users, sites should work across every major browser. Learn more.	^
	Site works cross-browser To reach the most number of users, sites should work across every major browser. Learn more. Page transitions don't feel like they block on the network Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of	^
	Site works cross-browser To reach the most number of users, sites should work across every major browser. Learn more. Page transitions don't feel like they block on the network Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. Learn more.	^

Runtime Settings

URL https://retrodome.herokuapp.com/

Fetch Time Nov 14, 2021, 11:29 PM GMT

Device Emulated Moto G4

Network throttling 150 ms TCP RTT, 1,638.4 Kbps throughput (Simulated)

CPU throttling 4x slowdown (Simulated)

Channel devtools

User agent (host) Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML,

like Gecko) Chrome/94.0.4606.81 Safari/537.36

User agent (network) Mozilla/5.0 (Linux; Android 7.0; Moto G (4)) AppleWebKit/537.36 (KHTML, like

Gecko) Chrome/94.0.4590.2 Mobile Safari/537.36 Chrome-Lighthouse

CPU/Memory Power 2581

Axe version 4.2.3

Generated by Lighthouse 8.3.0 | File an issue