



Performance

Metrics			=
First Contentful Paint	0.6 s	Time to Interactive	0.6 s
Speed Index	0.6 s	Total Blocking Time	0 ms
Largest Contentful Paint	0.6 s	Cumulative Layout Shift	0.014

Values are estimated and may vary. The performance score is calculated directly from these metrics. See calculator.

View Original Trace



Diagnostics — More information about the performance of your application. These numbers don't <u>directly affect</u> the Performance score.

Avoid chaining critical requests - 10 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. <u>Learn more</u>.

Maximum critical path latency: 170 ms

Initial Navigation

/privacy (flask-ms3-coffee.herokuapp.com)

- ...css/bootstrap.min.css (cdnjs.cloudflare.com) 30 ms, 23.18 KiB
- ...css/all.min.css (cdnjs.cloudflare.com)
 - ...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com) 40 ms, 77.33 KiB
 - ...webfonts/fa-regular-400.woff2 (cdnjs.cloudflare.com) 40 ms, 13.96 KiB

...css/style.css (flask-ms3-coffee.herokuapp.com)

/css2?family=... (fonts.googleapis.com)

...v10/9Bt33CxNw....woff2 (fonts.gstatic.com) - 20 ms, 198.55 KiB

...v11/X7n94bcuG....woff2 (fonts.gstatic.com) - 10 ms, 14.55 KiB

...dist/email.min.js (cdn.jsdelivr.net) - 20 ms, 9.10 KiB

/jquery-3.6.0.min.js (code.jquery.com) - 30 ms, 30.30 KiB

...umd/popper.min.js (cdnjs.cloudflare.com) - 30 ms, 6.55 KiB

...js/bootstrap.min.js (cdnjs.cloudflare.com) - 20 ms, 14.10 KiB

...js/script.js (flask-ms3-coffee.herokuapp.com) - 20 ms, 1.63 KiB

Keep request counts low and transfer sizes small - 15 requests • 495 KiB


To set budgets for the quantity and size of page resources, add a budget.json file. Learn more.

Resource Type	Requests	Transfer Size
Total	15	494.8 KiB
Font	4	304.4 KiB
Image	1	71.3 KiB
Script	5	61.7 KiB
Stylesheet	4	41.5 KiB
Document	1	15.9 KiB
Media	0	0.0 KiB
Other	0	0.0 KiB
Third-party	11	398.8 KiB

Largest Contentful Paint element - 1 element found

This is the largest contentful element painted within the viewport. Learn More

Element



Avoid large layout shifts - 5 elements found

These DOM elements contribute most to the CLS of the page.

Element CLS Contribution

div.col-12.mt-2		CLS	Contribution
	div.col-12.mt-2		
			0.004
	div.col-12.mt-2		
			0.004
	div.col-12.mt-2		
			0.004
	a.navbar-brand		
			0.001
	h1		
			0.001
		earn more	^
	Sho	w 3rd-party re	esources (0)
URL	Start	t Time	Duration
/privacy (flask-ms3-coffee.he	rokuapp.com) 26	87 ms	67 ms
ssed audits (32)			^
Eliminate render-blocking re	esources — Potential savings of 70 ms		^
Resources are blocking the f JS/styles. <u>Learn more</u> .	div.col-12.mt-2 div.col-12.mt-2 div.col-12.mt-2 0.004 h1 long main-thread tasks — 1 long task found he longest tasks on the main thread, useful for identifying worst contributors to input delay. Learn more Show-9rd-party-resources (0) Start Time Duration acy. (flask-ms3-coffee herokuspp.com) 287 ms 67 ms rate render-blocking resources — Potential savings of 70 ms rate render-blocking resources — Potential savings of 70 ms rates are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical		
	✓ Sho	w 3rd-party re	esources (2)
URL		Transfer Size	Potential Savings
css/bootstrap.min.css (co	dnjs.cloudflare.com)	23.2 KiB	260 ms

more.

	Transfer Size	Potential Savings
css/style.css (flask-ms3-coffee.herokuapp.com)	7.1 KiB	60 ms
dist/email.min.js (cdn.jsdelivr.net)	9.1 KiB	220 ms
Properly size images		^
Serve images that are appropriately-sized to save cellular data and improve load time.	<u>Learn more</u> .	
Defer offscreen images		^
Consider lazy-loading offscreen and hidden images after all critical resources have finis interactive. Learn more.	shed loading to lower time	to
Minify CSS		^
Minifying CSS files can reduce network payload sizes. Learn more.		
Minify JavaScript		^
Minifying JavaScript files can reduce payload sizes and script parse time. Learn more.		
Remove unused CSS — Potential savings of 33 KiB		^
Remove dead rules from stylesheets and defer the loading of CSS not used for above- unnecessary bytes consumed by network activity. <u>Learn more</u> .	the-fold content to reduce	;
	Show 3rd party r	esources (2)
URL	Transfer	
OI IL	Size	Potential Savings
css/bootstrap.min.css (cdnjs.cloudflare.com)		
	Size	Savings
css/bootstrap.min.css (cdnjs.cloudflare.com)	Size 23.2 KiB	Savings 22.1 KiB
css/bootstrap.min.css (cdnjs.cloudflare.com)css/all.min.css (cdnjs.cloudflare.com)	Size 23.2 KiB 10.6 KiB	Savings 22.1 KiB 10.5 KiB
css/bootstrap.min.css (cdnjs.cloudflare.com)css/all.min.css (cdnjs.cloudflare.com) Remove unused JavaScript — Potential savings of 23 KiB	Size 23.2 KiB 10.6 KiB	Savings 22.1 KiB 10.5 KiB
css/bootstrap.min.css (cdnjs.cloudflare.com)css/all.min.css (cdnjs.cloudflare.com) Remove unused JavaScript — Potential savings of 23 KiB	Size 23.2 KiB 10.6 KiB	Savings 22.1 KiB 10.5 KiB csources (1) Potential
css/bootstrap.min.css (cdnjs.cloudflare.com)css/all.min.css (cdnjs.cloudflare.com) Remove unused JavaScript — Potential savings of 23 KiB Remove unused JavaScript to reduce bytes consumed by network activity. Learn more	Size 23.2 KiB 10.6 KiB Show 3rd party r	Savings 22.1 KiB 10.5 KiB csources (1) Potential
css/bootstrap.min.css (cdnjs.cloudflare.com)css/all.min.css (cdnjs.cloudflare.com) Remove unused JavaScript — Potential savings of 23 KiB Remove unused JavaScript to reduce bytes consumed by network activity. Learn more	Size 23.2 KiB 10.6 KiB Show 3rd party r Transfer Size	Savings 22.1 KiB 10.5 KiB cesources (1) Potential Savings
css/bootstrap.min.css (cdnjs.cloudflare.com) css/all.min.css (cdnjs.cloudflare.com) Remove unused JavaScript — Potential savings of 23 KiB Remove unused JavaScript to reduce bytes consumed by network activity. Learn more URL /jquery-3.6.0.min.js (code.jquery.com)	Size 23.2 KiB 10.6 KiB Show 3rd party r Transfer Size	Savings 22.1 KiB 10.5 KiB esources (1) Potential Savings 22.7 KiB
css/bootstrap.min.css (cdnjs.cloudflare.com) css/all.min.css (cdnjs.cloudflare.com) Remove unused JavaScript — Potential savings of 23 KiB Remove unused JavaScript to reduce bytes consumed by network activity. Learn more URL /jquery-3.6.0.min.js (code.jquery.com) Efficiently encode images	Size 23.2 KiB 10.6 KiB Show 3rd party r Transfer Size	Savings 22.1 KiB 10.5 KiB esources (1) Potential Savings 22.7 KiB
css/bootstrap.min.css (cdnjs.cloudflare.com) css/all.min.css (cdnjs.cloudflare.com) Remove unused JavaScript — Potential savings of 23 KiB Remove unused JavaScript to reduce bytes consumed by network activity. Learn more URL /jquery-3.6.0.min.js (code.jquery.com) Efficiently encode images Optimized images load faster and consume less cellular data. Learn more.	Size 23.2 KiB 10.6 KiB Show 3rd party r Transfer Size 30.3 KiB	Savings 22.1 KiB 10.5 KiB cesources (1) Potential Savings 22.7 KiB
css/bootstrap.min.css (cdnjs.cloudflare.com)css/all.min.css (cdnjs.cloudflare.com) Remove unused JavaScript — Potential savings of 23 KiB Remove unused JavaScript to reduce bytes consumed by network activity. Learn more URL /jquery-3.6.0.min.js (code.jquery.com) Efficiently encode images Optimized images load faster and consume less cellular data. Learn more. Serve images in next-gen formats Image formats like JPEG 2000, JPEG XR, and WebP often provide better compression	Size 23.2 KiB 10.6 KiB Show 3rd party r Transfer Size 30.3 KiB	Savings 22.1 KiB 10.5 KiB cesources (1) Potential Savings 22.7 KiB

Preconnect to required origins	^
Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connections to important third-party origins. <u>Learn more</u> .	
Initial server response time was short — Root document took 30 ms	^
Keep the server response time for the main document short because all other requests depend on it. <u>Learn more</u> .	
Show 3rd-party resources (0))
URL Time Spec	nt
/privacy (flask-ms3-coffee.herokuapp.com) 30 ms	}
Avoid multiple page redirects	^
Redirects introduce additional delays before the page can be loaded. <u>Learn more</u> .	
Preload key requests	^
Consider using ` <link rel="preload"/> ` to prioritize fetching resources that are currently requested later in page load. <u>Learn more</u> .	
Use HTTP/2	^
HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. <u>Learn more</u> .	
Use video formats for animated content	^
Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. <u>Learn more</u>	
Remove duplicate modules in JavaScript bundles	^
Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity.	
Avoid serving legacy JavaScript to modern browsers	^
Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. <u>Learn More</u>	
Preload Largest Contentful Paint image	^
Preload the image used by the LCP element in order to improve your LCP time. Learn more.	
Avoids enormous network payloads — Total size was 495 KiB	^
Large network payloads cost users real money and are highly correlated with long load times. Learn more.	
Show 3rd-party resources (8))
URL Transfer Siz	<u>′</u> e
v10/9Bt33CxNwwoff2 (fonts.gstatic.com) 198.5 KiE	}
webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com) 77.3 KiE	}
img/nav_img.jpeg (flask-ms3-coffee.herokuapp.com) 71.3 KiE	3

URL		Transfer Siz
/jquery-3.6.0.min.js (code.jquery.com)		30.3 KiE
css/bootstrap.min.css (cdnjs.cloudflare.com)		23.2 KiE
/privacy (flask-ms3-coffee.herokuapp.com)		15.9 KiE
v11/X7n94bcuGwoff2 (fonts.gstatic.com)		14.6 Kil
js/bootstrap.min.js (cdnjs.cloudflare.com)		14.1 Ki
webfonts/fa-regular-400.woff2 (cdnjs.cloudfl	are.com)	14.0 Ki
css/all.min.css (cdnjs.cloudflare.com)		10.6 Ki
Uses efficient cache policy on static assets -	- 1 resource found	
A long cache lifetime can speed up repeat visit	s to your page. <u>Learn more</u> .	
	Show 3rd-party	/ resources (
URL	Cache TTL	Transfer S
dist/email.min.js (cdn.jsdelivr.net)	7 d	9 Ki
Avoids an excessive DOM size — 125 eleme	ents	
A large DOM will increase memory usage, caus	se longer <u>style calculations</u> , and produce costly <u>layout reflows</u> . <u>L</u>	earn more.
Statistic	Element	Va
Statistic Total DOM Elements	Element	
	Element label.form-label	12
Total DOM Elements		12
Total DOM Elements	label.form-label	12
Total DOM Elements Maximum DOM Depth	label.form-label	12
Total DOM Elements Maximum DOM Depth Maximum Child Elements User Timing marks and measures	label.form-label	12
Total DOM Elements Maximum DOM Depth Maximum Child Elements User Timing marks and measures Consider instrumenting your app with the User	label.form-label div.row	-
Total DOM Elements Maximum DOM Depth Maximum Child Elements User Timing marks and measures Consider instrumenting your app with the User experiences. Learn more. JavaScript execution time — 0.0 s	label.form-label div.row	12 1 ng key user
Total DOM Elements Maximum DOM Depth Maximum Child Elements User Timing marks and measures Consider instrumenting your app with the User experiences. Learn more. JavaScript execution time — 0.0 s Consider reducing the time spent parsing, com	label.form-label div.row Timing API to measure your app's real-world performance during	12 1 1 1 1 1 1 1 1 1 1 1 1 1
Total DOM Elements Maximum DOM Depth Maximum Child Elements User Timing marks and measures Consider instrumenting your app with the User experiences. Learn more. JavaScript execution time — 0.0 s Consider reducing the time spent parsing, com	label.form-label div.row Timing API to measure your app's real-world performance during appling, and executing JS. You may find delivering smaller JS pay	/loads helps

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>

Category	Time Spent
Rendering	102 ms
Other	29 ms
Style & Layout	11 ms
Script Evaluation	10 ms
Parse HTML & CSS	7 ms
Script Parsing & Compilation	2 ms
All text remains visible during webfont loads	^
Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. <u>Learn more</u> .	

Minimize third-party usage — Third-party code blocked the main thread for 0 ms

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. <u>Learn more</u>.

Show 3rd-party resources (0)

Third-Party	Transfer Size	Main-Thread Blocking Time
Google Fonts	214 KiB	0 ms
v10/9Bt33CxNwwoff2 (fonts.gstatic.com)	199 KiB	0 ms
v11/X7n94bcuGwoff2 (fonts.gstatic.com)	15 KiB	0 ms
Cloudflare CDN	146 KiB	0 ms
webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	77 KiB	0 ms
css/bootstrap.min.css (cdnjs.cloudflare.com)	23 KiB	0 ms
js/bootstrap.min.js (cdnjs.cloudflare.com)	14 KiB	0 ms
webfonts/fa-regular-400.woff2 (cdnjs.cloudflare.com)	14 KiB	0 ms
css/all.min.css (cdnjs.cloudflare.com)	11 KiB	0 ms
jQuery CDN	30 KiB	0 ms
/jquery-3.6.0.min.js (code.jquery.com)	30 KiB	0 ms
JSDelivr CDN	9 KiB	0 ms
dist/email.min.js (cdn.jsdelivr.net)	9 KiB	0 ms

Lazy load third-party resources with facades

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. Learn more.

Uses passive listeners to improve scrolling performance

Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. Learn more.

Avoids document.write()

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. <u>Learn more</u>.

Avoid non-composited animations

Animations which are not composited can be janky and increase CLS. Learn more

Image elements have explicit width and height

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. Learn more



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Navigation — These are opportunities to improve keyboard navigation in your application.

Dran anh canalanad bar district		
	nat do not skip levels convey the semantic structure of the page, making it easier to navigate assistive technologies. Learn more.	
Failing Elements		
	h6.h5.mt-2	
	neck (10) — These items address areas which an automated testing tool cannot cover. Sucting an accessibility review.	/
	ducting an accessibility review.	,
earn more in our guide on condearn more in our guide on the condearn more in our guide.	ducting an accessibility review.	
earn more in our guide on condessern more in our guide on the condesser more in our guide.	ducting an accessibility review. order lows the visual layout. Users cannot focus elements that are offscreen. Learn more.	
The page has a logical tab of Tabbing through the page fo	ducting an accessibility review. order lows the visual layout. Users cannot focus elements that are offscreen. Learn more.	
The page has a logical tab of Tabbing through the page fo	ducting an accessibility review. Order lows the visual layout. Users cannot focus elements that are offscreen. Learn more. Doard focusable are keyboard focusable and display a focus indicator. Learn more.	^
The page has a logical tab of Tabbing through the page for Interactive controls are keyl Custom interactive controls Interactive elements indicate the controls of the control of t	ducting an accessibility review. Order lows the visual layout. Users cannot focus elements that are offscreen. Learn more. Doard focusable are keyboard focusable and display a focus indicator. Learn more.	^

If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more.

User focus is not accidentally trapped in a region

A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order DOM order matches the visual order, improving navigation for assistive technology. Learn more. Offscreen content is hidden from assistive technology Offscreen content is hidden with display: none or aria-hidden=true. Learn more. HTML5 landmark elements are used to improve navigation Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. Passed audits (18) [aria-*] attributes match their roles Each ARIA 'role' supports a specific subset of 'aria-*' attributes. Mismatching these invalidates the 'aria-*' attributes. Learn more. [aria-hidden="true"] is not present on the document <body> Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. Learn more. [role]s have all required [aria-*] attributes Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more. Elements with an ARIA [role] that require children to contain a specific [role] have all required children. Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more. [role]s are contained by their required parent element Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more. [role] values are valid ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more. [aria-*] attributes have valid values Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more. [aria-*] attributes are valid and not misspelled Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more.

The page contains a heading, skip link, or landmark region Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more. Background and foreground colors have a sufficient contrast ratio Low-contrast text is difficult or impossible for many users to read. Learn more. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. ARIA IDs are unique The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn <html> element has a [lang] attribute If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more. <html> element has a valid value for its [lang] attribute Specifying a valid <u>BCP 47 language</u> helps screen readers announce text properly. <u>Learn more</u>. Links have a discernible name Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn more. Lists contain only elements and script supporting elements (<script> and <template>). Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more. List items (<1i>) are contained within <u1> or <o1> parent elements Screen readers require list items (') to be contained within a parent '' or '' to be announced properly. Learn more. [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5. Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more. Not applicable (25) [accesskey] values are unique Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more. button, link, and menuitem elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

[aria-hidden="true"] elements do not contain focusable descendents

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. <u>Learn more</u>.

ARIA input fields have accessible names

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

ARIA meter elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more.

ARIA progressbar elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more.

ARIA toggle fields have accessible names

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

ARIA tooltip elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

ARIA treeitem elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

Buttons have an accessible name

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. <u>Learn more</u>.

<dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements.

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn more.

Definition list items are wrapped in <dl> elements

Definition list items ('<dt>' and '<dd>') must be wrapped in a parent '<dl>' element to ensure that screen readers can properly announce them. <u>Learn more</u>.

[id] attributes on active, focusable elements are unique

All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more.

No form fields have multiple labels

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. <u>Learn more</u>.

<frame> or <iframe> elements have a title

Screen reader users rely on frame titles to describe the contents of frames. Learn more.

Image elements have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u>.

<input type="image"> elements have [alt] text

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. <u>Learn more</u>.

Form elements have associated labels

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more.

The document does not use <meta http-equiv="refresh">

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u>.

<object> elements have [alt] text

Screen readers cannot translate non-text content. Adding all text to `<object>` elements helps screen readers convey meaning to users. <u>Learn more</u>.

No element has a [tabindex] value greater than 0

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u>.

Cells in a element that use the [headers] attribute refer to table cells within the same table.

Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.

elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more</u>.

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn more</u>.

<video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.



Best Practices

18/07/2021 Passed audits (17) **Uses HTTPS** All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more. Links to cross-origin destinations are safe Add 'rel="noopener" or 'rel="noreferrer" to any external links to improve performance and prevent security vulnerabilities. Learn more. Avoids requesting the geolocation permission on page load Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more. Avoids requesting the notification permission on page load Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more. Avoids front-end JavaScript libraries with known security vulnerabilities Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. Learn more. Allows users to paste into password fields Preventing password pasting undermines good security policy. Learn more. Displays images with correct aspect ratio Image display dimensions should match natural aspect ratio. Learn more. Serves images with appropriate resolution Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn more. Page has the HTML doctype Specifying a doctype prevents the browser from switching to quirks-mode. Learn more. Properly defines charset

A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more.

Avoids unload event listeners

The 'unload' event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Consider using the 'pagehide' or 'visibilitychange' events instead. Learn more

Avoids Application Cache

Application Cache is deprecated. Learn more.

Detected JavaScript libraries

All front-end JavaScript libraries detected on the page. Learn more.

Name Version

Bootstrap 5.0.0-beta1

jQuery 3.6.0

core-js core-js-global@3.15.2

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. Learn more.

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. <u>Learn more</u>.

Show 3rd-party resources (2)

URL Map URL

- ...js/bootstrap.min.js (cdnjs.cloudflare.com) ...js/bootstrap.min.js.map (cdnjs.cloudflare.com)
- ...umd/popper.min.js (cdnjs.cloudflare.com) ...umd/popper.min.js.map (cdnjs.cloudflare.com)

No issues in the Issues panel in Chrome Devtools

Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Not applicable (1)

Fonts with font-display: optional are preloaded

Preload `optional` fonts so first-time visitors may use them. Learn more



These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. <u>Learn more</u>.

Structured data is valid	
Run the <u>Structured Data Testing Tool</u> and the <u>Structured Data Linter</u> to validate structured data. <u>Learn more</u> .	
Passed audits (9)	/
Has a <meta name="viewport"/> tag with width or initial-scale	
Add a ` <meta name="viewport"/> ` tag to optimize your app for mobile screens. Learn more.	
Document has a <title> element</td><td>_</td></tr><tr><td>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more</u>.</td><td></td></tr><tr><td>Document has a meta description</td><td>_</td></tr><tr><td>Meta descriptions may be included in search results to concisely summarize page content. <u>Learn more</u>.</td><td></td></tr><tr><td>Page has successful HTTP status code</td><td>/</td></tr><tr><td>Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more.</td><td></td></tr><tr><td>Links have descriptive text</td><td>/</td></tr><tr><td>Descriptive link text helps search engines understand your content. Learn more.</td><td></td></tr><tr><td>Links are crawlable</td><td>/</td></tr><tr><td>Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. <u>Learn More</u></td><td>S</td></tr><tr><td>Page isn't blocked from indexing</td><td>/</td></tr><tr><td>Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn more</td><td><u>ə</u>.</td></tr><tr><td>Document has a valid hreflang</td><td>,</td></tr><tr><td>hreflang links tell search engines what version of a page they should list in search results for a given language or region. <u>Learn more</u>.</td><td></td></tr><tr><td>Document avoids plugins</td><td>/</td></tr><tr><td>Search engines can't index plugin content, and many devices restrict plugins or don't support them. <u>Learn more</u>.</td><td></td></tr><tr><td>lot applicable (5)</td><td>/</td></tr><tr><td>robots.txt is valid</td><td></td></tr></tbody></table></title>	

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. Learn more.

Image elements have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u>.

Document has a valid rel=canonical

Canonical links suggest which URL to show in search results. Learn more.

Document uses legible font sizes

Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text $\ge 12px$. Learn more.

Tap targets are sized appropriately

Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. <u>Learn more</u>.



Progressive Web App

These checks validate the aspects of a Progressive Web App. Learn more.

Installable

▲ Web app manifest or service worker do not meet the installability requirements — 1 reason

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. Learn more.

Failure reason

No manifest was fetched

PWA Optimized

Does not register a service worker that controls page and start_url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

Does not redirect HTTP traffic to HTTPS

If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <u>Learn more</u>.

	Is not configured for a custom splash screen Failures: No manifest was fetched.	,
	A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn more</u> .	
_	Does not set a theme color for the address bar.	
A	Failures: No manifest was fetched, No ` <meta name="theme-color"/> ` tag found.	-
	The browser address bar can be themed to match your site. <u>Learn more</u> .	
	Content is sized correctly for the viewport	,
	If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. <u>Learn more</u> .	
	Has a <meta name="viewport"/> tag with width or initial-scale	,
	Add a ` <meta name="viewport"/> ` tag to optimize your app for mobile screens. <u>Learn more</u> .	
A	Does not provide a valid apple-touch-icon	,
	For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u> .	
<u> </u>	Manifest doesn't have a maskable icon No manifest was fetched	,
	A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device Learn more.).
	ditional items to manually check (3) — These checks are required by the baseline PWA Checklist but are not omatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.	/
	Site works cross-browser	_
	To reach the most number of users, sites should work across every major browser. <u>Learn more</u> .	
	Page transitions don't feel like they block on the network	

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. Learn more.

Each page has a URL

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. Learn more.

Runtime Settings

URL https://flask-ms3-coffee.herokuapp.com/privacy

Fetch Time Jul 18, 2021, 5:24 AM GMT+1

Device Emulated Desktop

Network throttling 40 ms TCP RTT, 10,240 Kbps throughput (Simulated) CPU throttling 1x slowdown (Simulated)

Channel devtools

User agent (host) Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML,

like Gecko) Chrome/91.0.4472.106 Safari/537.36

User agent (network) Mozilla/5.0 (Macintosh; Intel Mac OS X 10_14_6) AppleWebKit/537.36 (KHTML,

like Gecko) Chrome/90.0.4420.0 Safari/537.36 Chrome-Lighthouse

CPU/Memory Power 2610

Axe version 4.1.2

Generated by Lighthouse 7.2.0 | File an issue