

Breakout Sessie: Abonneren

VNG API-Lab Notificatie API

16 juni 2022

SUBSCRIBE



Search...

events >

domains >

subscriptions v

GET

List subscriptions

POST

Subscribe

GET

Request subscription info

PUT

Update subscription

DEL

Delete subscription

Documentation Powered by Redocly

Subscribe

Subscribe to receive events.

AUTHORIZATIONS: > *JWT-Claims*

REQUEST BODY SCHEMA: application/json

protocol	string (Protocol) Value: "HTTP" REQUIRED. Identifier of a delivery protocol.
protocolSettings >	HTTPSettings (object)
sink	string <url> REQUIRED. The address to which events shall be delivered using the selected protocol.
sinkCredential >	AccessTokenCredential (object) or AccessTokenCredential (object)
source	string <urn> OPTIONAL. Source to which the subscription applies. May be implied by the request address.
domain	string <reverse-dns> OPTIONAL. Domain to which the subscription applies.
types	Array of strings CloudEvent types eligible to be delivered by this subscription
filters >	Array of Filter (object) or Filter (object) or Filter (object) or Filter (object) or Filter (object) or Filter (object) (Filter entry) This filter evaluates to 'true' if all contained filters are 'true'
config >	object OPTIONAL. Implementation-specific configuration parameters needed by the subscription manager for acquiring events.
subscriberReference	string OPTIONAL. Events that are send to the subscriber will contain this reference. The subscriber can use the reference for internal routing of the event.

POST /subscriptions v

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{  "protocol": "HTTP",  - "protocolSettings": {    + "headers": { ... },    "method": "POST"  },  "sink": "https://endpoint.example.com/webhook",  - "sinkCredential": {    "credentialType": "ACCESSTOKEN",    "accessToken": "string",    "accessTokenExpiresUtc": "2019-08-24T14:15:22Z",    "accessTokenType": "bearer"  },  "source": "urn:nld:oin:00000001234567890000:systeem:2  "domain": "nl.vng.zaken",  - "types": [    "string"  ],  - "filters": [    + { ... }  ],  - "config": {    "property1": "string",    "property2": "string"  },  "subscriberReference": "1285c6bc-1b54-48d8-96e2-c55a3"}
```


protocol required	string (Protocol) Value: "HTTP" REQUIRED. Identifier of a delivery protocol.
protocolSettings >	HTTPSettings (object)
sink required	string <url> REQUIRED. The address to which events shall be delivered using the selected protocol.
sinkCredential >	AccessTokenCredential (object) or AccessTokenCredential (object)
source	string <urn> OPTIONAL. Source to which the subscription applies. May be implied by the request address.
domain	string <reverse-dns> OPTIONAL. Domain to which the subscription applies.
types	Array of strings CloudEvent types eligible to be delivered by this subscription
filters >	Array of Filter (object) or Filter (object) or Filter (object) or Filter (object) or Filter (object) or Filter (object) (Filter entry) This filter evaluates to 'true' if all contained filters are 'true'
config >	object OPTIONAL. Implementation-specific configuration parameters needed by the subscription manager for acquiring events.
subscriberReference	string OPTIONAL. Events that are send to the subscriber will contain this reference. The subscriber can use the reference for internal routing of the event.

REQUEST BODY SCHEMA: application/json

protocol required	string (Protocol) Value: "HTTP" REQUIRED. Identifier of a delivery protocol.
protocolSettings >	HTTPSettings (object)
sink required	string <url> REQUIRED. The address to which events shall be delivered using the selected
sinkCredential >	AccessTokenCredential (object) or AccessTokenCredential (object)
source	string <urn> OPTIONAL. Source to which the subscription applies. May be implied by the r
domain	string <reverse-dns> OPTIONAL. Domain to which
types	Array of strings CloudEvent types eligible to be delivered by this subscription
filters >	Array of Filter (object) or Filter (object) or Filter (object) or Filter (object) or Filter (o This filter evaluates to 'true' if all contained filters are 'true'
config >	object OPTIONAL. Implementation-specific configuration parameters needed by the
subscriberReference	string OPTIONAL. Events that are send to the subscriber will contain this reference. internal routing of the event.

```
{
  "protocol": "HTTP",
  - "protocolSettings": {
    + "headers": { ... },
    "method": "POST"
  },
  "sink": "https://endpoint.example.com/webhook",
  - "sinkCredential": {
    "credentialType": "ACCESSTOKEN",
    "accessToken": "string",
    "accessTokenExpiresUtc": "2019-08-24T14:15:22Z",
    "accessTokenType": "bearer"
  },
  "source": "urn:nld:oin:00000001234567890000:system:Zaaksysteem",
  "domain": "nl.vng.zaken",
  - "types": [
    "string"
  ],
  - "filters": [
    + { ... }
  ],
  - "config": {
    "property1": "string",
    "property2": "string"
  },
  "subscriberReference": "1285c6bc-1b54-48d8-96e2-c55a3f970c39"
}
```

Werking filters in subscription



Use case 1: Geen filter

```
{  
  "protocol": "HTTP",  
  "protocolSettings": {  
    "method": "POST"  
  },  
  "sink": "https://webhook.site/d1efae87-8fd1-4749-b8dc-3dbdcd606626",  
  "sinkCredential": {  
    "credentialType": "ACCESSTOKEN",  
    "accessToken": "abcd1234",  
    "accessTokenExpiresUtc": "2022-12-31T00:00:00.000Z",  
    "accessTokenType": "bearer"  
  }  
}
```



Hier staat geen filter

```
}
```

Use case 2: Filtering op domein en type

```
{
  "protocol": "HTTP",
  "protocolSettings": {
    "method": "POST"
  },
  "sink": "https://webhook.site/d1efae87-8fd1-4749-b8dc-3dbdcd606626",
  "sinkCredential": {
    "credentialType": "ACCESSTOKEN",
    "accessToken": "abcd1234",
    "accessTokenExpiresUtc": "2022-12-31T00:00:00.000Z",
    "accessTokenType": "bearer"
  },
  "domain": "nl.vng.zaken",
  "types": [
    "nl.vng.zaken.zaak_gecreerd",
    "nl.vng.zaken.zaak_gewijzigd",
    "nl.vng.zaken.zaak_verwijderd"
  ]
}
```

Filterattribuut



Use case 3: Filterexpressie - logisch

```
(
  domain = "nl.vng.zaken"
  and
  (
    type = "nl.vng.zaken.status_gewijzigd"
    or
    type = "nl.vng.zaken.zaak_gesloten"
  )
)


or

(
  domain = "nl.vng.documenten"
  and
  vertrouwelijkheid = "normaal"
)
```

Use case 3: Filterexpressie – Prefix notatie

https://en.wikipedia.org/wiki/Polish_notation

- any:
 - all:
 - exact:
 - attribute: domain
 - value: nl.vng.zaken
 - any:
 - exact:
 - attribute: domain
 - value: nl.vng.zaken
 - exact:
 - attribute: type
 - value: nl.vng.zaken.zaak_gesloten
- all:
 - exact:
 - attribute: domain
 - value: nl.vng.zaken
 - exact:
 - attribute: type
 - value: nl.vng.zaken.zaak_gesloten



Use case 3: Filterexpressie

Json:

<https://github.com/VNG-Realisatie/notificatieservices/blob/main/docs/api-specification/gedrag.md#het-filters-attribuut>

Use case 4: Domein + Typen + BSN ten behoeve van Zaak X

```
{
  ...

  "domain": "nl.brp",

  "types": [
    "nl.brp.persoon_verhuisd",
    "nl.brp.persoon_overleden"
  ],

  "filters": [{
    "exact": {
      "attribute": "bsn",
      "value": "1234567"
    }
  }],

  "subscriberReference": "https://open-zaak.test.sudwest-fryslan.opengem.nl/zaken/v1/zaken/dfc761b4-28d9-4b1d-a2f8-8f966322ea87"

}
```

Use case 5: Opgeven van protocol en sink niet toegestaan

```
{  
"protocol": "HTTP",  
"protocolSettings": {},  
"sink": "https://webhook.site/d1efae87-8fd1-4749-b8dc-3dbded606626",  
"sinkCredential": {},  
  
  "config": {  
    "SAP_Contract": "SAP1234567"  
  }  
  
  "domain": "nl.brk",  
  "types": [  
    "nl.brk.gebeurtenistype.eigendomsinformatie.koopovereenkomstverwerkt"  
  ],  
  "filters": [{  
    "exact": {  
      "attribute": "bsn",  
      "value": "1234567"  
    }  
  }],  
  
  "subscriberReference": "https://saas.notarissoftware.nl/zaken/v1/95e58558-a82c-42da-a089-976e819a365f"  
}
```

ReDoc

Search...

events>

domains>

subscriptions▼

GET

List subscriptions

POST

Subscribe

GET

Request subscription info

PUT

Update subscription

DEL

Delete subscription

Documentation Powered by Redocly

Upload a file

http://redocly.github.io/redoc?url=https://raw.githubusercontent.com/VNG-Realisatie/notificatieservices/main/docs/api-specification/notifications.yaml#tag/subscriptions/operation/subscribe

TRY IT

✓

CORS

Star

17,448

Subscribe

Subscribe to receive events.

AUTHORIZATIONS: >

JWT-Claims

REQUEST BODY SCHEMA: application/json

protocol

required

string (Protocol)

Value: "HTTP"

REQUIRED. Identifier of a delivery protocol.

protocolSettings >

HTTPSettings (object)

sink

required

string <url>

REQUIRED. The address to which events shall

sinkCredential >

AccessTokenCredential (object) or AccessTokenC

source

string <urn>

OPTIONAL. Source to which the subscription a

address.

domain

string <reverse-dns>

OPTIONAL. Domain to which the subscription a

types

Array of strings

CloudEvent types eligible to be delivered by this

filters >

Array of Filter (object) or Filter (object) or Filter (ob

(object) (Filter entry)

This filter evaluates to 'true' if all contained filter

config >

object

OPTIONAL. Implementation-specific configura

manager for acquiring events.

subscriberReference

string

OPTIONAL. Events that are send to the subscri

can use the reference for internal routing of the

Scope: Overeenkomst

protocol, protocolSettings, sink, sinkCredential
config (alternatieve verwijzing naar 'afspraken')

Scope: Soort taak/proces
'basis filtering'

domain, types

Scope: Zaak/Dossier
'fijnmazige filtering'

filters (met bijvoorbeeld BSN)
subscriberReference (zaak referentie)

Bron

- Toepassen doelbinding / Privacy
- Bij informatierijk notificeren content beperken

NRC

- Beperkt tot context attributen
- Eenvoudige op routing gerichte filtering
- Niet filteren in data

Afnemer

- Interne routing
- Filteren in data